
Prebatch / Precheck File Generator Reference Guide

Version: 1.3 | Maintained by: Ruvixx — Case Investigation Operations | Regions: MCC · CS

This guide covers all features of the Prebatch Generator app: file processing, pre-validation, batch distribution with four named batch types, delivery confirmation, persistent history, the Delivery ID string generator, and the GitHub configuration.

1. App Layout

Area	Contents
Top banner	GitHub history load status (green = connected, orange = error)
Sidebar	Logo · Documentation button · Delivery History · Session Log
Region selector	Two large buttons: MCC (orange) and CS (blue). Active region shown with coloured banner listing all countries.
File uploaders	Three slots: QS Delivery ID · PL Batch · Conflict Check
Batch Distribution	Optional pre-generation configuration. Section colour matches active region.
ID String Generator	Standalone tool to produce QuickSuite Delivery ID search strings
Processing area	Validate Batch · Generate Prebatch File buttons
Results area	Metrics · Preview · Download · Distribution results · Confirm Delivery

2. Region Selector

The region selector sits at the top of the app and controls the column structure of the output, the country lists available in the batch distribution, and the visual colour scheme throughout the page.

Region	Colour	Countries	Output
MCC	Orange (#F47920)	Mexico, Costa Rica, Panama, Dominican Republic, Honduras, Belize, Guatemala, Nicaragua, El Salvador	27 columns — includes Estimated Case Value, Last Updated At, NNS License Count
CS	Blue (#1E6FBF)	Chile, Argentina, Colombia, Ecuador, Peru, Uruguay, Bolivia, Paraguay	24 columns — uses Addresses and Country instead of Address and Countries

Switching region resets the batch validation, clears the confirm delivery state, and reloads the appropriate distribution profile.

3. Input Files

3.1 QS Delivery ID File

Column	Maps To	Notes
Case ID	Case ID	Join key. May be comma-separated for grouped entities.
Case Tier	Case Tier	1, 2, or 3
[Cfa]-Category	Case Category	Numeric category
[Cfa]-ActionableCategory	Actionable Category	Numeric actionable classification
Total Machines	# All Time Machines	Used by all batch type priority logic
Actionable Machines	# Actionable Machines	
[Cfa]-Difference	# Difference	Total minus actionable
Approved Machines	Actionable Machine IDs	
First Event	First Event	Normalized → YYYY-MM-DD HH:MM:SS
Last Event	Last Event	Normalized → YYYY-MM-DD HH:MM:SS

3.2 PL Batch File (Pleteo Export)

Column	Maps To	Notes
External Case ID	(join key)	Matches QS Case ID
Updated	Last Updated At	MCC only. Latest timestamp across grouped cases. Normalized to YYYY-MM-DD HH:MM:SS.

3.3 Conflict Check File

Column	Maps To	Notes
Case ID	(join key)	
Is Multi National	Is Multi-National	Auto-populated
Machine Overview	Machine Overview	Combined for grouped cases
Investigation Notes	Investigation Notes	Concatenated for grouped cases
Pleteo Entity Name	Entity Name	Falls back to QS Company Name if empty
Company Name	Company Name	
Cylynt Organization Name	Cylynt Organization Name	
Industry	Industry	
Address	Address / Addresses	MCC = Address, CS = Addresses
Countries	Countries / Country	MCC = Countries, CS = Country
Time Span	Time Span	e.g. '5 years 6 months'
Generic Email Addresses	Generic Email Address	Auto-populated
Actionable Domains	Actionable Domains	Primary; QS as fallback
Website	Website	Primary; QS as fallback

4. File Pre-Validation

As soon as any file is uploaded a validation panel appears. The Generate button is disabled until all three files pass.

File	Required Columns
QS Delivery ID	Case ID, Case Tier, Total Machines, Actionable Machines, Approved Machines, First Event, Last Event
PL Batch	External Case ID, Updated
Conflict Check	Case ID, Machine Overview, Investigation Notes, Pleteo Entity Name, Company Name, Actionable Domains

5. Processing Flow

Step 1 — Validate Batch

Checks all Case IDs in the QS file against the persistent delivery history. Repeated IDs show a warning listing the batch number and date they were previously delivered. This is informational only — generation is not blocked. Must be run at least once before Generate becomes available.

Step 2 — Generate Prebatch File

Merges all three files. Applies deduplication, date normalization (YYYY-MM-DD HH:MM:SS), and grouped-entity handling. If Batch Distribution is enabled, the selected batch type is applied automatically in the same step.

Step 3 — Download

Full Prebatch output available as Prebatch_MCC.xlsx or Prebatch_CS.xlsx. If distribution was applied, the distributed batch file is also available.

Step 4 — Confirm Batch Delivery

Registers the batch permanently. Enter the delivery date and batch number (pre-filled with last confirmed + 1 per region). MCC and CS counters are independent. On confirm the record is pushed to GitHub.

6. Output File — Column Structure

6.1 MCC Output (27 columns)

#	Column	Source	Status
1	Date Added to This Sheet	—	Blank — manual entry
2	Is Multi-National	Conflict Check	Auto-populated
3	Machine Overview	Conflict Check	Auto-populated
4	Investigation Notes	Conflict Check	Auto-populated
5	Case ID	QS Delivery ID	Auto-populated
6	Company Name	Conflict Check	Auto-populated
7	Entity Name	CC Pleteo Entity Name / QS fallback	Auto-populated
8	Cylynt Organization Name	Conflict Check	Auto-populated
9	Industry	Conflict Check	Auto-populated
10	Address	Conflict Check	Auto-populated
11	Countries	Conflict Check	Auto-populated

12	Estimated Case Value	—	Blank — manual entry
13	Case Tier	QS Delivery ID	Auto-populated
14	Case Category	QS [Cfa]-Category	Auto-populated
15	Actionable Category	QS [Cfa]-ActionableCategory	Auto-populated
16	# All Time Machines	QS Total Machines	Auto-populated
17	# Actionable Machines	QS Actionable Machines	Auto-populated
18	# Difference	QS [CFa]-Difference	Auto-populated
19	Actionable Machine IDs	QS Approved Machines	Auto-populated
20	First Event	QS Delivery ID	YYYY-MM-DD HH:MM:SS
21	Last Event	QS Delivery ID	YYYY-MM-DD HH:MM:SS
22	Time Span	Conflict Check	Auto-populated
23	Generic Email Address	CC Generic Email Addresses	Auto-populated
24	Actionable Domains	CC primary / QS fallback	Auto-populated
25	Website	CC primary / QS fallback	Auto-populated
26	Last Updated At	PL Batch (Updated)	YYYY-MM-DD HH:MM:SS
27	NNS License Count	—	Blank — manual entry

6.2 CS Output (24 columns)

Same structure as MCC with three differences: **Address** → **Addresses**, **Countries** → **Country**, and columns **Estimated Case Value**, **Last Updated At**, and **NNS License Count** are not included.

7. Batch Distribution

An optional tool to automatically distribute large Pleteo exports by country group and quota without manually selecting cases. Enable it before generating when working with a large uncurated batch. If cases were already manually selected, skip this section.

7.1 Batch Types

Select the batch type before generating. The type is applied automatically as part of the generation step. When the toggle is OFF, Batch Standard runs by default.

Type	Machine Filter	Algorithm	Warnings Triggered
■ Standard (default)	None	Fill each group's country quota by order of availability. No machine count ordering.	Overflow between groups · Total quota not met
■ Low	< 3 machines only	Filter to <3 machine cases first. Fill groups by country quota. Overflow from unused <3 cases.	Overflow between groups · Total quota not met
■ Traditional	50% ≥ 3, 50% < 3 (across total batch)	Pass 1: Distribute 3+ machine cases across groups by country, globally capped at 50% of total quota. Pass 2: Fill remaining per-group quota with <3 machine cases by country. Pass 3: Overflow — fill any remaining shortfalls from any unused cases.	Overflow between groups · Total quota not met
■ Golden	≥ 3 machines (overflow allows <3)	Phase 1: Fill groups from 3+ machine pool by country. Phase 2: Overflow from unused 3+ cases in other groups. Phase 3: If still short, fill with any remaining cases (including <3).	<3 machines used in Golden · Overflow between groups · Total quota not met

Overflow rule (all types)

After all groups have been processed, any group still below its quota borrows from unused cases outside its own country pool. A warning is shown for each group that received overflow cases. A separate warning is shown if the total batch quota was not met after exhausting all available cases.

7.2 Default Distributions

MCC — Standard MCC

Group	Countries	Default Quota
Mexico	Mexico	40
Panama · Costa Rica · Dominicana	Panama, Costa Rica, Dominican Republic	40
Central America	Honduras, Belize, Guatemala, Nicaragua, El Salvador	40

CS — Standard CS

Group	Countries	Default Quota
Chile	Chile	20
Argentina	Argentina	25
Colombia · Ecuador	Colombia, Ecuador	35
Peru	Peru	10
Uruguay · Bolivia · Paraguay	Uruguay, Bolivia, Paraguay	20

7.3 Profile Management

Action	How
Update existing profile	Edit groups/quotas in Edit Profile, click Update Profile
Save as new profile	Enter a name in 'Save as New' field, click Save as New
Set default profile	Select from dropdown, click Set as Default
Delete a profile	Select profile, click  Delete (disabled if only one exists)
Export all profiles	Import/Export expander → Export All Profiles as JSON
Import profiles	Import/Export expander → upload JSON file

Countries already assigned to one group are hidden from all other group dropdowns. The batch type is not saved as part of a profile — select it each run. Profiles are stored in session memory; export as JSON to persist across sessions.

7.4 Backlog Report

After distribution a Backlog Report shows all non-selected cases by country: Total Backlog · 3+ Machines · <3 Machines. Downloadable as Excel for planning the next batch.

8. Delivery ID Search String Generator

Generates External Case ID search strings for the QuickSuite SKU Case Delivery Backlog dashboard. Accessible via the collapsible section before the processing area.

- Upload a Pleteo export (CSV or XLSX).
- Select the ID column (auto-detects 'External Case ID').
- Set chunk size (default 100 — QuickSuite search limit).
- Each output string is comma-separated with no spaces.
- Use the native copy button (top-right of each code block) to paste directly into QuickSuite.

9. Persistent Delivery History

Confirmed deliveries are stored in `batch_history.json` in the GitHub repo and loaded on every app start.

Field	Description
batch_number	Sequential number per region (MCC and CS count independently)
delivery_date	Date confirmed (YYYY-MM-DD)
region	MCC or CS
profile	Distribution profile used, or 'Full Prebatch (no distribution applied)'
total_cases	Number of cases confirmed
cases	List of [Case ID, Entity Name] pairs

The sidebar Delivery History section shows the last 5 confirmed batches per region. The Validate Batch button cross-checks current Case IDs against all history and warns on repeats (warning only — generation is not blocked).

10. GitHub Setup & Configuration

10.1 Required Streamlit Secrets

Go to share.streamlit.io → your app → ■ → Settings → Secrets tab. Paste the following block:

```
GITHUB_TOKEN = "ghp_yourNewTokenHere" GITHUB_REPO = "YourUsername/your-repo-name" HISTORY_FILE_PATH = "batch_history.json" GITHUB_BRANCH = "main"
```

Critical: GITHUB_REPO must be in owner/repo-name format. Example: if the URL is github.com/Jesus-Ameneiro/prebatch-delivery then use Jesus-Ameneiro/prebatch-delivery.

GITHUB_BRANCH must match your repo's actual default branch name. GITHUB_TOKEN must have the repo scope. Never commit the token to the repository.

10.2 Connection Diagnostics

If the top banner shows a warning, or Confirm Batch Delivery fails, a diagnostic panel automatically runs 5 checks:

Check	Common fix
Token configured	Regenerate token with repo scope, update secret
Repo format (owner/repo)	Add the owner prefix before the slash
Repo accessible	Check spelling; confirm token has repo access
Branch matches default	Update GITHUB_BRANCH to match the repo's default branch
History file path	File is created automatically on first confirmed delivery

11. Repository Files

File	Purpose	Commit?
app.py	Main Streamlit application	Yes
requirements.txt	Python dependencies	Yes
logo.png	Ruvixx logo	Yes
DOCUMENTATION.pdf	This reference guide	Yes
batch_history.json	Persistent delivery history (auto-created by app)	Yes — created by app
.streamlit/secrets.toml	Local dev secrets only — never commit	No — add to .gitignore

12. Troubleshooting

Issue	Cause	Fix
File validation ✖	Wrong file in wrong slot or renamed columns	Check column names vs Section 3
Generate button disabled	Validate Batch not yet run	Click Validate Batch first
Empty Entity Name	CC Pleteo Entity Name and QS Company Name both empty	Check source files
Distribution produces no cases	Country column values don't match group country names	Check Countries/Country values in output preview
Golden batch <3 warning	Insufficient 3+ machine cases to fill total quota	Expected — overflow used. Review backlog report.

GitHub HTTP 404 on confirm	GITHUB_REPO missing owner prefix or wrong branch	Use owner/repo format; check GITHUB_BRANCH
GitHub HTTP 401 on confirm	Token expired or wrong scope	Regenerate with repo scope
History not loading on start	Secrets not saved or app not rebooted	Verify Streamlit secrets, reboot app
PDF button shows about:blank	Browser blocked data: URI navigation	Current fix uses blob: URL — should open correctly

Last updated: May 2026 · Prebatch Generator v1.3