
Prebatch / Precheck File Generator Reference Guide

Version: 1.4 | Maintained by: Ruvixx — Case Investigation Operations | Regions: MCC · CS

This guide covers all features of the Prebatch Generator: file processing, pre-validation, the unified batch flow, four batch types, delivery confirmation, persistent history, the Delivery ID string generator, and GitHub configuration.

1. App Layout

Area	Contents
Top banner	GitHub history load status (green = connected, orange = error)
Sidebar	Logo · Documentation · Delivery History · Session Log
Region selector	Two large buttons: MCC (orange) and CS (blue). Active region shown with coloured banner.
File uploaders	Three slots: QS Delivery ID · PL Batch · Conflict Check
Batch Distribution	Toggle to customise batch type and profile. Off = Batch Standard applied automatically.
ID String Generator	Collapsible. Generates QuickSuite Delivery ID search strings.
Processing area	Validate Batch · Generate Prebatch File
Results area	Unified output: metrics · warnings · preview · download · Confirm Delivery

2. Region Selector

Two full-width toggle buttons at the top of the app control the active region. The active button uses the region colour; the page theme, batch section header, and metric card accents all update to match.

Region	Colour	Countries	Output columns
MCC	Orange #F47920	Mexico, Costa Rica, Panama, Dominican Republic, Honduras, Belize, Guatemala, Nicaragua, El Salvador	27 — includes Estimated Case Value, Last Updated At, NNS License Count
CS	Blue #1E6FBF	Chile, Argentina, Colombia, Ecuador, Peru, Uruguay, Bolivia, Paraguay	24 — uses Addresses and Country instead of Address and Countries

Switching region resets batch validation, clears confirm state, and loads the appropriate default distribution profile.

3. Input Files

3.1 QS Delivery ID File

Column	Maps To	Notes
Case ID	Case ID	Join key. May be comma-separated for grouped entities.
Case Tier	Case Tier	1, 2, or 3
[Cfa]-Category	Case Category	Numeric category
[Cfa]-ActionableCategory	Actionable Category	
Total Machines	# All Time Machines	Used by all batch type priority logic
Actionable Machines	# Actionable Machines	
[Cfa]-Difference	# Difference	Total minus actionable
Approved Machines	Actionable Machine IDs	
First Event	First Event	→ YYYY-MM-DD HH:MM:SS
Last Event	Last Event	→ YYYY-MM-DD HH:MM:SS

3.2 PL Batch File (Pleteo Export)

Column	Maps To	Notes
External Case ID	(join key)	Matches QS Case ID
Updated	Last Updated At	MCC only. Latest across grouped cases. → YYYY-MM-DD HH:MM:SS

3.3 Conflict Check File

Column	Maps To	Notes
Case ID	(join key)	
Is Multi National	Is Multi-National	Auto-populated
Machine Overview	Machine Overview	Combined for grouped cases
Investigation Notes	Investigation Notes	Concatenated for grouped cases
Pleteo Entity Name	Entity Name	Falls back to QS Company Name if empty
Company Name	Company Name	
Cylynt Organization Name	Cylynt Org Name	
Industry	Industry	
Address	Address / Addresses	MCC = Address, CS = Addresses
Countries	Countries / Country	MCC = Countries, CS = Country
Time Span	Time Span	e.g. '5 years 6 months'
Generic Email Addresses	Generic Email Address	Auto-populated
Actionable Domains	Actionable Domains	Primary; QS as fallback
Website	Website	Primary; QS as fallback

4. File Pre-Validation

A validation panel appears as soon as any file is uploaded. The Generate button is disabled until all three pass.

File	Required Columns
QS Delivery ID	Case ID, Case Tier, Total Machines, Actionable Machines, Approved Machines, First Event, Last Event
PL Batch	External Case ID, Updated
Conflict Check	Case ID, Machine Overview, Investigation Notes, Pleteo Entity Name, Company Name, Actionable Domains

5. Unified Batch Flow

Every generation always produces one Prebatch file. Batch Distribution is a configuration step that controls how cases are selected — the output is always a single Prebatch regardless of the options chosen.

5.1 Batch Distribution toggle

Toggle state	Behaviour
OFF (default)	Batch Standard is applied automatically using the region's default profile (Standard MCC or Standard CS). Cases are distributed by country quota — the total always reflects the configured groups. No machine count ordering.
ON	User selects a profile and a batch type (Standard / Low / Traditional / Golden). The chosen type is applied on generation. Per-group metric cards are shown in the results.

In both states the Prebatch output is quota-constrained. Toggle OFF is not a 'return all cases' mode.

5.2 Batch Types

Type	Machine filter	Algorithm	Warnings
■ Standard (default)	None	Fill each group's country quota by availability. No machine ordering.	Overflow · Quota not met
■ Low	<3 machines only	Filter to <3 cases. Fill groups by country. Overflow from unused <3 pool.	Overflow · Quota not met
■ Traditional	50% ≥3, 50% <3 across total batch	Pass 1: distribute 3+ cases by country, capped at 50% of total quota globally. Pass 2: fill remaining per-group quota with <3 cases by country. Pass 3: overflow from any unused cases.	Overflow · Quota not met
■ Golden	≥3 first; fallback to <3	Phase 1: fill groups from 3+ pool by country. Phase 2: overflow unused 3+ from other groups. Phase 3: if still short, fill with any remaining cases including <3.	<3 used in Golden · Overflow · Quota not met

Overflow rule (all types)

After all groups are processed, any group still below quota borrows from unused cases outside its own country pool. A warning is shown per group that received overflow. A separate warning fires if the total batch quota was not met.

5.3 Processing steps

1. **Validate Batch** — checks all QS Case IDs against confirmed delivery history. Repeated IDs show warnings (informational only — generation is not blocked). Must be run once before Generate becomes available.
2. **Generate Prebatch File** — merges files, deduplicates, normalises dates, then applies batch distribution (always). Result is stored as the Prebatch.

3. **Download** — single Prebatch file: Prebatch_MCC.xlsx or Prebatch_CS.xlsx.

4. **Confirm Batch Delivery** — registers the Prebatch permanently. Enter delivery date and batch number (pre-filled with last confirmed + 1 per region). On confirm the record is pushed to GitHub.

6. Output File — Column Structure

6.1 MCC Output (27 columns)

#	Column	Source	Status
1	Date Added to This Sheet	—	Blank — manual entry
2	Is Multi-National	Conflict Check	Auto-populated
3	Machine Overview	Conflict Check	Auto-populated
4	Investigation Notes	Conflict Check	Auto-populated
5	Case ID	QS Delivery ID	Auto-populated
6	Company Name	Conflict Check	Auto-populated
7	Entity Name	CC Pleteo Entity Name / QS fallback	Auto-populated
8	Cylynt Organization Name	Conflict Check	Auto-populated
9	Industry	Conflict Check	Auto-populated
10	Address	Conflict Check	Auto-populated
11	Countries	Conflict Check	Auto-populated
12	Estimated Case Value	—	Blank — manual entry
13	Case Tier	QS Delivery ID	Auto-populated
14	Case Category	QS [Cfa]-Category	Auto-populated
15	Actionable Category	QS [Cfa]-ActionableCategory	Auto-populated
16	# All Time Machines	QS Total Machines	Auto-populated
17	# Actionable Machines	QS Actionable Machines	Auto-populated
18	# Difference	QS [Cfa]-Difference	Auto-populated
19	Actionable Machine IDs	QS Approved Machines	Auto-populated
20	First Event	QS Delivery ID	YYYY-MM-DD HH:MM:SS
21	Last Event	QS Delivery ID	YYYY-MM-DD HH:MM:SS
22	Time Span	Conflict Check	Auto-populated
23	Generic Email Address	CC Generic Email Addresses	Auto-populated
24	Actionable Domains	CC primary / QS fallback	Auto-populated
25	Website	CC primary / QS fallback	Auto-populated
26	Last Updated At	PL Batch (Updated)	YYYY-MM-DD HH:MM:SS
27	NNS License Count	—	Blank — manual entry

6.2 CS Output (24 columns)

Same as MCC except: **Address** → **Addresses**, **Countries** → **Country**, and **Estimated Case Value**, **Last Updated At**, **NNS License Count** are excluded.

7. Default Distribution Profiles

Each region ships with a pre-configured Standard profile. When the Batch Distribution toggle is OFF, this profile is applied automatically using Batch Standard.

7.1 Standard MCC

Group	Countries	Default Quota
Mexico	Mexico	40
Panama · Costa Rica · Dominicana	Panama, Costa Rica, Dominican Republic	40
Central America	Honduras, Belize, Guatemala, Nicaragua, El Salvador	40

7.2 Standard CS

Group	Countries	Default Quota
Chile	Chile	20
Argentina	Argentina	25
Colombia · Ecuador	Colombia, Ecuador	35
Peru	Peru	10
Uruguay · Bolivia · Paraguay	Uruguay, Bolivia, Paraguay	20

7.3 Profile Management

Action	How
Update existing profile	Edit in Edit Profile expander → Update Profile
Save as new profile	Enter name in 'Save as New' field → Save as New
Set default profile	Select in dropdown → Set as Default
Delete a profile	Select →  Delete (disabled if only one profile exists)
Export all profiles	Import/Export expander → Export All Profiles as JSON
Import profiles	Import/Export expander → upload JSON file

Countries assigned to one group are hidden from all other group dropdowns. The batch type is not saved inside a profile — it is selected per run when the toggle is ON. Profiles are stored in session memory; export as JSON to persist across deployments.

8. Results Section

The results section is unified — there is always one output regardless of whether batch distribution was applied.

Element	Toggle OFF	Toggle ON
Header line	Profile name · ■ Batch Standard · N of M cases selected	Profile name · batch type label · N of M cases selected
Group metric cards	Hidden (Standard applied silently)	Shown — filled / quota per group
Summary metrics	Cases in Prebatch · Total Available · Backlog · Duplicates	Same
Warnings	Overflow / quota not met if applicable	Same + Golden <3 warning if applicable
Full merge reference	Shown if distribution filtered any cases	Same
Backlog report	Collapsible — cases not in this Prebatch	Same
Preview table	Final Prebatch output	Final Prebatch output
Download button	Prebatch_{region}.xlsx	Prebatch_{region}.xlsx
Confirm Delivery	Always present after generation	Always present after generation

The download and Confirm Delivery always operate on the same file — the final Prebatch. There is no separate 'distributed batch' file distinct from the Prebatch.

9. Delivery ID Search String Generator

Collapsible section before the processing area. Generates External Case ID strings for the QuickSuite SKU Case Delivery Backlog search bar.

- Upload a Pleteo export (CSV or XLSX).
- Select the ID column (auto-detects 'External Case ID').
- Set chunk size (default 100 — QuickSuite limit).
- Each string is comma-separated with no spaces.
- Use the native copy button (top-right of each code block) to paste directly.

10. Persistent Delivery History

Confirmed Prebatch deliveries are stored in `batch_history.json` in the GitHub repo and loaded on every app start.

Field	Description
batch_number	Sequential per region — MCC and CS count independently
delivery_date	YYYY-MM-DD
region	MCC or CS
profile	Profile name · batch type label (or 'Full Prebatch' if no distribution was applied)
total_cases	Cases in the confirmed Prebatch
cases	List of [Case ID, Entity Name] pairs

The Validate Batch button cross-checks current Case IDs against history. Repeat IDs trigger a warning but do not block generation — cases may be relaunched.

11. GitHub Setup & Configuration

11.1 Required Streamlit Secrets

Go to share.streamlit.io → your app → ■ → Settings → Secrets tab and paste:

```
GITHUB_TOKEN = "ghp_yourTokenHere" GITHUB_REPO = "YourUsername/your-repo-name" HISTORY_FILE_PATH = "batch_history.json" GITHUB_BRANCH = "main"
```

GITHUB_REPO must be owner/repo-name. Example: URL is

github.com/Jesus-Ameneiro/prebatch-delivery → use Jesus-Ameneiro/prebatch-delivery.

GITHUB_TOKEN must have the repo scope. Never commit the token to the repository.

11.2 Connection Diagnostics

If the top banner shows a warning or Confirm Delivery fails, a diagnostic panel runs 5 checks automatically:

Check	Common fix
Token configured	Regenerate with repo scope, update secret
Repo format (owner/repo)	Add the owner prefix before the slash
Repo accessible	Check spelling; confirm token has repo access
Branch matches default	Update GITHUB_BRANCH to match the repo's actual default branch
History file path	Created automatically on first confirmed delivery

12. Repository Files

File	Purpose	Commit?
app.py	Main Streamlit application	Yes
requirements.txt	Python dependencies	Yes
logo.png	Ruvixx logo	Yes
DOCUMENTATION.pdf	This reference guide	Yes
batch_history.json	Persistent delivery history (auto-created by app)	Yes — created by app
.streamlit/secrets.toml	Local dev secrets only — never commit	No — add to .gitignore

13. Troubleshooting

Issue	Cause	Fix
File validation ✖	Wrong file in slot or renamed columns	Check Section 3 column names
Generate disabled	Validate Batch not yet run	Click Validate Batch first
Empty Entity Name	CC Pleteo Entity Name and QS Company Name both empty	Check source files
Distribution produces 0 cases	Country values don't match group names	Check Countries/Country column in output
Output = all cases, no filtering	ep (profile) is None — no default loaded	Ensure region has at least one saved profile
Golden batch <3 warning	Insufficient 3+ cases to fill total quota	Expected — overflow used. Review backlog.
GitHub HTTP 404	GITHUB_REPO missing owner prefix or wrong branch	Use owner/repo format; check GITHUB_BRANCH

GitHub HTTP 401	Token expired or missing repo scope	Regenerate token with repo scope
History not loading	Secrets not saved or app not rebooted	Verify secrets in Streamlit Cloud, reboot

Last updated: May 2026 · Prebatch Generator v1.4