
Prebatch / Precheck File Generator Reference Guide

Version: 1.2 | Maintained by: Ruvixx — Case Investigation Operations | Regions: MCC · CS

This guide covers all features of the Prebatch Generator app: file processing, pre-validation, batch distribution, delivery confirmation, persistent history, and the Delivery ID string generator.

1. Purpose

The Prebatch Generator automates the creation of the Prebatch/Precheck file for Trimble SketchUp License Compliance operations. It replaces manual cross-referencing of three source files with a single upload-and-generate step, and includes tools for batch validation, country-based distribution, delivery confirmation, and persistent history.

2. App Layout

Area	Contents
Top banner	GitHub history load status (green = connected, orange = error)
Sidebar	Logo · Documentation button · Delivery History · Session Log
Region toggle	Switch between MCC and CS — changes column structure and country lists
File uploaders	Three slots: QS Delivery ID · PL Batch · Conflict Check
Batch Distribution	Optional pre-generation configuration for country/quota-based selection
ID String Generator	Standalone tool to produce QuickSuite Delivery ID search strings
Processing area	Validate Batch · Generate Prebatch File buttons
Results area	Metrics · Preview · Download · Distribution results · Confirm Delivery

3. Input Files

3.1 QS Delivery ID File

Role: Master list, entity grouping, aggregated machine counts and event dates.

Column	Maps To	Notes
Case ID	Case ID	Join key. May be comma-separated for grouped entities.
Case Tier	Case Tier	1, 2, or 3
[Cfa]-Category	Case Category	Numeric category
[Cfa]-ActionableCategory	Actionable Category	Numeric actionable classification
Total Machines	# All Time Machines	Pre-aggregated for grouped entities
Actionable Machines	# Actionable Machines	
[Cfa]-Difference	# Difference	Total minus actionable
Approved Machines	Actionable Machine IDs	
First Event	First Event	Normalized to YYYY-MM-DD HH:MM:SS
Last Event	Last Event	Normalized to YYYY-MM-DD HH:MM:SS

3.2 PL Batch File (Pleteo Export)

Role: CRM timestamps — Last Updated At (MCC only).

Column	Maps To	Notes
External Case ID	(join key)	Matches QS Case ID
Updated	Last Updated At	MCC only. Latest across grouped cases.

3.3 Conflict Check File

Role: Investigation content, entity details, geographic attribution, multinational flag, generic emails.

Column	Maps To	Notes
Case ID	(join key)	
Is Multi National	Is Multi-National	Auto-populated
Machine Overview	Machine Overview	Combined for grouped cases
Investigation Notes	Investigation Notes	Concatenated for grouped cases
Pleteo Entity Name	Entity Name	Falls back to QS Company Name if empty
Company Name	Company Name	
Cylynt Organization Name	Cylynt Organization Name	
Industry	Industry	
Address	Address / Addresses	MCC=Address, CS=Addresses
Countries	Countries / Country	MCC=Countries, CS=Country
Time Span	Time Span	e.g. '5 years 6 months'
Generic Email Addresses	Generic Email Address	Auto-populated
Actionable Domains	Actionable Domains	Primary; QS as fallback

Website	Website	Primary; QS as fallback
---------	---------	-------------------------

4. File Pre-Validation

As soon as any file is uploaded, a validation panel appears showing ✓ or ✗ per file. The Generate button is disabled until all three files pass validation.

File	Required Columns
QS Delivery ID	Case ID, Case Tier, Total Machines, Actionable Machines, Approved Machines, First Event, Last Event
PL Batch	External Case ID, Updated
Conflict Check	Case ID, Machine Overview, Investigation Notes, Pleteo Entity Name, Company Name, Actionable Domains

If a file is uploaded in the wrong slot (e.g. Conflict Check placed in the QS slot), validation will fail and show the specific missing column names.

5. Processing Flow

The generation follows a strict sequence to ensure data integrity:

Step 1 — Validate Batch

Click **Validate Batch** to check all Case IDs in the QS file against the persistent delivery history. The result is one of two messages:

- **■ No repeated Case IDs** — all cases are new to the history, safe to proceed.
- **■■ Repeated Case IDs detected** — lists each repeated ID with the batch number and date it was previously delivered. This is a warning only, not a block. Cases may be relaunched or recontacts.

Validation must be run at least once before Generate becomes available. It resets automatically when the region or files change.

Step 2 — Generate Prebatch File

Available only after validation. The app merges the three files, applies deduplication, normalizes dates, and if Batch Distribution is enabled, applies the distribution automatically in the same step.

- **Deduplication:** If the same Case ID appears more than once in the QS file, only the first occurrence is kept. A 'Duplicates Removed' metric shows the count.
- **Date normalization:** First Event, Last Event, and Last Updated At are all converted to YYYY-MM-DD HH:MM:SS format regardless of input format.
- **Grouped entities:** Comma-separated Case IDs are handled — Machine Overviews are combined (deduplicated) and Investigation Notes are concatenated.

Step 3 — Download

After generation, the full Prebatch output is available for download as Prebatch_MCC.xlsx or Prebatch_CS.xlsx. If batch distribution was applied, the distributed file is also available.

Step 4 — Confirm Batch Delivery

After downloading, a Confirm Batch Delivery section appears. Fill in:

- **Delivery Date:** defaults to today.
- **Batch Number:** pre-filled with the last confirmed batch number + 1 (per region). MCC and CS maintain separate sequential counters.

Clicking **Confirm Batch Delivery** registers the batch in the persistent history and immediately pushes it to the GitHub repository. If a batch distribution was applied, only the distributed cases are confirmed; otherwise the full Prebatch is

confirmed.

6. Output File — Column Structure

6.1 MCC Output (27 columns)

#	Column	Source	Status
1	Date Added to This Sheet	—	Blank — manual entry
2	Is Multi-National	Conflict Check	Auto-populated
3	Machine Overview	Conflict Check	Auto-populated
4	Investigation Notes	Conflict Check	Auto-populated
5	Case ID	QS Delivery ID	Auto-populated
6	Company Name	Conflict Check	Auto-populated
7	Entity Name	CC Pleteo Entity Name / QS fallback	Auto-populated
8	Cylynt Organization Name	Conflict Check	Auto-populated
9	Industry	Conflict Check	Auto-populated
10	Address	Conflict Check	Auto-populated
11	Countries	Conflict Check	Auto-populated
12	Estimated Case Value	—	Blank — manual entry
13	Case Tier	QS Delivery ID	Auto-populated
14	Case Category	QS [Cfa]-Category	Auto-populated
15	Actionable Category	QS [Cfa]-ActionableCategory	Auto-populated
16	# All Time Machines	QS Total Machines	Auto-populated
17	# Actionable Machines	QS Actionable Machines	Auto-populated
18	# Difference	QS [Cfa]-Difference	Auto-populated
19	Actionable Machine IDs	QS Approved Machines	Auto-populated
20	First Event	QS Delivery ID	YYYY-MM-DD HH:MM:SS
21	Last Event	QS Delivery ID	YYYY-MM-DD HH:MM:SS
22	Time Span	Conflict Check	Auto-populated
23	Generic Email Address	CC Generic Email Addresses	Auto-populated
24	Actionable Domains	CC primary / QS fallback	Auto-populated
25	Website	CC primary / QS fallback	Auto-populated
26	Last Updated At	PL Batch (Updated)	YYYY-MM-DD HH:MM:SS
27	NNS License Count	—	Blank — manual entry

6.2 CS Output (24 columns)

Same structure as MCC with three differences: **Address** → **Addresses**, **Countries** → **Country**, and columns **Estimated Case Value**, **Last Updated At**, and **NNS License Count** are not included.

7. Batch Distribution

An optional tool to automatically distribute large Pleteo exports by country group and quota without manually selecting cases. Enable it before generating if working with a large batch that hasn't been pre-curved. If cases were already manually selected for delivery, skip this section.

7.1 Enabling

Toggle **Enable Batch Distribution** before clicking Generate. The distribution is applied automatically as part of the generation step.

7.2 Priority Toggle

- **ON (default):** Within each group, cases with Total Machines ≥ 3 from the Pleteo export fill the quota first. Remaining slots are filled with <3 machine cases.
- **OFF:** Fill each group's quota purely by country availability — no machine count ordering applied.

7.3 Distribution Profiles

Each region has its own set of profiles. The default profiles match the standard weekly distribution:

Region	Group	Countries	Default Quota
MCC	Mexico	Mexico	40
MCC	Panama · CR · DR	Panama, Costa Rica, Dominican Republic	40
MCC	Central America	Honduras, Belize, Guatemala, Nicaragua, El Salvador	40
CS	Chile	Chile	20
CS	Argentina	Argentina	25
CS	Colombia · Ecuador	Colombia, Ecuador	35
CS	Peru	Peru	10
CS	South Cone	Uruguay, Bolivia, Paraguay	20

7.4 Group Editing Rules

- Countries already assigned to one group are hidden from all other group dropdowns.
- A group can contain any combination of countries valid for that region.
- Quotas are per-group totals — not per individual country within the group.
- If a group's quota cannot be met from its own pool, the shortfall is filled from other groups' unused cases with a warning.

7.5 Profile Management

Action	How
Update existing profile	Edit groups/quotas in Edit Profile, click Update Profile
Save as new profile	Enter a new name in the Save as New field, click Save as New
Set default profile	Select profile from dropdown, click Set as Default
Delete a profile	Select profile, click  Delete (disabled if only one exists)

Export all profiles	Import/Export expander → Export All Profiles as JSON
Import profiles	Import/Export expander → upload a profiles JSON file

Profiles are stored in session memory. Export as JSON to save them across sessions.

7.6 Backlog Report

After distribution, a Backlog Report shows all cases not selected, broken down by country with columns: Total Backlog · 3+ Machines (Priority) · <3 Machines. Downloadable as a separate Excel file for planning the next batch.

8. Delivery ID Search String Generator

A standalone tool (collapsible, before the processing area) that generates External Case ID search strings for the QuickSuite SKU Case Delivery Backlog dashboard's Delivery ID Search bar.

How to use:

- Upload a Pleteo export file (CSV or XLSX).
- Select the column containing the External Case IDs (auto-detects 'External Case ID').
- Set the chunk size (default 100 — QuickSuite search bar limit).
- The tool produces one or more comma-separated strings, each with no spaces.
- Use the native **copy button** (clipboard icon, top-right of each code block) to copy directly into the QuickSuite search bar.

Example output for 248 IDs with chunk size 100:

```
String 1 of 3 (100 IDs): 1234567#1,2345678#1,...
String 2 of 3 (100 IDs): 3456789#1,...
String 3 of 3 (48 IDs): 4567890#1,...
```

9. Persistent Delivery History

Confirmed batch deliveries are stored permanently in a file called `batch_history.json` in the GitHub repository. The history is loaded automatically every time the app starts.

9.1 What is stored per batch

Field	Description
batch_number	Sequential number assigned by the user at confirmation time
delivery_date	Date the batch was confirmed (YYYY-MM-DD)
region	MCC or CS
profile	Distribution profile used, or 'Full Prebatch (no distribution applied)'
total_cases	Number of cases in the confirmed batch
cases	List of [Case ID, Entity Name] pairs

9.2 MCC and CS are stored separately

Batch numbers are sequential per region. MCC and CS each maintain their own independent counter. The suggested batch number shown at confirmation is always the highest existing number for that region + 1.

9.3 Viewing history

The sidebar Delivery History section shows the last 5 confirmed batches per region, each expandable to display the full case ID / entity name table.

9.4 Batch validation against history

The Validate Batch button checks every Case ID in the current QS file against all previously confirmed batches. Matches are reported as warnings (not blocks), since cases may be legitimately relaunched or recontacted.

10. GitHub Setup & Configuration

The app uses GitHub to persist the batch history file across sessions. This requires a Personal Access Token and four Streamlit secrets.

10.1 Create a GitHub Personal Access Token

1. Go to github.com → Profile photo → Settings
2. Left sidebar → Developer settings → Personal access tokens → Tokens (classic)
3. Click Generate new token (classic)
4. Set Note, Expiration, and check the repo scope
5. Click Generate token — copy it immediately (shown once only)

10.2 Configure Streamlit Secrets

Go to share.streamlit.io → your app → ■ → Settings → Secrets tab. Paste the following block:

```
GITHUB_TOKEN = "ghp_yourTokenHere" GITHUB_REPO = "YourUsername/your-repo-name" HISTORY_FILE_PATH = "batch_history.json" GITHUB_BRANCH = "main"
```

GITHUB_REPO must be in owner/repo-name format exactly as it appears in the GitHub URL. For example, if the URL is github.com/Jesus-Ameneiro/prebatch-delivery then use Jesus-Ameneiro/prebatch-delivery.

GITHUB_BRANCH must match your repo's actual default branch. Check the repo page — it shows the current branch name next to the file list.

10.3 Diagnosing Connection Problems

If the top banner shows a warning, or Confirm Batch Delivery fails, an automatic diagnostic panel runs 5 checks:

Check	What it validates	Common fix
Token configured	GITHUB_TOKEN is present and non-empty	Regenerate token, update secret
Repo format	Value contains exactly one slash (owner/repo)	Add the owner prefix
Repo accessible	Calls GitHub API to verify repo exists and token works	Check spelling; ensure token has repo scope
Branch matches default	Compares GITHUB_BRANCH vs repo's actual default branch	Update GITHUB_BRANCH to match
File path	Shows the path that will be used	Usually batch_history.json at root

The history file is created automatically on first confirmed delivery — you do not need to create it manually in the repository.

11. Repository Files

File	Purpose	Commit to repo?
app.py	Main Streamlit application	Yes
requirements.txt	Python dependencies	Yes
logo.png	Ruvixx logo for header and sidebar	Yes
DOCUMENTATION.pdf	This reference guide	Yes
batch_history.json	Persistent delivery history (auto-created on first confirm)	Yes — created by app

.streamlit/secrets.toml	Local secrets for development only	No — add to .gitignore
-------------------------	------------------------------------	------------------------

12. Troubleshooting

Issue	Cause	Fix
File validation ✖	Wrong file in wrong slot or renamed columns	Check column names match Section 3
Generate button disabled	Validate Batch not yet run	Click Validate Batch first
Empty Entity Name	CC Pleteo Entity Name empty and QS Company Name also empty	Check QS/CC files
Dates not normalized	Unrecognized date format in source	Value kept as-is; check source file format
Distribution produces empty groups	Country column doesn't match group country names	Check Countries/Country column values in output
GitHub HTTP 404 on confirm	GITHUB_REPO missing owner prefix	Use format owner/repo-name
GitHub HTTP 401 on confirm	Token expired or wrong scope	Regenerate token with repo scope
History not loading on startup	Secrets not saved or app not rebooted	Verify Streamlit secrets and reboot app

Last updated: May 2026 · Prebatch Generator v1.2