

Guia de Comandos Bandit

Level 0:

- `ssh bandit0@bandit.labs.overthewire.org -p 2220`

Level 0→1:

- `cat readme`
- Level 1→2:
- `cat ./-`
- `cat < -`

Level 2→3:

- `cat "spaces in this filename"`
- `cat spaces\ in\ this\ filename`

Level 3→4:

- `cd inhere`
- `ls -la`
- `cat .hidden`

Level 4→5:

- `file inhere/-file0*`
- `cat inhere/-file07`

Level 5→6:

- `find inhere/ -type f -size 1033c ! -executable`
- `cat inhere/maybehere07/.file2`

Level 6→7:

- `find / -user bandit7 -group bandit6 -size 33c 2>/dev/null`
- `cat /var/lib/dpkg/info/bandit7.password`

Level 7→8:

- `grep millionth data.txt`

Level 8→9:

- `sort data.txt | uniq -u`

Level 9→10:

- `strings data.txt | grep '=='`

Level 10→11:

- `base64 -d data.txt`

Level 11→12:

- `cat data.txt | tr 'A-Za-z' 'N-ZA-Mn-za-m'`

Level 12→13:

- `mkdir /tmp/bandit12 && cp data.txt /tmp/bandit12 && cd /tmp/bandit12`
- `xxd -r data.txt > data.bin`
- `file data.bin`
- `mv data.bin data.gz && gzip -d data.gz`
- `file data`
- `mv data data.bz2 && bzip2 -d data.bz2`
- `mv data data.tar && tar xf data.tar`
- `cat data8.bin`

Level 13→14:

- `ssh -i sshkey.private bandit14@localhost -p 2220`
- `cat /etc/bandit_pass/bandit14`

Level 14→15:

- `echo 'CONTRASEÑA' | nc localhost 30000`

Level 15→16:

- `echo 'CONTRASEÑA' | openssl s_client -connect localhost:30001 -quiet`

Level 16→17:

- `nmap -p 31000-32000 localhost`
- `echo 'CONTRASEÑA' | openssl s_client -connect localhost:31790 -quiet`

Level 17→18:

- `diff passwords.old passwords.new`

Level 18→19:

- `ssh bandit18@bandit.labs.overthewire.org -p 2220 'cat ~/readme'`

Level 19→20:

- `ls -la`
- `./bandit20-do cat /etc/bandit_pass/bandit20`

Level 20→21:

- `echo 'CONTRASEÑA' | nc -l -p 5555 &`
- `./suconnect 5555`

Level 21→22:

- `ls /etc/cron.d/`
- `cat /etc/cron.d/cronjob_bandit22`
- `cat /usr/bin/cronjob_bandit22.sh`
- `cat /tmp/t7O6lds9S0RqQh9aMcz6ShpAoZKF7fgv`

Level 22→23:

- `cat /etc/cron.d/cronjob_bandit23`
- `cat /usr/bin/cronjob_bandit23.sh`
- `echo I am user bandit23 | md5sum | cut -d ' ' -f 1`
- `cat /tmp/<hash_resultante>`

Level 23→24:

- `mkdir /tmp/b24`
- `cat > /tmp/b24/getpass.sh << 'EOF'`
- `#!/bin/bash`
- `cat /etc/bandit_pass/bandit24 > /tmp/b24/pass.txt`
- `EOF`
- `chmod 777 /tmp/b24 && chmod +x /tmp/b24/getpass.sh`
- `cp /tmp/b24/getpass.sh /var/spool/bandit24/foo/`
- `cat /tmp/b24/pass.txt`

Level 24→25:

- `for i in $(seq -w 0 9999); do echo 'CONTRASEÑA '$i; done | nc localhost 30002 | grep -v Wrong`

Level 25→26:

- `ssh -i bandit26.sshkey bandit26@localhost -p 2220`
- `v` (dentro de more, abre vim)
- `:set shell=/bin/bash` (en vim)
- `:shell` (en vim)

Level 26→27:

- `./bandit27-do cat /etc/bandit_pass/bandit27`

Level 27→28:

- `mkdir /tmp/b27 && cd /tmp/b27`
- `git clone ssh://bandit27-git@localhost:2220/home/bandit27-git/repo`
- `cat repo/README`

Level 28→29:

- `mkdir /tmp/b28 && cd /tmp/b28`
- `git clone ssh://bandit28-git@localhost:2220/home/bandit28-git/repo`
- `cd repo && git log --oneline`

- git show HEAD~1

Level 29→30:

- mkdir /tmp/b29 && cd /tmp/b29
- git clone ssh://bandit29-git@localhost:2220/home/bandit29-git/repo
- cd repo && git branch -a
- git checkout origin/dev
- cat README.md

Level 30→31:

- mkdir /tmp/b30 && cd /tmp/b30
- git clone ssh://bandit30-git@localhost:2220/home/bandit30-git/repo
- cd repo && git tag
- git show secret

Level 31→32:

- mkdir /tmp/b31 && cd /tmp/b31
- git clone ssh://bandit31-git@localhost:2220/home/bandit31-git/repo
- cd repo && echo 'May I come in?' > key.txt
- git add -f key.txt
- git commit -m 'add key'
- git push

Level 32→33:

- \$0
- cat /etc/bandit_pass/bandit33

Level 33→34:

- cat README.txt

Alumno: Jesús Julián García Jiménez