Page 2

LCD Expansion Connector

Page 3

Sequence Control, Config Memory and Touch Interface

Page 4

Backlight voltage generation

Page 5

3.5 inch display

Page 6

4.3 inch displays

Page 7

7 inch displays

LCD Expansion Connector

3.5 inch 320x240 pixel LCD

Configuration
E2PROM

4.3 inch 480x272 pixel LCD

Sequence Control and Backlight Dimming

7 inch 800x480 pixel LCD

Voltage Switches for +3.3V and +5V

Touch screen interface

Rev PB1

Added 7 inch LCD (UMSH-8173MD-8T). R44 changed to 0R. Added D5, R82 and SJ2 - SJ6. Added second backlight voltage generator (U8). Changed U1 to 33.333MHz.

Rev A

Added reset control for 3.5 inch LCD.



(C) Embedded Artists AB

TITLE: LCD Board rev PB1

Document Number:


Date: 2011-08-07 12:06:01 Sheet: 1/7


UL = UnLoaded = normally not mounted component.

Default jumper settings are indicated in the schematic. However, always check jumper positions on actual boards since there is no guarantee that all jumpers are in default place.

LCD Expansion Connector


LCD Expansion Connector









Sheet: 2/7






Date: 2011-08-07 12:06:01



Backlight voltage generation





(C) Embedded Artists AB

TITLE: LCD Board rev PB1


Document Number:


Date: 2011-08-07 12:06:01

Sheet: 4/7

3.5"320x240 pixel LCD


Model: UMSH-8252MD-1T from U.R.T.





4.3"480x272 pixel LCD

Model: HSD043I9W1-A00-0299 from HannStar Also compatible with model: A043FW02 V3 from AUO






Document Number:

Date: 2011-08-07 12:06:01 Sheet: 6/7

7" 800x480 pixel LCD

Model: AT070TN84 from INNOLUX



Model: UMSH-8173MD-8T from U.R.T.

