

Gaussian Process for the estimation of theory uncertainties

Jesús Urtasun Elizari

Italian Physical Society - Milan, September 2020



UNIVERSITÀ
DEGLI STUDI
DI MILANO



European
Research
Council

This project has received funding from the European Union's Horizon 2020 research and innovation program under grant agreement No 740006.

Outline

① QCD in a nutshell

- The Standard Model of particle physics
- LHC physics and theory uncertainties
- Factorization theorem

② Machine Learning


- Motivation for Machine Learning
- Neural Networks & general strategy

③ Gaussian Process and theory uncertainties

- The N3PDF project
- Kernel based methods
- Results & Conclusions

QCD in a nutshell

The Standard Model



Quantum Field Theory describing physics at the TeV scale


- Fermions composing matter (leptons and quarks)
- Bosons as mediators of the interactions
- Scalar Higgs generating mass

QCD in a nutshell

LHC physics

Standard Model Production Cross Section Measurements

Status: July 2018



QCD in a nutshell

Explore the strong interactions

How to explore proton's inner structure?




- Point-like projectile on the object \rightarrow DIS
- Smash the two objects \rightarrow LHC physics

"A way to analyze high energy collisions is to consider any hadron as a composition of point-like constituents \rightarrow **partons**" R.Feynman, 1969

QCD in a nutshell

Factorization theorem



Compute cross sections is a **hard problem** \rightarrow **QCD Factorization**

$$\sigma^F(p_1, p_2) = \int_0^1 dx_1 dx_2 f_\alpha(x_1, \mu_F^2) * f_\beta(x_2, \mu_F^2) * \hat{\sigma}_{\alpha\beta}^F(x_1 p_1, x_2 p_2, \alpha_s(\mu_R^2), \mu_F^2)$$

Machine learning

What is Machine Learning?

- 1 A subset of Artificial Intelligence (AI) algorithms
- 2 Used to solve *complex* tasks like classification and regression
- 3 Rely on comparison with data → **Learning** through minimization of some loss function






The N3PDF project

Machine Learning for subnuclear structure

- 1 Take the asymptotics of $\hat{\sigma}(N)$ computed by following [1303.3590](#) as input (training) data.
- 2 Assume the points are sampled from a Gaussian distribution $f(x) \sim N(\mu, K(\Theta, x, x'))$.
- 3 Train Θ by minimizing a $\chi^2(f(x)|\Theta, x)$ to guess the underlying law through exhaustive search \rightarrow [hyperoptimization](#)
- 4 Use the Mellin-space exact coefficient functions computed by [ggHiggs](#) as true values for testing and validation.

Results

Learning a physical quantity



- Combination of different kernels leads to better fit
- Excellent numerical agreement up to N3LO

When there is not theory prediction to compare to, use GP approach to estimate theory uncertainty

Summary & Conclusions

- ① Precise predictions are required towards precision era of the LHC
- ② ML provides an effective way of fitting a curve
- ③ Kernel-based methods particularly powerful for interpolation
- ④ Theory uncertainty can be extracted from the confidence interval given by the Gaussian Process

This project has received funding from the European Union's Horizon 2020 research and innovation program under grant agreement No 740006.