

S8_CerroNegro_isobar_comparison

March 19, 2021

```
[1]: import sys
      sys.path.append('.././.././../')

      import VESICAL as v
      import numpy as np
      import scipy
      import pandas as pd
      import matplotlib.pyplot as plt
```

```
[2]: #Import the data
      basalts = v.BatchFile("../././Datasets/cerro_negro.xlsx")

      #Calculate the average composition of the entire dataset
      columns = list(basalts.get_data())
      avg_vals = []
      for col in columns:
          try:
              avg_vals.append(basalts.data[col].mean())
          except:
              avg_vals.append("AVG")

      avg_dict = dict(zip(columns, avg_vals))
      avg_dict = v.get_oxides(avg_dict)
```

```
[3]: #Calculate isobars for all samples at 3,000 bars
      isobar_list = []
      for index, row in basalts.get_data().iterrows():
          isobar_list.append(v.calculate_isobars_and_isopleths(sample=basalts.
      ↪get_sample_composition(samplename=row.name, asSampleClass=True),
      ↪temperature=1200, pressure_list=[3000], isopleth_list=[0.5],
      ↪print_status=True).result[0])
```

Calculating isobar at 3000 bars
done.

Done!

Calculating isobar at 3000 bars
done.


Done!


```
Calculating isobar at 3000 bars
done.
Done!
Calculating isobar at 3000 bars
done.
Done!
Calculating isobar at 3000 bars
done.
Done!
Calculating isobar at 3000 bars
done.
Done!
Calculating isobar at 3000 bars
done.
Done!
Calculating isobar at 3000 bars
done.
Done!
```

```
[5]: #Calculate isobar at 3,000 bars for "Average Sample"
avg_isobar = v.calculate_isobars_and_isopleths(sample=v.Sample(avg_dict),
    ↳temperature=1200, pressure_list=[3000], isopleth_list=[0.5],
    ↳print_status=True).result[0]
```

```
Calculating isobar at 3000 bars
done.
Done!
```

```
[6]: #Plot all isobars from dataset
fig, ax = v.plot(isobars=[isobar for isobar in isobar_list], isobar_labels=[row.
    ↳name for index, row in basalts.get_data().iterrows()])
v.show()
```



```
[7]: #calculate area under each curve for dataset and "Average Sample"
areas = []
samples = [row.name for index, row in basalts.get_data().iterrows()]
for isobar in isobar_list:
    x_vals = np.array([row["H2O_liq"] for index, row in isobar.iterrows()])
    y_vals = np.array([row["CO2_liq"] for index, row in isobar.iterrows()])
    area_under_the_curve = scipy.integrate.simps(y_vals, x_vals)
    areas.append(area_under_the_curve)

average_area = scipy.integrate.simps(avg_isobar['CO2_liq'],
    ↪ avg_isobar['H2O_liq'])
```

```
[8]: #Get maximum and minimum areas from dataset, with corresponding sample names
area_dict = dict(zip(samples, areas))
max_sample = max(area_dict, key=area_dict.get)
min_sample = min(area_dict, key=area_dict.get)
print("ISM values for entire dataset: \n" + str(area_dict) + "\n")
print("'Average Sample' ISM = " + str(average_area))
```

ISM values for entire dataset:

```
{'10*': 0.7022828487675895, '19*': 0.7099131142452471, '25': 0.6857308764836786,
'29*': 0.6959245973174225, '31': 0.6857679600090202, '32a*': 0.6981011318157468,
'33*': 0.6794449586415775, '35*': 0.6983522136970503, '36a*':
0.6737990590298144, '36b': 0.700302027451814, '36c': 0.6967336243144274,
'39ab*': 0.7498555237770486, '39b*': 0.7254223767902859, '41ab*':
0.7551957184715765, '41b*': 0.823496578531669, '41c': 0.7722064502996333, '41d':
0.7707799763517975, '41e': 0.7414493381948651, '45*': 0.6989410687176959, '51':
```

```
0.68721735630067, '59a*': 0.739335114894365, '59b*': 0.7091202270350897, '65':  
0.7108222436239792, '66*': 0.7105778333531161}
```

```
'Average Sample' ISM = 0.7160086630830478
```

```
[9]: #Now, calculate isobars for the max and min samples at multiple pressures  
max_isobars, max_isopleths = v.calculate_isobars_and_isopleths(sample=basalts.  
    ↳get_sample_composition(max_sample, asSampleClass=True), temperature=1200,␣  
    ↳pressure_list=[500, 1000, 2000, 3000, 4000], isopleth_list=[0.5],␣  
    ↳print_status=True).result  
min_isobars, min_isopleths = v.calculate_isobars_and_isopleths(sample=basalts.  
    ↳get_sample_composition(min_sample, asSampleClass=True), temperature=1200,␣  
    ↳pressure_list=[500, 1000, 2000, 3000, 4000], isopleth_list=[0.5],␣  
    ↳print_status=True).result  
  
#Calculate isobars for the average composition  
avg_isobars, avg_isopleths = v.calculate_isobars_and_isopleths(sample=v.  
    ↳Sample(avg_dict), temperature=1200, pressure_list=[500, 1000, 2000, 3000,␣  
    ↳4000], isopleth_list=[0.5], print_status=True).result
```

```
Calculating isobar at 500 bars  
done.
```

```
Calculating isobar at 1000 bars  
done.
```

```
Calculating isobar at 2000 bars  
done.
```

```
Calculating isobar at 3000 bars  
done.
```

```
Calculating isobar at 4000 bars  
done.
```

```
Done!
```

```
Calculating isobar at 500 bars  
done.
```

```
Calculating isobar at 1000 bars  
done.
```

```
Calculating isobar at 2000 bars  
done.
```

```
Calculating isobar at 3000 bars  
done.
```

```
Calculating isobar at 4000 bars  
done.
```

```
Done!
```

```
Calculating isobar at 500 bars  
done.
```

```
Calculating isobar at 1000 bars  
done.
```

```
Calculating isobar at 2000 bars  
done.
```

```
Calculating isobar at 3000 bars
done.
Calculating isobar at 4000 bars
done.
Done!
```

```
[10]: #Make dataset with all data except for max and min values
other_data = basalts.get_data().drop([max_sample, min_sample])
```

```
[13]: #set up what to pass to v.plot
isobars = [max_isobars,
           min_isobars,
           avg_isobars]

isobar_labels = ["Max",
                 "Min",
                 "Avg"]

custom_H2O=[basalts.get_sample_composition(max_sample)["H2O"],
            basalts.get_sample_composition(min_sample)["H2O"],
            avg_dict["H2O"],
            other_data["H2O"]]

custom_CO2=[basalts.get_sample_composition(max_sample)["CO2"],
            basalts.get_sample_composition(min_sample)["CO2"],
            avg_dict["CO2"],
            other_data["CO2"]]

custom_labels = [str(max_sample) + " (max)",
                 str(min_sample) + " (min)",
                 "Average Sample",
                 "Cerro Negro MI"]


custom_colors = [v.vplot.color_list[0],
                 v.vplot.color_list[1],
                 v.vplot.color_list[2],
                 'silver']

custom_symbols = ['o',
                  'o',
                  'o',
                  'd']

fig, ax = v.plot(isobars=isobars, isobar_labels=isobar_labels,
                 custom_H2O=custom_H2O,
                 custom_CO2=custom_CO2,
                 custom_labels=custom_labels,
```

```
custom_colors=custom_colors,
custom_symbols=custom_symbols)
```

```
v.show()
```



```
[14]: pressure_vals = [500, 1000, 2000, 3000, 4000]

max_IMS_dict = {}
min_IMS_dict = {}
avg_IMS_dict = {}

IMS_dicts = [max_IMS_dict,
              min_IMS_dict,
              avg_IMS_dict]

for i in range(len(isobars)):
    IMS_dicts[i].update({"Pressure": pressure_vals})
    IMS_list = []
    for pressure in pressure_vals:
        IMS_list.append(scipy.integrate.simps(isobars[i].
        ↳loc[isobars[i]['Pressure']==pressure]["CO2_liq"], isobars[i].
        ↳loc[isobars[i]['Pressure']==pressure]["H2O_liq"])))
    IMS_dicts[i].update({"IMS": IMS_list})

labels = ["Maximum, Minimum, Average"]

fig, ax = plt.subplots(1, figsize = (8,5))

for i in range(len(IMS_dicts)):
```

```


    ax.plot(IMS_dicts[i]["Pressure"], IMS_dicts[i]["IMS"],
            label=custom_labels[i])
    ax.set_xlabel("Pressure bars")
    ax.set_ylabel("IMS value")

    ax.legend(bbox_to_anchor=(0., 1.02, 1., .102), loc='lower right',
              ncol=2, borderaxespad=0.)

    #fig.savefig('Cerro_Negro_img3.pdf')

```

[14]: <matplotlib.legend.Legend at 0x7fb6a9bd9f50>



[15]: max_IMS_dict

```

[15]: {'Pressure': [500, 1000, 2000, 3000, 4000],
      'IMS': [0.03964674041589094,
              0.12230513394511863,
              0.40131268243443224,
              0.823496578531669,
              1.4033483467221493]}

```



```

[16]: other_oxides = ["Al2O3", "FeO", "MgO", "CaO", "Na2O", "K2O"]
my_samples = [basalts.get_sample_composition(max_sample),
               basalts.get_sample_composition(min_sample),
               avg_dict,
               other_data]

fig, axs = plt.subplots(3,2, figsize = (15,15))
print(len(axs))

for j in range(len(my_samples)):
    axs[0][0].scatter(my_samples[j]["SiO2"], my_samples[j]["Al2O3"],
    ↪marker=custom_symbols[j], s=70, color=custom_colors[j],
    ↪label=custom_labels[j])
    axs[0][0].set_ylabel("Al$_2$O$_3$")
    axs[0][1].scatter(my_samples[j]["SiO2"], my_samples[j]["FeO"],
    ↪marker=custom_symbols[j], s=70, color=custom_colors[j],
    ↪label=custom_labels[j])
    axs[0][1].set_ylabel("FeO")
    axs[1][0].scatter(my_samples[j]["SiO2"], my_samples[j]["MgO"],
    ↪marker=custom_symbols[j], s=70, color=custom_colors[j],
    ↪label=custom_labels[j])
    axs[1][0].set_ylabel("MgO")
    axs[1][1].scatter(my_samples[j]["SiO2"], my_samples[j]["CaO"],
    ↪marker=custom_symbols[j], s=70, color=custom_colors[j],
    ↪label=custom_labels[j])
    axs[1][1].set_ylabel("CaO")
    axs[2][0].scatter(my_samples[j]["SiO2"], my_samples[j]["Na2O"],
    ↪marker=custom_symbols[j], s=70, color=custom_colors[j],
    ↪label=custom_labels[j])
    axs[2][0].set_ylabel("Na$_2$O")
    axs[2][0].set_xlabel("SiO$_2$")
    axs[2][1].scatter(my_samples[j]["SiO2"], my_samples[j]["K2O"],
    ↪marker=custom_symbols[j], s=70, color=custom_colors[j],
    ↪label=custom_labels[j])
    axs[2][1].set_ylabel("K$_2$O")
    axs[2][1].set_xlabel("SiO$_2$")


axs[0][1].legend(bbox_to_anchor=(0., 1.02, 1., .102), loc='lower right',
                 ncol=2, borderaxespad=0.)

#fig.savefig('Cerro_Negro_img4.pdf')

```

3

```
[16]: <matplotlib.legend.Legend at 0x7fb6aa2606d0>
```



1 Alternative plots

```
[18]: #Calculate Saturation Pressure for all samples
other_file = v.BatchFile_from_DataFrame(dataframe=other_data)
satP_other = other_file.calculate_saturation_pressure(temperature=1200)
satP_max = v.calculate_saturation_pressure(sample=basalts.
    ↳get_sample_composition(max_sample, asSampleClass=True), temperature=1200,
    ↳verbose=True).result
satP_min = v.calculate_saturation_pressure(sample=basalts.
    ↳get_sample_composition(min_sample, asSampleClass=True), temperature=1200,
    ↳verbose=True).result
```

```
satP_avg = v.calculate_saturation_pressure(sample=v.Sample(avg_dict),  
↳temperature=1200, verbose=True).result
```

[=====] 100% Working on sample 66*

```
[20]: #Create alternative plots using Matplotliblib
single_data = [satP_max,
               satP_min,
               satP_avg]

single_samples = [basalts.get_sample_composition(max_sample),
                  basalts.get_sample_composition(min_sample),
                  avg_dict]


fig, axs = plt.subplots(3, figsize = (8,15))
axs[0].scatter(satP_other["SaturationP_bars_VESIcal"], satP_other["H2O"],  
↳marker=custom_symbols[3], s=70, color=custom_colors[3],  
↳label=custom_labels[3])
axs[1].scatter(satP_other["SaturationP_bars_VESIcal"], satP_other["CO2"],  
↳marker=custom_symbols[3], s=70, color=custom_colors[3],  
↳label=custom_labels[3])
axs[2].scatter(satP_other["SaturationP_bars_VESIcal"],  
↳satP_other["XH2O_fl_VESIcal"], marker=custom_symbols[3], s=70,  
↳color=custom_colors[3], label=custom_labels[3])

for j in range(len(single_data)):
    axs[0].scatter(single_data[j]["SaturationP_bars"],  
↳single_samples[j]["H2O"], marker=custom_symbols[j], s=70,  
↳color=custom_colors[j], label=custom_labels[j])
    axs[0].set_ylabel("Dissolved H$_2$O wt%")
    axs[0].set_ylim(0)
    axs[0].set_xlim(0)
    axs[1].scatter(single_data[j]["SaturationP_bars"],  
↳single_samples[j]["CO2"], marker=custom_symbols[j], s=70,  
↳color=custom_colors[j], label=custom_labels[j])
    axs[1].set_ylabel("Dissolved CO$_2$ wt%")
    axs[1].set_ylim(0)
    axs[1].set_xlim(0)
    axs[2].scatter(single_data[j]["SaturationP_bars"],  
↳single_data[j]["XH2O_fl"], marker=custom_symbols[j], s=70,  
↳color=custom_colors[j], label=custom_labels[j])
    axs[2].set_ylabel("XH$_2$O$^{fluid}$ (VESIcal)")
    axs[2].set_ylim(0)
    axs[2].set_xlabel("Saturation Pressure, bars (VESIcal)")
    axs[2].set_xlim(0)

axs[0].legend(bbox_to_anchor=(0., 1.02, 1., .102), loc='lower right',
```

```
ncol=2, borderaxespad=0.)  
#fig.savefig('Cerro_Negro_img5.pdf')
```


[20]: <matplotlib.legend.Legend at 0x7fb6aa3bba10>



```
[22]: #Create alternative plots using VESIcal's scatterplot() function
single_samples = [basalts.get_sample_composition(max_sample),
                  basalts.get_sample_composition(min_sample),
                  avg_dict]

v.vplot.scatterplot(custom_x=[satP_max['SaturationP_bars'],
                              satP_min['SaturationP_bars'],
                              satP_avg['SaturationP_bars'],
                              satP_other['SaturationP_bars_VESIcal']],
                  custom_y=[single_samples[0]['H2O'],
                              single_samples[1]['H2O'],
                              single_samples[2]['H2O'],
                              satP_other['H2O']],
                  custom_symbols=custom_symbols,
                  custom_colors=custom_colors,
                  custom_labels=custom_labels,
                  xlabel="Saturation Pressure, bars (VESIcal)",
                  ylabel="Dissolved H2O wt%")
```

[22]: (<Figure size 864x576 with 1 Axes>,
<matplotlib.axes._subplots.AxesSubplot at 0x7fb6aa3cae90>)



2 Calculate saturation pressures for each composition

Here we calculate the saturation pressures of each melt inclusion using: a) the composition of the melt inclusion; b) the composition of the “minimum” melt inclusion (36a); c) *the composition of the “maximum” melt inclusion (41b)*; and d) the composition of the “average” melt inclusion as calculated above.

```
[23]: satP_data_orig = v.BatchFile('cerro_negro_satP_compare.xlsx')
      satP_data_min = v.BatchFile('cerro_negro_satP_compare.xlsx', sheet_name='min')
      satP_data_max = v.BatchFile('cerro_negro_satP_compare.xlsx', sheet_name='max')
      satP_data_avg = v.BatchFile('cerro_negro_satP_compare.xlsx', sheet_name='avg')
```

```
[26]: satP_orig = satP_data_orig.calculate_saturation_pressure(temperature=1200)
      satP_min = satP_data_min.calculate_saturation_pressure(temperature=1200)
      satP_max = satP_data_max.calculate_saturation_pressure(temperature=1200)
      satP_avg = satP_data_avg.calculate_saturation_pressure(temperature=1200)
```

```
[=====] 100% Working on sample 66*
[=====] 100% Working on sample 66*
[=====] 100% Working on sample 66*
[=====] 100% Working on sample 66*
```

```
[27]: fig, ax = v.vplot.scatterplot(custom_x=[satP_orig["SaturationP_bars_VESIcal"],
      ↪satP_orig["SaturationP_bars_VESIcal"],
      ↪satP_orig["SaturationP_bars_VESIcal"]],
      custom_y=[satP_max["SaturationP_bars_VESIcal"],
      ↪satP_min["SaturationP_bars_VESIcal"], satP_avg["SaturationP_bars_VESIcal"]],
      custom_labels=["Max", "Min", "Average"])
      v.show()
```

