

CSE 340

Winter Quarter 2020

1/17/2020

Professor: Dr. Jennifer Mankoff, Lauren Bricker

Note-taker email: jial8@uw.edu

Week 2 Lecture 3

Introduction to Layout

Notes

Badly Designed Website Example


“Responsive” page: page that scales to the user’s screen. Static is the opposite. The website has very small text, clashing colors, and strange grouping of interactors.

Why do we need layout?

- Be able to center something
- Lock it to an edge
- Have a reactive design layout (be able to shrink and expand without looking weird)

Layout 1 - Worksheet: Distributed during class

- **Views:** Base class for all UI elements, interactors
- **ViewGroups:** groups ≥ 1 views, can define specific layout properties
- **Vertical Container Components** (in the example)
 - **Linear layout** (every component on the same line in the tree). Always places its kids, in order in that direction
- **Spacers**
 - Works well with layout containers
 - **Struts:** fixed spaces, hold things fixed distance apart



- **Stretchy Space (springs):** push things apart as much as possible

What is XML? How to use Android GUI editor?

- Extensible Markup Language
- Is a superset of HTML
 - Tag names surrounded by brackets like “< >”
 - Generally in pairs
 - Can have attributes
- Use to describe widgets on the screen
- Android has a GUI layout editor
 - Can change the background color, size, location...etc of different Views
 - Many different attributes!
 - **strings.xml**
 - What if I want to change a lot of text to another language, or just something else?
 - TextViews’ attributes set to: @string/app_name
 - Change the text in strings.xml
 - Like the above example, Views can grab content from a resource file
- How to create two buttons next to each other?
 - Create a new **LinearLayout** (horizontal)
 - Make sure layout_width looks okay
- **Each thing on the screen has an ID, a meaning! Please name your buttons reasonably (not button1, button2...)**
 - Good names: nextButton, prevButton
 - Access a component programmatically by using [Component].getId() and setId()
 - Use this → implement tab navbar
- In code, you can set variables that we can access later
 - Ex: R.(file name).(value name)
- **PARAMS:** a class content, specifies layout parameters

Layout Containers

Automates layout tasks, make it simpler to ensure reliable results.

- **Constraints:** very general, can operate on multiple axes, has attachment options

