GAT ANDRES BONIFACIO HIGH SCHOOL

Linux and macOS Quick Start

Docker Compose terminal setup for a first-year IT operator

Evidence edition
Instructions match application snapshot 211483f07b901299b48ae42eda318c7448f1cbfd. Production credentials and school records are not included.

Before you begin

- Linux with Docker Engine + Compose v2, or macOS with Docker Desktop; Git; Node.js 20.9 or newer; at least 25 GB free local disk space.
- Internet access is required for the first build and model downloads.

1. Extract into a writable local folder

```
mkdir -p ~/nexora-source
unzip 03-SOURCE/nexora-source-211483f.zip -d ~/nexora-source
cd ~/nexora-source
```

2. Prepare unique local configuration

```
cp .env.compose.example .env
chmod 600 .env
${EDITOR:-nano} .env
```

- Replace every CHANGE_ME value. Keep database passwords aligned and keep the internal AI shared secret identical for backend and AI service.

3. Validate and start

```
docker compose config --quiet
docker compose up -d
```

4. Watch and verify

```
docker compose ps
docker compose logs --tail=100
curl --fail http://localhost:3000/api/health/ready
curl --fail http://localhost:3001
```

Done when
The six core services are healthy/running, readiness returns success, and the frontend returns HTTP 200.

5. Normal stop and restart

```
docker compose down
docker compose up -d
```

- Named volumes survive this restart. Never use docker compose down --volumes on a shared or valuable environment.