GAT ANDRES BONIFACIO HIGH SCHOOL

Configuration Reference

All current documentable environment keys and their safe handling rules

Evidence edition
Instructions match application snapshot 211483f07b901299b48ae42eda318c7448f1cbfd. Production credentials and school records are not included.

Configuration rules

No real secrets
The files in 05-CONFIG-TEMPLATES are sanitized starting points. Create .env only in the local source copy and never commit or return it to the external drive.

- Root .env is the default Docker Compose input; .env.compose.example is its template.
- AI_SERVICE_SHARED_SECRET must match backend and AI service, but must never appear in NEXT_PUBLIC_* or EXPO_PUBLIC_* values.
- Changing a build-time web/mobile public URL requires a rebuild.
- Keep reset, cascade erase, and maintenance controls disabled until their preview, audit, ownership, and recovery prerequisites are approved.

Complete current key index (98 keys)

Key	Purpose	Observed source(s)
ADMIN_CASCADE_ERASE_ENABLED	High-impact safety control; keep disabled until its governed workflow is approved.	.env.compose.example, backend/.env.example
ADMIN_LIFECYCLE_ENABLED	High-impact safety control; keep disabled until its governed workflow is approved.	.env.compose.example, backend/.env.example
ADMIN_MAINTENANCE_ENABLED	High-impact safety control; keep disabled until its governed workflow is approved.	.env.compose.example, backend/.env.example
AI_CLOUD_FALLBACK_API_KEY	Secret or credential; create uniquely, store outside source control, and rotate after exposure.	ai-service/.env.example
AI_CLOUD_FALLBACK_BASE_URL	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	ai-service/.env.example
AI_CLOUD_FALLBACK_ENABLED	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	ai-service/.env.example
AI_CLOUD_FALLBACK_MODEL	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	ai-service/.env.example
AI_CLOUD_FALLBACK_PROVIDER	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	ai-service/.env.example
AI_DATABASE_URL	Database connection or database behavior; keep the intended environment explicit.	.env.compose.example
AI_DEGRADED_ALLOWED	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	ai-service/.env.example, backend/.env.example
AI_EXTRACTION_BG_MAX_CONCURRENCY	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	ai-service/.env.example
AI_RUNTIME_MODE	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	ai-service/.env.example
AI_SERVICE_PORT	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	.env.compose.example

Key	Purpose	Observed source(s)
AI_SERVICE_SHARED_SECRET	Secret or credential; create uniquely, store outside source control, and rotate after exposure.	.env.compose.example, ai-service/.env.example, backend/.env.example
AI_SERVICE_TIMEOUT_CHAT_MS	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	backend/.env.example
AI_SERVICE_TIMEOUT_EXTRACTION_MS	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	backend/.env.example
AI_SERVICE_TIMEOUT_INDEXING_MS	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	backend/.env.example
AI_SERVICE_TIMEOUT_INTERNAL_EXTRACTION_MS	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	backend/.env.example
AI_SERVICE_TIMEOUT_INTERNAL_INTERVENTION_MS	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	backend/.env.example
AI_SERVICE_TIMEOUT_INTERNAL_QUIZ_MS	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	backend/.env.example
AI_SERVICE_TIMEOUT_LESSON_PLAN_MS	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	backend/.env.example
AI_SERVICE_TIMEOUT_QUIZ_MS	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	backend/.env.example
AI_SERVICE_TIMEOUT_TUTOR_START_MS	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	backend/.env.example
AI_SERVICE_URL	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	backend/.env.example
AI_TEACHER_BG_MAX_CONCURRENCY	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	ai-service/.env.example
AI_TUTOR_MAX_INFLIGHT	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	ai-service/.env.example
AI_TUTOR_REJECT_STATUS	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	ai-service/.env.example
AI_TUTOR_RETRY_AFTER_S	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	ai-service/.env.example
BACKEND_DATABASE_URL	Database connection or database behavior; keep the intended environment explicit.	.env.compose.example
BACKEND_INTERNAL_URL	Client-visible URL/origin or build-time value; public prefixes must never contain secrets.	ai-service/.env.example
BACKEND_PUBLIC_URL	Client-visible URL/origin or build-time value; public prefixes must never contain secrets.	backend/.env.example
COOKIE_DOMAIN	Client-visible URL/origin or build-time value; public prefixes must never contain secrets.	backend/.env.example
CORS_ALLOWED_ORIGINS	Client-visible URL/origin or build-time value; public prefixes must never contain secrets.	backend/.env.example
DATABASE_URL	Database connection or database behavior; keep the intended environment explicit.	ai-service/.env.example, backend/.env.example
DB_CONNECT_TIMEOUT_MS	Database connection or database behavior; keep the intended environment explicit.	backend/.env.example
DB_IDLE_TIMEOUT_MS	Database connection or database behavior; keep the intended environment explicit.	backend/.env.example
DB_POOL_MAX	Database connection or database behavior; keep the intended environment explicit.	backend/.env.example
EMAIL_FROM	Email or verification delivery behavior.	backend/.env.example

Key	Purpose	Observed source(s)
EMAIL_PASSWORD	Secret or credential; create uniquely, store outside source control, and rotate after exposure.	backend/.env.example
EMAIL_SERVICE	Email or verification delivery behavior.	backend/.env.example
EMAIL_USER	Email or verification delivery behavior.	backend/.env.example
EXPO_PUBLIC_API_URL	Client-visible URL/origin or build-time value; public prefixes must never contain secrets.	mobile/.env.example
FRONTEND_PORT	Environment-specific runtime configuration; document the owner and expected value.	.env.compose.example
FRONTEND_URL	Client-visible URL/origin or build-time value; public prefixes must never contain secrets.	backend/.env.example
GF_SMTP_ENABLED	Email or verification delivery behavior.	.env.compose.example
GF_SMTP_FROM_ADDRESS	Email or verification delivery behavior.	.env.compose.example
GF_SMTP_HOST	Email or verification delivery behavior.	.env.compose.example
GF_SMTP_PASSWORD	Secret or credential; create uniquely, store outside source control, and rotate after exposure.	.env.compose.example
GF_SMTP_USER	Email or verification delivery behavior.	.env.compose.example
GRAFANA_ADMIN_PASSWORD	Secret or credential; create uniquely, store outside source control, and rotate after exposure.	.env.compose.example
GRAFANA_ADMIN_USER	Environment-specific runtime configuration; document the owner and expected value.	.env.compose.example
GRAFANA_ALERT_EMAIL	Email or verification delivery behavior.	.env.compose.example
GRAFANA_ALERTING_ENABLED	Environment-specific runtime configuration; document the owner and expected value.	.env.compose.example
GRAFANA_PORT	Environment-specific runtime configuration; document the owner and expected value.	.env.compose.example
JWT_ACCESS_EXPIRY	Environment-specific runtime configuration; document the owner and expected value.	backend/.env.example
JWT_REFRESH_EXPIRY	Environment-specific runtime configuration; document the owner and expected value.	backend/.env.example
JWT_REFRESH_SECRET	Secret or credential; create uniquely, store outside source control, and rotate after exposure.	.env.compose.example, backend/.env.example
JWT_SECRET	Secret or credential; create uniquely, store outside source control, and rotate after exposure.	.env.compose.example, backend/.env.example
LESSON_PREVIEW_SECRET	Secret or credential; create uniquely, store outside source control, and rotate after exposure.	.env.compose.example, backend/.env.example
LOG_LEVEL	Environment-specific runtime configuration; document the owner and expected value.	ai-service/.env.example
LOKI_HOST	Environment-specific runtime configuration; document the owner and expected value.	.env.compose.example, backend/.env.example
LOKI_PORT	Environment-specific runtime configuration; document the owner and expected value.	.env.compose.example
MAX_RAW_TEXT	Environment-specific runtime configuration; document the owner and expected value.	ai-service/.env.example
MOBILE_URL	Client-visible URL/origin or build-time value; public prefixes must never contain secrets.	backend/.env.example
NEXT_FRONTEND_URL	Client-visible URL/origin or build-time value; public prefixes must never contain secrets.	backend/.env.example
NODE_ENV	Environment-specific runtime configuration; document the owner and expected value.	backend/.env.example

Key	Purpose	Observed source(s)
OLLAMA_BASE_URL	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	ai-service/.env.example, backend/.env.example
OLLAMA_EMBED_MODEL	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	.env.compose.example, ai-service/.env.example
OLLAMA_KEEP_ALIVE	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	ai-service/.env.example
OLLAMA_TEXT_MODEL	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	.env.compose.example, ai-service/.env.example, backend/.env.example
OLLAMA_TIMEOUT_CHAT_S	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	ai-service/.env.example
OLLAMA_TIMEOUT_EXTRACTION_S	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	ai-service/.env.example
OLLAMA_VISION_MODEL	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	.env.compose.example, ai-service/.env.example, backend/.env.example
OPENROUTER_EMBEDDING_MODEL	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	ai-service/.env.example
OPENROUTER_HTTP_REFERER	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	ai-service/.env.example
OPENROUTER_VISION_MODEL	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	ai-service/.env.example
OPENROUTER_X_TITLE	AI runtime, provider, model, retrieval, timeout, or concurrency setting.	ai-service/.env.example
OTEL_EXPORTER_OTLP_ENDPOINT	Environment-specific runtime configuration; document the owner and expected value.	.env.compose.example, backend/.env.example
OTP_PEPPER	Secret or credential; create uniquely, store outside source control, and rotate after exposure.	.env.compose.example, backend/.env.example
PORT	Environment-specific runtime configuration; document the owner and expected value.	backend/.env.example
POSTGRES_HOST_PORT	Database connection or database behavior; keep the intended environment explicit.	.env.compose.example
POSTGRES_PASSWORD	Secret or credential; create uniquely, store outside source control, and rotate after exposure.	.env.compose.example
PROMETHEUS_PORT	Environment-specific runtime configuration; document the owner and expected value.	.env.compose.example
REDIS_HOST_PORT	Redis or durable background-job behavior.	.env.compose.example
REDIS_URL	Redis or durable background-job behavior.	backend/.env.example
RETRIEVAL_AGGREGATE_TIMEOUT_SECONDS	Environment-specific runtime configuration; document the owner and expected value.	ai-service/.env.example
RUN_DB_MIGRATIONS	Database connection or database behavior; keep the intended environment explicit.	.env.compose.example
RUN_DB_SEED	Database connection or database behavior; keep the intended environment explicit.	.env.compose.example
SYSTEM_RESET_BACKEND_TOPOLOGY	High-impact safety control; keep disabled until its governed workflow is approved.	.env.compose.example, backend/.env.example
SYSTEM_RESET_ENABLED	High-impact safety control; keep disabled until its governed workflow is approved.	.env.compose.example, backend/.env.example
SYSTEM_RESET_ENVIRONMENT	High-impact safety control; keep disabled until its governed workflow is approved.	.env.compose.example, backend/.env.example

Key	Purpose	Observed source(s)
SYSTEM_RESET_REDIS_OWNERSHIP	Redis or durable background-job behavior.	.env.compose.example, backend/.env.example
SYSTEM_RESET_STORAGE_ID	High-impact safety control; keep disabled until its governed workflow is approved.	.env.compose.example, backend/.env.example
SYSTEM_RESET_STORAGE_OWNERSHIP	High-impact safety control; keep disabled until its governed workflow is approved.	.env.compose.example, backend/.env.example
TEMPO_OTLP_HTTP_PORT	Environment-specific runtime configuration; document the owner and expected value.	.env.compose.example
TEMPO_PORT	Environment-specific runtime configuration; document the owner and expected value.	.env.compose.example
TRUST_PROXY_HOPS	Environment-specific runtime configuration; document the owner and expected value.	backend/.env.example
UPLOAD_DIR	Environment-specific runtime configuration; document the owner and expected value.	ai-service/.env.example