GAT ANDRES BONIFACIO HIGH SCHOOL

Backup and Restore Runbook

Guarded PostgreSQL, uploads, checksum, and restore-drill procedure

Evidence edition
Instructions match application snapshot 211483f07b901299b48ae42eda318c7448f1cbfd. Production credentials and school records are not included.

What this protects

- PostgreSQL/pgvector database in custom pg_dump format.
- Uploaded files or object-storage export.
- Checksums, source commit, database server version, and operator notes.

Production rule
Use a documented consistency/maintenance window. Never place production credentials or unencrypted production data in this handoff folder.

Backup procedure

1. Confirm the exact environment, database host/name, owner, maintenance window, retention destination, and free space.
2. Quiesce application writes or use the approved consistency strategy. Record the start time and deployed commit.
3. Run the guarded backup script with explicit database URL, upload path, and a new output directory.
4. Verify MANIFEST.sha256 in the backup directory and store a second copy in authorized durable storage.
5. Resume writes only after the dump, files, manifest, and operator record are complete.

Restore drill

1. Choose a new empty disposable database whose name ends in _restore_test. Never point the first restore at production.
2. Verify the backup manifest before creating the target.
3. Run the guarded restore script. It refuses existing databases and does not delete a database automatically.
4. Run current migrations only if the restore procedure explicitly calls for forward compatibility; record each result.
5. Start an isolated app against the restored target and verify readiness, authentication, role isolation, representative files, one queue job, and one audit read.
6. Compare key row counts and business invariants. Document the drill and retain the source backup unchanged.

Example shell commands

```
./scripts/backup-nexora.sh --db-url 'postgresql://...' --uploads /srv/nexora/uploads --output
/secure/backups/nexora-YYYYMMDD
./scripts/restore-nexora-verify.sh --admin-url 'postgresql://...' --backup
/secure/backups/nexora-YYYYMMDD --target-db nexora_restore_test --confirm CREATE_EMPTY_TARGET
```

Do not cut over
A successful pg_restore is not enough. Cutover requires integrity checks, application smoke tests, explicit authorization, a rollback target, and an approved window.