GAT ANDRES BONIFACIO HIGH SCHOOL

Disaster Recovery Checklist

Preserve evidence, rehearse in isolation, validate, authorize, and cut over safely

Evidence edition
Instructions match application snapshot 211483f07b901299b48ae42eda318c7448f1cbfd. Production credentials and school records are not included.

Disaster recovery checklist

First principle
Preserve evidence and restore into a new target. Do not erase the damaged environment or overwrite production during diagnosis.

Phase	Required evidence
1. Stabilize	[ ] Stop unsafe writes; preserve logs, audit IDs, queue IDs, current binaries, and current database/files.
2. Declare	[ ] Record incident owner, severity, scope, start time, affected users, and communication channel.
3. Select	[ ] Choose the latest verified backup before the incident; verify checksum and compatibility.
4. Rehearse	[ ] Restore to a new isolated target and run migrations/integrity checks without touching production.
5. Validate	[ ] Prove health, authentication, role isolation, academic evidence, files, queues, notifications, and audit reads.
6. Decide	[ ] Obtain explicit cutover authorization with expected data loss window and rollback decision.
7. Cut over	[ ] Change one controlled dependency at a time; monitor; retain the prior target read-only.
8. Close	[ ] Reconcile data, notify stakeholders, rotate exposed credentials, and write the incident report.

Minimum acceptance evidence

- Exact source commit/build and environment configuration key map.
- Database and file checksums plus restore command output.
- Readiness, role smoke, representative academic-history, upload, queue, notification, and audit checks.
- Named approver, cutover time, expected recovery point, rollback target, and post-cutover observation result.