IT-Security (ITS) B1

DIKU, E2022

Today’s agenda

Forensics defined

Disk forensics

Memory forensics

Forensics defined

Digital forensics is a branch of forensic science encompassing the recovery and investigation of material found on digital devices

Applied in a **corporate**, **civil**, or **criminal** setting (originated in law enforcement)

Applied to a **security** investigation (of an intrusion) or a **personnel** investigation

In security investigations, forensics either means a **root cause** or **impact analysis** of a cyber-attack, often post-mortem, **or simply techniques** used in the process of uncovering, understanding, and responding to a security incident

In security, **DFIRMA** = digital forensics + incident response + malware analysis

DFIRMA in practice

```
while true:
        intrusion analysis

        if intrusion suspected:
                preliminary analysis

                if intrusion verified:
                        repeat until incident fully grasped:
                                incident analysis
                                forensic analysis
                                malware anaysis

                        incident response

        update plans
```

Recap: Intrusion detection



Many forms of forensics

Digital forensics =

- Computer forensics
- Memory forensics
- Network forensics
- Mobile forensics
- Etc. forensics

} **Our focus today**

Disk (or, file system) forensics

Classic disk forensic approach

Forensic workstation

Write blocker



Seized harddrive

Forensics in a nutshell

Understanding the low-level details



- File names, directories
- Structure information about files/directories
- Partition information
- Sectors, blocks, clusters
- The drive itself, and partitions

Disk forensic example: DOS partitions



MBR/EBR same layout

Bytes	Content
0-445	Upstart code, disk signature
446-461	Partition entry 1
462-477	Partition entry 2
478-493	Partition entry 3
494-509	Partition entry 4
510-511	MBR/EBR signature (0xAA55)

Bytes	Content
0	0x00 not boot, 0x80 boot
1-3	Cylinder-head-sector (CHS) of start sector
4	Partition type
5-7	Cylinder-head-sector (CHS) of end sector
8-11	Logical block addressing (LBA) of start sector
12-15	Number of sectors in partition

Type	FAT12	FAT16	FAT32	Linux native	Linux swap	Extended	NFTS
Hex value	0x01	0x0E	0x0C	0x83	0x82	0x05	0x07

File system example: NTFS

File system example: NTFS



Master File Table (MFT)

An entry in the MFT describes a file

- Filename and metadata like permissions, timestamps
- Entries are 1024 bytes
- For larger files (non-resident files), the MFT entry contains links to areas of the disk where the file data resides

Data / File storage area

Clusters (Windows) or **blocks** (Unix) = 1 or more 512-byte **sectors**

Custers/blocks either **allocated**

- Actively being used by a file

Or **unallocated**

- Not being used by a file
- May contain deleted or unused data

Deleted != destroyed

When a file is deleted, **data still exists** on disk until overwritten

If overwritten, **remnants may still exist** in

- extra copies of the file
- page/swap/hibernation file, or
- elsewhere on the disk due to (de)fragmentation

However, if disk wiped, only just once, recovery infeasible

Think libraries

Format is not wiping

Formats create and replace file system structures

Files are not overwritten

Regular formats take longer as the disk is scanned for bad sectors

Use wiping software for wiping



Slack space


slack.txt - Notepad
File Edit Format Help
Forensics


slack.txt Properties
General
Security
Summary
slack.txt
Type of file: Text Document
Opens with: Notepad
Change...
Location: C:\Documents and Settings\Administrator\Desktop
Size: 9 bytes (9 bytes)
Size on disk: 4,00 KB (4.096 bytes)
Created: 6. februar 2003, 23:04:41
Modified: 6. februar 2003, 23:05:45
Accessed: 6. februar 2003, 23:05:45
Attributes: Read-only Hidden
Advanced...
OK
Cancel
Apply

Timeline (Modified, Accessed, Changed)



Searching for file types

Slack.txt



Slack.exe

Slack.pdf

Slack.zip

Slack.dat

Slack.mp3

Slack.dll

Further reading



Memory forensics

Memory forensics

From Wikipedia:

“Memory forensics is forensic analysis of a computer's **memory dump**.

Its primary application is investigation of advanced computer attacks which are stealthy enough to avoid leaving data on the computer's hard drive.”

First, get a copy

- Live acquisition
  - Different techiniques
- Live analysis
  - Direct analysis of the running kernel
- Dead acquisition
  - Hibernation files, page files
- Virtualization - thank you

What to find in memory?

- Running processes
- Listening sockets
- Open connections
- Encryption keys
- Credentials
- Memory only malware
- Closed connections
- Terminated processes
- Open file handles
- Deobfuscated code

Memory forensic analysis process

1: Find rogue processes

2: Analyse DLLs

3: Review network artefacts

4: Look for evidence of code injections

5: Dump suspicious processes → further analysis

How to find processes (on Windows)

EPROCESS objects in memory:



How to find processes (on Windows)

Scan for EPROCESS objects:



Process enumeration (on Windows)



Key concept in memory forensics:

Walking a list, or **scanning for objects**

Step 1 revisited: Find rogue processes

Those that:

- Hide
- Have odd parents
- Do network comm but shouldn’t
- Have unusually many handles open
- Contain maliciously injected code
- ...

Direct kernel objection manipulation (DKOM)



Volatility

Volatility is an open source memory analysis framework writtin in Python



Example:

Stuxnet

Stuxnet


DO WE HAVE A BACKUP?
Stuxnet VIRUS
CHAPPATTE
Int'l Herald Tribune

Stuxnet



Natanz Nuclear Facility in Iran

Stuxnet


YouTube DK
Search
HUNGRYBEAST
0:01 / 3:29
STUXNET: The Virus that Almost Started WW3

Volatility and Stuxnet



Further reading