MGM VARVEL
POWER TRANSMISSION

Data sheet - Three phase - Squirrel cage motors (Brake motor)

BAX 112M 4 240.415 50 B5, P-3.7kW, IE2, CLF, IP55, S1, Vb=Vm

Data sheet no.	**DS-025-2028**	**Rev.**	**A**

Rated power	P_N	3.7	kW	Bearing	DE	6306Z	
Number of poles		4			NDE	6306Z	
Frame size	IEC	112M		Bearing life time	L10m	40000	Hrs
Type of mounting		B5		Lubrication type		Pre-lubricated	
Rated voltage	U	240Δ / 415Y	V	Voltage variation		± 10	%
Rated frequency	f	50	Hz	Frequency variation		± 5	%
Stator connection	(Δ/Y)	Y		Combined variation		± 10	%
Rated current	I_N	14/8.1	A	Environmental condition		+ 50°C / 1000m	
Rated speed	n_N	1456	rpm	Direction of rotation		Bi-directional	
Rated torque	M_N	24.3	Nm	Housing material		Aluminium	
Efficiency class		IE2		Flange material		Cast iron	
Duty type		S1		Motor weight		50	kgs
Insulation class		F		Lifting eyebot size		-	
Temperature rise class		B		Terminal box position (view from NDE)		Top	
Degree of protection		IP55		Type of terminal box		Std + DM	
Method of cooling		TEFC / IC 411		Material of terminal box		Aluminium	
Locked rotor current	I_A	64.0	A	Terminal size		M4	
Locked rotor torque	M_A	111.8	Nm	No. of terminals		6	Nos
Breakdown torque	Mk	121.5	Nm	Cable entry thread size		2xM25x1.5	
Efficiency* η	100%	86.3	%	No. of cable glands		1	Nos
	75%	86.7	%	Cable diameter		3…..18	mm
	50%	84.7	%	Max. Cable size		3Cx6	mm²
Power factor* cos ϕ	100%	0.75		Painting cycle		Standard	
	75%	0.65		Color / Paint Shade **		RAL 5010 Blue	
	50%	0.50		Vibration severity grade		A (Standard)	
Reference standard		IS:12615/IEC 60034-1		Sound pressure level - 50Hz		61	±3dB(A)

Brake Details

Brake type	AC	Brake torque	80	Nm
Input supply voltage	415 (AC) V	Brake safety factor	3.3	
No. of Phase	3ø	Brake reaction time	9	m.sec
Brake coil voltage	415 (AC) V	Brake current	0.28	A

Special Designs

** Value is valid only for DOL operation with motor design IC411.* *** Aluminium parts are unpainted*

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.