

MPS MONITOR API Documentation

Read the How to connect section to see how to connect to our services, passing the required authentication credentials.

Go to API References (/api3docs/SwaggerUi) to see the available services, along with request\response definitions .

How to connect

1 - Register your application

Access the developer section of the portal and create the APP credentials.

2- Get the authentication token

In order to obtain a valid access token, you must perform a **x-www-form-urlencoded** POST to our **/token** endpoint, passing the following parameters:

- **client_id**: the client identifier we gave you in the step 1
- **client_secret**: the client password we gave you in the step 1
- **grant_type**: fixed value to **password**
- **username**: the identifier of the user that wants to login
- **password**: the password\token of the user that wants to login
- **scope**: the type of MPS access level(account)

Please note that the **access token** has an expiration and you should refresh it before that happens (see step 4) or you must perform this step again.

Sample Request

```
POST /token HTTP/1.1
Host: EndpointApiUri
Content-Type: application/x-www-form-urlencoded
Cache-Control: no-cache
client_id=YourClientId&client_secret=YourClientSecret&grant_type=password&username=test%40t
```

Sample Response

```
{
  "access_token": "WDqEbIZNQ2zpFvulchVP8JXT5IpLlHzMkLmmBKbJmsPF",
  "token_type": "bearer",
  "expires_in": 1799,
  "refresh_token": "f1efdf74ecc043b69f60c110af41a3f1",
  "as:client_id": "YourClientId",
  "userName": "test%40test.com",
  ".issued": "Mon, 30 Jan 2017 13:40:47 GMT",
  ".expires": "Mon, 30 Jan 2017 14:10:47 GMT"
}
```

3- Call the service

Once you have retrieved valid access token, you must pass the **access_token** value, for every following request to our endpoints, in the **Authorization** header as **Bearer**.

Sample Request

```
GET /account/getaccount HTTP/1.1
Host: EndpointApiUri
Content-Type: application/json
Authorization: bearer WDqEbIZNQ2zpFvulchVP8JXT5IpLlHzMkLmmBKbJmsPF
Cache-Control: no-cache
```

4- Refresh the authentication token

In order to refresh the access token, you must perform a **x-www-form-urlencoded** POST to our **/token** endpoint, passing the following parameters:

- **client_id**: the client identifier we gave you in the step 1
- **client_secret**: the client password we gave you in the step 1
- **grant_type**: fixed value to **refresh_token**
- **refresh_token**: the **refresh_token** (not **access_token**) value obtained in step 2

Sample Request

```
POST /token HTTP/1.1
Host: EndpointApiUri
Content-Type: application/x-www-form-urlencoded
Cache-Control: no-cache
client_id=YourClientId&client_secret=YourClientSecret&grant_type=refresh_token&refresh_token=YourRefreshToken
```

Sample Response

```
{
  "access_token": "mFpZAd4MXC9syF1KxAdf23HwcXhZ9NMiwrrZxnv",
  "token_type": "bearer",
  "expires_in": 1799,
  "refresh_token": "b99af13fc24840f188b21dde192634db",
  "as:client_id": "YourClientId",
  "userName": "test%40test.com",
  ".issued": "Mon, 30 Jan 2017 13:40:47 GMT",
  ".expires": "Mon, 30 Jan 2017 14:10:47 GMT"
}
```