

Credit Transaction Fix Summary

Date: November 13, 2025

Problem

The API verify endpoint (`/api/v1/verify`) was working but failing when trying to deduct credits with the following error:

```
null value in column "user_id" of relation "credit_transactions" violates not-null constraint
```

Root Cause

- The `credit_transactions` table had a NOT NULL constraint on both `customer_id` and `user_id`
- API transactions are authenticated via API keys, which are associated with customers (not users)
- When the `deductCredits()` function in `api-auth.ts` tried to create a transaction record, it only provided `customer_id` but the database required `user_id`
- This created a mismatch between the API authentication model (customer-based) and the transaction tracking model (requiring users)

Solution Implemented

1. Database Schema Change

File: `database/migrations/014_make_user_id_nullable_in_credit_transactions.sql`

Made the `user_id` column nullable in the `credit_transactions` table to support two types of transactions:

- **User transactions** (purchases via UI): Have `user_id` populated
- **API transactions** (usage via API): Have `user_id` as NULL (only `customer_id`)

```
ALTER TABLE credit_transactions  
ALTER COLUMN user_id DROP NOT NULL;
```

2. Code Changes

File: `src/app/lib/api-auth.ts`

Updated the `deductCredits()` function to:

- ☒ Lock the row using `FOR UPDATE` to prevent race conditions
- ☒ Retrieve `balance_before` from `customer_credits`
- ☒ Check for sufficient credits before attempting to deduct
- ☒ Calculate `balance_after` correctly
- ☒ Update both `balance` and `total_used` fields
- ☒ Insert transaction record with `user_id = NULL` for API transactions
- ☒ Include proper balance tracking (`balance_before` , `balance_after`)
- ☒ Use correct transaction type: `'USAGE'` (matching the credits library convention)

Changes Made:

Before:

```
await query(
  `INSERT INTO credit_transactions
    (customer_id, amount, transaction_type, description)
  VALUES ($1, $2, 'debit', $3)`,
  [customerId, -amount, description]
);
```

After:

```
await query(
  `INSERT INTO credit_transactions
    (customer_id, user_id, transaction_type, amount, balance_before, balance_after, de-
    scription)
  VALUES ($1, NULL, 'USAGE', $2, $3, $4, $5)`,
  [customerId, -amount, balanceBefore, balanceAfter, description]
);
```

Files Created/Modified

New Files:

1. database/migrations/014_make_user_id_nullable_in_credit_transactions.sql - Migration SQL
2. database/migrations/APPLY_014_MIGRATION.md - Migration instructions and documentation
3. CREDIT_TRANSACTION_FIX.md - This summary document

Modified Files:

1. src/app/lib/api-auth.ts - Updated deductCredits() function

How to Apply the Fix

Step 1: Apply Database Migration

You need to apply the migration to your Supabase database. See detailed instructions in:

- database/migrations/APPLY_014_MIGRATION.md

Quick Steps:

1. Go to Supabase Dashboard → SQL Editor
2. Copy contents of 014_make_user_id_nullable_in_credit_transactions.sql
3. Run the migration
4. Verify: user_id column should be nullable

Step 2: Deploy Code Changes

The code changes in api-auth.ts will be automatically deployed when you push to main branch.

Step 3: Test

After applying both changes:

1. Make an API call to /api/v1/verify with your API key
2. Verify credits are deducted successfully
3. Check that transaction records are created with user_id = NULL

```

SELECT
    id, customer_id, user_id, transaction_type,
    amount, balance_before, balance_after, description
FROM credit_transactions
WHERE user_id IS NULL
ORDER BY created_at DESC
LIMIT 5;

```

Benefits

- ✓ **Fixes API Credit Deduction** - API calls can now successfully deduct credits
- ✓ **Proper Balance Tracking** - Maintains `balance_before` and `balance_after` for audit trail
- ✓ **Data Integrity** - Uses row locking to prevent race conditions
- ✓ **Backward Compatible** - Existing user transactions continue to work with `user_id` populated
- ✓ **No Data Loss** - All existing transaction records remain intact

Transaction Types Supported

After this fix:

Transaction Type	user_id	customer_id	Use Case
PURCHASE	✓ Set	✓ Set	User purchases credits via UI
USAGE (User)	✓ Set	✓ Set	User performs searches via UI
USAGE (API)	✗ NULL	✓ Set	API calls via API keys
REFUND	✓ Set (optional)	✓ Set	Credit refunds
ADJUSTMENT	✓ Set (optional)	✓ Set	Manual credit adjustments

Verification Queries

Check if migration was applied:

```

SELECT column_name, is_nullable
FROM information_schema.columns
WHERE table_name = 'credit_transactions' AND column_name = 'user_id';
-- Should show: is_nullable = 'YES'

```

View API transactions:

```

SELECT * FROM credit_transactions
WHERE user_id IS NULL
ORDER BY created_at DESC;

```

View customer credit balance:

```
SELECT c.id, c.name, cc.balance, cc.total_used, cc.total_purchased
FROM customers c
JOIN customer_credits cc ON c.id = cc.customer_id;
```

Rollback Plan

If issues arise, you can rollback the migration:

 **Warning:** Rollback will delete all API transaction records!

```
BEGIN;
-- Delete API transactions (user_id IS NULL)
DELETE FROM credit_transactions WHERE user_id IS NULL;

-- Restore NOT NULL constraint
ALTER TABLE credit_transactions ALTER COLUMN user_id SET NOT NULL;
COMMIT;
```

Testing Checklist

- [] Migration applied successfully to database
- [] Code deployed to production
- [] API verify endpoint works without errors
- [] Credits are deducted correctly
- [] Transaction records created with NULL user_id
- [] Balance tracking is accurate (balance_before/after)
- [] Existing user transactions still work
- [] No performance degradation


Related Documentation

- API Documentation: `/api-docs` (Swagger UI)
- Credits System: `src/app/lib/credits/index.ts`
- API Authentication: `src/app/lib/api-auth.ts`
- Database Schema: Supabase Dashboard → Table Editor

Support

If you encounter any issues:

1. Check the migration was applied: See “Verification Queries” above
 2. Check application logs for errors
 3. Verify API key is valid and customer has credits
 4. Test with Postman/Thunder Client before production use
-

Status:  Ready for deployment

Priority: High - Fixes critical API functionality

Breaking Changes: None

Rollback Risk: Low (only if you need to revert user_id to NOT NULL)