

**System and Software Design Description(SSDD):  
Incorporating Architectural Views and Detailed Design Criteria  
For  
Swords and Sorcery**

Keith Drew, ...

May 7, 2014

# Swords and Sorcery Design

## Table of Contents

<b>1</b>	<b>Introduction</b>	<b>3</b>
1.1	Document Purpose, Context, and Intended Audience . . . . .	3
1.1.1	Document Purpose . . . . .	3
1.1.2	Document Context . . . . .	3
1.1.3	Intended Audience . . . . .	3
1.2	Software Purpose, Context, and Intended Audience . . . . .	3
1.2.1	System and Software Purpose . . . . .	3
1.2.2	System and Software Context . . . . .	3
1.2.3	Intended Users of System and Software . . . . .	3
1.3	Definitions, Acronyms, and Abbreviations . . . . .	4
1.4	Document References . . . . .	4
1.5	Overview of Document . . . . .	5
1.6	Document Restrictions . . . . .	5
<b>2</b>	<b>Constraints and Concerns</b>	<b>5</b>
2.1	Constraints . . . . .	5
2.2	Stakeholder Concerns . . . . .	6
<b>3</b>	<b>System and Software Architecture</b>	<b>6</b>
3.1	Developer's Architectural View . . . . .	6
3.1.1	Developer's View Identification . . . . .	6
3.1.2	Developer's View Representation and Description . . . . .	6
3.1.3	Developer's Architectural Rationale . . . . .	6
3.2	User's Architectural View . . . . .	7
3.2.1	User's View Identification . . . . .	7
3.2.2	User's View Representation and Description . . . . .	7
3.3	Consistency of Architectural Views . . . . .	7
3.3.1	Detail of Inconsistencies Between Architectural Views . . . . .	7
3.3.2	Consistency Analysis and Inconsistency Mitigations . . . . .	7
<b>4</b>	<b>Software Detailed Design</b>	<b>7</b>
4.1	Developer's Viewpoint Detailed Software Design . . . . .	7
4.2	Component Dictionary . . . . .	8
4.3	Component Detailed Design . . . . .	9
4.4	Detailed Design for Component: Army Unit . . . . .	9
4.5	Detailed Design for Component: Army Combat Results Table . . . . .	9
4.6	Detailed Design for Component: Characters . . . . .	10
4.7	Detailed Design for Component: Movable Unit . . . . .	10
4.7.1	Detailed Design for Component: Movement Calculator . . . . .	11
4.8	Data Dictionary . . . . .	11
<b>5</b>	<b>Requirements Traceability</b>	<b>12</b>
5.1	Movement . . . . .	12
5.2	Traceability Analysis . . . . .	12

# 1 Introduction

This is the System and Software Design Document for Swords and Sorcery. This is one of five documents that describe the computer adaptation of the Swords and Sorcery board game developed by the Software Engineering class at the University of Idaho in Spring 2014.

## 1.1 Document Purpose, Context, and Intended Audience

### 1.1.1 Document Purpose

The purpose of this document is to describe the system and software design of Swords and Sorcery.

### 1.1.2 Document Context

This document is written as part of a larger document that describes the Swords and Sorcery project developed by the CS383 students at University of Idaho, in Spring 2014. This document only describes the system and software design of the project, which is only a subset of the project.

### 1.1.3 Intended Audience

This document is intended to be read by Dr. Clinton Jeffery and members of the class, as well as any interested members of the University of Idaho Computer Science department. This document is not intended to be distributed publicly in any way.

## 1.2 Software Purpose, Context, and Intended Audience

### 1.2.1 System and Software Purpose

The purpose of the Swords and Sorcery system and software is to provide a computer adaptation of the complex board game of the same name. The system is designed to provide multiplayer functionality over the internet, and to simplify the complex rules of the original Swords and Sorcery.

### 1.2.2 System and Software Context

The context of this project is, again, restrained to the classroom, as it is an educational project, not intended for distribution. However, the source code for the project, as well as many resources, are available publicly on [github.com](https://github.com).

### 1.2.3 Intended Users of System and Software

The intended users of the Swords and Sorcery system are...

### 1.3 Definitions, Acronyms, and Abbreviations

Term	Definition
AD	Architectural Description: "A collection of products to document an architecture."ISO/IEC 42010:2007
Alpha Test	Limited release(s) to selected, outside testers.
Architectural View	"A representation of a whole system from the perspective of a related set of concerns."ISO/IEC 42010:2007
Architecture	"The fundamental organization of a system embodied in its components, their relationships to each other, and to the environment, and the principles guiding its design and evolution."ISO/IEC 42010:2007
Beta Test	Limited release(s) to cooperating customers wanting early access to developing systems.
Design Entity	"An element (component) of a design that is structurally and functionally distinct from other elements and that is separately named and referenced."IEEE STD 1016-1998
Design View	"A subset of design entity attribute information that is specifically suited to the needs of a software project activity."IEEE STD 1016-1998
Edge	The edge between two hexes. Edges can include roads, walls, streams, etc. and can effect movement or combat
GUI	Graphical User Interface - What the user sees and interacts with - also called the HUD.
Hexagon	A hexagon shaped location on the game or diplomacy map that can contain things like units, edges, or terrain. Or the mathematical hexagon shape.
HUD	Heads Up Display - What the user sees, with respect to interface - also called the GUI.
IP	Internet Protocol - Typically refers to an IP Address.
S&S	Swords and Sorcery
SSDD	System and Software Design Document
SSRS	System and Software Requirements Specification
System	"A collection of components organized to accomplish a specific function or set of functions."ISO/IEC 42010:2007
System Stakeholder	"An individual, team, or organization (or classes thereof) with interests in, or concerns, relative to, a system."ISO/IEC 42010:2007

### 1.4 Document References

1. CSDS, textitSystem and Software Requirements Specification Template, Version 1.0, July 31, 2008, Center for Secure and Dependable Systems, University of Idaho, Moscow, ID, 83844.
2. ISO/IEC/IEEE, *IEEE Std 1471-2000 Systems and software engineering – Recommended practice for architectural description of software intensive systems*, First edition 2007-07-15, International Organization for Standardization and Interna-

tional Electrotechnical Commission, (ISO/IEC), Case postale 56, CH-1211 Geneve 20, Switzerland, and The Institute of Electrical and Electronics Engineers, Inc., (IEEE), 445 Hoes Lane, Piscataway, NJ 08854, USA.

3. IEEE, *IEEE Std 1016-1998 Recommended Practice for Software Design Descriptions*, 1998-09-23, The Institute of Electrical and Electronics Engineers, Inc., (IEEE) 445 Hoes Lane, Piscataway, NJ 08854, USA.
4. 3) ISO/IEC/IEEE, *IEEE Std. 15288-2008 Systems and Software Engineering – System life cycle processes*, Second edition 2008-02-01, International Organization for Standardization and International Electrotechnical Commission, (ISO/IEC), Case postale 56, CH-1211 Geneve 20, Switzerland, and The Institute of Electrical and Electronics Engineers, Inc., (IEEE), 445 Hoes Lane, Piscataway, NJ 08854, USA.
5. ISO/IEC/IEEE, *IEEE Std. 12207-2008, Systems and software engineering – Software life cycle processes*, Second edition 2008-02-01, International Organization for Standardization and International Electrotechnical Commission, (ISO/IEC), Case postale 56, CH-1211 Geneve 20, Switzerland, and The Institute of Electrical and Electronics Engineers, Inc., (IEEE), 445 Hoes Lane, Piscataway, NJ 08854, USA.

## 1.5 Overview of Document

**Section 2** of this document describes the concerns and constraints of the system and software, with respect to environmental constraints, system requirement constraints, and user characteristic constraints. Section 2 also describes stakeholder concerns.

**Section 3** of this document describes the System and Software architecture of Swords and Sorcery, from different points of view, namely the user’s point of view and the developer’s point of view.

**Section 4** of this document describes the finer details of the software design, listing software and system components that are crucial to the operation of the Swords and Sorcery game.

**Section 5** of this document describes the requirements traceability of the Swords and Sorcery project, highlighting how our original project requirements have been met, modified, and implemented.

## 1.6 Document Restrictions

This document is for LIMITED USE ONLY to UI CS personnel working on the project.

# 2 Constraints and Concerns

## 2.1 Constraints

Swords and Sorcery requires the Java Runtime Environment 8 to run. S&S also requires the JDK 8.0 and Netbeans 8.0 or better to develop. The game will run on Windows,

Mac, and Linux, provided those systems have the mentioned software packages (JRE to play, JDK/Netbeans to develop). To play the game, a network connection is required, as well as the IP Address of the game server. As S&S is a multiplayer game, one client is required for each player. Typically, this should be done using multiple computers, however, multiple clients can be run on the same computer.

## 2.2 Stakeholder Concerns

There are no financial stakeholders, however, Dr. Clinton Jeffery can be considered a stakeholder, as well as each class member. As a class member, our concerns are providing a quality product, while Dr. Jeffery's concerns may include using good design principles, as this is a Software Engineering course. Other concerns include design requirements such as portability,

# 3 System and Software Architecture

## 3.1 Developer's Architectural View

### 3.1.1 Developer's View Identification

There are multiple developer views within the scope of the S&S project for CS383. The views represent each subteam, and there are three subteams - HUD Team, Rules Team, and Networking Team. The descriptions of each sub-view follow:

**HUD Team View** The HUD Team view includes all software related to the HUD/GUI and handles how the user(s) interact with the S&S game.

**Rules Team View** The Rules Team view includes all software implementations of the S&S rule set, some of which overlaps with other views. Typically, Rules Team is in charge of implementing internal logic and data structures.

**Networking Team View** The Networking Team view includes all network communication related to the S&S game. This includes the client/server model, the communication protocols, the server setup and more.

### 3.1.2 Developer's View Representation and Description

**HUD Team View Representation and Description** [Insert Description of graphics (UML) here]

**Rules Team View Representation and Description** [Insert Description of graphics (UML) here]

**Networking Team View Representation and Description** [Insert Description of graphics (UML) here]

### 3.1.3 Developer's Architectural Rationale

it breaks without text so often it seems

## **3.2 User's Architectural View**

### **3.2.1 User's View Identification**

### **3.2.2 User's View Representation and Description**

## **3.3 Consistency of Architectural Views**

### **3.3.1 Detail of Inconsistencies Between Architectural Views**

### **3.3.2 Consistency Analysis and Inconsistency Mitigations**

## **4 Software Detailed Design**

### **4.1 Developer's Viewpoint Detailed Software Design**

## 4.2 Component Dictionary

Name	Type/Range	Purpose	Dependencies	Subordinates
Army Combat Result Table	Static Method	Determine results of combat lookup	Two Ar-rayLists: Attackers, Defenders	None
Army Unit	Class	Unit Sub-Class	Moveable Unit	All indi-vidual unit types
Characters	Class	Unit Sub-Class	Moveable Unit	None
Hexagon Classes	Model	Represents a hexagon	Hex Edge Classes, Ter-rain Classes, UnitPool	
Hex Edge Classes	Model	Classes to collect and represent elements on hexagon edges	Hex Classes	
Hexagon Map Classes	Model	Classes to represent a "map" of hexagons, either diplo-macy or game.	Hex Classes	
MainMenuController	Controller	Define and limit access to main menu	Game.java	
Map Rendering Classes	View	Renders the game map and things on it	MapView, Hexagon Classes, Hex Edge Classes	
MapView	View	A GUI wid-get to act as a container for the Map Ren-dering code	Hexagon Classes, Map Rendering Classes	
Moveable Unit	Class	Unit Super-Class	None	ArmyUnit, Character, Monster
MovementCalculator	Static Class	Determine Legal Moves	UnitPool, MainMap	Retreat/Move



## 4.3 Component Detailed Design

### 4.4 Detailed Design for Component: Army Unit

**Purpose** This class contains the data of the Army Units in the game and extends the Movable Unit class. This class contains new data like the strength of a unit and whether or not the units is conjured or demoralized. If a unit is conjured then there are special member variables that contain values that are associated with conjured units. If a unit is demoralized then the strength of the unit is different so a demoralized strength variable was added to the class. The strength and demoralized strength variables are used during the combat phase of a users turn and is used to determine the outcome of combat.

**Input** The only Inputs to this class are the ones needed to fill the member variables of this class.

**Output** This class by itself has no output produced other than the getter functions in the class.

**Process** Output is obtained by calling the getter functions.

**Design Constraints and Performance Requirements** In order for this class to perform correctly all of the needed variables need to be filled out.

### 4.5 Detailed Design for Component: Army Combat Results Table

**Purpose** The purpose of this method is a lookup for the results of Combat.

**Input** Input needs to be two Array Lists: one is called attackers and one defenders. Also the hex object that the defenders are positioned on is needed. The attackers array list is comprised of all of the attacking Army Units in the combat and the defenders are all of the defending Army Units in the combat. The defenders hex is needed in order to calculate the defence multipliers that the defending units get from the terrain values of the hex object.

**Output** The output of this function is a simple 2 value array corresponding the result of the combat. The first value is what's required of the attackers and the second value is what's required of the defenders. A -1 means the units were killed, a 0 means that there was no result of the combat and any positive number represents the number of hexes a unit has to retreat.

**Process** The function adds the total strengths of both the attackers and defenders. Then applies the terrain multiplier to the defenders total strength. Finally the ratio of attackers over defenders plus a random dice roll determines the outcome of the combat.

**Design Constraints and Performance Requirements** One design constraint of the table was that in the game the ratio's have to be reduced to the smallest possible fraction in favour of the defending units. To work around this an index was made to match the determined ratio to the correct look up value on the table. Also the units strength and race is required to be filled out in order for this function to work properly.

## 4.6 Detailed Design for Component: Characters

**Purpose** This class contains the data of a Character in the game and extends the Movable Unit class. This class has variables unique to a character: magic level, magic potential, current manna, magic colour, and leadership. The magic level determines the high level of spell that a character can cast. The magic potential is the maximum amount of manna that a character can have. The magic colour of a character determines when a character's spells have the most effect. Leadership is the influence that a character has in determining the result of army combat. Characters have the special ability to cast spells which uses the magic and manna values to determine the amount and effectiveness of their spells.

**Input** The only Inputs to this class are the ones needed to fill the member variables of this class.

**Output** This class by itself has no output produced other than the getter functions in the class.

**Process** Output is obtained by calling the getter functions.

**Design Constraints and Performance Requirements** In order for this class to perform correctly all of the member variables need to be filled out.

## 4.7 Detailed Design for Component: Movable Unit

**Purpose** The purpose of this class is to have a common class of all moving units that the movement functions can access. This class is a super class of all units that can undergo a movement process. This allows for common data to be accessible by the appropriate functions. This common superclass also allows for the ability to store the data of all units in a single-typed data structure. This class contains member variables for movement allocation of a unit, the working movement allocation of a unit or the amount of movement left in a game turn, the race of the unit, the type of subclass that is inheriting from this class (such as armyUnit or Character), and the unique ID of the unit. The movement allocation of a unit is the amount of movement points allowed at the beginning of a turn then the working movement takes over. The working movement is used in order to keep track of how much a unit has move in a single turn. This allows for a user to partially move a unit in their turn then return to that unit and finish moving it later in the same turn. The race is used in many different calculations for units such as the movement cost per hex of a unit in a particular terrain. The subclass variable is used for typecasting the moveable unit back to the proper subclass in order for the subclass based operations to be executed. Finally the unique ID is used for network based communications to identify the unit that is being acted on.

**Input** Input needed to make this class function properly are values to fill the member variables of this class.

**Output** The only output of this class is by getters of the member variables of the class.

**Process** Call the getter functions.

**Design Constraints and Performance Requirements** One constraint of this class was the necessity to be casted back into the appropriate subclass this was solved by creating

the unitType(subclass Type) variable. Also in order for this class to preform right with other classes and functions all of the variables need to be set.

#### 4.7.1 Detailed Design for Component: Movement Calculator

**Purpose** The movement calculator is a static java class that handles most forms of movement.

**Input** The movement calculator takes two inputs to generate a list of moves: the unit moving, and the hex object they are beginning from. To calculate a retreat, the movement calculator takes as input the unit retreating, the hex they are retreating from, and the number of hexes they are required to retreat.

**Output** The movement calculator produces two main outputs: A hashmap of moves that a unit can reach (within the rules of movement specified by the board game) during a given movement phase, paired with their remaining movement cost after moving to a key hex in the hashmap, or an arraylist of moves that a unit can move to while retreating, during the combat phase.

**Process** The movement calculator uses recursion to examine the neighbors of the provided hex location. From each neighbor, it evaluates their neighbors, and so on. In both cases (movement/retreat) the recursion is terminated by reaching a lower bound (0) on the limiting value for their movement. For a moving unit, this is their given movement allowance per turn. For a retreating unit, this is the number generated from the combat results table that indicates how many hexes a unit must retreat. For each step of recursion, decisions are made within control flow that are designed to model the rules of the original S&S board game. These factors include, but are not limited to, hex terrain types, hex edge types, geographical obstacles, and enemy occupation.

**Design Constraints and Performance Requirements** The design was constrained by two factors - code complexity and time. By designing the movement calculator to use recursion, the complexity of the component was greatly reduced. However, due to the many factors involved in movement, the design is still complex. Also, the moves available to a unit need to be calculated quickly. However, recursion is not very fast. Thankfully, Colin Clifford added some optimization code to the calculator, which has greatly increased performance with respect to time.

### 4.8 Data Dictionary

Name	Type/Range	Defined By...	Referenced By...	Modified By...
HexMap	class/HashMap	HexMap.java	MainMap, DiplomacyMap	HUDController, ...
UnitPool	Sorted TreeMap	UnitPool.java	Movement Calculator, Networking, MainMap, etc.	HUDController

## 5 Requirements Traceability

### 5.1 Movement

**Requirements Description** Our requirement for movement was that a unit would be selected from the GUI and the GUI would highlight all available moves for the given unit. The player could then select the desired location for movement and the unit would move there.

**Implementation Description** Our implementation of movement uses recursion to generate a list of available moves that are highlighted in the GUI. The moves are then displayed as highlighted hexes. When the controlling player then right-clicks the desired hex (within the highlighted set), the unit moves to the indicated hex.

**Differences** There is no difference between our requirement for movement and our implementation of movement.

### 5.2 Traceability Analysis

[Describe the consistency of our requirements descriptions and implementation in general]

## 6 Appendix A