



Swords and Sorcery Implementation Description
University of Idaho, CS 383, Spring 2014
May 8, 2014

1 Introduction and Document Description

This is a description of the Swords and Sorcery implementation, both in general and the implementation of major code modules.

This document particularly describes what was not covered in the design documentation, as well as places where implementation differs from design.

Sections are:

- Implemetation Overview
- Deployment, System Requirements, and Libraries
- Building
- Major Code Modules

2 Implementation Overview

Swords and Sorcery is programmed in Java 8 (after switching from Java 7), and is cross platform across Windows, Mac and Linux.

It uses a 2D top-down view and graphics based on the physical game by SPI, has a GUI programmed in JavaFX and swing, and some TCP networking support.

Unfortunately the implementation remains incomplete, so while some basic functionality exists, users will find it impossible to face eachother in battle over the internet.

What works or partially works (to the best of my knowledge) includes:

1. Starting a new game (partial)
2. Selecting a Scenario
3. End Inter-Phase
4. Move
5. Teleport
6. Select Unit From Stack
7. Attack
8. Advancing Units (partial)

9. Retreating (partial
10. View Unit Statistics
11. Spellcasting (partial)
12. Starting a client
13. Starting a server
14. Connecting to a server and communicating back and forth
15. Viewing Army Units, Terrain, or basic Hex Edges on the Main Map
16. Viewing a blank Diplomacy Map
17. Starting a server
18. Seeing the solar display or game phases change when ending a turn

What does not work (to the best of my knowledge) includes:

1. Join Game
2. Set Up
3. Resume Game
4. Save Game
5. Select Ally Candidate
6. Carry
7. Choose Leader
8. Spend Combat Manna
9. Rally
10. Manna Transfer
11. Diplomacy or Emissaries or Prisoners
12. Sacrifice
13. Dragon Blockades
14. Game State Synchronization between clients
15. Special Hex Rendering
16. Character or Monster Rendering
17. MiniMap or Diplomacy Map
18. Random Events
19. Starting a server

3 Running, Deployment, System Requirements, and Libraries

Swords and Sorcery requires the Java 8 JRE installed to run. This must be installed by the user independantly before trying to launch the game.

There is no installer package. The program takes the form of two .jar files (one for the client, and one for the server), along with a library folder and a resources folder.

In Windows the user should be able to launch the program by double clicking one of these .jar files.

In other supported operating systems the user should be able to launch the program with Java from the command line, with one of the following commands to launch the client or server respectively:

1. `java -jar client.jar`
2. `java -jar server.jar`

The program must be launched from the command line in this manner if the user wishes to view debug output.

The only required libraries are

- json-simple 1.1.1
- controlsfx 8.0.5

.jar distributions of these two libraries are included.

Swords and Sorcery isn't the fastest Java code on the block, but should be runnable by most contemporary systems running Windows, Mac, or Linux.

The folder for a swordsrc distribution should contain the following:

1. lib - containing library jars
2. resources
3. client.jar
4. server.jar

4 Building

Swords and Sorcery is hosted on github. If git is installed then the source can be downloaded with the following command:

```
git clone https://github.com/cjeffery/sworsorc.git
```

Swords and Sorcery can be compiled from inside Netbeans 8 by selecting either the `default config` or the `Game` build targets to build the client. The server can be built by selecting the `Server` target.

Other build targets exist for debugging or legacy reasons and should be ignored.

Alternatively Swords and Sorcery can be built from the command line with ant, using a build script similar to the following:

```
ant -f build.xml -q -Dconfig=Game jar ant -f build.xml -q -Dconfig=Server jar
```

to build the client and server respectively.

Be aware that however the project is built, both client and server will build a file called `sworsorc.jar`

If both client and server have to exist side by side, then the `.jar` files will have to be renamed to avoid overwriting eachother.

5 Major Code Modules

Swords and Sorcery has several major code modules. Amongst them the following have interesting enough implementations to bear discussing:

- The JavaFX HUD
- The Map Rendering and the Map View Code
- The Networking System
- The Map File Format
- The Movement Calculator
- Various Gameplay Classes

6 The JavaFX HUD

JavaFX was chosen over swing for the GUI because it's newer and more active than swing. And because it supports scaling natively (as opposed to needing to use kludges to scale stuff in swing).

JavaFX organizes user interfaces into Stages and Scenes. A stage displays a scene. Very theatrical.

JavaFX uses .fxml files to describe interfaces. These can be thought of as similar to HTML.

mainMenu.fxml describes the layout for the Main Options menu which is the first menu that is seen on program launch.

Likewise hud.fxml describes the layout of the actual game screen.

JavaFX also has classes called Controller Classes, that determine the behavior of programs that use these layouts.

In our project MainMenuController.java controls the Main Menu, and is in charge of, for instance, calling a function that actually starts the game when the user hits the "Start Game" button.

HUDController likewise controls the Main Game screen and has several notable features:

- Load the game map into it's panel
- Update the Sun Position Display at the end of every turn
- Select units when the map is clicked on. And display their stats
- Send messages from the chat box to the server, and vice versa

7 JavaFX MapView interaction

The GUI was switched to JavaFX partway through the project.

This proved a challenge for the Map View implementation, as there are unique challenges using swing widgets in JavaFX based code.

Passable support was fortunately very doable using the SwingNode class, as implemented by TODO: WHO DID THIS?

But one unresolved implementation issue was threading concerns.

Any interaction between swing and JavaFX has to be done on the appropriate thread. But there wasn't enough time to resolve these threading concerns.

The code seems to work OK, but this bug could conceivably lead to weird or inexplicable behavior on certain systems or edge cases.

8 The Map Rendering Code and the Map View

None of the Map Rendering code or Map View code was designed. It was just pulled out of thin air, using the time-honored alchemical process of spontaneous generation.

Fortunately this worked pretty well, as Java's libraries dictate a lot of the design up front, and I (Colin) have had some experience in the past with Java swing programming.

8.1 The Map Rendering Code

There are a few questionable design decisions, and a bit of duplicate code, but overall it worked pretty well and the implementation didn't end up inherently broken.

The Map Rendering code is done with Java's swing framework. All rendering is done onto standard swing Graphics2D objects that are passed in from the Map View.

It consists of two main classes that work in similar ways:

1. UnitPainter
2. HexPainter

Both of these classes are similar, and if they were ever refactored it might make sense to have them both inherit from the same class.

Both classes have methods that accept a Graphics2D object from Java's 2D API to render on to.

Both classes load a variety of PNG images from disk to assist in rendering. Most of the terrain images were drawn by Joe Higley. The unit images were drawn by Colin Clifford.

HexPainter is in charge of rendering Hexagons and edges, and passes off Unit rendering to UnitPainter.

Unit Rendering involves drawing a partially transparent unit icon, and (in the case of Army Units) a status string.

Due to time constraints only Army Units are mostly supported. With characters being stubbed in and looking weird.

Edges are rendering using simple straight colored lines using swing. There's a bit of hexagon math to prevent two elements of the same edge from obscuring each other, and to draw roads / trails from the center of the hexagon to the edge.

8.2 The Map View Code

Most of the Map View code is in a single class called (appropriately enough) `MapView`.

`MapView` is a Swing widget, but the GUI is JavaFX based. So the GUI wraps `MapView` inside a `SwingNode` object.

`MapView` does two main things:

1. Implement various swing widget methods (most notably `PaintComponent`)
2. Contain methods for necessary math for determining hexagon tiling

`MapView` implements scrollable, so it can be added to a `JScrollPane` to support scrolling.

The `PaintComponent` method is what interacts with the Map Rendering code.

The hexagon tiling math is interesting

8.2.1 Hexagon Math

Hexagon math was cobbled together from various sources on the internet and frenzied scribbles on note-paper.

It's honestly pretty hairy, so I tried to include helpful comments in `MapView`.

I will not fully describe all the hexagon math here, but I'll share the general principles.

Hexagons are oriented such that the top and bottom are horizontal lines, as per the physical Swords and Sorcery map.

The width of one hexagon is 64px. But as columns fit together smoothly the distance between a column and it's neighbors is 3/4ths that.

The height of a hexagon is the radius (32px) times the square root of 3.

But the key to hexagon tiling was this stackoverflow post: <http://gamedev.stackexchange.com/a/20762>

Which is to say, Hexagon picking involves converting between hexagon shaped and rectangle shaped tilings. Pretty cool.

With this I was able to tile hexagons graphically, and convert mouse coordinates to hexagons or hexagon edges.

8.3 Interaction Between MapView and Map Rendering

The Map Rendering code has three main entry points:

1. Draw a hexagon
2. Draw a hexagon edge
3. Highlight a hexagon

Each of these take a Graphics2D object that is assumed to be pre-translated so that the Rendering Code only has to draw off of the origin.

The first two cases used to be merged, but it was important to avoid drawing a given edge twice, and to avoid an edge being obscured by a neighboring hexagon.

So MapView takes the following passes:

1. Requests the Map Rendering code to draw all the hexagons
2. Requests the Map Rendering code to highlight any hexagons that need highlighting
3. Requests the Map Rendering code to draw all the edges

This "layered" approach gives a pretty smooth look, where nothing draws on top of stuff it shouldn't too much.

9 The Networking System

Unfortunately the networking system didn't get very well integrated with the rest of the codebase. It should be pointed out that despite this the Network implementation is good code and had a lot of work put into it.

There is some limited integration, and it can be used for communicating between different clients. However clients cannot effectively play a game together.

Networking is divided into client/server. With "thick" clients. The server mainly exists to forward messages between clients, or make decisions that need to be made on the server.

One effect of this is that cheating is trivial, fortunately the game isn't implemented enough to make cheating worthwhile.

Network messages have a TAG and a FLAG. These are the core of the networking protocol, a TAG is a category and a FLAG is the particular message type.

Network messages can pass an array of Java objects. Anything that can be serialized with the Java Serialization library.

10 The Map File Format

The MainMap data is stored in a large XML file

It has the following information including

- Hex ID
- Whether it's a capital, town, city, or castle hex
- Whether it's a town hex
- Neighboring Hex IDs
- Province Name
- Whether it's a vortex or portal
- What sorts of hex edges there are
- Whether the hex has a name

11 The Movement Calculator

The MovementCalculator class has 12 methods and two static fields. The static fields are for optimization of movement and retreating. The optimization of movement uses the allowanceCache HashMap to hold only the fast routes that the method getValidMoves(...) finds. getValidMoves(...) is a public static method that recursively populates an ArrayList of MapHex objects based on constraints that apply to the unit that is moving. These constraints include terrain types, hex edges, enemy occupation and zone of control, and the movement allowance allotted to the unit per turn. The hashmap that optimizes

the `getValidMoves(...)` method holds each valid `MapHex` that the unit can reach as a key and the unit's remaining movement allowance for moving into that hex. This allows a dynamic movement system, where a player may move a unit twice or more in a movement phase, while the unit still remains in the bound of its movement allowance. The other field in `MovementCalculator`, `retreatAllowanceCache`, serves a similar purpose as allowance cache, but is used by the retreat methods. Retreating is also done recursively, and all valid moves for a retreating unit are generated and added to the hashmap, `retreatAllowanceCache`. From there, the hash map is filtered according to the S&S rules for retreating from combat. There is a stated hierarchy of locations that a unit can retreat to, which the method filters for and follows, ultimately generating and returning a list of hexes that a unit can retreat to. If the size of the `ArrayList` returned is zero, or if the `ArrayList` is null, then the unit has no valid retreat locations, and should be destroyed. The remaining methods that are undescribed here are simply helper methods for the main methods, or wrappers, as in the case of `wrapperMovement(...)`.

12 Gameplay Model Classes

12.1 Army Units

When implementation came around we discovered that having sub-classes for every different army unit sub-type was not practical. Instead a single army unit is with different flags to describe the unit is used. The main super class of movable units is still used with the sub-classes army unit, character, and monster but then stops there. Also a race and nation variable unit had to be added to the class in order for things like the movement calculator to work.

12.2 Characters

Characters have a series of variables needed for spell casting, leadership, and diplomacy. Something new is the idea of a spell book, a class that reads it's character's information to determine what spells can be cast. In order for this class to work properly the character class contains a spell book and the spell book contains its corresponding character. In order for the scenario reader to work properly a character creator was made in the character class that takes the name of a character, finds the matching data on the character, and creates a character with the data.

12.3 Spells

For spells to work properly they needed to exist separate from the main program. This was implemented by creating a separate GUI for spells. When a character "casts" a spell, the spell book class is called upon which created a GUI with all spell options that

character has. Once a spell is chosen the user has the option of reading the details of the spell or casting the spell.

Once a spell is "cast", the specific spell class will be called and ask to select target(s) to cast. After a target is selected, limitations will be checked to see if succeed to cast the spell or not. If succeed, the effects of the spell are added to the games state. If not, there are two choise: "Recast" depending on different limitations or "OK" to terminate current spell implementation. Whatever the spell is cast or not, options that cast other spells or end spell phase are available.

12.4 Combat

12.4.1 LaunchCombat

The LaunchCombat functin first takes inputs Movable units, this connects with the HUD-Controller class: left mouse click to get selected stack, and right mouse click to get target stack. When a player in the combat phase, they should pick both units then press 'A' to launch the combat. When clicked A button, first it shows dialogs to ask the attacker player if they want to add friendly units which surround the defender units into the combat, and then it will pop out units detail include Attackers strength, Defenders strength, Defenders Terrain type, and Defenders strength after Terrain Type bonus with a confirmation dialog. The certain player should click yes button for showing combat result, or click no for doing nothing. If the player clicks yes button, the Combat result will shows as a notification on the right bottom conner, with this result both attacker player and defender player may meet three situations: Nothing Change, Retreat, Elimination. If the combat result returns 0, then the certain player does not need to do any reactions from this combat, if the result is a negative number, the certain player should eliminate numbers(since result is a integer number) of units from the units list; if the result is a positive number, then the player should decide to eliminate the unit OR retreat the unit.

12.4.2 Retreat

First the result came from the LaunchCombat, so the player can get its result value(negative, positive integer, or zero), if the result is a positive number then the player should decide to retreat the units or not, if not, then they should eliminate the unit, if yes, execute the Retreat function. The retreat function will send necessary input for the method getRetreatMove in the class Movement Calculator, so it can get which hexes that the certain units can move to. And it will highlight those available hexes with red color, then the units will be randomly assigned to move to an available hex.

12.5 Unit Pool

Unitpool wasn't in the design.

It was added as a design modification during one of our sprints. The rules of the game required tracking of units, manipulation of persistent units, a way to create, and destroy those units. The class name is UnitPool.

12.6 HexStack

HexStack was originally going to be named Stack, and a component of a Hex.

In the implementation it exists to aggregate units in the UnitPool.

It's named HexStack instead of Stack to avoid a name conflict with the Java library.