


PRACTICAL WEEK-12

1 . Implement the **Producer-Consumer problem** using counting semaphores and POSIX threads. Evaluate synchronization correctness and system throughput under different buffer sizes.

Aim : To implement producer-consumer synchronization using POSIX threads and counting semaphores, and compare throughput for different buffer sizes.

Program :



```
GNU nano 7.2
#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>
#include <semaphore.h>
#include <unistd.h>
#include <time.h>

#define ITEMS 100000

int *buffer;
int buffer_size;

int in = 0;
int out = 0;

sem_t empty;
sem_t full;

pthread_mutex_t mutex;

void *producer(void *arg)
{
    for (int i = 0; i < ITEMS; i++)
    {
        sem_wait(&empty);

        pthread_mutex_lock(&mutex);

        buffer[in] = i + 1;
        in = (in + 1) % buffer_size;

        pthread_mutex_unlock(&mutex);

        sem_post(&full);
    }

    return NULL;
}

void *consumer(void *arg)
{
    long long sum = 0;

    for (int i = 0; i < ITEMS; i++)
    {
        sem_wait(&full);
```



alekhya@Alekhyareddy: ~/OS



GNU nano 7.2

```
        sem_wait(&full);

        pthread_mutex_lock(&mutex);

        sum += buffer[out];
        out = (out + 1) % buffer_size;

        pthread_mutex_unlock(&mutex);

        sem_post(&empty);
    }

    printf("Consumer processed %d items.\n", ITEMS);
    printf("Consumer checksum: %lld\n", sum);

    return NULL;
}

int main(int argc, char *argv[])
{
    pthread_t producer_thread;
    pthread_t consumer_thread;

    struct timespec start, end;

    if (argc != 2)
    {
        printf("Usage: %s <buffer_size>\n", argv[0]);
        return 1;
    }

    buffer_size = atoi(argv[1]);

    if (buffer_size <= 0)
    {
        printf("Buffer size must be greater than 0.\n");
        return 1;
    }

    buffer = malloc(buffer_size * sizeof(int));

    if (buffer == NULL)
    {
        perror("malloc");
        return 1;
    }
}
```

Help
 Exit


Write Out
 Read File

Where Is
 Replace

Cut
 Paste



alekhya@Alekhyareddy: ~/OS



GNU nano 7.2

```
sem_init(&empty, 0, buffer_size);
sem_init(&full, 0, 0);

pthread_mutex_init(&mutex, NULL);

printf("Producer-Consumer Problem\n");
printf("-----\n");
printf("Buffer size : %d\n", buffer_size);
printf("Items      : %d\n\n", ITEMS);

clock_gettime(CLOCK_MONOTONIC, &start);

pthread_create(&producer_thread,
              NULL,
              producer,
              NULL);

pthread_create(&consumer_thread,
              NULL,
              consumer,
              NULL);

pthread_join(producer_thread, NULL);
pthread_join(consumer_thread, NULL);

clock_gettime(CLOCK_MONOTONIC, &end);

double elapsed =
    (end.tv_sec - start.tv_sec) +
    (end.tv_nsec - start.tv_nsec) / 1000000000.0;

double throughput = ITEMS / elapsed;

printf("\nSynchronization completed successfully.\n");
printf("Execution time : %.6f seconds\n", elapsed);
printf("Throughput    : %.2f items/second\n", throughput);

sem_destroy(&empty);
sem_destroy(&full);
pthread_mutex_destroy(&mutex);

free(buffer);

return 0;
```

}

^G Help
^X Exit

^O Write Out
^R Read File

^W Where Is
^_ Replace

^K Cut
^U Paste

Output :

```
alekhya@Alekhyareddy: ~/OS × + v
alekhya@Alekhyareddy:~$ cd ~/OSSP
alekhya@Alekhyareddy:~/OSSP$ nano producer_consumer.c
alekhya@Alekhyareddy:~/OSSP$ gcc -Wall -Wextra -pthread producer_consumer.c -o producer_consumer
alekhya@Alekhyareddy:~/OSSP$ ./producer_consumer 10
Producer-Consumer Problem
-----
Buffer size : 10
Items       : 100000

Consumer processed 100000 items.
Consumer checksum: 5000050000

Synchronization completed successfully.
Execution time : 0.935473 seconds
Throughput    : 106897.74 items/second
alekhya@Alekhyareddy:~/OSSP$ ./producer_consumer 1
Producer-Consumer Problem
-----
Buffer size : 1
Items       : 100000

Consumer processed 100000 items.
Consumer checksum: 5000050000

Synchronization completed successfully.
Execution time : 4.511584 seconds
Throughput    : 22165.16 items/second
alekhya@Alekhyareddy:~/OSSP$ ./producer_consumer 5
Producer-Consumer Problem
-----
Buffer size : 5
Items       : 100000

Consumer processed 100000 items.
Consumer checksum: 5000050000

Synchronization completed successfully.
Execution time : 1.014745 seconds
Throughput    : 98546.90 items/second
alekhya@Alekhyareddy:~/OSSP$ ./producer_consumer 10
Producer-Consumer Problem
-----
Buffer size : 10
Items       : 100000

Consumer processed 100000 items.
Consumer checksum: 5000050000

Synchronization completed successfully.
Execution time : 0.873530 seconds
Throughput    : 114478.04 items/second
alekhya@Alekhyareddy:~/OSSP$ ./producer_consumer 50
Producer-Consumer Problem
-----
Buffer size : 50
Items       : 100000

Consumer processed 100000 items.
Consumer checksum: 5000050000

Synchronization completed successfully.
Execution time : 0.179109 seconds
Throughput    : 558320.70 items/second
```

```

alekhya@Alekhyareddy:~/OSSP$ ./producer_consumer 100
Producer-Consumer Problem
-----
Buffer size : 100
Items       : 100000

Consumer processed 100000 items.
Consumer checksum: 5000050000

Synchronization completed successfully.
Execution time : 0.097906 seconds
Throughput     : 1021392.19 items/second
alekhya@Alekhyareddy:~/OSSP$ |

```

2 . Design a deadlock scenario involving multiple threads competing for shared resources. Demonstrate deadlock occurrence, identify the four necessary conditions for deadlock, and implement a deadlock prevention strategy using **resource ordering**.

Aim : To demonstrate a deadlock between multiple POSIX threads competing for shared mutex resources and prevent the deadlock by acquiring resources in a fixed order.

Program :

```

GNU nano 7.2
#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>
#include <unistd.h>

pthread_mutex_t resource1;
pthread_mutex_t resource2;

void *thread1_function(void *arg)
{
    (void)arg;

    printf("Thread 1: Trying to acquire Resource 1\n");
    pthread_mutex_lock(&resource1);

    printf("Thread 1: Acquired Resource 1\n");
    sleep(1);

    printf("Thread 1: Trying to acquire Resource 2\n");
    pthread_mutex_lock(&resource2);

    printf("Thread 1: Acquired Resource 2\n");

    pthread_mutex_unlock(&resource2);
    pthread_mutex_unlock(&resource1);

    return NULL;
}

```



alekhya@Alekhyareddy: ~/OS



GNU nano 7.2

```
}  
  
void *thread2_function(void *arg)  
{  
    (void)arg;  
  
    printf("Thread 2: Trying to acquire Resource 2\n");  
    pthread_mutex_lock(&resource2);  
  
    printf("Thread 2: Acquired Resource 2\n");  
    sleep(1);  
  
    printf("Thread 2: Trying to acquire Resource 1\n");  
    pthread_mutex_lock(&resource1);  
  
    printf("Thread 2: Acquired Resource 1\n");  
  
    pthread_mutex_unlock(&resource1);  
    pthread_mutex_unlock(&resource2);  
  
    return NULL;  
}  
  
int main()  
{  
    pthread_t thread1, thread2;  
  
    pthread_mutex_init(&resource1, NULL);  
    pthread_mutex_init(&resource2, NULL);  
  
    printf("Deadlock Demonstration\n");  
    printf("-----\n");  
  
    pthread_create(&thread1, NULL, thread1_function, NULL);  
    pthread_create(&thread2, NULL, thread2_function, NULL);  
  
    pthread_join(thread1, NULL);  
    pthread_join(thread2, NULL);  
  
    pthread_mutex_destroy(&resource1);  
    pthread_mutex_destroy(&resource2);  
  
    printf("Program completed.\n");  
  
    return 0;  
}
```

Help
 Exit

Write Out
 Read File

Where Is
 Replace

Cut
 Paste

Tab
 Jump



alekhya@Alekhyareddy: ~/OS



GNU nano 7.2

```
#include <stdio.h>
#include <stdlib.h>
#include <pthread.h>
#include <unistd.h>

pthread_mutex_t resource1;
pthread_mutex_t resource2;

void *thread1_function(void *arg)
{
    (void)arg;

    printf("Thread 1: Acquiring Resource 1\n");
    pthread_mutex_lock(&resource1);

    printf("Thread 1: Acquired Resource 1\n");
    sleep(1);

    printf("Thread 1: Acquiring Resource 2\n");
    pthread_mutex_lock(&resource2);

    printf("Thread 1: Acquired Resource 2\n");

    printf("Thread 1: Using both resources\n");
    sleep(1);

    pthread_mutex_unlock(&resource2);
    pthread_mutex_unlock(&resource1);

    printf("Thread 1: Resources released\n");

    return NULL;
}

void *thread2_function(void *arg)
{
    (void)arg;

    /*
     * Resource ordering:
     * Resource 1 must always be acquired before Resource 2.
     */

    printf("Thread 2: Acquiring Resource 1\n");
    pthread_mutex_lock(&resource1);

    printf("Thread 2: Acquired Resource 1\n");
    sleep(1);

    printf("Thread 2: Acquiring Resource 2\n");
    pthread_mutex_lock(&resource2);

    printf("Thread 2: Acquired Resource 2\n");
```



alekhya@Alekhyareddy: ~/OS



GNU nano 7.2

```
* Resource ordering:
* Resource 1 must always be acquired before Resource 2.
*/

printf("Thread 2: Acquiring Resource 1\n");
pthread_mutex_lock(&resource1);

printf("Thread 2: Acquired Resource 1\n");
sleep(1);

printf("Thread 2: Acquiring Resource 2\n");
pthread_mutex_lock(&resource2);

printf("Thread 2: Acquired Resource 2\n");

printf("Thread 2: Using both resources\n");
sleep(1);

pthread_mutex_unlock(&resource2);
pthread_mutex_unlock(&resource1);

printf("Thread 2: Resources released\n");

return NULL;
}

int main()
{
    pthread_t thread1, thread2;

    pthread_mutex_init(&resource1, NULL);
    pthread_mutex_init(&resource2, NULL);

    printf("Deadlock Prevention Using Resource Ordering\n");
    printf("-----\n");

    printf("Resource order: Resource 1 -> Resource 2\n\n");

    pthread_create(&thread1, NULL, thread1_function, NULL);
    pthread_create(&thread2, NULL, thread2_function, NULL);

    pthread_join(thread1, NULL);
    pthread_join(thread2, NULL);

    pthread_mutex_destroy(&resource1);
    pthread_mutex_destroy(&resource2);

    printf("\nAll threads completed successfully.\n");
    printf("Deadlock prevented using resource ordering.\n");

    return 0;
}
```

Help
 Exit

Write Out
 Read File

Where Is
 Replace

Cut
 Paste

Output :

```
alekhya@Alekhyareddy: ~/OS X + v
alekhya@Alekhyareddy:~$ cd ~/OSSP
alekhya@Alekhyareddy:~/OSSP$ nano deadlock.c
alekhya@Alekhyareddy:~/OSSP$ gcc -Wall -Wextra -pthread deadlock.c -o deadlock
alekhya@Alekhyareddy:~/OSSP$ ./deadlock
Deadlock Demonstration
-----
Thread 1: Trying to acquire Resource 1
Thread 2: Trying to acquire Resource 2
Thread 2: Acquired Resource 2
Thread 1: Acquired Resource 1
Thread 2: Trying to acquire Resource 1
Thread 1: Trying to acquire Resource 2
^C
alekhya@Alekhyareddy:~/OSSP$ cd ~/OSSP
alekhya@Alekhyareddy:~/OSSP$ nano deadlock_prevention.c
alekhya@Alekhyareddy:~/OSSP$ gcc -Wall -Wextra -pthread deadlock_prevention.c -o deadlock_prevention
alekhya@Alekhyareddy:~/OSSP$ ./deadlock_prevention
Deadlock Prevention Using Resource Ordering
-----
Resource order: Resource 1 -> Resource 2

Thread 2: Acquiring Resource 1
Thread 2: Acquired Resource 1
Thread 1: Acquiring Resource 1
Thread 2: Acquiring Resource 2
Thread 2: Acquired Resource 2
Thread 2: Using both resources
Thread 2: Resources released
Thread 1: Acquired Resource 1
Thread 1: Acquiring Resource 2
Thread 1: Acquired Resource 2
Thread 1: Using both resources
Thread 1: Resources released

All threads completed successfully.
Deadlock prevented using resource ordering.
alekhya@Alekhyareddy:~/OSSP$ |
```

