


Function fitting


Lecture 4; Reading: ISLR sections 2.1, 3.2.1, 3.5


IFT6758, Fall 2020





Leveraging Input → Output relationship in data





Leveraging Input → Output relationship in data

Examples:

- Genetic profile → Chance of developing disease
- Person's characteristics → Whether they'll vote
- Marketing plan → Total sales amount
- Image pixel values → What's in the image

Leveraging Input → Output relationship in data

Examples:

- Genetic profile → Chance of developing disease
- Person's characteristics → Whether they'll vote
- Marketing plan → Total sales amount
- Image pixel values → What's in the image

Mathematical expression

- $x_i = (x_{i_1}, \dots, x_{i_p}) \leftarrow \text{inputs}$
- $y_i = f(x_i) \leftarrow \text{inputs to output relationship}$



Observed and predicted values






Observed and predicted values


$$y_i = f(x_i) + \epsilon_i$$

Observed and predicted values


$$y_i = f(x_i) + \epsilon_i$$



Observed and predicted values

$$\rightarrow y_i = f(x_i) + \epsilon_i$$

Why is this decomposition?




Observed and predicted values

➤ $y_i = f(x_i) + \epsilon_i$

Why is this decomposition?

➤ f describes **systematic variation** in y_i




Observed and predicted values

➤ $y_i = f(x_i) + \epsilon_i$

Why is this decomposition?

- f describes **systematic variation** in y_i
- ϵ_i reflects variations whose source is unknown to us. Consider coin tosses.





Why care?





Why care?

- **Why not just visualize the data we have?**
- 



Why care?

- Why not just visualize the data we have?
- Reason 1: Prediction
 - We may want the y_i corresponding to an input x_i
 - Inputs may be much easier to collect than outputs
- Reason 2: Inference
 - We may care about the form of f , for personal understanding
 - e.g., is a particular input relevant at all?



Why care?

- Why not just visualize the data we have?
- Reason 1: Prediction
 - We may want the y_i corresponding to an input x_i
 - Inputs may be much easier to collect than outputs
- Reason 2: Inference
 - We may care about the form of f , for personal understanding
 - e.g., is a particular input relevant at all?

We want **quantitative estimates**, not visual summaries



Estimates and Predictions






Estimates and Predictions

- ▶ In reality, we won't know f
- 



Estimates and Predictions


- In reality, we won't know f
 - We estimate it from data and call the result \hat{f}
- 

Estimates and Predictions

- In reality, we won't know f
- We estimate it from data and call the result \hat{f}
- To predict y_i for some input x_i , we'd use $\hat{y} = \hat{f}(x_i)$

Estimates and Predictions

- In reality, we won't know f
- We estimate it from data and call the result \hat{f}
- To predict y_i for some input x_i , we'd use $\hat{y} = \hat{f}(x_i)$





Sources of error






Sources of error

- **Approximation error:** \hat{f} isn't close to f
 - This error is *reducible* (use a better algorithm)


Sources of error

- **Approximation error:** \hat{f} isn't close to f
 - This error is *reducible* (use a better algorithm)





Sources of error

- **Approximation error:** \hat{f} isn't close to f
 - This error is *reducible* (use a better algorithm)
- **Irreducible error:** y_i isn't close to $f(x_i)$
 - Incur this error even if f were perfectly known



Sources of error

- **Approximation error:** \hat{f} isn't close to f
 - This error is *reducible* (use a better algorithm)
- **Irreducible error:** y_i isn't close to $f(x_i)$
 - Incur this error even if f were perfectly known







Extendable to high dimension



Extendable to high dimension





How to find \hat{f} ?






How to find \hat{f} ?

- Propose a model family F : e.g., set of all linear functions of x_i



How to find \hat{f} ?


- Propose a model family F : e.g., set of all linear functions of x_i
 - Define a procedure to choose $\hat{f} \in F$ based on the data
- 

How to find \hat{f} ?

- Propose a model family F : e.g., set of all linear functions of x_i
- Define a procedure to choose $\hat{f} \in F$ based on the data
 - E.g., the choice \hat{f} that minimizes $\sum_i (y_i - \hat{f}(x_i))^2$

How to find \hat{f} ?

- Propose a model family F : e.g., set of all linear functions of x_i
- Define a procedure to choose $\hat{f} \in F$ based on the data
 - E.g., the choice \hat{f} that minimizes $\sum_i (y_i - \hat{f}(x_i))^2$





Find a 'good enough' fit






Find a 'good enough' fit

- Ultimately, you want your **model to perform well on out-of-sample data**

Find a 'good enough' fit

- Ultimately, you want your **model to perform well on out-of-sample data**




Find a 'good enough' fit

➤ Ultimately, you want your **model to perform well on out-of-sample data**

➤ **Bias-Variance trade-off:**


➤ **Bias** \equiv model inaccuracy

➤ **Variance:** Different samples \longrightarrow Different \hat{f}



Find a 'good enough' fit

- Ultimately, you want your **model to perform well on out-of-sample data**
- **Bias-Variance trade-off:**
 - Bias \equiv model inaccuracy
 - Variance: Different samples \longrightarrow Different \hat{f}
- **Incurring some bias can lead to better stability and overall better predictions**





Model Flexibility - Takeaways






Model Flexibility - Takeaways

- If you **don't have too many samples**, you should prefer a **simpler model**
- 




Model Flexibility - Takeaways

- If you **don't have too many samples**, you should prefer a **simpler model**
 - If you have **many samples**, you can afford a **more complex model**
- 



Model Flexibility - Takeaways

- If you **don't have too many samples**, you should prefer a **simpler model**
 - If you have **many samples**, you can afford a **more complex model**
 - We'll need **some sort of mechanism** to tell which regime we're in
- 



Model Flexibility - Takeaways

- If you **don't have too many samples**, you should prefer a **simpler model**
- If you have **many samples**, you can afford a **more complex model**
- We'll need **some sort of mechanism** to tell which regime we're in
- Examples of different model families