



[SWE2015-41] Introduction to Data Structures (자료구조개론)

# Red-Black Trees


**Department of Computer Science and Engineering**

**Instructor:** Hankook Lee (이한국)

# (Recap) Binary Search Trees (BSTs)




- **Binary Search Tree (BST)** satisfies the following conditions:
  1. Any two nodes **A** and **B** are comparable: **A** < **B**, **A** > **B**, or **A** == **B**
    - E.g., you can compare numbers numerically or strings in the alphabetical/dictionary order
    - Such a comparable value of a node is called **KEY** value



# (Recap) Binary Search Trees (BSTs)




- **Binary Search Tree (BST)** satisfies the following conditions:
  2. For any node **X**, all nodes in its **left subtree** are less than **X**
  3. For any node **X**, all nodes in its **right subtree** are greater than **X**



# (Recap) Binary Search Trees (BSTs)




- **Binary Search Tree (BST)** satisfies the following conditions:
  2. For any node **x**, all nodes in its **left subtree** are less than **x**
  3. For any node **x**, all nodes in its **right subtree** are greater than **x**



# (Recap) Balanced Binary Trees




- The **balance factor** of a node **X** in a binary tree is defined by  
$$\text{balance}(\mathbf{X}) = \text{height}(\text{left subtree}) - \text{height}(\text{right subtree})$$



# (Recap) Balanced Binary Trees




- The **balance factor** of a node **X** in a binary tree is defined by  
$$\text{balance}(\mathbf{X}) = \text{height}(\text{left subtree}) - \text{height}(\text{right subtree})$$



# (Recap) Balanced Binary Trees




- The **balance factor** of a node **X** in a binary tree is defined by
$$\text{balance}(\mathbf{X}) = \text{height}(\text{left subtree}) - \text{height}(\text{right subtree})$$



# (Recap) Balanced Binary Trees



- The **balance factor** of a node **X** in a binary tree is defined by
$$\text{balance}(\mathbf{X}) = \text{height}(\text{left subtree}) - \text{height}(\text{right subtree})$$
- A binary tree  $T$  is **balanced** if  $|\text{balance}(\mathbf{X})| \leq 1$  for any node **X**






# (Recap) Balanced Binary Trees




- The **balance factor** of a node **X** in a binary tree is defined by
$$\text{balance}(\mathbf{X}) = \text{height}(\text{left subtree}) - \text{height}(\text{right subtree})$$
- A binary tree  $T$  is **balanced** if  $|\text{balance}(\mathbf{X})| \leq 1$  for any node **X**




# (Recap) AVL Trees - Rotations



(Q) How to re-balance the tree after insertion/deletion?




Left-Left Case



LL Rotation


Updated Tree




# (Recap) AVL Trees - Rotations



(Q) How to re-balance the tree after insertion/deletion?




Right-Right Case



RR Rotation


Updated Tree




# (Recap) AVL Trees - Rotations




(Q) How to re-balance the tree after insertion/deletion?



Left-Right Case




Updated Tree




# (Recap) AVL Trees - Rotations



(Q) How to re-balance the tree after insertion/deletion?




Right-Left Case



RL Rotation

Updated Tree



# Red-Black Trees

---




- **Red-Black Tree** is another **self-balancing** BST
  - Its height is  $O(\log N)$  like AVL Tree
- Red-Black Tree should satisfy the following properties:
  1. Every node is either **red** or **black**
  2. The root node is always **black**
  3. All NULL leaf node are **black**
  4. Every **red** node has both the children colored in **black**
  5. Every **path from a given node to any of its leaf nodes** has an equal number of **black nodes**

# Red-Black Trees - Examples



## Red-Black Tree Properties

1. Every node is either **red** or **black**
2. The root node is always **black**
3. All NULL leaf node are **black**
4. Every **red** node has both the children colored in **black**
5. Every **path from a given node to any of its leaf nodes** has an **equal number of black nodes**



NOT a Red-Black Tree  
since (2) is violated


← NULL leaf nodes

# Red-Black Trees - Examples



## Red-Black Tree Properties

1. Every node is either **red** or **black**
2. The root node is always **black**
3. All NULL leaf node are **black**
4. Every **red** node has both the children colored in **black**
5. Every **path from a given node to any of its leaf nodes** has an **equal number of black nodes**



NOT a Red-Black Tree  
since (3)-(5) are violated

← NULL leaf nodes




# Red-Black Trees - Examples



## Red-Black Tree Properties

1. Every node is either **red** or **black**
2. The root node is always **black**
3. All NULL leaf node are **black**
4. Every **red** node has both the children colored in **black**
5. Every **path from a given node to any of its leaf nodes** has an **equal number of black nodes**



NOT a Red-Black Tree  
since (4)-(5) are violated


← NULL leaf nodes

# Red-Black Trees - Examples



## Red-Black Tree Properties

1. Every node is either **red** or **black**
2. The root node is always **black**
3. All NULL leaf node are **black**
4. Every **red** node has both the children colored in **black**
5. Every **path from a given node to any of its leaf nodes** has an **equal number of black nodes**



NOT a Red-Black Tree  
since (5) is violated


← NULL leaf nodes

# Red-Black Trees - Examples



## Red-Black Tree Properties

1. Every node is either **red** or **black**
2. The root node is always **black**
3. All NULL leaf node are **black**
4. Every **red** node has both the children colored in **black**
5. Every **path from a given node to any of its leaf nodes** has an **equal number of black nodes**



A Red-Black Tree


← NULL leaf nodes

# Red-Black Trees - Heights



- The black-height of a node is **the number of black nodes** in a path from the node to its leaf node

- $BH(A) = 3$
- $BH(B, C) = 2$
- $BH(D, E, F, G) = 2$
- $BH(H, I, J) = 1$



# Red-Black Trees - Heights

---



- The black-height of a node is **the number of black nodes** in a path from the node to its leaf node

**(Q)** Why the height of a red-black tree of  $N$  nodes =  $O(\log N)$  ?

# Red-Black Trees - Heights



- The black-height of a node is **the number of black nodes** in a path from the node to its leaf node

**(Q)** Why the height of a red-black tree of  $N$  nodes =  $O(\log N)$  ?

**(Step 1)** Any node  $X$  with height  $H(X)$  has  $BH(X) \geq H(X)/2$

- Consider a longest path from  $X$  to a leaf  $Y$

$$X=Z_1 \rightarrow Z_2 \rightarrow Z_3 \rightarrow \dots \rightarrow Z_{H(X)-2} \rightarrow Z_{H(X)-1} \rightarrow Y=Z_{H(X)}=NULL$$

# Red-Black Trees - Heights



- The black-height of a node is **the number of black nodes** in a path from the node to its leaf node

**(Q)** Why the height of a red-black tree of  $N$  nodes =  $O(\log N)$  ?

**(Step 1)** Any node  $X$  with height  $H(X)$  has  $BH(X) \geq H(X)/2$

- Consider a longest path from  $X$  to a leaf  $Y$

$$X=Z_1 \rightarrow Z_2 \rightarrow Z_3 \rightarrow \dots \rightarrow Z_{H(X)-2} \rightarrow Z_{H(X)-1} \rightarrow Y=Z_{H(X)}=NULL$$

- Since the properties (3) any NULL leaf nodes is black and (4) the children of any red node are black, the maximum number of red nodes in the path is  $H(X)/2$
- In other words, the minimum number of black nodes is  $H(X)/2$

# Red-Black Trees - Heights

---



- The black-height of a node is **the number of black nodes** in a path from the node to its leaf node

**(Q)** Why the height of a red-black tree of  $N$  nodes =  $O(\log N)$  ?

**(Step 2)** A subtree rooted at any node  $X$  has at least  $2^{\text{BH}(X)} - 1$  nodes

- By induction on  $H(X)$ , the height of  $X$




# Red-Black Trees - Heights



- The black-height of a node is **the number of black nodes** in a path from the node to its leaf node

**(Q)** Why the height of a red-black tree of  $N$  nodes =  $O(\log N)$  ?

**(Step 2)** A subtree rooted at any node  $X$  has at least  $2^{BH(X)} - 1$  nodes

- By induction on  $H(X)$ , the height of  $X$
- Base case:  $H(X)=1$   ← NULL leaf node

# Red-Black Trees - Heights




- The black-height of a node is **the number of black nodes** in a path from the node to its leaf node

**(Q)** Why the height of a red-black tree of  $N$  nodes =  $O(\log N)$  ?

**(Step 2)** A subtree rooted at any node  $X$  has at least  $2^{BH(X)} - 1$  nodes

- By induction on  $H(X)$ , the height of  $X$
- Inductive case:  
Assume the above statement is true when  $H(X) \leq h$ .  
If  $H(X) = h+1$  and  $X$  is **red**, then  $BH(X) = BH(L)$ , ...



# Red-Black Trees - Heights




- The black-height of a node is **the number of black nodes** in a path from the node to its leaf node

**(Q)** Why the height of a red-black tree of  $N$  nodes =  $O(\log N)$  ?

**(Step 2)** A subtree rooted at any node  $X$  has at least  $2^{BH(X)} - 1$  nodes

- By induction on  $H(X)$ , the height of  $X$
- Inductive case:  
Assume the above statement is true when  $H(X) \leq h$ .  
If  $H(X) = h+1$  and  $X$  is **black**, then  $BH(L, R) = BH(X) - 1, \dots$



# Red-Black Trees - Heights



- The black-height of a node is **the number of black nodes** in a path from the node to its leaf node

**(Q)** Why the height of a red-black tree of  $N$  nodes =  $O(\log N)$  ?

**(Step 1)** Any node  $X$  with height  $H(X)$  has  $BH(X) \geq H(X)/2$

**(Step 2)** A subtree rooted at any node  $X$  has at least  $2^{BH(X)} - 1$  nodes

$$N \geq 2^{BH(X)} - 1 \geq 2^{H(X)/2} - 1$$

$$2 \log(N+1) \geq H(X)$$

# (Recap) Height of Balanced Binary Trees




- The **balance factor** of a node  $X$  in a binary tree is defined by
$$\text{balance}(X) = \text{height}(\text{left subtree}) - \text{height}(\text{right subtree})$$
- A binary tree  $T$  is **balanced** if  $|\text{balance}(X)| \leq 1$  for any node  $X$

**(Q)** Why the height of a balanced binary tree of  $N$  nodes  $= O(\log N)$  ?

**(A)** A subtree rooted at any node  $X$  has at least  $2^{H(X)/2} - 1$  nodes

- By induction on  $H(X)$ , the height of  $X$
- Base case:  $H(X)=1$  and  $H(X)=2$



# (Recap) Height of Balanced Binary Trees




- The **balance factor** of a node  $X$  in a binary tree is defined by
$$\text{balance}(X) = \text{height}(\text{left subtree}) - \text{height}(\text{right subtree})$$
- A binary tree  $T$  is **balanced** if  $|\text{balance}(X)| \leq 1$  for any node  $X$

**(Q)** Why the height of a balanced binary tree of  $N$  nodes  $= O(\log N)$  ?

**(A)** A subtree rooted at any node  $X$  has at least  $2^{H(X)/2} - 1$  nodes

- By induction on  $H(X)$ , the height of  $X$
- Inductive case:  
Assume the above statement is true when  $H(X) \leq h$ .

$$\begin{aligned} N(h+1) &\geq 1 + N(h) + N(h-1) \\ &\geq 2^{h/2} + 2^{(h-1)/2} - 1 \\ &\geq 2^{(h+1)/2} - 1 \end{aligned}$$



# Red-Black Trees - Insertion

---



- How to insert a new node into a Red-Black tree?
  1. Insert an element as usual in the BST (i.e., replace NULL by the new node)
  2. Color the node **RED**
  3. Check if the properties of the red-black tree are violated
  4. If violated, modify the tree in the bottom-up direction

# Red-Black Trees - Insertion

---



- How to insert a new node into a Red-Black tree?
  1. Insert an element as usual in the BST (i.e., replace NULL by the new node)
  2. Color the node **RED**
  3. Check if the properties of the red-black tree are violated
  4. If violated, modify the tree in the bottom-up direction
- Which properties may be violated?
  1. Every node is either **red** or **black**
  2. The root node is always **black**
  3. All NULL leaf node are **black**
  4. Every **red** node has both the children colored in **black**
  5. Every **path from a given node to any of its leaf nodes** has an **equal number of black nodes**



# Red-Black Trees - Insertion

---




- How to insert a new node into a Red-Black tree?
  1. Insert an element as usual in the BST (i.e., replace NULL by the new node)
  2. Color the node **RED**
  3. Check if the properties of the red-black tree are violated
  4. If violated, modify the tree in the bottom-up direction
- Which properties may be violated?
  1. Every node is either **red** or **black**
  2. The root node is always **black**
  3. All NULL leaf node are **black**
  4. Every **red** node has both the children colored in **black**
  5. Every **path from a given node to any of its leaf nodes** has an equal number of **black nodes**

# Red-Black Trees - Insertion



- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **(Case 1)** **X** is not root, and its uncle is **red**



# Red-Black Trees - Insertion




- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **(Case 1)** **X** is not root, and its uncle is **red**
    1. Perform **Color Promotion**
    2. Check the grandparent **G** recursively



# Red-Black Trees - Insertion




- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **(Case 2)** **X** is not root, and its uncle is **black**, and **X** is on the **left-left** subtree
    1. Perform **LL Rotation** with color changes



# Red-Black Trees - Insertion




- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **(Case 2)** **X** is not root, and its uncle is **black**, and **X** is on the **right-right** subtree
    1. Perform **RR Rotation** with color changes



# Red-Black Trees - Insertion




- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **(Case 3)** **X** is not root, and its uncle is **black**, and **X** is on the **left-right** subtree
    1. Perform **LR Rotation** with color changes



# Red-Black Trees - Insertion




- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **(Case 3)** **X** is not root, and its uncle is **black**, and **X** is on the **right-left** subtree
    1. Perform **RL Rotation** with color changes



# Red-Black Trees - Insertion



- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **(Case 0)** **X** is root, and its color is **red**
    1. Color it **black**






# Red-Black Trees - Insertion




- Example - Insert 7



# Red-Black Trees - Insertion




- Example - Insert 7



# Red-Black Trees - Insertion




- Example - Insert 7



# Red-Black Trees - Insertion



- Example - Insert 7



# Red-Black Trees - Deletion

---



- How to delete a node from a Red-Black tree?
  1. Delete an element as usual in the BST
  2. Check if a property of the red-black tree is violated
  3. If violated, modify the tree in the **bottom-up** direction

# Red-Black Trees - Deletion

---




- How to delete a node from a Red-Black tree?
  1. Delete an element as usual in the BST
  2. Check if a property of the red-black tree is violated
  3. If violated, modify the tree in the **bottom-up** direction
- Which properties may be violated?
  1. Every node is either **red** or **black**
  2. The root node is always **black**
  3. All NULL leaf node are **black**
  4. Every **red** node has both the children colored in **black**
  5. Every **path from a given node to any of its leaf nodes** has an **equal number of black nodes**

# Red-Black Trees - Deletion



- (Recap) How to delete an element in the BST?
  - **(Case 1)** If the node has no child, it can be simply deleted
  - **(Case 2)** If the node has one child, it can be deleted like the linked list structure
  - **(Case 3)** If the node has two children, must find a replacement node
    - You don't need to care about this case
    - Check the replacement node in a recursive manner



# Red-Black Trees - Deletion

---




- How to delete a node from a Red-Black tree?
  1. Delete an element as usual in the BST
  2. Check if a property of the red-black tree is violated
  3. If violated, modify the tree in the **bottom-up** direction
- Which properties may be violated?
  1. Every node is either **red** or **black**
  2. The root node is always **black**
  3. All NULL leaf node are **black**
  4. Every **red** node has both the children colored in **black**
  5. Every **path from a given node to any of its leaf nodes** has an **equal number of black nodes**



# Red-Black Trees - Deletion




- How to delete a node from a Red-Black tree?
  1. Delete an element as usual in the BST
  2. Check if a property of the red-black tree is violated
  3. If violated, modify the tree in the **bottom-up** direction



# Red-Black Trees - Deletion




- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **(Case 1)**  $BH(L)+1=BH(R)$  and **L** is **red**
  - **(Solution)** Simply color **L** **black**



# Red-Black Trees - Deletion




- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **(Case 1)**  $BH(L)+1=BH(R)$  and **L** is **red**
  - **(Solution)** Simply color **L** **black**



# Red-Black Trees - Deletion




- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - (Case 2)  $BH(L)+1=BH(R)$ , L is **black**, and R is **red**



# Red-Black Trees - Deletion




- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - (Case 2)  $BH(L)+1=BH(R)$ , L is **black**, and R is **red**



# Red-Black Trees - Deletion




- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **(Case 2)**  $BH(L)+1=BH(R)$ ,  $L$  is **black**, and  $R$  is **red**
  - **(Solution)** Perform Rotation



# Red-Black Trees - Deletion




- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **(Case 2)**  $BH(L)+1=BH(R)$ ,  $L$  is **black**, and  $R$  is **red**
  - **(Solution)** Perform Rotation



# Red-Black Trees - Deletion



- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **(Case 2)**  $BH(L)+1=BH(R)$ , L is **black**, and R is **red** + **(a)** A is **black**
  - **(Solution)** Perform Rotation + **(a)** Nothing to do






# Red-Black Trees - Deletion




- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **(Case 2)**  $BH(L)+1=BH(R)$ , L is **black**, and R is **red** + **(b)** A & B are **red**
  - **(Solution)** Perform Rotation + **(b)** Color Promotion



# Red-Black Trees - Deletion




- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **(Case 2)**  $BH(L)+1=BH(R)$ , L is **black**, and R is **red** + **(b)** A & B are **red**
  - **(Solution)** Perform Rotation + **(b)** Color Promotion



# Red-Black Trees - Deletion




- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - (Case 2)  $BH(L)+1=BH(R)$ , L is **black**, and R is **red** + (c) A is **red** & B is **black**
  - (Solution) Perform Rotation + (c) Perform Rotation again



# Red-Black Trees - Deletion




- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **(Case 2)**  $BH(L)+1=BH(R)$ ,  $L$  is **black**, and  $R$  is **red** + **(c)**  $A$  is **red** &  $B$  is **black**
  - **(Solution)** Perform Rotation + **(c)** Perform Rotation again



# Red-Black Trees - Deletion




- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - (Case 3)  $BH(L)+1=BH(R)$ , L is **black**, and R is **black**



# Red-Black Trees - Deletion




- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **(Case 3)**  $BH(L)+1=BH(R)$ ,  $L$  is **black**, and  $R$  is **black** + **(a)**  $RL$  is **black**
  - **(Solution)** Perform Rotation



# Red-Black Trees - Deletion




- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **(Case 3)**  $BH(L)+1=BH(R)$ ,  $L$  is **black**, and  $R$  is **black** + **(a)**  $RL$  is **black**
  - **(Solution)** Perform Rotation



# Red-Black Trees - Deletion



- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **(Case 3)**  $BH(L)+1=BH(R)$ ,  $L$  is **black**, and  $R$  is **black** + (b)  $RL$  is **red**
  - **(Solution)** Perform Rotation






# Red-Black Trees - Deletion



- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **(Case 3)**  $BH(L)+1=BH(R)$ ,  $L$  is **black**, and  $R$  is **black** + **(b)**  $RL$  is **red**
  - **(Solution)** Perform Rotation



# Red-Black Trees - Deletion




- How to modify the red-black tree?
  - Modify the tree in the **bottom-up** direction
  - **A** & **B** are left & right children of **RL**, respectively
- (Case 1)  $BH(L)+1=BH(R)$  and **L** is **red**
- (Case 2)  $BH(L)+1=BH(R)$ , **L** is **black**, and **R** is **red** + (a) **A** is **black**
- (Case 2)  $BH(L)+1=BH(R)$ , **L** is **black**, and **R** is **red** + (b) **A** & **B** are **red**
- (Case 2)  $BH(L)+1=BH(R)$ , **L** is **black**, and **R** is **red** + (c) **A** is **red** & **B** is **black**
- (Case 3)  $BH(L)+1=BH(R)$ , **L** is **black**, and **R** is **black** + (a) **RL** is **black**
- (Case 3)  $BH(L)+1=BH(R)$ , **L** is **black**, and **R** is **black** + (b) **RL** is **red**
- (Case 0) The root color is **red**

# Red-Black Trees - Deletion




- Example - Delete 2



# Red-Black Trees - Deletion




- Example - Delete 2



# Red-Black Trees - Deletion




- Example - Delete 2



# Red-Black Trees - Deletion



- Example - Delete 2



(Case 2a)

# Any Questions?

---

