

Technological Institute of the Philippines		Quezon City - Computer Engineering	
Course Code:	CPE 018		
Code Title:	Emerging Technologies in CpE 1 - Fundamentals of Computer Vision		
1st Semester	AY 2023-2024		
<u>ACTIVITY NO. 2</u>		<u>Basic I/O Scripting, Part 1</u>	
Name	Bautista, Jhon Hendricks		
Section	CPE31S4		
Date Performed:	06/08/2025		
Date Submitted:	06/08/2025		
Instructor:	Engr. Robin Valenzuela		

✓ 1. Objectives

This activity aims to introduce students to the OpenCV's I/O functionality.

2. Intended Learning Outcomes (ILOs)

After this activity, the students should be able to:

- Read and write an image file
- Convert between image and raw bytes
- Access image data with `numpy.array`

✓ 3. Procedures and Outputs

Most CV applications need to get images as input. Most also produce images as output. An interactive CV application might require a camera as an input source and a window as an output destination. However, other possible sources and destinations include image files, video files, and raw bytes.

For example, raw bytes might be transmitted via a network connection, or they might be generated by an algorithm if we incorporate procedural graphics into our application. Let's look at each of these possibilities.

✓ 4.1 Reading and Writing Image Files

OpenCV provides the `imread()` and `imwrite()` functions that support various file formats for still images. The supported formats vary by system but should always include the BMP format. Typically, PNG, JPEG, and TIFF should be among the supported formats too. Let's explore the anatomy of the representation of an image in Python and NumPy. No matter the format, each pixel has a value, but the difference is in how the pixel is represented.

For example, we can create a black square image from scratch by simply creating a 2D NumPy array:

```
# Uncomment if you encounter an error importing numpy
```

```
# !pip install numpy
```

```
Requirement already satisfied: numpy in /usr/local/lib/python3.10/dist-packages (1.23
```

```
import numpy as np
```

```
img = np.zeros((3,3), dtype=np.uint8)
```

If we print this image to a console, we obtain the following result:

```
img
```

```
array([[0, 0, 0],
       [0, 0, 0],
       [0, 0, 0]], dtype=uint8)
```

Each pixel is represented by a single 8-bit integer, which means that the values for each pixel are in the 0-255 range.

Let's now convert this image into Blue-green-red (BGR)

```
import cv2
```

```
img = cv2.cvtColor(img, cv2.COLOR_GRAY2BGR)
```

What changes can you observe when you print `img` ?

```
# Code Here
```

```
""" Observation Here """
```

You can check the structure of an image by inspecting the shape property, which returns rows, columns, and the number of channels (if there is more than one).

Consider this example:

```
img = np.zeros((3,3), dtype=np.uint8)
img.shape

(3, 3)
```

If you then converted the image to BGR, the shape would be (3,3,3), which indicates the presence of three channels per pixel.

Images can be loaded from one file format and saved to another. For example, let's convert an image from PNG to JPEG:

```
image = cv2.imread('/content/drive/MyDrive/EmTech1 Files/sample.jpg')
cv2.imwrite('/content/drive/MyDrive/EmTech1 Files/testing.jpg', image)

True
```

By default, `imread()` returns an image in the BGR color format even if the file uses a grayscale format. BGR represents the same color space as red-green-blue (RGB), but the byte order is reversed.

Optionally, we may specify the mode of `imread()` to be one of the following enumerators:

- `IMREAD_ANYCOLOR` = 4
- `IMREAD_ANYDEPTH` = 2
- `IMREAD_COLOR` = 1
- `IMREAD_GRAYSCALE` = 0
- `IMREAD_LOAD_GDAL` = 8
- `IMREAD_UNCHANGED` = -1

For example, let's load a PNG file as a grayscale image (losing any color information in the process), and then, save it as a grayscale PNG image:

```
grayImage = cv2.imread('/content/drive/MyDrive/EmTech1 Files/sample.jpg', cv2.IMREAD_GRAY)
cv2.imwrite('/content/drive/MyDrive/EmTech1 Files/sampleGRAY.jpg', grayImage)
```

```
-----
NameError                                Traceback (most recent call last)
/tmp/ipython-input-3304310204.py in <cell line: 0>()
      2 cv2.imwrite('/content/drive/MyDrive/EmTech1 Files/sampleGRAY.jpg',
      - \
```

```
grayImage)
3
----> 4 cv2_imshow(grayImage)

NameError: name 'cv2_imshow' is not defined
```

```
from google.colab import drive
drive.mount('/content/drive')
```

```
Mounted at /content/drive
```

Note: Regardless of the mode, `imread()` discards any alpha channel (transparency). The `imwrite()` function requires an image to be in the BGR or grayscale format with a certain number of bits per channel that the output format can support. For example, bmp requires 8 bits per channel, while PNG allows either 8 or 16 bits per channel.

✓ 4.2 Converting between an image and raw bytes

Conceptually, a byte is an integer ranging from 0 to 255. In all real-time graphic applications today, a pixel is typically represented by one byte per channel, though other representations are also possible.

An OpenCV image is a 2D or 3D array of the `.array` type. An 8-bit grayscale image is a 2D array containing byte values. A 24-bit BGR image is a 3D array, which also contains byte values. We may access these values by using an expression, such as `image[0, 0]` or `image[0, 0, 0]`. The first index is the pixel's y coordinate or row, 0 being the top. The second index is the pixel's x coordinate or column, 0 being the leftmost. The third index (if applicable) represents a color channel.

For example, in an 8-bit grayscale image with a white pixel in the upper-left corner, `image[0, 0]` is 255. For a 24-bit BGR image with a blue pixel in the upper-left corner, `image[0, 0]` is `[255, 0, 0]`.

Provided that an image has 8 bits per channel, we can cast it to a standard Python bytearray, which is one-dimensional:

```
byteArray = bytearray(image)
```

Conversely, provided that `bytearray` contains bytes in an appropriate order, we can cast and then reshape it to get a `numpy.array` type that is an image. As a more complete example, let's convert `bytearray`, which contains random bytes to a grayscale image and a BGR image:

```
import os

# Make an array of 120,000 random bytes
randomByteArray = bytearray(os.urandom(120000))
flatNumpyArray = np.array(randomByteArray)

# Convert the array to make a 400x300 grayscale image
grayImage = flatNumpyArray.reshape(300,400)
cv2.imwrite('/content/drive/MyDrive/EmTech1 Files/random.jpg', grayImage)

# Convert the array to make a 400x100 color image
bgrImage = flatNumpyArray.reshape(100,400,3)
cv2.imwrite('/content/drive/MyDrive/EmTech1 Files/random1.jpg', bgrImage)

True
```

After running this script, we should have a pair of randomly generated images, RandomGray.png and RandomColor.png, in the script's directory.

✓ 4.3 Accessing image data with numpy.array

Now that you have a better understanding of how an image is formed, we can start performing basic operations on it. We know that the easiest (and most common) way to load an image in OpenCV is to use the `imread` function. We also know that this will return an image, which is really an array (either a 2D or 3D one, depending on the parameters you passed to `imread()`).

The `y.array` structure is well optimized for array operations, and it allows certain kinds of bulk manipulations that are not available in a plain Python list. These kinds of `.array` type-specific operations come in handy for image manipulations in OpenCV.























Let's explore image manipulations from the start and step by step though, with a basic example: say you want to manipulate a pixel at the coordinates, (0, 0), of a BGR image and turn it into a white pixel.

```
img = cv2.imread('swolevscheems.png')
img[0:25, 0:25] = [0,0,0]
```

If you then showed the image with a standard `imshow()` call, you will see a black square in the top-left corner of the image. Naturally, this isn't very useful, but it shows what can be accomplished. Let's now leverage the ability of `numpy.array` to operate transformations to an array much faster than a plain Python array.

```
# cv2.imshow('swolevscheems.png')

# If running in Colab, uncomment code above and comment the codes below
from google.colab.patches import cv2_imshow








































































































































































































































































































































```

Let's say that you want to change the blue value of a particular pixel, for example, the pixel at coordinates, (150, 120). The `numpy.array` type provides a very handy method, `item()`, which takes three parameters: the x (or left) position, y (or top), and the index within the array at (x, y) position (remember that in a BGR image, the data at a certain position is a three-element array containing the B, G, and R values in this order) and returns the value at the index position. Another `itemset()` method sets the value of a particular channel of a particular pixel to a specified value (`itemset()` takes two arguments: a three-element tuple (x, y, and index) and the new value).

In this example, we will change the value of blue at (150, 120) from its current value to an arbitrary 127:

```
import cv2
```

```
import numpy as np

img = cv2.imread('swolevscheems.png')
print(img.item(150,120,0))

255

img.itemset((150,120,0), 127)
print(img.item(150,120,0))

127
```

Remember that we do this with `numpy.array` for two reasons: `numpy.array` is an extremely optimized library for these kind of operations, and because we obtain more readable code through NumPy's elegant methods rather than the raw index access of the first example.

This particular code doesn't do much in itself, but it does open a world of possibilities. It is, however, advisable that you utilize built-in filters and methods to manipulate an entire image; the above approach is only suitable for small regions of interest.

Now, let's take a look at a very common operation, namely, manipulating channels. Sometimes, you'll want to zero-out all the values of a particular channel (B, G, or R).

This is a fairly impressive piece of code and easy to understand. The relevant line is the last one, which basically instructs the program to take all pixels from all rows and columns and set the resulting value at index one of the three-element array, representing the color of the pixel to 0. If you display this image, you will notice a complete absence of green.

There are a number of interesting things we can do by accessing raw pixels with NumPy's array indexing; one of them is defining regions of interests (ROI). Once the region is defined, we can perform a number of operations, namely, binding this region to a variable, and then even defining a second region and assigning it the value of the first one (visually copying a portion of the image over to another position in the image):

```
img = cv2.imread('swolevscheems.png')
my_roi = img[0:100, 0:100]
img[300:400, 300:400] = my_roi

# Display the image with the roi indicated as shown in the code above
```

It's important to make sure that the two regions correspond in terms of size. If not, NumPy will (rightly) complain that the two shapes mismatch.

Finally, there are a few interesting details we can obtain from `numpy.array`, such as the image properties using this code:

```
img = cv2.imread('swolevscheems.png')
print(img.shape)
print(img.size)
print(img.dtype)

(1400, 1500, 3)
6300000
uint8
```

These three properties are in this order:

- **Shape:** NumPy returns a tuple containing the width, height, and—if the image is in color—the number of channels. This is useful to debug a type of image; if the image is monochromatic or grayscale, it will not contain a channel's value.
- **Size:** This property refers to the size of an image in pixels.
- **Datatype:** This property refers to the datatype used for an image (normally a variation of an unsigned integer type and the bits supported by this type, that is, `uint8`).

All in all, it is strongly advisable that you familiarize yourself with NumPy in general and `numpy.array` in particular when working with OpenCV, as it is the foundation of an image processing done with Python.

✓ 4. Supplementary Activity

Perform the following tasks, add code blocks below to demonstrate each.

1. Load an RGB .png image of your favorite fictional character (animated is allowed). Make sure that they have a face that can be seen in the image.
2. Display the image.
3. Change the file type to .jpg then display the image.
4. Create a new image file that is a grayscale version of the original image from #1.
5. Use all 6 enumerators of the `cv2.imread()` function and provide an observation for each.
6. Experiment with values to obtain an ROI that captures the full face of your favorite character. Display this new image.
7. Save the new image from from #6 as "character_face.png".

1. Load an RGB .png image of your favorite fictional character

- ✓ (animated is allowed). Make sure that they have a face that can be seen in the image.

```
import cv2 # import relevant library  
image = cv2.imread('/content/drive/MyDrive/EmTech1 Files/sample.png') # use imread functi
```

- ✓ 2. Display the image.

```
from google.colab.patches import cv2_imshow # import relevant library  
  
cv2_imshow(image) # function to display image
```



✓ 3. Change the file type to .jpg then display the image.

```
cv2.imwrite('/content/drive/MyDrive/EmTech1 Files/newSample.jpg', image) # function for w
newIMG = cv2.imread('/content/drive/MyDrive/EmTech1 Files/newSample.jpg')

cv2_imshow(newIMG)
```


- ✓ 4. Create a new image file that is a grayscale version of the original image from

```
grayImage = cv2.imread('/content/drive/MyDrive/EmTech1 Files/newSample.jpg', cv2.IMREAD_GRAYSCALE)
cv2.imwrite('/content/drive/MyDrive/EmTech1 Files/sampleGRAY.jpg', grayImage)

cv2_imshow(grayImage)
```

- ✓ 5. Use all 6 enumerators of the `cv2.imread()` function and provide an observation for each.

```
# IMREAD_ANYCOLOR
```

```
img_color = cv2.imread('/content/drive/MyDrive/EmTech1 Files/sample.png', cv2.IMREAD_ANYC  
cv2.imwrite('/content/drive/MyDrive/EmTech1 Files/sample_imgColor.jpg', img_color)
```

```
cv2_imshow(img_color)
```

```
# IMREAD_ANYDEPTH
img_depth = cv2.imread('/content/drive/MyDrive/EmTech1 Files/sample.png', cv2.IMREAD_ANYD
```

```
cv2.imwrite('/content/drive/MyDrive/EmTech1 Files/sample_imgAnyDepth.jpg', img_depth)

cv2_imshow(img_depth)
```



```
# IMREAD_COLOR
img_color = cv2.imread('/content/drive/MyDrive/EmTech1 Files/sample.png', cv2.IMREAD_COLOR)
cv2.imwrite('/content/drive/MyDrive/EmTech1 Files/sample_imgAnyDepth.jpg', img_color)

cv2.imshow('img_color')
```

```
# IMREAD_GRAYSCALE
img_gray = cv2.imread('/content/drive/MyDrive/EmTech1 Files/sample.png', cv2.IMREAD_GRAYSCALE)
cv2.imwrite('/content/drive/MyDrive/EmTech1 Files/sample_imggray.jpg', img_gray)

cv2.imshow('img_gray')
```



```
# IMREAD_LOAD_GDAL
img_loadGal = cv2.imread('/content/drive/MyDrive/EmTech1 Files/sample.png', cv2.IMREAD_LO
cv2.imwrite('/content/drive/MyDrive/EmTech1 Files/sample_imgAnyDepth.jpg', img_loadGal)

cv2_imshow(img_loadGal)
```

```
# IMREAD_UNCHANGED
img_unchanged = cv2.imread('/content/drive/MyDrive/EmTech1 Files/sample.png', cv2.IMREAD_
cv2.imwrite('/content/drive/MyDrive/EmTech1 Files/sample_imgAnyDepth.jpg', img_unchanged)

cv2_imshow(img_unchanged)
```

OBSERVATIONS

Based on the outputs of the different enumerations for the `IMREAD` function, I only observed minimal changes from the different enumerations. Firstly since we are using a png image upon using the `Load_GDAL` and `UNCHANGED` enumerations, the image appears to have a filled background unlike the others. Then for the `Grayscale` and `AnyDepth` they were able to turn the whole image in to grayscale while the `ANYCOLOR` was outputting the image normally.

- ✓ 6. Experiment with values to obtain an ROI that captures the full face of your favorite character. Display this new image.

```
expImage = cv2.imread('/content/drive/MyDrive/EmTech1 Files/sample.png')
expImage[450:560, 450:520] = [0,255,255] # coordinates to cover up the eye

cv2_imshow(expImage)
```

✓ 7. Save the new image from from #6 as "character_face.png".

```
cv2.imwrite('/content/drive/MyDrive/EmTech1 Files/character_face.png.jpg', expImage)

True
```

✓ 5. Summary, Conclusions and Lessons Learned

After accomplishing the activity I was able to learn the use of OpenCV when dealing with Image manipulation. In following the porcedure I learned how to properly load and read an image from my storage by using the cv2 library. Afterwards I was able to convert the image to raw bytes and represent them in arrays. Due to this I was able to change the values of some pixels in a sample image and modify its apperance. Overall, I learned that through the OpenCV library we are to represent images in an array form in which we can modify its properties to output our desired modification on the image

Property of the Technological Institute of the Philippines (T.I.P.). No part of the materials made and uploaded in this learning management system by T.I.P. may be copied, photographed, printed, reproduced, shared, transmitted, translated, or reduced to any electronic medium or machine-readable form, in whole or in part, without the prior consent of T.I.P.