Swagger
Supported by SMARTBEAR

API de Exemplo - Documentação Swagger 1.0.0 OAS 3.0

Documentação da API de Exemplo

Exemplos

POST `/api/exemplos` Cria um novo registro de exemplo

Endpoint responsável por cadastrar um novo exemplo no sistema web

Parameters Cancel

No parameters

Request body required — application/json

Edit Value | Schema

```
{
  "nome": "string",
  "estado": true,
  "preco": 0
}
```

Execute | Clear

Responses

Curl

```
curl -X 'POST' \
  'http://localhost:3000/api/exemplos' \
  -H 'accept: */*' \
  -H 'Content-Type: application/json' \
  -d '{
  "nome": "string",
  "estado": true,
  "preco": 0
}'
```

Request URL

```
http://localhost:3000/api/exemplos
```

Server response

Code	Details
201	Response body

```
{
  "message": "Registro criado com sucesso!",
  "data": {
    "id": 9,
    "nome": "string",
    "estado": true,
    "preco": "0"
  }
}
```

Download

Response headers

```
connection: keep-alive
content-length: 100
content-type: application/json; charset=utf-8
date: Mon,30 Mar 2026 12:18:14 GMT
```

```
keep-alive: timeout=5
x-powered-by: Express
```

Responses

Code	Description	Links
201	Exemplo criado com sucesso	*No links*
400	Dados inválidos ou campos obrigatórios não informados	*No links*
500	Erro interno do servidor	*No links*

GET `/api/exemplos` Busca todos os registros de exemplo

Endpoint responsável por buscar todos os registros de exemplo no sistema web Permite filtrar os resultados utilizando parâmetros de consulta (query params).

Parameters Cancel

Name	Description
nome `string` *(query)*	j
estado `boolean` *(query)*	--
preco `number` *(query)*	preco

Execute | Clear

Responses

Curl

```
curl -X 'GET' \
  'http://localhost:3000/api/exemplos?nome=j' \
  -H 'accept: */*'
```

Request URL

```
http://localhost:3000/api/exemplos?nome=j
```

Server response

Code	Details
200	**Response body**

```
[
  {
    "id": 8,
    "nome": "Jhonatan",
    "estado": true,
    "preco": "10"
  }
]
```

Download

Response headers

```
content-length: 55
content-type: application/json; charset=utf-8
date: Mon,30 Mar 2026 12:18:29 GMT
etag: W/"37-ltpzrOa34w4xSk+0QreSGUyN6oE"
x-powered-by: Express
```

Responses

Code	Description	Links
200	Registros encontrados com sucesso	*No links*
400	Nenhum registro encontrado	*No links*
500	Erro interno do servidor	*No links*

GET `/api/exemplos/{id}` Busca um registro de exemplo

Endpoint responsável por buscar um registro de exemplo por ID

Parameters Cancel

Name	Description
id * required integer *(path)*	2

Execute | Clear

Responses

Curl

```
curl -X 'GET' \
  'http://localhost:3000/api/exemplos/2' \
  -H 'accept: */*'
```

Request URL

```
http://localhost:3000/api/exemplos/2
```

Server response

Code	Details
200	Response body

```
{
  "data": {
    "id": 2,
    "nome": "Monitor",
    "estado": true,
    "preco": "1800"
  }
}
```

Download

Response headers

```
connection: keep-alive
content-length: 63
content-type: application/json; charset=utf-8
date: Mon,30 Mar 2026 12:18:39 GMT
etag: W/"3f-oFHn+lEFiNNitDH+rF4KFXL+qIQ"
keep-alive: timeout=5
x-powered-by: Express
```

Responses

Code	Description	Links
200	Registro encontrado com sucesso	*No links*
404	Registro não encontrado	*No links*
500	Erro interno do servidor	*No links*

PUT `/api/exemplos/{id}` Atualiza um registro de exemplo

Endpoint responsável por atualizar um registro de exemplo por ID

Parameters Cancel

Name	Description
id * required integer *(path)*	3

Request body required — application/json

Edit Value | Schema

```
{
  "nome": "string",
```

```
  "estado": true,
  "preco": 0
}
```

Execute | Clear

Responses

Curl

```
curl -X 'PUT' \
  'http://localhost:3000/api/exemplos/3' \
  -H 'accept: */*' \
  -H 'Content-Type: application/json' \
  -d '{
  "nome": "string",
  "estado": true,
  "preco": 0
}'
```

Request URL

```
http://localhost:3000/api/exemplos/3
```

Server response

Code	Details
200	

Response body

```
{
  "message": "O registro \"string\" foi atualizado com sucesso!",
  "data": {
    "id": 3,
    "nome": "string",
    "estado": true,
    "preco": "0"
  }
}
```

Download

Response headers

```
connection: keep-alive
content-length: 121
content-type: application/json; charset=utf-8
date: Mon,30 Mar 2026 12:18:51 GMT
etag: W/"79-VSISk5qYduQtnig98h3xJVCls30"
keep-alive: timeout=5
x-powered-by: Express
```

Responses

Code	Description	Links
200	Registro encontrado com sucesso	*No links*
404	Registro não encontrado	*No links*
500	Erro interno do servidor	*No links*

DELETE /api/exemplos/{id} Deleta um registro de exemplo

Endpoint responsável por deletar um registro de exemplo por ID

Parameters | Cancel

Name	Description
id * required integer *(path)*	4

Execute | Clear

Responses

Curl

```
curl -X 'DELETE' \
  'http://localhost:3000/api/exemplos/4' \
  -H 'accept: */*'
```

Request URL

```
http://localhost:3000/api/exemplos/4
```

Server response

Code	Details
200	

Response body


```
{
  "message": "O registro \"string\" foi deletado com sucesso!",
  "deletado": {
    "id": 4,
    "nome": "string",
    "estado": true,
    "preco": "0"
  }
}
```


Download

Response headers

```
connection: keep-alive
content-length: 123
content-type: application/json; charset=utf-8
date: Mon,30 Mar 2026 12:19:01 GMT
etag: W/"7b-pqdRYfIY4Xzz0qovjMSmkh1GdpA"
keep-alive: timeout=5
x-powered-by: Express
```

Responses

Code	Description	Links
200	Registro encontrado com sucesso	*No links*
400	ID inválido	*No links*
404	Registro não encontrado	*No links*
500	Erro interno do servidor	*No links*

Schemas

ReqBodyExemplo {

nome	string
estado*	boolean
preco*	number

}