

Contents

1	Setting	1
1.1	Header	1
1.2	vimrc	1
1.3	Sublime text	2
2	String	2
2.1	KMP	2
2.2	Aho Chorasick	2
2.3	Suffix array	3
2.4	Manacher’s algorithm	3
2.5	Z algorithm	4
3	Graph & Flow	4
3.1	Dinic	4
3.2	Bipartite matching (simple)	5
3.3	MCMF	5
3.4	Articulation Point	6
3.5	Articulation Edge	6
3.6	2SAT & answer recover	7
3.7	SCC	8
4	Query	8
4.1	HLD	8
4.2	Centroid decomposition	9
4.3	Mo’s algorithm	9
4.4	Mo’s algorithm on tree	10
4.5	Parallel binary search	11
4.6	Lazy Propagation 1	12
4.7	PST	13
5	Geometry	14
5.1	Closest pair	14
5.2	Convex hull	14
5.3	Rotating Calipers	15
6	Miscellaneous	15
6.1	Grundy number	15
6.2	Hungarian	15
6.3	Convex Hull trick	17
6.4	Gaussian Elimination	17
6.5	FFT	17
6.6	Math	18
6.7	Extended Euclidean	18

6.8	Persistence Segment Tree	18
-----	--------------------------	----

1 Setting

1.1 Header

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <iostream>
#include <memory.h>
#include <math.h>
#include <assert.h>
#include <queue>
#include <map>
#include <set>
#include <string>
#include <algorithm>
#include <functional>
#include <vector>
#include <stack>

using namespace std;
typedef long long ll;
typedef unsigned long long ull;
typedef pair<int, int> Pi;
typedef pair<ll,ll> Pll;

#define Fi first
#define Se second
#define pb(x) push_back(x)
#define sz(x) (int)x.size()
#define rep(i, n) for(int i=0;i<n;i++)
#define repp(i, n) for(int i=1;i<=n;i++)
#define all(x) x.begin(), x.end()

#define INF 987654321
#define IINF 987654321987654321

1.2 vimrc

syntax on
set nu ai ci si nobk et ar ru nocp hls
set bs=2 ts=4 sw=4 sts=4
set cb=unnamed
set mouse=an
command PS vsp %:r.in|sp %:r.out|vert res 30|wa
command RIO wall|!g++ -O2 -std=c++14 -Wall -lm %:r.cpp && ./a.out < %:r.in > %:r.out
command RI wall|!g++ -O2 -std=c++14 -Wall -lm %:r.cpp && ./a.out < %:r.in
```

### 1.3 Sublime text

```
{
    "shell_cmd": "g++ -O2 -std=c++11 \"${file}\" -o \"${file_path}/${file_base_name}\" && \"${file_path}/${file_base_name}\" < input.txt",
    "working_dir": "${file_path}",
    "selector": "source.c++",
}
```

## 2 String

### 2.1 KMP

```
vector<int> preprocess(string p){
    int m = p.size();
    vector<int> fail(m);
    fail[0] = 0; int j = 0;
    for(int i=1;i<m;i++){
        while(j>0&&p[i]!=p[j]) j = fail[j-1];
        if( p[i] == p[j] ){
            fail[i] = j+1; j++;
        }else{
            fail[i] = 0;
        }
    }
    return fail;
}

vector<int> kmp(string s, string p){
    auto fail = preprocess(p);
    vector<int> ans; int n = s.size(), m = p.size();
    int j = 0;
    for(int i=0;i<n;i++){
        while(j>0 && s[i]!=p[j]) j = fail[j-1];
        if( s[i] == p[j] ){
            if( j == m-1 ){
                ans.pb(i-m+1); j = fail[j];
            }else{
                j++;
            }
        }
    }
    return ans;
}
```

### 2.2 Aho Chorasick

```
struct AhoCorasick{
    struct Node{
        int fail;
        vector<int> output;
```

```
        int children[26];

        Node(){
            for(int i=0;i<26;i++) children[i] = -1;
            fail = -1;
        }
    };

    vector<Node> trie;
    int new_node(){
        Node x;
        trie.push_back(x);
        return (int)trie.size()-1;
    }

    void add(int node, string &s, int idx, int string_num){
        //cout << node << " " << idx << endl;
        if( idx == s.size() ){
            trie[node].output.push_back(string_num);
            return;
        }
        int c = s[idx] - 'a';
        if( trie[node].children[c] == -1 ){
            int next = new_node();
            trie[node].children[c] = next;
        }

        add(trie[node].children[c], s, idx+1, string_num);
    }

    void build(vector<string> v){
        int root = new_node();
        for(int i=0;i<v.size();i++){
            add(root,v[i],0,i);
        }

        queue<int> q;
        q.push(root); trie[root].fail = root;
        while( !q.empty() ){
            int cur = q.front(); q.pop();
            for(int i=0;i<26;i++){
                int next = trie[cur].children[i];
                if( next == -1 ) continue;

                // build fail
                if( cur == root ){
                    trie[next].fail = root;
                }
                else{
                    int x = trie[cur].fail;
                    while( x != root && trie[x].children[i] == -1 ) x = trie[x].fail;
                    if( trie[x].children[i] != -1 ) x = trie[x].children[i];
                    trie[next].fail = x;
                }
            }
        }
    }
}
```

```

        // build output
        int f = trie[next].fail;
        for(auto e : trie[f].output) trie[next].output.push_back(e);
        q.push(next);
    }
}

vector<Pi> find(string s){
    int n = (int) s.size();
    int cur = 0, root = 0;
    vector<Pi> ans;
    for(int i=0; i<n; i++){
        int c = s[i] - 'a';
        while( cur != root && trie[cur].children[c] == -1 ) cur = trie[cur].fail;
        if( trie[cur].children[c] != -1 ) cur = trie[cur].children[c];

        for(auto e : trie[cur].output){
            ans.push_back({e, i});
        }
    }
    return ans;
}
};

```

## 2.3 Suffix array

```

// Make sure to add !, #, $, %, & at the end of input string
class SuffixArray{
public:
    int n;
    string s;
    vector<int> rank, temprank, sa, temp_sa, c;
    vector<int> lcp;
    SuffixArray(string _s){
        n = _s.size(); s = _s;
        rank.resize(n); temprank.resize(n); sa.resize(n); temp_sa.resize(n);
        lcp.resize(n);
        constructSA();
        constructLCP();
    }

    void countingSort(int k){
        int sum = 0, maxi = max(270, n); //ASCII 256
        c.clear(); c.resize(maxi+10);
        for(auto& e : c) e = 0;
        for(int i=0; i<n; i++) c[ i+k<n ? rank[i+k] : 0 ] ++;
        for(int i=0; i<maxi; i++){
            int t = c[i]; c[i] = sum; sum += t;
        }
        for(int i=0; i<n; i++) temp_sa[ c[ sa[i]+k < n ? rank[sa[i]+k] : 0 ] ++ ]
            = sa[i];
    }
}

```

```

        for(int i=0; i<n; i++) sa[i] = temp_sa[i];
    }

    void constructSA(){
        for(int i=0; i<n; i++) rank[i] = s[i];
        for(int i=0; i<n; i++) sa[i] = i;
        for(int k=1; k<n; k<=1){
            countingSort(k);
            countingSort(0);
            int r = 0;
            temprank[sa[0]] = 0;
            for(int i=1; i<n; i++){
                temprank[sa[i]] = (rank[sa[i]] == rank[sa[i-1]] && rank[sa[i]+k]
                    == rank[sa[i-1]+k]) ? r : ++r;
            }
            for(int i=0; i<n; i++) rank[i] = temprank[i];
            if( rank[sa[n-1]] == n-1 ) break;
        }
    }

    // lcp Implementation from
    // http://m.blog.naver.com/dark__nebula/220419358547
    void constructLCP(){
        int h = 0;
        for(int i=0; i<n; i++){
            if( rank[i] ){
                int j = sa[rank[i]-1];
                while( s[i+h] == s[j+h] ) h++;
                lcp[rank[i]] = h;
            }
            if( h > 0 ) h--;
        }
    }
};

```

## 2.4 Manacher's algorithm

```

// finds radius of longest palindrome centered at s[i]
// If you also want to find even-length palindromes, use dummy characters
// baab -> #b#a#a#b#
vector<int> ManacherAlgorithm(string s){
    int n = (int) s.size();
    int p = -1, r = -1;
    vector<int> A(n);
    for(int i=0; i<n; i++){
        if( r < i ){
            A[i] = 0;
            int j = 0;
            while( i + A[i] < n && i - A[i] >= 0 && s[ i+A[i] ] == s[ i-A[i] ] )
                A[i]++;
        }
    }
}

```

```

        A[i]--;
    }
    else{
        A[i] = min( A[2*p - i] , r-i );
        while( i + A[i] < n && i - A[i] >= 0 && s[ i+A[i] ] == s[ i-A[i] ] )
            A[i]++;
        A[i]--;
    }

    // update r
    if( r < i + A[i] ){
        r = i + A[i];
        p = i;
    }
}
return A;
}
}

```

## 2.5 Z algorithm

```

// Calculates LCP[i] for all 0 <= i < n
vector<int> Zalgorithm(string s){
    int l=0, r=0;
    int n = (int) s.size();
    vector<int> Z(n);
    Z[0] = n;
    for(int i=1; i<n; i++){
        // reset and calculate again
        if( i > r ){
            l = r = i;
            while( r<n && s[r] == s[r-l] ) r++;
            r--;
            Z[i] = r-l+1;
        }

        // extend [l,r]
        else{
            int k = i-l;
            // not enough matching at position k
            if( Z[k] < r-i+1 ) Z[i] = Z[k];
            // enough matching. extend [l,r]
            else{
                l = i;
                while( r<n && s[r] == s[r-l] ) r++;
                r--;
                Z[i] = r-l+1;
            }
        }
    }
    return Z;
};

```

## 3 Graph & Flow

### 3.1 Dinic

```

struct MaxFlowDinic{
    struct Edge{
        // next, inv, residual
        int to, inv; ll res;
    };

    int n;
    vector<vector<Edge>> graph;

    vector<int> lev,work;

    void init(int x){
        n = x+10;
        graph.resize(x+10);
        lev.resize(n); work.resize(n);
    }

    void make_edge(int s, int e, ll cap, ll caprev = 0){
        Edge forward = {e, (int)graph[e].size(), cap};
        Edge backward = {s, (int)graph[s].size(), caprev};
        graph[s].push_back(forward);
        graph[e].push_back(backward);
    }

    bool bfs(int source, int sink){
        queue<int> q;
        for(auto& e : lev) e = -1;
        lev[source] = 0; q.push(source);
        while(!q.empty()){
            int cur = q.front(); q.pop();
            for(auto e : graph[cur]){
                if(lev[e.to]==-1 && e.res > 0){
                    lev[e.to] = lev[cur]+1;
                    q.push(e.to);
                }
            }
        }
        return lev[sink] != -1;
    }

    ll dfs(int cur, int sink, ll flow){
        if( cur == sink ) return flow;
        for(int &i = work[cur]; i < (int)graph[cur].size(); i++){
            Edge &e = graph[cur][i];
            if( e.res == 0 || lev[e.to] != lev[cur]+1 ) continue;
            ll df = dfs(e.to, sink, min(flow, e.res) );
            if( df > 0 ){
                e.res -= df;
                graph[e.to][e.inv].res += df;
                return df;
            }
        }
    }
};

```

```

    }
    return 0;
}

ll solve( int source, int sink ){
    ll ans = 0;
    while( bfs(source, sink) ){
        for(auto& e : work) e = 0;
        while( true ){
            ll flow = dfs(source,sink,54321987654321LL);
            if( flow == 0 ) break;
            ans += flow;
        }
    }
    return ans;
}
};

```

### 3.2 Bipartite matching (simple)

```

int yx[5000], xy[5000];
bool vis[5000];
vector<int> E[5000];
int dfs(int x){
    vis[x] = true;
    for(auto e : E[x]){
        if( yx[e] == -1 || (vis[yx[e]] == false && dfs(yx[e])) ){
            yx[e] = x;
            xy[e] = e;
            return 1;
        }
    }
    return 0;
}

int main(){
    memset(yx,-1,sizeof yx);
    int ans = 0;
    rep(i,N){
        memset(vis,0,sizeof vis);
        ans += dfs(i);
    }
    cout << ans;
}

```

### 3.3 MCMF

```

struct MCMF{
    struct edge{

```

```

        int to, inv, cap, flow, cost;
        int res(){
            return cap - flow;
        }
    };

    vector<vector<edge>> graph;
    vector<int> pv, pe;
    vector<int> dist, inq;

    void init(int x){
        graph.resize(x+10);
        for(auto& e : graph) e.resize(x+10);
        pv.resize(x+10); pe.resize(x+10);
        dist.resize(x+10);
        inq.resize(x+10);
    }

    void make_edge(int from, int to, int cap, int cost){
        //printf("%d -> %d | cost = %d\n",from,to,cost);
        edge forward = {to, (int)graph[to].size(), cap, 0, cost};
        edge backward = {from, (int)graph[from].size(), 0, 0, -cost};
        graph[from].push_back(forward);
        graph[to].push_back(backward);
    }

    int solve(int source, int sink){
        int ans = 0;
        int totalflow = 0;
        while(true){
            for(auto& e : dist) e = INF;
            for(auto& e : inq) e = 0;
            queue<int> q;
            q.push(source); inq[source] = 1;
            dist[source] = 0;

            while(!q.empty()){
                int cur = q.front(); q.pop();
                inq[cur] = 0;
                for(int i=0;i<(int)graph[cur].size();i++){
                    auto& e = graph[cur][i];
                    if( e.res() > 0 && dist[e.to] > dist[cur] + e.cost ){
                        dist[e.to] = dist[cur] + e.cost;
                        pv[e.to] = cur; pe[e.to] = i;
                        if( inq[e.to] == 0 ){
                            q.push(e.to); inq[e.to] = 1;
                        }
                    }
                }
            }

            if( dist[sink] == INF ) break;

            // add this limit when we don't require maxflow
            //if( dist[sink] > 0 ) break;

```

```

int mnflow = INF;
for( int v = sink; v != source; v = pv[v] ){
    mnflow = min( mnflow, graph[pv[v]][pe[v]].res() );
}

for( int v = sink; v != source; v = pv[v] ){
    int tmp = graph[pv[v]][pe[v]].inv;
    graph[pv[v]][pe[v]].flow += mnflow;
    graph[v][tmp].flow -= mnflow;
}
totalflow += mnflow;
ans += dist[sink] * mnflow;
}
return ans;
}
};

```

### 3.4 Articulation Point

```

int N,M,cnt=0;

// DFS discover time of vertex
int vis[100500];
vector<int> E[100500];
set<int> articulation;

// Returns the earliest discover time that x's child can visit
// without using x
int dfs(int x, int p){
    vis[x] = ++cnt;
    int child = 0;
    int res = vis[x];
    for(auto e : E[x]){
        if(vis[e]==0){
            // low : the earliest discover time that e can visit
            // without using x
            int low = dfs(e,x);
            child++;
            // check if not root
            if( p != -1 && low >= vis[x] ) articulation.insert(x);
            res = min(res,low);
        }
        else{
            res = min(res,vis[e]);
        }
    }

    // check if root
    if( p == -1 && child >= 2 ) articulation.insert(x);

    return res;
}

```

```

int main()
{
    geti(N,M);
    rep(i,M){
        int a,b; geti(a,b);
        E[a].pb(b); E[b].pb(a);
    }

    repp(i,N) if( vis[i] == 0 ) dfs(i,-1);

    printf("%d\n",(int)articulation.size());
    for(auto e : articulation) printf("%d ",e);
}

```

### 3.5 Articulation Edge

```

int N,M,cnt=0;

// DFS discover time of vertex
int vis[100500];
vector<int> E[100500];
set<pair<int,int>> articulation;

// Returns the earliest discover time that x's child can visit
// without using edge (p,x)
int dfs(int x, int p){
    vis[x] = ++cnt;
    int child = 0;
    int res = vis[x];
    for(auto e : E[x]){
        if(e==p) continue;
        if(vis[e]==0){
            // low : the earliest discover time that e can visit
            // without using edge (x,e)
            int low = dfs(e,x);
            child++;
            // keep in mind: in edge problem, low==vis[x] case
            // is not considered as articulation edge
            // also, root checking is not needed
            if( low > vis[x] )
                articulation.insert({min(e,x),max(e,x)});
            res = min(res,low);
        }
        else{
            res = min(res,vis[e]);
        }
    }

    // no root check needed for edge problem

    return res;
}

```

```

int main()
{
    geti(N,M);
    rep(i,M){
        int a,b; geti(a,b);
        E[a].pb(b); E[b].pb(a);
    }

    repp(i,N) if( vis[i] == 0 ) dfs(i,-1);

    printf("%d\n",(int)articulation.size());
    for(auto e : articulation) printf("%d %d\n",e.first,e.second);
}

```

### 3.6 2SAT & answer recover

```

#define MAX_V 20010
int V,M;

vector<int> Edge[MAX_V];
vector<int> rEdge[MAX_V];
vector<int> vs;

bool vis[MAX_V];
int cmp[MAX_V];
set<int> printSet[MAX_V];

void addEdge(int from, int to){
    Edge[from].push_back(to);
    rEdge[to].push_back(from);
}

void dfs(int v){
    vis[v] = true;
    for (int i = 0; i < Edge[v].size(); i++){
        if (!vis[Edge[v][i]]) dfs(Edge[v][i]);
    }
    vs.push_back(v);
}

void rdfs(int v, int k){
    vis[v] = true;
    cmp[v] = k;
    printSet[k].insert(v);
    for (int i = 0; i < rEdge[v].size(); i++){
        if (!vis[rEdge[v][i]]) rdfs(rEdge[v][i], k);
    }
}

bool cmp1(set<int>& a, set<int>& b) {
    return *a.begin() < *b.begin();
}

```

```

int main()
{
    //freopen("in.txt", "r", stdin);
    geti(V); geti(M);
    int cnt = 0;
    while (M--){
        int a, b;
        scanf("%d%d", &a, &b);
        if (a > 0 && b > 0 ){
            addEdge(a + V, b);
            addEdge(b + V, a);

        }
        else if (a > 0 && b < 0 ){
            b = -b;
            addEdge(a + V, b + V);
            addEdge(b , a);
        }
        else if (a < 0 && b > 0 ){
            a = -a;
            addEdge(a, b);
            addEdge(b + V, a + V);
        }
        else{
            a = -a; b = -b;
            addEdge(a, b + V);
            addEdge(b, a + V);
        }
    }

    memset(vis, false, sizeof(vis));
    for (int i = 1; i <= 2*V; i++){
        if (!vis[i]) dfs(i);
    }

    memset(vis, false, sizeof(vis));
    int k = 0;
    for (int i = vs.size()-1; i >= 0 ; i--){
        if (!vis[vs[i]]) rdfs(vs[i],k++);
    }

    for (int i = 1; i <= V; i++){
        if (cmp[i] == cmp[V + i]){
            printf("0\n");
            return 0;
        }
    }
    printf("1\n");
}

```

```

    for (int i = 1; i <= V; i++){
        if (cmp[i] > cmp[V + i]){
            printf("1 ");
        }
        else printf("0 ");
    }
}

```

### 3.7 SCC

## 4 Query

### 4.1 HLD

```

// 1-index
#define L(x) ((x)<<1)
#define R(x) (((x)<<1)+1)

const int MAXN = 100050;
const int LOGN = 17;

vector<int> adj[MAXN];
int st[6 * MAXN], sub[MAXN], pa[MAXN];
int idx[MAXN], head[MAXN], pos[MAXN], rev[MAXN];
int sz, cnt;

void init(int n) {
    fill(st, st + 6*n, INF);
    fill(head, head + n, -1);
}

void dfs(int x, int p) {
    sub[x] = 1;
    for(auto c : adj[x]) {
        if(c != p) {
            pa[c] = x;
            dfs(c, x);
            sub[x] += sub[c];
        }
    }
}

void update(int x, int id = 1, int l = 0, int r = sz) {
    if(x < l || x >= r) return;
    if(r - l <= 1) {
        if(st[id] == INF)
            st[id] = l;
        else
            st[id] = INF;
        return;
    }
    int mid = (l + r) >> 1;

```

```

    update(x, L(id), l, mid);
    update(x, R(id), mid, r);
    st[id] = min(st[L(id)], st[R(id)]);
}

int query(int x, int y, int id = 1, int l = 0, int r = sz) {
    if(y <= l || r <= x) return INF;
    if(x <= l && r <= y) return st[id];
    int mid = (l + r) >> 1;
    return min(query(x, y, L(id), l, mid), query(x, y, R(id), mid, r));
}

void HLD(int x, int p) {
    if(head[cnt] == -1)
        head[cnt] = x;
    idx[x] = cnt;
    pos[x] = sz;
    rev[sz] = x;
    sz++;

    int cindex = -1;
    for(int i = 0; i < adj[x].size(); i++) {
        if(adj[x][i] != p)
            if(cindex == -1 || sub[adj[x][cindex]] < sub[adj[x][i]])
                cindex = i;
    }
    if(cindex != -1)
        HLD(adj[x][cindex], x);
    for(int i = 0; i < adj[x].size(); i++) {
        if(adj[x][i] != p && i != cindex) {
            cnt++;
            HLD(adj[x][i], x);
        }
    }
}

int queryTree(int v) {
    if(v == 0) {
        int ans = query(pos[0], pos[0] + 1);
        if(ans == INF)
            return -1;
        else
            return 1;
    }
    int vchain, ans = INF;
    while(1) {
        vchain = idx[v];
        if(idx[v] == 0) {
            ans = min(ans, query(pos[0], pos[v]+1));
            break;
        }
        ans = min(ans, query(pos[head[vchain]], pos[v]+1));
        v = pa[head[vchain]];
    }
}

```



```

    if(ans == INF)
        return -1;
    else
        return rev[ans] + 1;
}

void updateTree(int v) {
    update(pos[v]);
}

int main() {
    int n, q;
    geti(n, q);
    for(int i = 1; i < n; i++) {
        int u, v;
        geti(u, v);
        u--; v--;
        adj[u].pb(v);
        adj[v].pb(u);
    }

    init(n);
    dfs(0, -1);
    HLD(0, -1);

    while(q--) {
        int type, x;
        geti(type, x);
        x--;
        if(type == 0) {
            updateTree(x);
        } else {
            printf("%d\n", queryTree(x));
        }
    }
}

```

## 4.2 Centroid decomposition

```

int n;
set<int> adj[MAXN];
int sub[MAXN], dep[MAXN];

void dfsSubtree(int node, int pnode) {
    sub[node] = 1;
    for(auto cnode : adj[node]) {
        if(cnode != pnode) {
            dfsSubtree(cnode, node);
            sub[node] += sub[cnode];
        }
    }
}

int findCentroid(int node, int pnode, int size) {

```

```

    for(auto cnode : adj[node]) {
        if(cnode != pnode && sub[cnode] > size / 2)
            return findCentroid(cnode, node, size);
    }
    return node;
}

bool decompose(int node, int depth) {
    bool result = true;
    if(depth >= 26) {
        return false;
    }
    dfsSubtree(node, -1);
    int ctr = findCentroid(node, -1, sub[node]);
    dep[ctr] = depth;
    for(auto cnode : adj[ctr]) {
        adj[cnode].erase(ctr);
        result &= decompose(cnode, depth + 1);
    }
    adj[ctr].clear();
    return result;
}

int main() {
    geti(n);
    rep(i, n-1) {
        int u, v;
        geti(u, v);
        adj[u].insert(v);
        adj[v].insert(u);
    }
    if(decompose(1, 0)) {
        repp(i, n) printf("%c ", dep[i] + 'A');
    } else {
        cout << "Impossible!";
    }
}

```

## 4.3 Mo's algorithm

```

int N,M,K,tc;
ll c[1000005];
ll p[1000005]; int Bsize;
typedef struct query{
    int l,r,n; ll ans;
} query;
bool cmp(query& a, query& b){
    if( a.l/Bsize == b.l/Bsize ) return a.r < b.r;
    else return a.l/Bsize < b.l/Bsize;
}
bool cmp2(query&a, query& b ){ return a.n < b.n; }
int main(void)
{
    geti(N,M); rep(i,N) scanf("%lld",p+i);

```

```

Bsize = (int) sqrt(1.0*N);
vector<query> q;
rep(i,M){
    int a,b; geti(a,b); a--;b--;
    q.push_back({a,b,i});
}

sort(all(q),cmp);
int l=0, r=-1; ll sum = 0;

for(int i=0;i<q.size();i++){
    query& e = q[i];
    int ql = e.l, qr = e.r;
    while( r < qr ){
        r++;
        sum += p[r]*(2*c[p[r]]+1); c[p[r]]++;
    }
    while( r > qr ){
        sum += p[r]*(1-2*c[p[r]]); c[p[r]]--;
        r--;
    }
    while( l < ql ){
        sum += p[l]*(1-2*c[p[l]]); c[p[l]]--;
        l++;
    }
    while( l > ql ){
        l--;
        sum += p[l]*(2*c[p[l]]+1); c[p[l]]++;
    }
    e.ans = sum;
}

sort(all(q),cmp2);
for(auto e : q ){
    printf("%lld\n",e.ans);
}
}

```

#### 4.4 Mo's algorithm on tree

```

int N;
int g[MAXN];
int f[MAXN];
int pa[LOGV][MAXV]; int level[MAXN];
int ST[MAXN], EN[MAXN], arr[MAXN*3];
int tt = 0;
vector<int> E[MAXN];

void dfs_build(int x, int p, int lev){
    pa[0][x] = p;
    level[x] = lev;
    ST[x] = ++tt; arr[tt] = x;
    for(auto e : E[x])if(e!=p){
        dfs_build(e,x,lev+1);
    }
}

```

```

    }
    EN[x] = ++tt; arr[tt] = x;
}

void lca_build(){
    for(int k=1;k<LOGV;k++){
        repp(i,N){
            if( pa[k-1][i] != -1 )pa[k][i] = pa[k-1][pa[k-1][i]];
            else pa[k][i] = -1;
        }
    }
}

int lca(int x, int y){
    if( level[x] < level[y] ) swap(x,y);
    int diff = level[x] - level[y];
    for(int k=0;k<LOGV;k++){
        if( diff & (1<<k) ) x = pa[k][x];

        if( x == y ) return x;
        for(int k=LOGV-1;k>=0;k--){
            if( pa[k][x] != pa[k][y] ){
                x = pa[k][x]; y = pa[k][y];
            }
        }
        return pa[0][x];
    }
}

int Bsize;
struct query{
    int l,r,n;
};
bool cmp1(query& a, query& b){
    if( a.l/Bsize == b.l/Bsize ) return a.r < b.r;
    else return a.l/Bsize < b.l/Bsize;
};
bool cmp2(query&a, query& b ){ return a.n < b.n; }

ll ans[100500];
ll cnt[2][200500];
int vis[100500];
ll sum = 0;

void update(int x, int type){
    // add node to range
    if( type == 1 ){
        sum += cnt[g[x]^1][f[x]];
        cnt[g[x]][f[x]]++;
    }
    // remove node from range
    if( type == 0 ){
        sum -= cnt[g[x]^1][f[x]];
        cnt[g[x]][f[x]]--;
    }
}

```

```

int main(void){
    geti(N);
    repp(i,N) geti(g[i]);
    repp(i,N) geti(f[i]);

    set<int> flist;
    map<int,int> fmp;
    repp(i,N) flist.insert(f[i]);
    int tmp = 1;
    for(auto e: flist) fmp[e] = tmp++;
    repp(i,N) f[i] = fmp[f[i]];

    repp(i,N-1){
        int a,b; geti(a,b);
        E[a].pb(b); E[b].pb(a);
    }
    tt = 0;
    dfs_build(1,-1,0);
    lca_build();
    Bsize = (int) sqrt(1.0*tt);

    int Q; geti(Q);
    vector<query> v;
    repp(q,Q){
        int a,b; geti(a,b);
        if( ST[a] > ST[b] ) swap(a,b);
        int l = lca(a,b);
        if( a == l || b == l ){
            v.push_back({ST[a],ST[b],q});
        }
        else{
            v.push_back({EN[a],ST[b],q});
        }
    }

    sort(all(v),cmp1);
    int l=1, r=0;
    for(int i=0;i<v.size();i++){
        query& e = v[i];
        int ql = e.l, qr = e.r;
        while( r < qr ){
            r++;
            int node = arr[r];
            vis[node]++;
            if( vis[node] == 1 ) update(node,1);
            if( vis[node] == 2 ) update(node,0);
        }
        while( r > qr ){
            int node = arr[r];
            vis[node]--;
            if( vis[node] == 0 ) update(node,0);
            if( vis[node] == 1 ) update(node,1);
            r--;
        }
        while( l < ql ){

```

```

            int node = arr[l];
            vis[node]--;
            if( vis[node] == 0 ) update(node,0);
            if( vis[node] == 1 ) update(node,1);
            l++;
        }
        while( l > ql ){
            l--;
            int node = arr[l];
            vis[node]++;
            if( vis[node] == 1 ) update(node,1);
            if( vis[node] == 2 ) update(node,0);
        }

        int u = arr[ql]; int v = arr[qr];
        int l = lca(u,v);

        if( u != l && v != l ){
            int node = l;
            vis[node]++;
            if( vis[node] == 1 ) update(node,1);
            if( vis[node] == 2 ) update(node,0);
        }

        ans[e.n] += sum;

        if( u != l && v != l ){
            int node = l;
            vis[node]--;
            if( vis[node] == 0 ) update(node,0);
            if( vis[node] == 1 ) update(node,1);
        }
    }
    repp(i,Q) printf("%lld\n",ans[i]);
}

```

## 4.5 Parallel binary search

```

int N,M,K,Q;

vector<Pi> edge[1000500];
int pa[MAXN]; int sz[MAXN];

// each query's answer
Pi ans[MAXN];
// each query's possible answer range for binary search
int low[MAXN], high[MAXN];
// focus[x] : list of query # where it's mid value is x
vector<int> focus[1000500];

int find(int x){
    if( x == pa[x] ) return x;
    return pa[x] = find(pa[x]);
}

```

```

}
int x[MAXN], y[MAXN];

void uni(int a, int b){
    a = find(a); b = find(b);
    if( a == b ) return;
    pa[a] = b;
    sz[b] += sz[a];
}

int main(void){
    //ios::sync_with_stdio(false);
    geti(N,M);
    int C = -1;
    repp(i,M){
        int a,b,c; geti(a,b,c);
        edge[c].push_back({a,b});
        C = max(C, c);
    }

    geti(Q);
    repp(i,Q){
        int a,b;
        geti(a,b); x[i] = a; y[i] = b;
        ans[i] = {INF,-1};
        // Initially, every query has answer in [0,C] range
        low[i] = 0; high[i] = C;
    }

    bool changed = true;
    while( changed ){
        changed = false;

        // Clear variables
        rep(i,C+1) focus[i].clear();
        repp(i,N) pa[i] = i, sz[i] = 1;

        // Put each query into corresponding focus group
        repp(i,Q){
            if( low[i] > high[i] ) continue;
            focus[ (low[i] + high[i])/2 ].push_back(i);
        }

        // for every time 0~C
        for(int k=0;k<=C;k++){
            // perform action of that time
            for(auto e : edge[k]) uni(e.Fi,e.Se);

            // for each focus group
            // determine it's answer & next position
            for(auto e : focus[k]){
                changed = true;
                int a = x[e]; int b = y[e];
                if( find(a) == find(b) ){
                    ans[e].Fi = min(ans[e].Fi, k);

```

```

                    ans[e].Se = sz[find(a)];
                    high[e] = k-1;
                }
            } else{
                low[e] = k+1;
            }
        }
    }

    repp(i,Q){
        if( ans[i].Fi == INF ) printf("%d\n",-1);
        else printf("%d %d\n",ans[i].Fi, ans[i].Se);
    }
}

```

## 4.6 Lazy Propagation 1

```

int N,M,K;

struct segTree{
    struct Node{
        ll d, lazy;
    };
    vector<Node> data;
    int n;
    void init(int x){
        n = 1; while( n < x ) n *= 2;
        data.resize(n*2+10);
    }
    void propagate(int node, int nodeL, int nodeR){
        if( data[node].lazy == 0 ) return;
        ll len = nodeR - nodeL + 1;
        data[node].d += len*data[node].lazy;
        if( len > 1 ){
            data[node*2].lazy += data[node].lazy;
            data[node*2+1].lazy += data[node].lazy;
        }
        data[node].lazy = 0;
    }

    void update(int l, int r, ll val, int node, int nodeL, int nodeR){
        propagate(node, nodeL, nodeR);
        if( l > nodeR || r < nodeL ) return;
        if( l <= nodeL && nodeR <= r ){
            data[node].lazy += val;
            propagate(node,nodeL,nodeR);
            return;
        }
        update(l,r,val,node*2,nodeL,(nodeL+nodeR)/2);
        update(l,r,val,node*2+1,(nodeL+nodeR)/2+1,nodeR);
        data[node].d = data[node*2].d + data[node*2+1].d;
    }
}

```

```

ll query(int l, int r, int node, int nodeL, int nodeR){
    propagate(node, nodeL, nodeR);
    if( l > nodeR || r < nodeL ) return 0;
    if( l <= nodeL && nodeR <= r ){
        return data[node].d;
    }
    ll sum = 0;
    sum += query(l,r,node*2,nodeL,(nodeL+nodeR)/2);
    sum += query(l,r,node*2+1,(nodeL+nodeR)/2+1,nodeR);
    return sum;
}

};

int main(){
    ios_base::sync_with_stdio(false);
    cin.tie(NULL);
    segTree tree;
    cin >> N >> M >> K;
    tree.init(N);
    repp(i,N){
        ll x; cin >> x;
        tree.update(i,i,x,1,1,tree.n);
    }
    repp(i,M+K){
        int a; cin >> a;
        if( a == 1 ){
            int b,c; ll d;
            cin >> b >> c >> d;
            tree.update(b,c,d,1,1,tree.n);
        }
        else{
            int b,c; cin >> b >> c;
            printf("%lld\n",tree.query(b,c,1,1,tree.n));
        }
    }
}

```

## 4.7 PST

```

const int MAXN = 1e5 + 50;
const int LOGN = 18;

int root[MAXN], pos[MAXN], a[MAXN], rev[MAXN];
int n, cnt;

struct node {
    int sum, left, right;
} tree[3 * MAXN * LOGN];

int build(int l = 0, int r = n) {
    int id = ++cnt;

```

```

    if(r - l <= 1) {
        tree[id] = {0, 0, 0};
        return id;
    }
    int mid = (l + r) >> 1;
    tree[id] = {0, build(l, mid), build(mid, r)};
    return id;
}

int update(int x, int prev, int l = 0, int r = n) {
    if(x < l || r <= x) return prev;
    int id = ++cnt;
    if(r - l <= 1) {
        tree[id] = {1, 0, 0};
        return id;
    }
    int mid = (l + r) >> 1;
    int L = update(x, tree[prev].left, l, mid);
    int R = update(x, tree[prev].right, mid, r);
    tree[id] = {tree[L].sum + tree[R].sum, L, R};
    return id;
}

int findKth(int x, int y, int k, int l = 0, int r = n) {
    if(r - l <= 1) return l;
    int mid = (l + r) >> 1;
    int t = tree[x].left.sum - tree[tree[y].left].sum;
    if(t >= k)
        return findKth(tree[x].left, tree[y].left, k, l, mid);
    else
        return findKth(tree[x].right, tree[y].right, k - t, mid, r);
}

// find ans in [lb, ub)
long long ans(int lb, int ub) {
    if(ub - lb <= 1) return 0;
    int k = (ub - lb + 1) / 2;
    int mid = a[findKth(root[lb], root[ub], k)];
    return ans(lb, mid) + ans(mid+1, ub) + (long long)(ub - lb);
}

```

```

int main() {
    geti(n);
    for(int i = 0; i < n; i++) {
        geti(a[i]);
        a[i]--;
        pos[a[i]] = i;
    }

    // ith segment tree: xth element is 1 iff a[x] >= i
    root[n] = build();
    for(int i = n-1; i >= 0; i--)
        root[i] = update(pos[i], root[i+1]);
}

```

```

    cout << ans(0, n) << endl;
}

```

## 5 Geometry

### 5.1 Closest pair

```

int N,M,T,K,V;

typedef struct Point{
    int x,y;
    bool operator<(const Point& l) const{
        if( y == l.y ) return x < l.x;
        return y < l.y;
    }
    bool operator==(const Point& l) const{
        return (x==l.x)&&(y==l.y);
    }
} Point;

bool cmp(const Point& l, const Point& r){
    if(l.x == r.x ) return l.y < r.y;
    return l.x < r.x;
}

int dist(Point& l, Point& r ){
    return (l.x-r.x)*(l.x-r.x) + (l.y-r.y)*(l.y-r.y);
}

int main(void)
{
    geti(N); vector<Point> v(N);
    for(int i=0;i<N;i++){
        int x ,y; geti(x,y); v[i].x = x; v[i].y = y;
    }
    sort(all(v),cmp);
    int ans = dist(v[0],v[1]); int left = 0;
    set<Point> possible; possible.insert(v[0]); possible.insert(v[1]);

    for(int i=2;i<N;i++){
        while( (v[i].x - v[left].x)*(v[i].x - v[left].x ) > ans ){
            possible.erase(v[left]);
            left++;
        }
        int d = (int) sqrt(ans) + 1;
        auto bottom = possible.lower_bound({-100000,v[i].y-d});
        auto top = possible.upper_bound({100000,v[i].y+d});
        for(auto it = bottom; it != top; it++){
            Point cur = *it;
            if( dist(v[i],cur) < ans ) ans = dist(v[i],cur);
        }
        possible.insert(v[i]);
    }
}

```

```

    }
    cout << ans;
}

```

### 5.2 Convex hull

```

typedef struct Point{
    ll x,y,n;
} Point;

ll ccw(Point a, Point b, Point c){
    b.x -= a.x, b.y -= a.y;
    c.x -= a.x, c.y -= a.y;
    return b.x*c.y - c.x*b.y;
}

vector<Point> convex_hull(vector<Point> ps){
    if (ps.size() < 3)return ps;
    vector<Point> upper, lower;
    sort(ps.begin(), ps.end(), [](const Point &a, const Point &b) {
        if (a.x == b.x) return a.y < b.y; return a.x < b.x;
    });
    for(const auto &p : ps){ // ccw without `=` when include every point in
        convex hull
        while(upper.size() >= 2 && ccw(++upper.rbegin(), *upper.rbegin(), p) >=
            0)upper.pop_back();
        while(lower.size() >= 2 && ccw(++lower.rbegin(), *lower.rbegin(), p) <=
            0)lower.pop_back();
        upper.emplace_back(p);
        lower.emplace_back(p);
    }
    lower.insert(lower.end(), ++upper.rbegin(), --upper.rend());
    return lower;
}

vector<Point> convex_hull2(vector<Point> ps){ // sorting angle
    if (ps.size() < 3)return ps;
    vector<Point> convex;
    sort(ps.begin(), ps.end(), [](Point &a, Point &b){
        if(a.x == b.x)return a.y < b.y; return a.x<b.x;
    });
    Point d = ps[0];
    for(auto &p : ps){
        p.x -= d.x;p.y -= d.y;
    }
    sort(ps.begin(), ps.end(), [](Point &a, Point &b){
        if (ccw({0,0},a,b) == 0) return a.x*a.x + a.y*a.y < b.x*b.x + b.y*b.y;
        return ccw({0,0},a,b) > 0;
    });
    for(auto &p : ps){
        while(convex.size() >= 2 && ccw(++convex.rbegin(), *convex.rbegin(), p)
            <= 0)convex.pop_back();
        convex.emplace_back(p);
    }
}

```

```

    for(auto &p : convex){
        p.x += d.x;p.y += d.y;
    }
    return convex;
}

```

### 5.3 Rotating Calipers

```

int main(){
    vector<Point> convex;
    int ans = 0;

    int mid = 0;
    // if you want iterate `only` antipodal pairs
    // while(ccw(convex.back(), convex[0], convex[mid], convex[mid+1]) > 0) mid
    ++;

    for(int i=0,j=mid; i < convex.size();){
        // do something with pair of i, j

        int nextj = (j+1) % convex.size();
        int nexti = (i+1) % convex.size();
        if (ccw(convex[i], convex[nexti], convex[j], convex[nextj]) > 0)j =
            nextj;
        else i++;
    }
}

```

## 6 Miscellaneous

### 6.1 Grundy number

```

map<set<int>,int> grundy;
map<ll,set<int>> mp;

int get_grundy(set<int> x){
    // base case
    if( sz(x) == 0 ) return 0;
    if( grundy.find(x) != grundy.end() ) return grundy[x];

    set<int> S;
    int res = 0;

    auto iter = x.end(); iter--;
    int mx = *iter;

    // transition : which k to select
    for(int i=1;i<=mx;i++){
        set<int> nxt;
        for(auto e : x){
            if( e < i ) nxt.insert(e);
            else if( e == i ) continue;

```

```

            else nxt.insert(e-i);
        }
        S.insert(get_grundy(nxt));
    }

    // find mex and return
    while( S.find(res) != S.end() ) res++;
    grundy[x] = res;
    return res;
}

int main(void){
    int n; geti(n);

    // Simple prime factorization
    rep(i,n){
        ll x; scanf("%lld",&x);
        for(ll i=2;i*i<=x;i++){
            if( x>0 && x%i == 0 ){
                int cnt = 0;
                while( x>0 && x%i == 0 ){
                    cnt++; x/= i;
                }
                mp[i].insert(cnt);
            }
        }
        if( x > 1 ){
            mp[x].insert(1);
        }
    }

    int res = 0;
    for(auto e : mp){
        res ^= get_grundy(e.Se);
    }

    if( res == 0 ) printf("Arpa");
    else printf("Mojtaba");
}

```

### 6.2 Hungarian

```

// Min cost bipartite matching via shortest augmenting paths
//
// This is an  $O(n^3)$  implementation of a shortest augmenting path
// algorithm for finding min cost perfect matchings in dense
// graphs. In practice, it solves 1000x1000 problems in around 1
// second.
//
// cost[i][j] = cost for pairing left node i with right node j
// Lmate[i] = index of right node that left node i pairs with
// Rmate[j] = index of left node that right node j pairs with
//
// The values in cost[i][j] may be positive or negative. To perform

```

```
// maximization, simply negate the cost[][] matrix.

typedef vector<double> VD;
typedef vector<VD> VVD;
typedef vector<int> VI;

double MinCostMatching(const VVD &cost, VI &Lmate, VI &Rmate) {
    int n = int(cost.size());

    // construct dual feasible solution
    VD u(n);
    VD v(n);
    for (int i = 0; i < n; i++) {
        u[i] = cost[i][0];
        for (int j = 1; j < n; j++) u[i] = min(u[i], cost[i][j]);
    }
    for (int j = 0; j < n; j++) {
        v[j] = cost[0][j] - u[0];
        for (int i = 1; i < n; i++) v[j] = min(v[j], cost[i][j] - u[i]);
    }

    // construct primal solution satisfying complementary slackness
    Lmate = VI(n, -1);
    Rmate = VI(n, -1);
    int mated = 0;
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < n; j++) {
            if (Rmate[j] != -1) continue;
            if (fabs(cost[i][j] - u[i] - v[j]) < 1e-10) {
                Lmate[i] = j;
                Rmate[j] = i;
                mated++;
                break;
            }
        }
    }

    VD dist(n);
    VI dad(n);
    VI seen(n);

    // repeat until primal solution is feasible
    while (mated < n) {

        // find an unmatched left node
        int s = 0;
        while (Lmate[s] != -1) s++;

        // initialize Dijkstra
        fill(dad.begin(), dad.end(), -1);
        fill(seen.begin(), seen.end(), 0);
        for (int k = 0; k < n; k++)
            dist[k] = cost[s][k] - u[s] - v[k];

        int j = 0;
```

```
while (true) {

    // find closest
    j = -1;
    for (int k = 0; k < n; k++) {
        if (seen[k]) continue;
        if (j == -1 || dist[k] < dist[j]) j = k;
    }
    seen[j] = 1;

    // termination condition
    if (Rmate[j] == -1) break;

    // relax neighbors
    const int i = Rmate[j];
    for (int k = 0; k < n; k++) {
        if (seen[k]) continue;
        const double new_dist = dist[j] + cost[i][k] - u[i] - v[k];
        if (dist[k] > new_dist) {
            dist[k] = new_dist;
            dad[k] = j;
        }
    }
}

// update dual variables
for (int k = 0; k < n; k++) {
    if (k == j || !seen[k]) continue;
    const int i = Rmate[k];
    v[k] += dist[k] - dist[j];
    u[i] -= dist[k] - dist[j];
}
u[s] += dist[j];

// augment along path
while (dad[j] >= 0) {
    const int d = dad[j];
    Rmate[j] = Rmate[d];
    Lmate[Rmate[j]] = j;
    j = d;
}
Rmate[j] = s;
Lmate[s] = j;

mated++;
}

double value = 0;
for (int i = 0; i < n; i++)
    value += cost[i][Lmate[i]];

return value;
}
```



### 6.3 Convex Hull trick

```
ll a[MAXN], b[MAXN], dp[MAXN];
ll la[MAXN], lb[MAXN];
int sz, cur, n;

double cross(int x, int y) {
    return (double)(lb[x] - lb[y]) / (la[y] - la[x]);
}

void newLine(ll p, ll q) {
    la[sz] = p;
    lb[sz] = q;

    while(sz > 1 && cross(sz-1, sz-2) > cross(sz, sz-1)) {
        la[sz-1] = la[sz];
        lb[sz-1] = lb[sz];
        sz--;
    }
    sz++;
}

ll find(ll x) {
    while(cur+1 < sz && x > cross(cur, cur+1)) cur++;
    return la[cur] * x + lb[cur];
}

int main() {
    scanf("%d", &n);
    for(int i = 1; i <= n; i++)
        cin >> a[i];
    for(int i = 1; i <= n; i++)
        cin >> b[i];

    dp[1] = 0;
    newLine(b[1], 0);
    for(int i = 2; i <= n; i++) {
        dp[i] = find(a[i]);
        newLine(b[i], dp[i]);
    }
    cout << dp[n];
}
```

### 6.4 Gaussian Elimination

```
#define MAX_N 300 // adjust this value as needed
struct AugmentedMatrix { double mat[MAX_N][MAX_N + MAX_N + 10]; };
struct ColumnVector { double vec[MAX_N]; };

// 0 indexed row and column
AugmentedMatrix GaussianElimination(int N, AugmentedMatrix Aug) {
    // input: N X 2N matrix [A I], output: [I invA]
```

```
    // forward eliminataion phase
    for(int i=0;i<N;i++){
        int l = i;
        // which row has largest column value
        for(int j=i+1;j<N;j++){
            if( fabs(Aug.mat[j][i]) > fabs(Aug.mat[l][i]) )
                l = j;
        }
        // swap this pivot row to minimize error
        for(int k=i;k<2*N;k++){
            swap(Aug.mat[i][k],Aug.mat[l][k]);
        }
        // calculate forward elimination
        for(int j=i+1;j<N;j++){
            for(int k=2*N-1;k>=i;k--){
                Aug.mat[j][k] -= Aug.mat[i][k] * Aug.mat[j][i] /
                    Aug.mat[i][i];
            }
        }

        // normalize pivots
        for(int i=0;i<N;i++){
            for(int j=2*N-1;j>=i;j--){
                Aug.mat[i][j] /= Aug.mat[i][i];
            }
        }

        // backward elimination
        for(int i=N-1;i>0;i--){
            for(int j=i-1;j>=0;j--){
                for(int k=2*N-1;k>=i;k--){
                    Aug.mat[j][k] -= Aug.mat[i][k] * Aug.mat[j][i] /
                        Aug.mat[i][i];
                }
            }
        }

        return Aug;
    }

    int main() {

        AugmentedMatrix Aug;
        int N; geti(N);
        rep(i,N) rep(j,N) scanf("%lf",&Aug.mat[i][j]);
        for(int i=N;i<2*N;i++) Aug.mat[i-N][i] = 1;

        AugmentedMatrix res = GaussianElimination(N, Aug);

        // Print inversion of A
        for(int i=0;i<N;i++){
            for(int j=N;j<2*N;j++) printf("%f ",res.mat[i][j]);
            printf("\n");
        }

        return 0;
    }
}
```

### 6.5 FFT

```
#include <cmath>
#include <complex>
using namespace std;
typedef pair<int,int> pii;
typedef complex<double> base;

void fft(vector<base> &a, bool invert){
    int n = a.size();
    for(int i=1,j=0;i<n;i++){
        int bit = n >> 1;
        for (;j>=bit;bit>>=1)j -= bit;
        j += bit;
        if (i < j) swap(a[i], a[j]);
    }
    for(int len=2;len<=n;len<=<=1){
        double ang = 2*acos(-1)/len*(invert?-1:1);
        base wlen(cos(ang),sin(ang));
        for(int i=0;i<n;i+=len){
            base w(1);
            for(int j=0;j<len/2;j++){
                base u = a[i+j], v = a[i+j+len/2]*w;
                a[i+j] = u+v;
                a[i+j+len/2] = u-v;
                w *= wlen;
            }
        }
    }
    if (invert) {
        for(int i=0;i<n;i++) a[i] /= n;
    }
}

void multiply(const vector<int> &a, const vector<int> &b, vector<int> &res){
    vector<base> fa(a.begin(), a.end()), fb(b.begin(),b.end());
    int n = 1;
    while(n < max(a.size(), b.size())) n <<= 1;
    n <<= 1;
    fa.resize(n); fb.resize(n);
    fft(fa,false);fft(fb,false);
    for(int i=0;i<n;i++) fa[i] *= fb[i];
    fft(fa,true);
    res.resize(n);
    for(int i=0;i<n;i++) res[i] = int(fa[i].real() + (fa[i].real() > 0 ? 0.5 :
        -0.5));
}
```

## 6.6 Math

Complete Permutation ( Derangement )  
 $D_0 = 1, D_1 = 0, D_2 = 1, D_3 = 2,$   
 $D_n = (n-1)(D_{n-1} + D_{n-2})$   
 $D_n = n! * \sum_{k=0 \sim n} \{(-1)^k / k!\}$

Catalan Number

$$C_n = (1 / (n+1)) * combination(2n,n)$$

$$= (2n)! / (n!(n+1)!)$$

## 6.7 Extended Euclidean

```
pair<int,int> ext_gcd(int a,int b){
    if(b){
        auto tmp = ext_gcd(b, a%b);
        return {tmp.second, tmp.first - (a/b) * tmp.second};
    } else return {1, 0};
}

int mod_inv(int a, int M){
    return (ext_gcd(a, M).first + M) % M;
}
```

## 6.8 Persistence Segment Tree

```
int n, cnt;
int root[MAXN];

struct node {
    int sum, left, right;
} tree[3 * MAXN * LOGN];

int build(int l = 0, int r = n) {
    int idx = ++cnt;
    if(r - l <= 1) {
        tree[idx] = {0, 0, 0};
        return idx;
    }
    int mid = (l + r) >> 1;
    tree[idx] = {0, build(l, mid), build(mid, r)};
    return idx;
}

int update(int x, int prev, int l = 0, int r = n) {
    if(x < l || r <= x) return prev;
    int idx = ++cnt;
    if(r - l <= 1) {
        tree[idx] = {1, 0, 0};
        return idx;
    }

    int mid = (l + r) >> 1;
    int L = update(x, tree[prev].left, l, mid);
    int R = update(x, tree[prev].right, mid, r);
    tree[idx] = {tree[L].sum + tree[R].sum, L, R};
    return idx;
}

int query(int x, int y, int k, int l = 0, int r = n) {
    if(r - l <= 1) return l;
```

```
    int mid = (l + r) >> 1;
    int leftSum = tree[y].left.sum - tree[tree[x].left].sum;
    if(leftSum >= k)
        return query(tree[x].left, tree[y].left, k, l, mid);
    else
        return query(tree[x].right, tree[y].right, k - leftSum, mid, r);
}
```

```
int a[MAXN], rev[MAXN];
map<int, int> M;

int main() {
    int q;
    geti(n, q);
    for(int i = 1; i <= n; i++) {
        geti(a[i]);
        rev[i-1] = a[i];
    }
    sort(rev, rev + n);
    for(int i = 0; i < n; i++)
        M[rev[i]] = i;
    for(int i = 1; i <= n; i++)
        a[i] = M[a[i]];

    root[0] = build();
    for(int i = 1; i <= n; i++)
        root[i] = update(a[i], root[i-1]);

    while(q--) {
        int i, j, k;
        geti(i, j, k);
        printf("%d\n", rev[query(root[i-1], root[j], k)]);
    }
}
```