

Create and Deploy a DAG in Apache Airflow

1. Access the Running Container

```
docker exec -it airflow bash
```

2. Navigate to the DAGs Directory

```
cd /opt/airflow/dags
```

3. Create a New DAG File

```
cat > first_dag.py
```

Paste the below code:

```
from airflow import DAG  
from airflow.operators.python import PythonOperator  
from datetime import datetime
```

```
def task1_function():  
    print("Task 1 Started")
```

```
def task2_function():  
    print("Task 2 Running")
```

```
def task3_function():  
    print("Task 3 Completed")
```

```
with DAG(  
    dag_id="first_training_dag",  
    start_date=datetime(2025, 1, 1),  
    schedule="@daily",  
    catchup=False,  
    tags=["training"]  
) as dag:  
  
    task1 = PythonOperator(  
        task_id="task1",  
        python_callable=task1_function  
    )
```

```

task2 = PythonOperator(
    task_id="task2",
    python_callable=task2_function
)

task3 = PythonOperator(
    task_id="task3",
    python_callable=task3_function
)

task1 >> task2 >> task3

```

Press **Ctrl + D** to save the file.

4. Verify the DAG File

ls

5. Exit the Container

exit

6. Verify DAG in Airflow UI

- Open the Airflow Web UI (via Port 8080 in Killer Coda).
- Locate the DAG named **first_training_dag**.
- Enable the DAG using the toggle switch.
- Trigger the DAG manually if required.



