#### Hello, Ladies and Gentlemen.

女士们先生们大家好

Bonjour, Mesdames et Messieurs.

Witajcie, Panie i Panowie.

Здравствуйте, дамы и господа.

Hallo, Damen und Herren.

Buna ziua, Doamenelor si Domnilor.

Ciao, signore e signori.

Zeyuan Zhu, Grade 12, Nanjing Foreign

Language School, Jiangsu, China.

朱泽园,高三,南京市外国语

江苏,中国

Zevuan Zhi

# **New algorithm for Half-plane** Intersection and its Practical Value

-- Thesis for Chinese Team Selecting Contest 2006

半平面交的新算法及其实用价值

-- 中国代表队 2006 年选拔赛论文

Zeyuan Zhu, Grade 12, Nanjing Foreign Language School, Jiangsu, Chir 朱泽园,高三,南京市外国语, ,江苏,中国 Zeyuan Zhu

# Project Overview - 全文总揽



- Aim: Present a new O(nlogn) algorithm for half-plane intersection (abbr. HPI), which is one of the most heatedly discussed problems in computer science; emphasize its advantages in practical application, and to some extent, reduce the complexity to O(n). However, the new algorithm will be extraordinarily easy to be implemented.
  - ②主旨:半平面的交是当今学术界热烈讨论的问题之一,本文将介绍一个全新的 O(nlogn) 半平面交算法,强调它在实际运用中的价值,并且在某种程度上将复杂度下降至 O(n) 线性。最重要的是,我将介绍的算法非常便干字现


# Project Overview - 全文总揽

- **@§1** introduces what Half-Plane Intersection (HPI) is. 什么是半平面交.
- ②§2 prepares a convex polygon intersection (CPI). 凸多边形交预备知识.
- @§3 briefly discuss a common solution for HPI D&C. 简要介绍旧 D&C 算法.
- ②§4 my new algorithm S&I emerges detailedly. 揭开我的新算法 S&I 神秘面纱.
- **est** conclusion and discussion on further practical use. 总结和实际运用.










A line in plane is usually represented as ax+by=c. Similarly, its inequality form  $ax+by \leq (\geq) c$ represents a half-plane (also named h-plane for short) as one side of this line.

**②**众所周知,直线常用 **ax+by=c** 表示, 类似地半平面以 **ax+by ≤(≥)c** 为定义。

March 8, 2016






©给定n个形如a<sub>i</sub>x+b<sub>i</sub>y≤c<sub>i</sub>的半平面,

找到所有满足它们的点所组成的点集 Zevuan Zhu



© Feasible region forms a shape of convex hull possibly unbounded.
Add four h-planes forming a rectangle, to make the intersection area finite.




March 8, 2016

Zeyuan Zhu






Pay attention that intersection sometimes yields a line, a ray, a line-segment, a point or an empty region.







②注意相交后的区域,有可能是一个 直线、射线、线段或者点,当然也

可能是空集。

Zeyuan Zhu




# 2. Convex PolygonIntersection – CPI凸多边形交预备知识



2016年3月8日 Zeyuan Zhu

- Intersecting two convex polygons A and B into a single one.
- We will sketch out an efficient way, named plane sweep method.



求两个凸多边形 A 和 B 的交(一个新凸多边形)。

② 我们描绘一个 平面扫描法。

Polygon A

- Main idea: Regard intersections of edges as cutting points, and break boundaries of A and B, into outer edges and inner edges.
- Segments of inner edges establish ties to each other, and form a polygon. (in bold)

Polygon B

@ 主要思想:以两凸 边形边的交点为分 界点,将边分为内 、外两种。

> 内边互相连接,成 为所求多边形(图 中粗线条

- Suppose there is a vertical sweep line, performing left-to-right sweep.
- At anytime, there are at most four intersections from sweep line to either given polygon.




March 8, 2016




18

the lower one between Au and Bu, and the upper one between Al and Bl, form an interval of the current inner region – the red segment in bold.



Zeyuan Zhu


- Let us call the x-coordinates to be swept x-events.
- Obviously, the sweep line may not go through all the x-event with rational coordinates!







Next x-event should be chosen among four endpoints of e1, e2, e3 and e4, and four potential intersections: e1∩e3, e1∩e4, e2∩e3 and e2∩e4.



称 Au, Al, Bu, Bl 所在的边叫 做 e1,e2,e3,e4

下一个 x 事件将 在这四条边的端 点,以及两两交 点中洗出

March 8, 2

20



# 3. Common solution: Divide-and-Conquer Algorithm - D&C 通常的分治解法

2016年3月8日 Zeyuan Zhu 2

#### 3. Divide-and-Conquer Algorithm



- Divide: Partition the n h-planes into two sets of size n/2.
- Conquer: Compute feasible region recursively of both two subsets.
- © Combine: Compute intersection of two convex region, by CPI§2
- ② 分:将n个半平面分成两个n/2的集合。
- ②治:对两子集合递归求解半平面交.
- ② 合:将前一步算出来的两个交(凸多边形)利用第2章的CPI求解.

#### 3. Divide-and-Conquer Algorithm

- The total time complexity of the solution can be calculated via recursive equation.
- @ 总时间复杂度可以用递归分析法.

$$T(n) = 2T(\frac{n}{2}) + O(n)$$

**CPI** 

$$T(n) = O(n \log n)$$




# 4. My New Solution: Sort-and-Incremental Algorithm - S&I 我自创的排序增量算法

2016年3月8日 Zeyuan Zhu 2





- Definition of h-plane's polar angle: for h-plane like  $x-y \ge constant$ , we define its polar angle to  $\frac{1}{4}\pi$ .
- 半平面的极角定义:比如 *x-y*≥常数的半平面,定义它的极角为 ¼π.








- Step 1: Separate the h-planes into two sets. One has polar angles of  $(-\frac{1}{2}\pi, \frac{1}{2}\pi]$ , the other has those of  $(-\pi, -\frac{1}{2}\pi] \cup (\frac{1}{2}\pi, \pi]$ .
- Step 1: 将半平面分成两部分,一部分极角范围 (-½π,½π],另一部分范围 (-π,-½π]∪(½π,π]




• Step 2: Consider the set of h-planes in  $(-\frac{1}{2}\pi, \frac{1}{2}\pi]$  (the other set should also go through step 3 and 4 similarly). Sort them by the polar angle. For the h-planes with the same polar angle, we can keep only one down (delete all others) according to the constant of these h-planes





28


 Step 3: Starting from two h-planes with the least polar angle, compute their intersection. Push them two into a stack.



•从排序后极角最小两个半平面开始,求出它们的交点并且将他们押入栈。



 Step 3: Each time, add one more h-plane by increasing order of polar angles, and calculate the intersection of it and the top h-plane in stack.




•每次按照极角从小到 大顺序增加一个半平面 ,算出它与栈顶半平面 的交点。



30

• Step 3: If this intersection is to the right of the intersection of top two h-planes in stack, we pop the stack once.




·如果当前的交点在栈 顶两个半平面交点的右 边,出栈(pop)。





Step 3: ...we pop the stack once. Once?
Is it enough? Nie! Do this repeatedly until
it is to the left of the top intersection.




•前问我们说到出栈,出栈只需要一次么? Nie! 我们要继续交点检查, 如果还在右边我们要继续出栈, 直到当前交点 在栈顶交点的左边。

March 8, 2016

Zeyuan Zhu



• Step 4: Intersections of adjacent h-plane pairs in stack form half a convex polygon. For the two sets, we have two halves –  $(-\frac{1}{2}\pi, \frac{1}{2}\pi]$  gives an upper hull and  $(-\pi, -\frac{1}{2}\pi] \cup (\frac{1}{2}\pi, \pi]$  gives a lower hull.



•相邻半平面的交点组成半个凸多边形。我们有两个点集, (-½π, ½π) 给出上半个, (-π, -½π] ∪ (½π, π] 给出下

March 8, 2016


Zeyuan Zhu



34




• Step 4: Intersections of adjacent h-plane pairs in stack form half a convex polygon. For the two sets, we have two halves –  $(-\frac{1}{2}\pi, \frac{1}{2}\pi]$  gives an upper hull and  $(-\pi, -\frac{1}{2}\pi] \cup (\frac{1}{2}\pi, \pi]$  gives a lower hull.



•相邻半平面的交点组成半个凸多边形。我们有两个点集, (-½π, ½π)给出上半个, (-π, -½π]∪(½π, π)给出下

- - Step 4: At the beginning, four pointers *p1*, *p2*, *p3* and *p4* indicate leftmost/rightmost edges of both upper and lower hulls.
  - p1 and p3 move rightwards, while p2 and p4 walks leftwards.




•初始时候,四个指针 p1, p2, p3 and p4 指 向上 I 下凸壳的最左最 右边

•p1, p3 向右走, p2, p4 向左走

March 8, 2016

Zeyuan Zhu


- Step 4: At anytime, if the leftmost intersection is against the feasible region provided by *p1* or *p3*, we are sure the leftmost one is to be removed.
- Naturally, *p1* or *p3* walks rightwards to its adjacent edge.



•任意时刻,如果最左边的交点不满足 p1/p3 所在半平面的限制,我们相信这个交点需要删除 •p1 或 p3 走向它右边的相邻边



• Step 4: The judgment holds analogously for rightmost intersection with *p2* and *p4*.




•类似地我们处理最右边的交点



38


• Step 4: The judgment holds analogously for rightmost intersection with *p2* and *p4*.



•类似地我们处理最右边的交点



 Step 4: Do the above removing repeatedly until there is no more update.



•重复运作直到不再有更新出现——迭代





- Everything except sorting (Step 2) in S&I algorithm remain linear O(n) running time. Usually we use quick-sort. The total complexity is O(nlogn), with fairly small constant factor hidden.
- •除了Step2中的排序以外,S&I算法的每一步都是线性的。通常我们用快速排序实现Step2,总的时间复杂度为O(nlogn),隐蔽其中的常数因子很小



# 5. Conclusion and Practical Use 总结和实际应用



2016年3月8日 Zeyuan Zhu





- © Great ideas need landing gear as well as wings. S&I algorithm seems to work in the same time complexity as D&C algorithm, but some overwhelming advantages of implementing S&I holds.
- @Great ideas need landing gear as well as wings. S&I 算法似乎和 D&C 算法时间复杂度相同,但是它有着压倒性 (overwhelming) 的优势。





that is much easier to code S&I program than D&C one. The program in C++ programming language takes less than 3KB.

◆新的 S&I 算法代码容易编写,相对于 D&C 大大简单化, C++ 程序语言实现 S&I 算法仅需 3KB 不到 .





The coefficient hidden under S&I algorithm's complexity is extraordinarily smaller than D&C, since we no longer need O(nlogn) number of intersection calculates. In general speaking, S&I program runs approx five times faster than D&C one.

中S&I 算法复杂度中的系数,远小于D&C,因为我们不再需要 O(nlogn)次交点运算.通常意义上来讲, S&I程序比 D&C 快五倍。





 $\Phi$  If the given h-planes are all in  $(-\frac{1}{2}\pi, \frac{1}{2}\pi)$  (or any span of  $\pi$ ), S&I program can be shorten remarkably (to approximately twenty lines in C++), but D&C program may not. An informatics problem appeared in USA Invitational Computing Olympiad contest with such purpose.

中如果给定半平面均在 (-½π, ½π)(或任意一个跨度为 π 的区间), S&I 算法可被显著缩短, C++ 程序只需要约二十行。 USAICO 比赛中就出现了这样一题。





- ◆ The bottleneck of this algorithm is sorting. Pay attention the sorting is NOT a comparison sort (sorting based on comparison)! Since then, we can replace the O(nlogn) quick-sort to O(n) radix-sort to decrease the asymptotical time complexity to O(n).
- ◆本算法瓶颈是排序,这里的排序不是比较排序,因此可以将快速排序替换成基数排序,降低程序渐进时间复杂度到线性。
- Anyway O(n) approach usually runs slower than nlogn ones for its additional memory usage!





- 中<美丽心灵 > 诺贝尔奖得主 John Nash
- 中的解的pat maiginality, the
- opening of new frontiers.


新

◆思想

中实践

March 8, 2016

Zeyuan Zhu



March 8, 2016

Zeyuan Zhu