

```

1 // Solution to the exam set in 02157 Functional Programming, 2016 Dec
2 //                               Michael R. Hansen, 24-11-2020
3 //
4
5 //Problem 1
6
7 type Name = string
8 type Event = string
9 type Point = int
10 type Score = Name * Event * Point
11
12 type Scoreboard = Score list
13
14 let sb = [("Joe", "June Fishing", 35); ("Peter", "May Fishing", 30);
15          ("Joe", "May Fishing", 28); ("Paul", "June Fishing", 28)];;
16
17 //1 inv: Scoreboard -> bool
18 let rec inv = function
19     | []                                -> true
20     | [(n,e,p)]                        -> p>=0
21     | (n,e,p)::(n1,e1,p1)::sb         -> p>=p1 && inv ((n1,e1,p1)::sb)
22
23
24 //2 insert: Score -> Scoreboard -> Scoreboard
25 let rec insert (n,e,p) = function
26     | []                                -> [(n,e,p)]
27     | (n1,e1,p1)::sb when p>p1         -> (n,e,p)::(n1,e1,p1)::sb
28     | (n1,e1,p1)::sb                    -> (n1,e1,p1)::insert (n,e,p) sb;;
29
30 //3 get: Name*Scoreboard -> (event*Point) list
31 let rec get(n,sb) =
32     match sb with
33     | []                                -> []
34     | (n1,e1,p1)::sb1 when n=n1         -> (e1,p1)::get(n,sb1)
35     | _::sb1                            -> get(n,sb1);;
36
37 //4 top: int -> Scoreboard -> Scoreboard option
38 let rec top n = function
39     | _ when n=0 -> Some []
40     | []         -> None
41     | s::sb      -> match top (n-1) sb with
42         | None -> None
43         | Some res -> Some(s::res)
44
45 top 2 sb
46
47 // Problem 2
48 //1
49 let rec replace a b = function

```

```

49         | x::xs when a=x -> b::replace a b xs    (* 1 *)
50         | x::xs          -> x::replace a b xs    (* 2 *)
51         | []              -> [];;
52
53 // The most general type must have the form: t1 -> t2 -> t3 -> t4,
54 // for some types t1, t2, t3, t4, due to the form of the declaration,
55 // where a:t1, b:t2, t3 = t1 list due to x=a in (* 1 *)
56 // Furthermore, t2 = t1 and t4 = t1 list due to b::... in (* 1 *) and x::... in ↗
57 // The only constraint on t1 is that it must support equality.
58 // Hence, most general type is: 'a -> 'a -> 'a list -> 'a list when 'a: ↗
59 // equality
60 // Replace is not tail-recursive, because when the recursive call in (* 1 *) ↗
61 // terminates,
62 // then the cons operation b:: ... remains to be executed,
63 // that is, this recursive call is not a tail call. Similarly for (* 2 *)
64
65 //3 A version with an accumulating parameter is:
66 let rec replaceA res a b = function
67     | x::xs when a=x -> replaceA (b::res) a b xs
68     | x::xs          -> replaceA (x::res) a b xs
69     | []              -> List.rev res;;
70
71
72 // Problem 3
73
74 let pos = Seq.initInfinite (fun i -> i+1) ;;
75 let seq1 = seq { yield (0,0)
76                 for i in pos do
77                     yield (i,i)
78                     yield (-i,-i) }
79
80 let val1 = Seq.take 5 seq1;;
81
82 let nat = Seq.initInfinite id;;
83 let seq2 = seq { for i in nat do
84                 yield (i,0)
85                 for j in [1 .. i] do
86                     yield (i,j) }
87
88 let val2 = Seq.toList(Seq.take 10 seq2);;
89
90 //1
91 // pos has type seq<int> and denotes the infinite sequence of
92 // positive natural numbers: 1, 2, ... i, ...
93 // seq1 has type seq<int*int> and denotes the infinite sequence of
94 // pairs: (0,0), (1,1), (-1,-1), ... (i,i), (-i,-i), ...

```

```

95 // val1 has type seq<int*int> and denotes the following sequence
96 // of pairs: (0, 0), (1, 1), (-1, -1), (2, 2), (-2, -2)
97
98 // seq2 has the type seq<int*int>. It denotes the infinite sequence:
99 // (0,0), (1,0), (1,1), (2,0), (2,1), (2,2), ....., (i,0), (i,1), ..., (i,
    i-1), (i,i), ...
100 // That is, it denotes the infinite sequence of natural number pairs (i,j)
    where i >= j.
101 // The order of the pairs is determined by the lexicographical ordering:
102 // (i,j) occurs before (i',j') if i < i' or (i=i' and j<j').
103
104 // Problem 4
105
106 type Tree<'a,'b> = A of 'a | B of 'b | Node of Tree<'a,'b>*Tree<'a,'b>;;
107
108 // Three values of type Tree<bool, int list>
109
110 let v1 = A false;;
111 let v2 = B [1];;
112 let v3 = Node(v1,v2);;
113
114 //2
115 let rec countA_Leaves = function | A _ -> 1
116                                | B _ -> 0
117                                | Node(t1,t2) -> countA_Leaves t1 +
    countA_Leaves t2;;
118
119 //3
120 let rec subst a va b vb = function
121     | Node(t1,t2) -> Node(subst a va b vb t1, subst a
    va b vb t2)
122     | A a' when a=a' -> A va
123     | B b' when b=b' -> B vb
124     | leaf -> leaf;;
125
126 let rec g = function
127     | Node(t1,t2) -> Node(g t2, g t1)
128     | leaf -> leaf;;
129
130 let rec f = function
131     | A a -> ([a],[])
132     | B b -> ([], [b])
133     | Node(t1,t2) -> let (xs1,ys1) = f t1
134                       let (xs2,ys2) = f t2
135                       (xs1@xs2, ys1@ys2);;
136 // 4
137 // The most general type for g is Tree<'a,'b> -> Tree<'a,'b>
138 // The value of g t is a tree t' that is the mirror image of t.
139 // It would be natural to support this description with a figure.

```

```

140 // It is formed by exchange of left and right subtrees in t all the way down.
141
142 // The most general type of f is Tree<'a,'b> -> 'a list * 'b list
143 // The value of f t:
144 // let A x_1, ..., A x_m be the sequence of A-leaves of t as they appear from ↗
    left to right and
145 // let B y_1, ..., B y_n be the sequence of B-leaves of t as they appear from ↗
    left to right.
146 // Then f t = ([x_1; ...;x_m] ,[y_1; ...; y_n]).
147
148 // 5
149 let rec fK t k = match t with
150     | A a          -> k([a],[])
151     | B b          -> k([], [b])
152     | Node(t1,t2) -> fK t1 (fun (xs1,ys1) -> fK t2 (fun (xs2,ys2) ↗
        -> k(xs1@xs2,ys1@ys2)));;
153
154
155 // Problem 5
156
157 type T<'a> = N of 'a * T<'a> list;;
158 type Path = int list;;
159
160 let td = N("g", []);;
161 let tc = N("c", [N("d",[]); N("e",[td])]);;
162 let tb = N("b", [N("c",[])]);;
163 let ta = N("a", [tb; tc; N("f",[])])
164
165 //1
166 let rec toList (N(v,ts)) = v::List.collect toList ts;;
167
168 // A solution based on mutual recursive functions:
169 let rec toList1(N(v,ts)) = v :: toListAux ts
170 and toListAux = function
171     | [] -> []
172     | t::ts -> toList1 t @ toListAux ts
173
174 //2
175
176 // map has type: ('a -> 'b) -> T<'a> -> T<'b>
177
178 let rec map f (N(v,ts)) = N(f v, List.map (map f) ts);;
179
180 // A solution based on mutual recursion
181 let rec map1 f (N(v,ts)) = N(f v, mapAux f ts)
182 and mapAux f = function
183     | [] -> []
184     | t::ts -> map1 f t :: mapAux f ts;;
185

```

```

186 //3
187 let rec isPath path t =
188     match (path, t) with
189     | ([], _) -> true
190     | (i::path', N(v,ts)) when 0 <= i && i < List.length ts -> isPath path' (List.item i ts)
191     | _ -> false;;
192
193 //4
194 let rec get1 path t =
195     match (path,t) with
196     | ([],_) -> t
197     | (i::is, N(_,ts)) -> get1 is (List.item i ts);;
198
199
200 //5
201 let rec tryFindPathTo v (N(v',ts)) = if v=v' then Some []
202                                     else tryFindInList 0 v ts
203 and tryFindInList i v = function
204     | [] -> None
205     | N(v',_)::ts when v=v' -> Some [i]
206     | N(_,ts')::ts -> match tryFindInList 0 v ts'
207                         with
208                         | None -> tryFindInList (i
209                         +1) v ts
210                         | Some is -> Some(i::is);;
211
212
213

```