Information-Consistent Evaluation of Li-ion Battery Remaining Useful Life: An Information-Level Framework for Retrospective Oracles

Jiapei Jiang[a,*]

[a]*School of Business, Guilin University of Electronic Technology, Guilin 541004, China*

Abstract

Data-driven remaining useful life (RUL) studies often compare models by test error, yet rarely specify which information is allowed at prediction cycle t. A common cycle feature is cycle_norm $= t/T$, where T is the cell's completed lifetime and the label is $\mathrm{RUL}_t = T - t$. Because the same T then appears in both the input and the label, this feature is a retrospective oracle: it is informative after life has ended, but it is not online-valid when T is still unknown. This paper treats prediction-time information as part of the evaluation protocol. We define *information-consistent evaluation* as four coupled elements: a named information hierarchy (L0: raw t; L1: leave-target prior t/T^{prior}; L1P: SOH-matched sibling remaining life; L2: target oracle t/T_{target}), a declared fit protocol (within-cell Protocol A versus leave-target-cell-out Protocol B), a provenance audit of every input, and a fillable report row. End-of-life is the first cycle with SOH$\leq$ 0.7, with right-censored cells flagged. MLP and Patch-TF are matched ranking instruments only. On Severson Protocol B (n=24), median MLP RUL RMSE falls from 222.1 (L0) to 33.5 (L1), 30.3 (L1P), and 12.0 (L2), and L0 exceeds L2 on every cell (Wilcoxon $p = 1.2\times10^{-7}$). The counterintuitive result is L1P: on NASA Protocol A, an SOH-indexed local prior beats the target-life oracle (B0005: 5.06 vs. 23.58). We trace the mechanism rather than treating it as an anomaly:

*Corresponding author.

Email address: jjp@mails.guet.edu.cn (Jiapei Jiang)

October 23, 2026

the chronological split places every scored test window of the L2 clock above its training support, where the trained network compresses late-life variation and over-predicts RUL by 10–23 cycles; L1P instead remains within a small SOH matching distance and its residual tracks that distance. The inversion is therefore a support-and-learnability effect, not a refutation of the hierarchy, and it reverses under Protocol B (L1P 30.3 vs. L2 12.0). The contribution is a reproducible reporting standard for RUL benchmarks, not a new RUL architecture.

Keywords: Lithium-ion battery, RUL, Information availability, Evaluation protocol, Retrospective oracle, Leave-one-cell-out

---

1. Introduction

Battery management systems need remaining useful life (RUL) and state of health (SOH) estimates for safety and maintenance planning [10, 8]. Recent reviews document rapid progress in data-driven RUL models [9, 20, 24, 25], and new predictors continue to appear under diverse architectures [21, 26, 31, 37]. Yet many tables still rank models by test RMSE under a fixed feature set, without stating which quantities are allowed at prediction cycle t. If an input already contains the target cell's completed lifetime, a model can look accurate while answering a retrospective question rather than an online one.

A concrete case is the relative-life feature

$$\text{cycle_norm} = \frac{t}{T}, \tag{1}$$

paired with the label $\text{RUL}_t = T - t$. The same end-of-life (EOL) time T that defines the label then enters X_t. On NASA B0005, when record length was used as T, Patch-TF RUL RMSE rose from 2.28 ± 0.96 with this channel to 18.83 ± 3.88 without it [1]. Geslin et al. showed that lifetime features must match the intended use case [14]. Recent LOCO and group-wise validation studies likewise show that optimistic splits inflate reported accuracy [35, 36, 23]. Here we isolate the cycle-index version of that information mismatch.

Three gaps remain in current RUL evaluation practice. First, benchmarks rarely define graded prediction-time information levels for the cycle channel. Second, information level is often mixed with the fit protocol (same-cell chronological training versus leave-target-cell-out). Third, papers often omit the T definition, the persistence baseline, or a one-row auditable report of the experiment. A binary "leaked / not leaked" label then replaces a named information regime and use-case claim.

This paper asks a protocol question rather than an architecture question: under a fixed model budget, do RUL error and ranking change with the information available at prediction time t? As a compact shorthand we write

$$\boxed{\mathrm{Rank}(M_1, \ldots, M_k \mid \mathcal{I}_t) \;=\; f(\mathcal{I}_t),} \tag{2}$$

to mean that rankings can change with the allowed information set. We answer with four cycle-channel levels (L0, L1, L1P, L2), first-EOL labels with censoring flags, a provenance audit, named L0 persistence baselines, and two fit protocols (A and B). MLP and Patch-TF serve only as matched ranking instruments.

Two results organise the evidence. Under Severson Protocol B (n=24), median MLP RUL RMSE falls from 222.1 at L0 to 12.0 at L2, and L0 exceeds L2 on every scored cell. Under NASA Protocol A, L1P can beat the target-life oracle L2 (B0005: 5.06 vs. 23.58). The second result is not a paradox once the training support of each channel is inspected: the oracle clock is *sufficient* but, on the scored windows, *outside* its training support, whereas the SOH-indexed prior stays inside a small matching neighbourhood. We therefore report both the ranking inversion and its mechanism.

Contributions.. (C1) **Core protocol.** A prediction-time information hierarchy for the cycle channel, with T defined as the first cycle at SOH$\leq$ 0.7 (censored cells flagged), a clean split between information level and fit protocol (A vs. B), a provenance audit, and named L0 persistence baselines, with leave-target-cell-out evidence on Severson (n=24, $p = 1.2\times10^{-7}$). (C2) **Mechanism.** A controlled explanation of the L1P<L2 inversion: information sufficiency, out-of-support extrapolation of the oracle clock, and

SOH-neighbourhood interpolation by the local prior, including its reversal under Protocol B and on CALCE. (C3) **Reporting standard.** A fillable one-row report and a mapping to existing benchmark platforms, so that the information condition becomes an auditable field rather than a footnote. The contribution is evaluation methodology for benchmark validity, not a new architecture.

2. Related work

Leakage as illegitimate target information.. Kaufman et al. define leakage as target information that should not be legitimately available to the learner [4]. Kapoor and Narayanan show that such leakage produces irreproducible machine-learning leaderboards [15]. Similar inflation appears when row-wise splits leak subject identity [17]. In batteries, random within-cell splits and optimistic validation can likewise overstate SOH/RUL accuracy relative to cell-held-out tests [36, 35]. RUL labels *must* use a future EOL by definition; the illegitimate step under an online claim is copying that future into X_t.

BMS monitoring, SOH, and RUL.. On-board monitoring and state estimation remain core BMS requirements [10]. SOH reviews separate electrochemical diagnosis from data-driven mapping [8]. RUL surveys catalogue filters, neural nets, and hybrid learners [9, 20, 24, 25], but they often leave the cycle clock outside the evaluation protocol. Capacity regeneration and mixed degradation modes further break a constant-fade story [7, 28, 38].

Data-driven RUL learners and recent benchmarks.. Classical prognostic baselines remain useful reference points [2]. Recent work spans inter-cell deep learning [21], physics-informed early-life predictors [26, 27], and sequence models such as Transformers, Mamba, and dual-path state-space networks [6, 16, 31, 39, 37, 33, 32, 29, 30, 34]. Open platforms and multi-dataset benchmarks show that architecture tables alone do not fix evaluation regimes [18, 22, 19]. MC-Dropout is retained here only as an appendix UQ foil [5]. We use a matched Patch-TF versus MLP pair only as a ranking instrument under controlled $\mathcal{I}_t$, not as an architecture claim.

What benchmark platforms do and do not audit.. BatteryML standardises data ingestion, feature extraction, and model training for degradation studies [18]; BatteryLife aggregates 16 corpora and benchmarks 18 methods under a common pipeline [22]. These platforms make data and model choices reproducible, which is complementary to the present work. To our knowledge, however, neither makes the prediction-time information level a required evaluation field: the scaler source, the T definition, the within-cell versus leave-target protocol, and the presence of t/T_{target} are not reported as separate auditable rows. We do not claim that either platform is leaky; we claim that their reporting cards leave the information condition implicit, so a model that consumes T_{target} and a model that does not can appear in the same table without distinction. The ladder proposed here can be recorded alongside their dataset and model cards as an additional field.

Lifetime datasets, features, and evaluation protocols.. Public cycle-life corpora include NASA PCoE [1, 2], CALCE [3], and the MIT/Stanford set [11]; expanded lifelong and multi-condition datasets continue to appear [19, 22, 21]. Geslin et al. showed that feature legitimacy depends on the use case [14]. Field data add further availability constraints [13]. Cell-grouped and LOCO validation are increasingly recommended when the claim is out-of-cell generalization [12, 23, 35, 36]. Our L2 channel t/T_{target} is a deliberate retrospective relative-life clock: informative for completed-life studies, but information-inconsistent under an online-valid claim. The gap addressed here is an operational L0/L1/L1P/L2 ladder, named fit protocols, a support check for the cycle channel, and a fillable report row.

3. Information-consistent protocol

3.1. Observation set and lifetime

Prediction is cycle-level after completed discharge t. Capacity Q_t is obtained by integrating discharge current. SOH is Q_t/Q_1 on that cell. EOL

threshold is 0.7 throughout. We define

$$T \;=\; \begin{cases} \min\{\tau : \mathrm{SOH}_\tau \le 0.7\}, & \text{if the set is non-empty,} \\ T_{\mathrm{record}}, & \text{otherwise (right-censored),} \end{cases} \tag{3}$$

and

$$\mathrm{RUL}_t \;=\; \max(0,\, T - t). \tag{4}$$

Capacity regeneration after the first crossing does not reopen a positive countdown to a later crossing: T and (4) use one global first EOL. Using the last recorded cycle instead of T makes NASA B0005–B0007 look like identical lifetimes (record length 168) even though EOL values are 161, 106, and 167 (Table 4).

A cell that never crosses the threshold has a *censored* lifetime: T is then the end of observation, and RUL_t counts down to the record horizon rather than to a failure event. We flag this case explicitly (Table 4) because absolute RUL errors on a censored cell are not comparable with errors on a cell that truly failed, even though all information levels share the same labels and their *ranking* remains internally valid. B0007 is the only censored cell in this study (final SOH ≈ 0.76); its role is discussed in Section 5.7.

The observation set $\mathcal{O}_t$ may include $\{Q_\tau, \overline{V}_\tau, \overline{I}_\tau, \overline{T}_\tau, \mathrm{std}(V)_\tau\}_{\tau \le t}$ (NASA; CALCE uses SOH and t only), the raw index t, and scalers fit on training time of the same cell (or leave-target siblings) only. It excludes T_{target}, t/T_{target}, and any transform that needs the full target trajectory, except under the named L2 deliberate-oracle condition below.

Hard rule for online-valid inputs:

$$\boxed{T \in Y, \qquad T \notin X_t, \qquad X_t \subseteq \mathcal{O}_t.} \tag{5}$$

L2 deliberately violates $T \notin X_t$; that violation is the oracle condition being measured, not an unnamed protocol error.

3.2. Levels L0 / L1 / L2 and diagnostic L1P

Only the cycle channel c_t changes; other input channels stay fixed. Nesting is on the *permitted lifetime constants* used to build c_t, not on a claim that prediction-time observables about the target trajectory form a strict information filtration:

$$\begin{aligned} &\mathcal{K}_0 = \emptyset, && \mathcal{K}_1 = \{T^{\text{prior}}\}, \quad \mathcal{K}_2 = \{T^{\text{prior}}, T_{\text{target}}\}, \\ &\quad \mathcal{K}_0 \subset \mathcal{K}_1 \subset \mathcal{K}_2, \\ &c_t^{(0)} = t, && c_t^{(1)} = \frac{t}{T^{\text{prior}}}, \qquad c_t^{(2)} = \frac{t}{T_{\text{target}}}. \end{aligned} \tag{6}$$

We write $\mathcal{I}_k$ for the evaluation condition that uses channel $c_t^{(k)}$. Here $T^{\text{prior}} = \text{median}\{T_i : i \in D_{\text{train}}\}$ uses leave-target training cells only; $\text{median}(T_{\text{all}})$ is forbidden. L2 is a *deliberate oracle*: completed target life enters X_t by construction. Relative to an online-valid claim (T_{target} unavailable at t), the same channel is information-inconsistent; that online reading is stated only when the use case is online BMS. Because T^{prior} and T_{target} are constants with respect to t,

$$c_t^{(1)} = \alpha\, c_t^{(0)}, \qquad c_t^{(2)} = \beta\, c_t^{(0)}, \qquad \alpha = (T^{\text{prior}})^{-1},\ \beta = T_{\text{target}}^{-1}, \tag{7}$$

so L0/L1/L2 are mutually affine (strictly monotone) transforms of the same index t at the *input* level.

What the affine identity does and does not imply.. Equation (7) is a statement about inputs, not about trained predictors. Table 1 separates the three levels of the argument. The identity guarantees the same ordering of cycles and the same information in an idealised function class; it does not guarantee equal network outputs, equal test error, or equal learnability. Empirically, L1 and L2 predictions under Protocol A differ by 0.02–0.25 cycles on average ($\rho > 0.97$), which is consistent with numerical scale robustness of the fitted network, whereas under Protocol B their median RMSE differs by a factor of 2.8. The reconciliation is that an affine rescaling changes the numerical range on which the network is fitted, and therefore changes how it extrapolates

outside that range; it does not change what the channel contains. Section 5.3 uses this distinction to explain the L1P inversion.

Table 1: Affine identity versus empirical error equality. The table records what Equation (7) proves, what it does not, and the observation that separates the two.

Statement	Status	Evidence / remark
$c^{(1)} = \alpha c^{(0)}$, $c^{(2)} = \beta c^{(0)}$ with $\alpha, \beta > 0$	proved	Equation (7); strictly monotone in t
L0/L1/L2 preserve the ordering of cycles	implied	monotone transform of the same index
Trained outputs satisfy $\hat{y}^{(1)} = \hat{y}^{(2)}$	not implied	mean $\lvert\hat{y}^{L1} - \hat{y}^{L2}\rvert = 0.02$–$0.25$ cycles under A ($\rho > 0.97$); L1 33.5 vs. L2 12.0 under B
RUL RMSE invariant to rescaling	not implied	A: 23.62 vs. 23.58; clock $t/1000$: 23.11; raw t: 14.92 (B0005)
L1P is affine in t	false by construction	SOH-indexed lookup, Eq. (8); $\rho(\text{L1P}, \text{L2})$ from -0.12 to -0.82

Training support.. For level k, let $C_k = \{c_t^{(k)} : t \in \text{training windows}\}$. A scored window is *support-covered* if its channel value lies in $[\min C_k, \max C_k]$. Because Protocol A splits windows chronologically and $c^{(2)}$ is increasing in t, every scored test window of L2 lies above $\max C_2$ by construction; the oracle clock is therefore evaluated entirely by extrapolation. L0 and L1 inherit the same ordering but differ in numerical scale, and L1P has no such monotone relation to t because it is indexed by SOH. This observation is used in Section 5.3 and is not a property of the model family.

Separately, the diagnostic channel

$$\text{L1P}_t \;=\; \text{median}\big\{\text{RUL}_{\tau_i}^{(i)} : i \in D_{\text{train}},\ \tau_i = \arg\min_{\tau} \lvert\text{SOH}_{\tau}^{(i)} - \text{SOH}_t^{\text{target}}\rvert\big\} \quad (8)$$

is the median sibling remaining life at the sibling cycle whose SOH is nearest to the target's observed SOH at t. The target SOH trajectory is truncated at t before the lookup; $\text{SOH}_{>t}^{\text{target}}$ and T_{target} are unused. L1P uses the same D_{train} as L1 but is *not* an element of the nested chain (6): it is a non-affine population-RUL map, written L1P rather than $\mathcal{K}_{1\text{P}}$. Matching quality is reported by the absolute SOH distance at the matched sibling cycle (Section 5.5).

Windows with RUL = 0 (at or after first EOL) are dropped before the chronological split, so test RMSE is not dominated by a trivial all-zero tail.

3.3. Decision guide: Protocol A versus Protocol B

Information level and fit protocol are separate axes, and the protocol must be chosen from the claim and the available data, not from convenience. Protocol B is the default when the claim is leave-target-cell generalization or when lifetimes are heterogeneous and absolute t is not comparable across cells. Protocol A is the only feasible choice when no sibling pool exists, and it is a legitimate choice when the claim is a within-cell retrospective countdown under a fixed experimental protocol; it is not evidence about cross-cell information levels. Table 2 makes the choice operational. Two rules follow. First, if a cell has no siblings, L1 and L1P cannot be constructed at all (there is no T^{prior} and no SOH–RUL map), so a single-cell study can compare L0 with the named L2 oracle but cannot order L0/L1/L2 as an information hierarchy. Second, if a target cell has no early history (a new cell from a fleet), Protocol A is impossible and only Protocol B is meaningful. When both are feasible, report both; a disagreement between them is a finding about protocol sensitivity, not an inconsistency to be averaged away.

3.4. Fit protocols

Information level ($\mathcal{I}_t$) and fit protocol are separate axes.

Protocol A (within-cell retrospective evaluation). Pre-EOL windows of the *target* cell are ordered by cycle and split chronologically: the early 80% form the support set and the late 20% are held out as test. Within that early-80% support, the final 15% of windows (still in chronological order) are reserved for validation; the remaining 85% update parameters. No validation or test window is used for feature scaling / $z(t)$ fitting or for parameter estimation; early stopping restores the checkpoint with lowest validation RUL RMSE. Adjacent sliding windows (W=50) still overlap in time, so chronological validation reduces but does not eliminate dependence between train and val; we do not claim i.i.d. window sampling. Even at L0/L1 with $T \notin X_t$, labels $\text{RUL}_t = T_{\text{target}} - t$

Table 2: Protocol selection by claim and data. "Feasible levels" lists what can actually be constructed; "licensed claim" is the strongest statement the design supports.

Data situation	Feasible protocol	Feasible levels	Licensed claim
One cell, no fleet	A only	L0, L2 (oracle); L1/L1P undefined	Within-cell retrospective countdown; no hierarchy or cross-cell ranking
Several cells, homogeneous T	A (B possible but degenerate)	L0, L2; L1≈L2	Within-cell diagnostics; B adds little because $T^{\text{prior}} \approx T_{\text{target}}$
Several heterogeneous cells, target has history	A and B	all four	Prefer B for ranking; A as protocol-sensitivity check
Several cells, new target, no history	B only	L0, L1, L1P, L2	Leave-target generalization; L1P requires SOH overlap with siblings
Fleet plus target history, online claim	A and B	L0, L1, L1P (L2 named oracle)	Online-valid claim only if $T_{\text{target}} \notin X_t$

on early target windows encode that cell's lifetime. NASA and CALCE use Protocol A; Severson Protocol A is a same-window support comparison only.

Protocol B (strict leave-target-cell-out evidence). No target-cell sample enters fitting, validation, scaler fitting, or L1/L1P construction; test windows remain the same late-20% cut. Sibling windows are shuffled with a seed-fixed permutation, then the last 15% of that pool are validation and the rest training (early stopping as in Protocol A). Protocol B is the Severson main evidence (Table 6). Code: `--fit-protocol leave_target` in `scripts/run_info_levels_v2.py`.

3.5. Persistence

We report named RUL baselines, because a single unnamed "persistence" is not reproducible.

- **persist_fade** (mandatory L0 foil): constant fade rate from first to last SOH in the window, extrapolated to SOH= 0.7. Uses only $X_t \subseteq \mathcal{O}_t$.

- **linear**: least-squares SOH versus local cycle index in the window (also L0-valid).
- **persist_recursive**: $\widehat{\mathrm{RUL}}_t = \max(\widehat{\mathrm{RUL}}_{t-1} - 1, 0)$, initialized by persist_fade at the last training window. No ground-truth RUL labels.
- **persist_hold** (oracle diagnostic): $\widehat{\mathrm{RUL}}_t = \mathrm{RUL}_{t-1}$ using the previous true label. Prediction-time BMS does not observe $T - t$; this walk is not an L0 baseline.

3.6. Provenance audit

Table 3 is the information-flow matrix. Labels may depend on T; inputs may not. $I(\text{error}; T) > 0$ is not treated as proof of an illegitimate oracle: short-lived cells can be harder under L0.

Table 3: Information-flow audit. Labels may use T; inputs may not. L1 statistics come from D_{train} only.

Pipeline stage	L0	L1 / L1P	L2
Raw observation	$\tau \leq t$	same	full target trajectory allowed
Target lifetime T	forbidden	forbidden	allowed
Label construction	T in Y only	same	same
Target normalization t/T	forbidden	forbidden	allowed
Train-cell T^{prior} / SOH–RUL map	forbidden	allowed (not target)	allowed
Training scaler / $z(t)$	train-time only	train-time only	train-time only
Test-set statistics	forbidden	forbidden	allowed in oracle runs
VMD/EMD	causal only	causal only	full trajectory allowed
Windows	past only	past only	past only here
HP / feature selection	train/val only	same	same

3.7. Reporting template

Every experiment is one row (model, corpus, cell, level, cycle-channel formula, W, H, scaler source, T definition and censoring flag, RUL RMSE, persist_fade RMSE, optional SOH RMSE, and whether the channel value is inside its training support). Appendix Table 18 is the fillable form. Minimum report for an RUL table: L0 and persist_fade, an explicit T definition, the fit protocol, and the information level of every learned row.

4. Experimental setup

Data and roles.. NASA PCoE B0005–B0007 [1] are the diagnostic corpus under Protocol A (within-cell retrospective evaluation): identical 2 Ah protocol, shared record length, heterogeneous EOL, and a same-cell chronological countdown. CALCE CS2_35–38 [3] are the Protocol A cross-corpus check (EOL in $\{349, 418, 410, 388\}$; SOH plus cycle channel only). The MIT/Stanford Severson set [11] is the main heterogeneous stress test under Protocol B, with Protocol A as same-window support. After Braatz exclusions, 119 cells reach published 80%-of-nominal EOL (T from QDischarge/1.1 $\leq$ 0.8). The scored subset is a stratified stress design fixed a priori as n=24=8+8+8: sort by T, take eight shortest, eight longest, and eight contiguous cells centred on the median T (not a population estimate of the 119). Cell ids and T values are in `outputs/info_levels_severson/selection.json`. Every scored cell completes L0/L1/L1P/L2 under Protocol B (leave-target-cell-out fit; Table 6) and under Protocol A on the same test windows (Table 5). T^{prior} and L1P use the leave-target remainder of the full 119-cell pool, never median(T_{all}). Under Protocol B the scored target is also excluded from model fitting and from L1/L1P construction. NASA/CALCE keep T at SOH$\leq$ 0.7.

Models.. MLP and Patch-TF (matched dual SOH/RUL heads, soft physics, d=64, two layers, W=50, H=5, seeds $\{42, 43, 44\}$, 80 epochs, early stopping on validation RUL RMSE as defined in Section 3.4). Patch-TF follows patch-wise sequence Transformers [6, 16] and is not proposed as a new backbone.

Hardware is CPU in the revision runs; ranking claims do not depend on a particular GPU.

Mechanism diagnostics.. Section 5.3 reuses the same Protocol A windows, model, and budget but logs per-window predictions, the channel value at the window end, the target SOH, and the SOH matching distance for every seed. The diagnostic runs reproduce the ladder RMSE to two decimals (e.g. B0005 L1P 5.06, L2 23.6), so they describe the same fitted objects rather than a new experiment. A separate SOH-head control (Section 5.5) compares the paper loss $\mathcal{L}_{\mathrm{SOH}} + 0.5\,\mathcal{L}_{\mathrm{RUL}}$ with a loss-normalised variant $\mathcal{L}_{\mathrm{SOH}} + 0.5\,\mathcal{L}_{\mathrm{RUL}/T}$ (predictions rescaled by T at evaluation) and with an SOH-only model early-stopped on SOH RMSE. For the paper loss we also log the ratio of gradient norms at the shared trunk, $\|\nabla_\theta \mathcal{L}_{\mathrm{RUL}}\| / \|\nabla_\theta \mathcal{L}_{\mathrm{SOH}}\|$, over the first three epochs.

Metrics.. RUL RMSE (cycles) is the headline. SOH RMSE is an auxiliary control on the same windows; it is not a performance claim (Section 5.5). MC-Dropout PICP/PINAW is appendix-only [5]; we do not claim calibrated UQ.

Statistics.. For each cell and model, seed-level RMSE values (n=3) are reported as technical replicates. The independent unit for ranking-shift claims is the cell: $e_i = \mathrm{RMSE}_{L0,i} - \mathrm{RMSE}_{L2,i}$ with paired Wilcoxon across cells. The test evaluates whether L0 and L2 errors differ; it does not by itself decide use-case legitimacy. NASA+CALCE use n=7; Severson uses the n=24 stratified subset. **Primary inference is restricted to Severson Protocol B.** NASA/CALCE results are protocol-sensitivity demonstrations and are not pooled with Severson.

5. Results

We report results in three layers. Primary: under Severson Protocol B (n=24), median MLP RUL RMSE falls from 222.1 (L0) to 33.5 (L1), 30.3 (L1P), and 12.0 (L2), and L0 exceeds L2 on every cell (Fig. 2; Tables 6–8). Secondary: under NASA Protocol A, L1P can beat L2 (Fig. 4); Section 5.3 shows that this is an out-of-support extrapolation effect of the or-

acle clock, not evidence that less information is better. Exploratory: the NASA/CALCE ladder and Protocol A reversals in Section 5.4 are protocol-sensitivity demonstrations; CALCE and MC-Dropout stay demoted controls.

5.1. EOL, not record length, restores L1

Table 4 and Fig. 1 show the structural fix. NASA record lengths are identical; EOL values are not. L1 for B0005 uses $T_{\text{med}} = \text{median}(106, 167) = 136.5$ against $T_{\text{target}} = 161$; for B0006, 164 against 106; for B0007, 133.5 against 167. L1 is therefore no longer a copy of L2. CALCE sibling medians likewise differ from each target (e.g. CS2_35: $T = 349$ vs. sibling median 410). The last column of Table 4 marks whether the EOL threshold was actually reached; B0007 is the sole censored cell.

Table 4: Lifetime definitions. T_{record} is the last discharge index; T_{EOL} is the first cycle with SOH$\leq$ 0.7. Regeneration is the sum of positive SOH increments. "EOL reached" is "no" when T is a right-censoring time (last observed cycle).

Corpus	Cell	n	T_{record}	T_{EOL}	regen. sum	EOL reached
NASA	B0005	168	167	161	0.222	yes
NASA	B0006	168	167	106	0.367	yes
NASA	B0007	168	167	167	0.182	no (censored)
CALCE	CS2_35	882	881	349	1.665	yes
CALCE	CS2_36	936	935	418	1.929	yes
CALCE	CS2_37	972	971	410	2.011	yes
CALCE	CS2_38	996	995	388	2.341	yes

5.2. Severson Protocol B (primary evidence)

This subsection is the primary evidence. On Severson [11] a stratified short/mid/long subset (n=24; T from 147 to 1933) is scored with MLP under both fit protocols, with L1/L1P from the full leave-target sibling pool (Braatz exclusions; T at published 80% of nominal 1.1 Ah). Protocol B is the primary leave-target-cell-out evidence (Fig. 2; Table 6); Protocol A is the same late-20% test windows under within-cell retrospective fitting (Table 5). Cross-cell median RUL RMSE under Protocol B is 222.1 (L0), 33.5 (L1), 30.3




Figure 1: NASA SOH versus cycle. (A) Record length is 168 for all three cells; vertical dotted lines mark T_{EOL}. (B) Late-life B0007 remains above 0.7 with frequent upward ticks; constant-fade persistence then infers a near-flat slope and a large remaining life.

(L1P), and 12.0 (L2). Paired Wilcoxon on $e_i = \mathrm{RMSE}_{L0,i} - \mathrm{RMSE}_{L2,i}$ gives $p = 1.2{\times}10^{-7}$; L0 exceeds L2 on every scored cell. Named L0 baselines on the same test windows (Table 7) give median persist_fade 242.8 and persist_recursive 499.4; persist_hold remains 1.0 (oracle label walk). MLP L0 (222.1) is therefore in the same regime as persist_fade, while L2 (12.0) is not explained by a trivial fade foil. Relative to Protocol A on the same cells (Table 5: L2/L1/L1P/L0 medians 15.9/16.9/19.0/73.4), removing target-cell training labels widens the L0–L2 gap. Under Protocol B, input affinity (7) no longer yields L1≈L2 in RMSE: a constant population clock does not restore the target-specific relative-life scale across $T \in [147, 1933]$. Absolute cycle index is non-comparable across heterogeneous lifetimes; t/T_{target} restores that scale as a deliberate retrospective oracle (information-inconsistent only under an online-valid claim). L1P remains the non-affine diagnostic outside (6) (Table 8); importantly, its median error (30.3) is *above* L2 (12.0) here, so the inversion reported next is protocol-specific.

5.3. Why L1P can beat L2: support, not information

Table 10 and Fig. 4 report the inversion: on NASA Protocol A, MLP L1P RMSE is 5.06 ± 0.23 (B0005), 5.45 ± 0.45 (B0006), and 8.66 ± 0.10 (B0007),




Figure 2: Severson Protocol B information ladder (primary evidence; n=24 stratified cells). Per-cell MLP trajectories with boxplots and cross-cell median overlay. Medians: L0 222.1, L1 33.5, L1P 30.3, L2 12.0 cycles. L0>L2 on every scored cell (paired Wilcoxon $p = 1.2\times10^{-7}$).

Table 5: Severson Protocol A within-cell retrospective evaluation (chronological fit; MLP; stratified 24 cells; leave-target T^{prior} only). Cross-cell median RUL RMSE (cycles). Support comparison.

Fit	L2	L1	L1P	L0
Protocol A ($n = 24$)	15.9	16.9	19.0	73.4

Table 6: Severson Protocol B strict leave-target-cell-out evidence (MLP; same stratified 24 cells and same late-20% test windows; train/val on sibling cells only; L1/L1P from the leave-target 119-cell pool). Cross-cell median RUL RMSE (cycles). Main evidence.

Fit	L2	L1	L1P	L0
Protocol B ($n = 24$)	12.0	33.5	30.3	222.1

Table 7: Severson L0-valid classical foils on the same late-20% test windows as Protocol B ($n = 24$). Cross-cell median RUL RMSE (cycles). persist_hold = 1 is an oracle label walk, not an L0 foil.

Baseline	persist_fade	linear	persist_recursive
Protocol B test windows	242.8	228.2	499.4

Table 8: Severson Protocol B per-cell MLP RUL RMSE excerpt (mean over three seeds). Short / mid / long T strata.

Cell	L2	L1	L1P	L0
b2c1	158.2	17.1	20.5	557.7
b2c0	13.7	14.3	10.0	408.1
b2c3	10.4	10.3	15.1	388.0
b2c47	8.0	13.5	36.0	219.0
b1c15	4.9	27.7	16.3	215.0
b1c32	8.4	13.3	13.5	225.2
b3c45	15.4	39.0	64.0	133.8
b3c7	21.6	37.2	51.9	124.9
b3c38	19.0	39.3	71.6	121.2

against L2 23.58 ± 3.85, 10.62 ± 1.69, and 20.19 ± 3.80; Patch-TF reproduces the ordering (B0005: 2.84 vs. 19.17). The first concern is a matching artefact, and it is excluded: the mean absolute SOH matching distance is 0.0039 (B0005), 0.0307 (B0006), and 0.0010 (B0007), so the sibling lookup is local. The second concern is that L1P secretly uses more information; it does not: the target SOH trajectory is truncated at t, and neither T_{target} nor future SOH enters Eq. (8). The remaining question is why a channel with *less* target-life information produces a lower error.

The oracle clock is sufficient but not learnable here.. Under first-EOL labels, $\text{RUL} = T(1 - c^{(2)})$, so a linear readout of the L2 channel recovers RUL exactly; the appendix OLS check reports zero error for raw t on NASA and CALCE. The information is therefore present; the failure is in the fitted predictor. Because Protocol A splits windows chronologically, every scored test window has $c^{(2)} > \max C_2$ (Section 3.2): the network never sees the late-life segment of the clock during training. On that out-of-support segment

the MLP response compresses (prediction s.d. 0.42–0.50 of the true s.d.) and over-predicts RUL by 10–23 cycles, with a signed-error slope of 107–166 cycles per unit of $c^{(2)}$ beyond the training maximum (Table 9, Fig. 3B). The error is largest exactly where it matters for maintenance: for RUL < 10, L2 RMSE reaches 28–30 cycles, while L1P is 6–13 (Fig. 3C). This is the sense in which "more information" did not help: the extra information was present in the channel but outside the region where the learner could use it.

The local prior is interpolation, and its residual says so.. L1P is indexed by the target's current SOH, not by cycle progress, so its lookup remains inside the sibling SOH range even when the cycle clock has left its training support. At test, L1P is biased upward by 4.4–7.9 cycles, roughly half the L2 bias, and its absolute error correlates with the SOH matching distance on the scored windows ($r = 0.75$, 0.76, 0.27). The pooled correlation over a whole trajectory is negative (-0.53, -0.59, -0.10) because early-life windows combine a tight SOH match with a large absolute RUL; conditioning on the evaluated late-life band reverses the sign. L1P is also not a trivial copy of its channel: the prior alone has RMSE 7.25 (B0005), 3.26 (B0006), and 23.61 (B0007), while the fitted model reaches 5.06, 5.46, and 8.66, so the shared trunk uses the SOH trajectory to correct the prior (most visibly on censored B0007).

Boundary conditions.. The inversion requires three things at once: (i) Protocol A, so that the target's early trajectory is in the training set; (ii) an oracle clock whose scored values lie outside its training support; and (iii) a sibling pool whose SOH range covers the target's late-life SOH. Remove any one and the inversion disappears. Under Protocol B, L1P (30.3) is worse than L2 (12.0), because a population prior cannot recover a target-specific lifetime scale across heterogeneous cells. On CALCE, CS2_36 reverses the NASA order (L1P 60.69 vs. L2 2.20), because the CALCE sibling SOH–RUL relation is not locally stable under strong regeneration. L1P is therefore a diagnostic of local population structure, not a default online estimator.

Implication for online BMS.. When T is unknown, a progress clock cannot be used at all; among the online-valid options, an SOH-indexed fleet prior is a safer plug-in than an uncalibrated extrapolation of cycle progress, provided that a comparable fleet exists and its SOH coverage overlaps the target's operating range. If no such fleet exists, the L0 recursive walk remains the fallback, and the L2 oracle should be reported only as a retrospective upper bound. This is a use-case statement, not a claim that L1P dominates L2 in general.

Table 9: Error structure of the L1P inversion (NASA Protocol A; test windows, three seeds pooled). Bias is mean$(\hat{y} - y)$ in cycles. "s.d. ratio" is s.d.$(\hat{y})$/s.d.(y) for L2 on the scored windows; values below one indicate a compressed response. The last column is the Pearson correlation between the L1P SOH matching distance and its absolute error on the scored windows.

Cell	L2 RMSE	L2 bias	L2 s.d. ratio	L1P RMSE	L1P bias	$r(\text{dist}, \lvert e \rvert)$
B0005	23.79	+22.60	0.50	5.06	+4.38	0.75
B0006	10.70	+10.01	0.42	5.46	+5.18	0.76
B0007	20.43	+19.05	0.50	8.66	+7.93	0.27




Figure 3: Mechanism of the L1P inversion (NASA Protocol A; MLP, three seeds). (A) On B0005 the L2 prediction is nearly flat at $\sim$ 35 cycles while the true RUL falls to zero; the band is ± 1 s.d. over seeds. (B) L2 signed error grows with the distance of the scored channel value beyond its training maximum, for all three cells. (C) L2 error is largest for short RUL, the regime that matters for maintenance.




Figure 4: NASA Protocol A L1P versus L0/L1/L2 (MLP mean RMSE). L1P undershoots L2 on all three cells (e.g. B0005: 5.06 vs. 23.58); Section 5.3 traces this to the out-of-support L2 clock rather than to a failure of the information hierarchy.

5.4. Protocol sensitivity: NASA/CALCE ladder (exploratory)

This subsection demonstrates how rankings move with the fit protocol; it is *not* evidence for the information hierarchy and is not pooled with Severson. Figure 5 and Table 10 report re-training with $T := T_{\mathrm{EOL}}$, L0 = raw t, pre-EOL windows only, and B0006 included. L1 and L2 *denominators* are distinct (Table 4); RMSE need not follow the same staircase.

On NASA under Protocol A, L1 and L2 RUL RMSE agree to two decimals for Patch-TF (e.g. B0005: both 19.17 ± 2.42). This is consistent with input affinity (7) plus empirical scale robustness (Section 5.5), not a proof that T^{prior} was learned as a lifetime scale. Raw-t L0 is often easier on this within-cell retrospective split (Patch-TF B0005 10.21 ± 1.21; B0006 4.63 ± 0.33; MLP B0005 L0 11.77 ± 0.15 vs. L2 23.58 ± 3.85): the late-life test set satisfies RUL $\approx c - t$, so unscaled t can match the label without an oracle denominator. The L0-drop result in Section 5.6 shows that *removing* the cycle channel collapses accuracy; rescaling t does not. Because RUL $= T - t$, an on-window OLS identity check recovers T algebraically from raw t; this is not treated

as a predictive baseline (Appendix Table 15). L1P breaks affine equivalence with L2 ($\rho(\text{L1P}, \text{L2})$ from -0.12 to -0.82). For B0005, median$(T_{\text{all}}) = 161 = T_{\text{target}}$ while $T^{\text{prior}} = 136.5$, so pooling the test cell into the prior would collapse L1 toward L2 by construction.

On CALCE the same diagnostic is not a staircase: CS2_36 L1P is 60.69 ± 20.40 versus L2 2.20 ± 1.30 and L0 40.33 ± 2.14 (Table 10). Hence Rank_{L1P} can differ from Rank_{L2} without a universal L2 $\prec$ L1P $\prec$ L0 order. With first-EOL labels, CS2_35–38 show affine L1 tracking L2 while raw-t L0 is harder (e.g. CS2_36: L1 2.28 ± 1.12, L2 2.20 ± 1.30, L0 40.3 ± 2.1). Patch-TF on the two-channel CALCE extract is not a reliable architecture ranking; we report it as a matched run, not as a winner.

Across seven cells, paired Wilcoxon on MLP $e_i = \text{RMSE}_{L0,i} - \text{RMSE}_{L2,i}$ gives $p = 0.219$ (Table 12): NASA L0 is easier, CALCE L0 is harder, so there is no single cell-population staircase. This null result is expected under the design: Protocol A asks a within-cell question, and the seven cells mix two corpora with opposite late-life behaviour. It is reported as a descriptive sensitivity check; the primary cell-level contrast remains Severson Protocol B (Section 5.2). Seed-level Wilcoxon tests (Table 17, Appendix) have $n = 3$ and are not used for inference.




Figure 5: NASA Protocol A exploratory ladder (mean±s.d., three seeds). Dashed line: persist_fade. L1 uses leave-target-out median T_{EOL}. L1 and L2 traces overlap; raw-t L0 is a same-cell countdown.

Table 10: Information ladder RUL RMSE (cycles; mean±s.d. over three seeds). T is the EOL cycle (SOH$\leq$ 0.7). L0 uses raw t. L1 uses t/T^{prior} from leave-target training cells. L1P is MLP only: SOH-matched sibling RUL.

Model	Cell	L2	L1	L1P	L0
NASA					
mlp	B0005	23.58±3.85	23.62±3.89	5.06±0.23	11.77±0.15
mlp	B0006	10.62±1.69	10.52±1.70	5.45±0.45	6.46±0.99
mlp	B0007	20.19±3.80	20.16±3.70	8.66±0.10	11.22±2.68
patch-tf	B0005	19.17±2.43	19.17±2.42	2.84±0.89	10.21±1.21
patch-tf	B0006	10.11±0.23	10.11±0.23	3.10±0.19	4.63±0.33
patch-tf	B0007	15.25±2.27	15.26±2.27	3.62±0.73	10.84±2.08
CALCE					
mlp	CS2_35	2.73±1.38	3.00±2.15	18.19±9.40	33.42±2.78
mlp	CS2_36	2.20±1.30	2.28±1.12	60.69±20.40	40.33±2.14
mlp	CS2_37	2.72±1.00	2.86±1.11	15.68±0.97	45.28±2.45
mlp	CS2_38	11.87±1.95	12.40±1.60	53.74±3.25	46.00±3.99
patch-tf	CS2_35	24.85±12.20	32.00±4.12	13.25±0.63	23.80±3.12
patch-tf	CS2_36	33.74±9.75	41.34±0.95	23.33±5.26	27.05±6.08
patch-tf	CS2_37	34.65±7.25	35.74±0.78	24.51±6.81	26.11±10.75
patch-tf	CS2_38	41.56±12.26	25.31±9.90	40.66±9.34	28.93±2.13

Table 11: Classical RUL baselines on chronological test windows with RUL$>$ 0. persist_fade: SOH fade in the window (L0-valid). persist_recursive: $\widehat{\text{RUL}}_t = \max(\widehat{\text{RUL}}_{t-1} - 1, 0)$ initialized by persist_fade (no labels). persist_hold uses true RUL_{t-1} and is an oracle walk, not an L0 BMS baseline. linear: least-squares SOH fit. Fade RMSE > 500 is marked unstable.

Corpus	Cell	fade	recursive	hold (oracle)	linear
calce	CS2_35	unstable	5.07	1.00	123.37
calce	CS2_36	unstable	262.71	1.00	47.55
calce	CS2_37	unstable	7.83	1.00	79.85
calce	CS2_38	unstable	265.78	1.00	308.31
nasa	B0005	7.63	6.14	1.00	7.92
nasa	B0006	3.68	0.48	1.00	7.33
nasa	B0007	30.29	15.53	1.00	28.10

Table 12: Cell-level MLP RUL RMSE (mean over three seeds). The experimental unit is the cell (n=7). Paired Wilcoxon on $\text{RMSE}_{L0} - \text{RMSE}_{L2}$: $p = 0.219$; on $\text{RMSE}_{L1} - \text{RMSE}_{L2}$: $p = 0.156$. Signs mix across NASA (L0 easier) and CALCE (L0 harder); seed tests are not a substitute.

Corpus	Cell	L2	L1	L0
calce	CS2_35	2.73	3.00	33.42
calce	CS2_36	2.20	2.28	40.33
calce	CS2_37	2.72	2.86	45.28
calce	CS2_38	11.87	12.40	46.00
nasa	B0005	23.58	23.62	11.77
nasa	B0006	10.62	10.52	6.46
nasa	B0007	20.19	20.16	11.22




Figure 6: CALCE CS2 exploratory ladder (demoted relative to Severson Protocol B). MLP on CS2_36–38 shows L2≈L1 ≪ L0; persist_fade (dashed) explodes under regeneration.

5.5. Revision controls: scale, matching, SOH heads, support

Four controls bound the mechanism in Section 5.3 (artifacts in `outputs/revision_controls/` and `outputs/l1p_mechanism/`).

Scale control.. An independent matched MLP re-run (seeds $\{42, 43, 44\}$; same Protocol A windows; not the Table 10 training run) isolates numerical scale from the lifetime label. In that re-run, L1 and L2 RUL RMSE agree to within $\sim$ 0.1 cycle (B0005: 23.62 ± 3.17 vs. 23.58 ± 3.15; similarly B0006/B0007), while raw-t L0 is lower on B0005 (14.92 ± 1.48) and B0007 (13.58 ± 2.76). An L0 clock $t/1000$ recovers L1/L2-like errors (23.11 ± 3.07 on B0005). Means for L2 match Table 10 to two decimals; seed-wise s.d. and L0 means differ because the runs are not identical, so scale-control numbers

must not be mixed with Table 10 as one estimate. This control indicates that the L1/L2 behaviour is partly attributable to numerical scale rather than to the semantic meaning of the lifetime constant alone. Pointwise $|\hat{y}^{\mathrm{L1}} - \hat{y}^{\mathrm{L2}}|$ has mean < 0.25 cycle and correlation > 0.97 across seeds, supporting empirical scale robustness without claiming invariance.

Channel support.. On every scored NASA test window, the L2 channel lies above its training maximum: $c^{(2)}$ test ranges are 0.85–0.99 (B0005), 0.89–0.99 (B0006), and 0.83–0.97 (B0007), against training maxima 0.85, 0.88, and 0.83. The same holds for window-interior values (the often-cited "24% above train max" counts cycles inside test windows, not window-end values, and understates the issue). L1 and L0 are monotone in t and inherit the same out-of-support status, but their numerical ranges differ; raw t happens to extrapolate better than the compressed clock $c^{(2)}$, which is a scale effect rather than an information effect. This is why Section 5.3 reads the L2 failure as learnability, not as insufficiency.

L1P matching distance.. Mean absolute SOH matching distances are small (B0005 0.0039; B0006 0.0307; B0007 0.0010), so L1P undershoot of L2 is not an artifact of failed nearest-neighbour SOH lookup. Over full trajectories the correlation between matching distance and absolute RUL error is weak-to-negative (B0005 -0.53; B0006 -0.59; B0007 -0.10) because early-life windows combine tight matches with large absolute RUL. On the scored late-life windows the sign reverses (0.75, 0.76, 0.27; Table 9), which is the relevant check: where L1P is used, a poorer SOH match does predict a larger error.

SOH-only versus dual-head.. Table 13 isolates the dual-head anomaly reported in earlier drafts. With the paper loss, SOH RMSE is 0.56–0.81 while an SOH-only head on the same windows reaches 0.017–0.031; the gradient norm of the RUL term at the shared trunk is 64–130 times that of the SOH term, and early stopping is driven by validation RUL RMSE. The SOH head is therefore under-trained, not unlearnable: normalising the RUL target by T (so that both losses are $O(1)$) recovers SOH RMSE to 0.026–0.177, close to the SOH-only floor, while RUL RMSE changes by at most ~ 5 cycles and

does not alter any ranking in this paper. We conclude that the earlier gap was a loss-scale and early-stopping artifact of sharing a trunk under a RUL-dominated objective. The full per-level dual-head table is retained only in the Appendix (Table 16); it is a multi-task diagnostic, not an SOH benchmark, and no RUL conclusion depends on it.

Table 13: Dual-head SOH anomaly and its repair (NASA Protocol A, L2 channel, three seeds, mean±s.d.). "Paper loss" is $\mathcal{L}_{\mathrm{SOH}} + 0.5\mathcal{L}_{\mathrm{RUL}}$; "normalised" divides the RUL target by T so both terms are $O(1)$; "SOH-only" early-stops on SOH RMSE. The last column is the ratio $g_{\mathrm{RUL}}/g_{\mathrm{SOH}}$ of RUL-loss to SOH-loss gradient norms at the shared trunk over the first three epochs (mean over runs).

Cell	SOH (paper)	SOH (norm.)	SOH-only	RUL (paper)	RUL (norm.)	$g_{\mathrm{RUL}}/g_{\mathrm{SOH}}$
B0005	0.706 ± 0.184	0.034 ± 0.022	0.017 ± 0.002	23.58 ± 3.85	19.43 ± 6.36	124
B0006	0.812 ± 0.294	0.177 ± 0.060	0.031 ± 0.005	10.62 ± 1.69	15.42 ± 7.94	64
B0007	0.562 ± 0.142	0.026 ± 0.014	0.020 ± 0.003	20.19 ± 3.80	24.51 ± 3.89	130

5.6. Legacy L2 under T_{record}

This subsection is a historical oracle baseline under T_{record}, not primary evidence. Table 14 restates the earlier matched chronological comparison that used T_{record} in cycle_norm. Those numbers describe ranking when relative progress to the *recorded* end is known, and when L1 cannot separate from L2. They are not deleted; they are relabeled as an oracle with a degenerate lifetime definition.

Table 14: Legacy L2 (oracle with $T = T_{\mathrm{record}}$) matched RUL RMSE (cycles; three seeds). Persistence here is persist_fade on the untruncated chronological tail.

Model	B0005	B0007
persist_fade	6.81	30.30
Linear extrap.	7.01	28.10
MLP	5.22 ± 0.99	$\mathbf{5.91 \pm 1.91}$
Patch-TF	$\mathbf{2.28 \pm 0.96}$	9.67 ± 2.95

Dropping cycle_norm while keeping the other five channels (L0-drop, same legacy split) collapsed Patch-TF and MLP to about 19–22 RMSE on

both cells. That remains the sharpest single demonstration that the legacy headline error was not a property of capacity/voltage channels alone.

5.7. Why persist_fade fails on B0007, and why T is censored

On the legacy split, persist_fade is 6.81 cycles on B0005 and 30.3 on B0007. Fig. 1B shows the mechanism: B0007's recorded SOH ends near 0.76 and never crosses 0.7, so T equals the last observed cycle, and late increments are often positive. A window fade rate near zero maps to an enormous implied RUL. The failure therefore has two coupled causes: the local fade is non-monotone, and the target is *right-censored*, so extrapolating to 0.7 asks the baseline to invent a decline that was never observed. The L0-valid recursive walk, initialized by persist_fade then counting down by one cycle, is 15.53 on B0007 versus 6.14 on B0005 (Table 11). persist_hold remains 1.0 because it copies true RUL_{t-1} and is an oracle. "Learned models beat persistence under L0 on B0007" is therefore true for persist_fade (30.29) and must not be written against persist_hold. Because B0007 is censored, its absolute RUL RMSE is a record-horizon error and should not be compared numerically with B0005/B0006; it is used here as a stress case for the L1P mechanism and for persist_fade, not as a lifetime benchmark.

6. Discussion

Finding 1: information level changes the ranking.. Under Severson Protocol B (n=24), median MLP RMSE falls from 222.1 at L0 to 12.0 at L2, and L0 exceeds L2 on every scored cell (Fig. 2). That leave-target-cell-out ladder is the primary support for $\mathrm{Rank}(\cdot \mid \mathcal{I}_t) = f(\mathcal{I}_t)$. The L0 error is in the same regime as persist_fade (242.8), so the ladder is not an artefact of a weak model family.

Finding 2: the L1P inversion is a support-and-learnability effect.. NASA Protocol A adds a narrower second lesson, and the mechanism analysis sharpens it. L1P can beat L2 even when SOH matching distances stay small (Fig. 4), because the L2 clock is evaluated outside its training support and the fitted network compresses late-life variation, while L1P is an SOH-indexed local

average that remains inside its matching neighbourhood (Section 5.3). This is not a case of "less information is better". It is a case in which additional information was *sufficient but not learnable* on the scored windows under the chosen fit protocol, a distinction that a single RMSE column cannot reveal. The inversion disappears under Protocol B (L1P 30.3 vs. L2 12.0) and reverses on CALCE CS2_36 (L1P 60.69 vs. L2 2.20), so the correct claim is conditional, not universal.

Finding 3: Protocol A and Protocol B answer different questions.. Equation (7) explains why L1 and L2 look alike under Protocol A: they are affine rescalings of the same t (Table 1). Scale-control runs confirm empirical robustness of the trained networks, but they do not prove invariance. Protocol B breaks the practical L1≈L2 pattern because a single sibling prior cannot restore target-specific relative life across $T \in [147, 1933]$. Under Protocol A, raw t can also beat L2 when the late-life test set is essentially a within-cell countdown. That pattern is a Protocol A artifact; it does not overturn the Protocol B result, and it is the reason Section 5.4 is labelled exploratory.

Relation to benchmark platforms.. BatteryML [18] and BatteryLife [22] make data pipelines and model comparisons reproducible; this paper addresses a different axis, the auditability of the information condition. The two are complementary: dataset and model cards can carry an "information level / fit protocol / T definition / scaler source / support status" row for every reported score, and the ladder can be implemented as a wrapper around their evaluation harness without changing the models. We do not claim that current platforms are leaky; we claim that their reporting cards leave the information condition implicit, which is enough for two incomparable scores to appear side by side.

Practical guidance.. For an online BMS claim, L2 must be reported as a named retrospective oracle and never as a deployable result. When T is unknown and a comparable fleet exists, an SOH-indexed sibling prior is a reasonable online-valid plug-in, with the caveat that it needs SOH coverage and a stable local SOH–RUL relation; when no fleet exists, keep the L0

recursive walk and report the oracle only as an upper bound. For a benchmark claim, report Protocol B; for a within-cell retrospective study, report Protocol A and state that L1/L1P may be undefined without siblings.

Limitations.. NASA and CALCE stay Protocol A diagnostics, and the mechanism analysis rests on three NASA cells. Severson Protocol B uses a stratified 24-cell stress subset of 119 usable cells, not a random population sample. B0007 is right-censored, so its absolute errors are record-horizon errors. Beyond NASA cycle aggregates, the extracts omit full in-cycle V/I/T trajectories. All scores are cycle-level after a completed discharge. The SOH head is a diagnostic, not a validated SOH estimator, and its repair is demonstrated only on NASA. Finally, L1P is a local prior: it is only as good as the sibling coverage, and its failure on CALCE CS2_36 is part of the result rather than an outlier to be removed.

7. Conclusion

RUL benchmarks should encode prediction-time information in the protocol itself. Information-consistent evaluation couples four things that are usually reported separately: a named information level, a declared fit protocol, a provenance and support audit, and a fillable report row. Under first-EOL labels and named L0/L1/L1P/L2 cycle channels, leave-target evaluation on Severson (n=24) shows that information level changes RUL error (L0 222.1 vs. L2 12.0; $p = 1.2\times10^{-7}$). NASA Protocol A further shows a setting-specific reversal, L1P beating L2, which we trace to the oracle clock leaving its training support while an SOH-indexed local prior stays inside its matching neighbourhood. Future tables should report information level, fit protocol, the T definition and censoring status, channel support, and persist_fade with RMSE, not the architecture name alone.

Table 15: Appendix OLS identity check on evaluated chronological windows (RUL>0). OLS is an algebraic diagnostic of RUL $= \max(0, T - t)$, not an out-of-sample predictive baseline: it is fit with an intercept on the same scored windows. Under that identity, OLS RMSE on raw t is numerically zero on NASA and CALCE. ρ is Pearson correlation; $\rho(\mathrm{L1}, \mathrm{L2}) = 1$ because L1 and L2 are affine in t. L1P is not affine in t.

Corpus	Cell	$\rho(\mathrm{L1}, \mathrm{L2})$	$\rho(\mathrm{L1P}, \mathrm{L2})$	OLS t	OLS L1P
nasa	B0005	1.000	-0.703	0	14.20
nasa	B0006	1.000	-0.598	0	15.57
nasa	B0007	1.000	-0.824	0	13.28
calce	CS2_35	1.000	-0.122	0	98.18
calce	CS2_36	1.000	-0.706	0	101.04
calce	CS2_37	1.000	-0.654	0	99.90
calce	CS2_38	1.000	-0.621	0	96.29

Table 16: SOH RMSE (dimensionless; mean±s.d. over three seeds) under the same information ladder.

Model	Cell	L2	L1	L0
mlp	B0005	0.7063±0.1843	0.7007±0.1826	0.3302±0.0660
mlp	B0006	0.8120±0.2939	0.8180±0.2988	0.2879±0.0462
mlp	B0007	0.5625±0.1420	0.5640±0.1332	0.3358±0.0264
patch-tf	B0005	0.3593±0.0567	0.3583±0.0565	0.5132±0.1256
patch-tf	B0006	0.5564±0.3209	0.5548±0.3199	0.4427±0.0678
patch-tf	B0007	0.4028±0.0108	0.4044±0.0119	0.6538±0.4076

Appendix. OLS identity check

Appendix. Seed-level contrasts and full SOH table

Appendix. Reporting template

Required fields: corpus, cell id, T definition and whether EOL was reached, whether post-EOL windows are dropped, persist_fade RMSE, fit protocol, channel support status, and the information level of every learned row. Optional: SOH RMSE as an auxiliary control; PICP/PINAW in the appendix.

Table 17: Seed-level paired contrasts of RUL RMSE (selected). The experimental unit is the random seed on a fixed cell ($n = 3$), not the cell. Wilcoxon p=0.25 is the smallest two-sided value when all three seeds move in the same direction. Full contrasts are in `outputs/info_levels_v2/stats.json`.

Contrast	Corpus	Model	Cell	ΔRMSE	Cohen's d	p
L2-vs-L0	calce	mlp	CS2_35	30.69	13.98	0.250
L2-vs-L1	calce	mlp	CS2_35	0.27	0.15	0.750
L2-vs-L0	calce	mlp	CS2_36	38.13	21.52	0.250
L2-vs-L1	calce	mlp	CS2_36	0.08	0.07	0.750
L2-vs-L0	calce	mlp	CS2_37	42.55	22.73	0.250
L2-vs-L1	calce	mlp	CS2_37	0.14	0.13	0.500
L2-vs-L0	calce	mlp	CS2_38	34.13	10.86	0.250
L2-vs-L1	calce	mlp	CS2_38	0.53	0.30	0.500
L2-vs-L0	nasa	mlp	B0005	-11.81	-4.33	0.250
L2-vs-L1	nasa	mlp	B0005	0.04	0.01	0.750
L2-vs-L0	nasa	mlp	B0006	-4.16	-3.00	0.250
L2-vs-L1	nasa	mlp	B0006	-0.10	-0.06	0.250
L2-vs-L0	nasa	mlp	B0007	-8.97	-2.73	0.250
L2-vs-L1	nasa	mlp	B0007	-0.03	-0.01	1.000
L2-vs-L0	nasa	patch-tf	B0005	-8.95	-4.67	0.250
L2-vs-L1	nasa	patch-tf	B0005	0.01	0.00	1.000
L2-vs-L0	nasa	patch-tf	B0006	-5.49	-19.33	0.250
L2-vs-L1	nasa	patch-tf	B0006	-0.01	-0.03	0.750
L2-vs-L0	nasa	patch-tf	B0007	-4.41	-2.03	0.250
L2-vs-L1	nasa	patch-tf	B0007	0.02	0.01	0.500

Table 18: Minimum report row (copy per model × cell × level).

Model	Level	Cycle channel	W, H	Scaler	Support	RUL RMSE
Patch-TF	L0	raw t	50, 5	train	in	…
Patch-TF	L1	t/T_{med}	50, 5	train	in	…
Patch-TF	L2	t/T_{target}	50, 5	train	out (oracle)	…
persist_fade	—	SOH only	50, —	—	—	…

Appendix. Uncertainty (not a calibration claim)

Table 19: Appendix. MC-Dropout 95% intervals ($n_{\mathrm{MC}} = 20$) for Patch-TF RUL on NASA. PICP is empirical coverage of mean±1.96 std; PINAW is width normalized by the test RUL range. Not used as a calibration claim.

Cell	L2 PICP	L2 PINAW	L0 PICP	L0 PINAW
B0005	0.058±0.025	0.599±0.077	0.522±0.174	0.879±0.167
B0006	0.056±0.048	0.709±0.041	0.528±0.210	0.878±0.265
B0007	0.217±0.075	0.607±0.097	0.377±0.280	0.792±0.165

Statements and Declarations

Funding.. None.

Competing interests.. None.

Data availability.. NASA PCoE cells B0005–B0007 [1]; CALCE CS2 cells [3]; Severson/MATR batches [11]. Replication scripts: `scripts/run_info_levels_v2.py`, `scripts/run_revision_controls.py`, `scripts/run_l1p_mechanism.py`, `outputs/info_levels_v2/`, `outputs/info_levels_severson/`, `outputs/info_levels_severson_loco/`, `outputs/revision_controls/`, `outputs/l1p_mechanism/`.

References

[1] B. Saha, K. Goebel, Battery Data Set, NASA Ames Prognostics Data Repository, Moffett Field, CA (2007).

[2] B. Saha, K. Goebel, J. Christophersen, Comparison of prognostic algorithms for estimating remaining useful life of batteries, Trans. Inst. Meas. Control 31 (3–4) (2009) 293–308.

[3] W. He, N. Williard, M. Osterman, M. Pecht, Prognostics of lithium-ion batteries based on Dempster–Shafer theory and the Bayesian Monte Carlo method, J. Power Sources 196 (23) (2011) 10314–10321.

[4] S. Kaufman, S. Rosset, C. Perlich, O. Stitelman, Leakage in data mining: Formulation, detection, and avoidance, ACM Trans. Knowl. Discov. Data 6 (4) (2012) 1–21.

[5] Y. Gal, Z. Ghahramani, Dropout as a Bayesian approximation: representing model uncertainty in deep learning, in: Proc. 33rd Int. Conf. Mach. Learn., PMLR 48 (2016) 1050–1059.

[6] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A.N. Gomez, L. Kaiser, I. Polosukhin, Attention is all you need, in: Adv. Neural Inf. Process. Syst. 30 (2017) 5998–6008.

[7] C.R. Birkl, M.R. Roberts, E. McTurk, P.G. Bruce, D.A. Howey, Degradation diagnostics for lithium ion cells, J. Power Sources 341 (2017) 373–386.

[8] R. Xiong, L. Li, J. Tian, Towards a smarter battery management system: a critical review on battery state of health monitoring methods, J. Power Sources 405 (2018) 18–29.

[9] M.S.H. Lipu, M.A. Hannan, A. Hussain, M.M. Hoque, P.J. Ker, S.M.A. Saad, A. Ayob, A review of state of health and remaining useful life estimation methods for lithium-ion battery in electric vehicles: challenges and recommendations, J. Clean. Prod. 205 (2018) 115–133.

[10] X. Hu, F. Feng, K. Liu, L. Zhang, J. Xie, B. Liu, State estimation for advanced battery management: key challenges and future trends, Renew. Sustain. Energy Rev. 114 (2019) 109334.

[11] K.A. Severson, P.M. Attia, N. Jin, N. Perkins, B. Jiang, Z. Yang, M.H. Chen, M. Aykol, P.K. Herring, D. Fraggedakis, M.Z. Bazant, S.J. Harris, W.C. Chueh, R.D. Braatz, Data-driven prediction of battery cycle life before capacity degradation, Nat. Energy 4 (2019) 383–391.

[12] D. Roman, S. Saxena, V. Robu, M. Pecht, D. Flynn, Machine learning pipeline for battery state-of-health estimation, Nat. Mach. Intell. 3 (2021) 447–456.

[13] V. Sulzer, P. Mohtat, A. Aitio, S. Lee, Y.T. Yeh, F. Steinbacher, M.U. Khan, J.W. Lee, J.B. Siegel, A.G. Stefanopoulou, D.A. Howey, The challenge and opportunity of battery lifetime prediction from field data, Joule 5 (2021) 1934–1955.

[14] A. Geslin, B. van Vlijmen, X. Cui, A. Bhargava, P.A. Asinger, R.D. Braatz, W.C. Chueh, Selecting the appropriate features in battery lifetime predictions, Joule 7 (2023) 1956–1965.

[15] S. Kapoor, A. Narayanan, Leakage and the reproducibility crisis in machine-learning-based science, Patterns 4 (9) (2023) 100804.

[16] Y. Nie, N.H. Nguyen, P. Sinthong, J. Kalagnanam, A time series is worth 64 words: long-term forecasting with transformers, in: Int. Conf. Learn. Represent. (2023).

[17] M. Rosenblatt, L. Tejavibulya, R. Jiang, S.M. Noble, D. Scheinost, Data leakage inflates prediction performance in connectome-based machine learning models, Nat. Commun. 15 (2024) 1829.

[18] H. Zhang, X. Gui, S. Zheng, Z. Lu, Y. Li, J. Bian, BatteryML: An open-source platform for machine learning on battery degradation, in: Int. Conf. Learn. Represent. (2024).

[19] T. Li, Z. Zhou, A. Thelen, D.A. Howey, C. Hu, Predicting battery lifetime under varying usage conditions from early aging data, Cell Rep. Phys. Sci. 5 (4) (2024) 101891.

[20] S. Wang, R. Zhou, Y. Ren, M. Jiao, H. Liu, C. Lian, Advanced data-driven techniques in AI for predicting lithium-ion battery remaining useful life: a comprehensive review, Green Chem. Eng. 6 (2) (2025) 139–153.

[21] H. Zhang, Y. Li, S. Zheng, Z. Lu, X. Gui, W. Xu, J. Bian, Battery lifetime prediction across diverse ageing conditions with inter-cell deep learning, Nat. Mach. Intell. 7 (2025) 270–277.

[22] R. Tan, W. Hong, J. Tang, X. Lu, R. Ma, X. Zheng, J. Li, J. Huang, T.-Y. Zhang, BatteryLife: A comprehensive dataset and benchmark for battery life prediction, arXiv:2502.18807 (2025).

[23] S.S. Madani, M. Hébert, L. Boulon, A. Lupien-Bédard, F. Allard, Comparative analysis of ML and DL models for data-driven SOH estimation of LIBs under diverse temperature and load conditions, Batteries 11 (11) (2025) 393.

[24] Z. Xu, J. Mao, Y. Han, H. Yuan, A comprehensive review of lithium-ion battery remaining useful life prediction: methodologies, datasets, performance metrics, and future perspectives, Meas. Sci. Technol. 36 (8) (2025) 082001.

[25] Y. Yang, S. Wang, Y. Zhou, C. Fernandez, A critical review of AI-based battery remaining useful life prediction for energy storage systems, Batteries 11 (10) (2025) 376.

[26] Y. Deng, X. Le, T.T. Nguyen, C. Gogu, A generic physics-informed machine learning framework for battery remaining useful life prediction using small early-stage lifecycle data, Appl. Energy 384 (2025) 125314.

[27] I. Oyewole, W. Hassanieh, M. Chelbi, A. Chehade, Uncertainty-aware deep learning with physics-informed bayesian sampling for lithium-ion battery prognostics, Appl. Energy 402 (2025) 126880.

[28] S. Aliakbari, M. Masih-Tehrani, FuseDR-Net: a fusion-based network for battery remaining useful life prediction using causally decomposed health indicators, Energy Convers. Manag. X 28 (2025) 101341.

[29] X. Ge, Y. Jiang, B. Xu, Deep Koopman operator-based remaining useful life prediction of Lithium-ion batteries under multi-condition scenarios, J. Energy Storage 119 (2025) 116369.

[30] J. Li, Z. Wang, D. Tian, Z. Sun, Y. Niu, A novel RUL prediction framework based on the adaptability feature perception fusion model method, J. Energy Storage 119 (2025) 116322.

[31] J. Huang, L. Liu, H. Zhao, T. Li, B. Li, RUL-Mamba: Mamba-based remaining useful life prediction for lithium-ion batteries, J. Energy Storage 120 (2025) 116376.

[32] A. Tian, H. Yu, Z. Hu, Y. Wang, T. Wu, J. Jiang, A novel remaining useful life prediction method based on CNN-Attention combined with SMA-GPR, Energy 321 (2025) 135233.

[33] X. Yi, J. Xiao, G. Lei, X.-H. Hu, Z. Feng, A lithium-ion battery remaining useful life prediction model based on multilayer perceptron expert networks and temporal feature composition, J. Power Sources 659 (2025) 238371.

[34] K. Wang, J. Wang, Z. Wang, H. Li, An enhanced deep learning framework for state of health and remaining useful life prediction of lithium-ion battery based on discharge fragments, J. Energy Storage 107 (2025) 114952.

[35] B. Ali, I. Matloob, N. Alkhalifa, A.K. Alkhalifa, N. Asim, S. Kanwal, S. Inam, Deep learning-based RUL and SOH prediction of lithium-ion batteries using LOCO, Sci. Rep. 16 (2026) 27853.

[36] A. Barua, J.M. Collins, M.R. Islam, S. Barua, Predictor structure modulates validation inflation and cell-transfer reliability in battery state-of-health estimation, Batteries 12 (9) (2026) 342.

[37] Y. Sun, F. Gao, SG-DiTs: A physics-informed diffusion-transformer hybrid framework for reliable battery RUL prediction, J. Energy Storage 152 (2026) 120479.

[38] Y. Fan, Z. Xu, H. Zhu, Y. Yu, Physics-informed signal decomposition and data-driven RUL estimation for lithium-ion batteries, Meas. Sci. Technol. 37 (18) (2026) 186103.

[39] X. Li, H. Zhang, DpMamba: a dual-path state space model for reliable remaining useful life prediction of lithium-ion batteries, Meas. Sci. Technol. 37 (34) (2026) 346105.