

EVODUET: Bilevel Co-Evolution of Web Searching and Task Solving for Scientific Discovery

Young-Jun Lee¹ Jinheon Baek^{2*} Soyeong Jeong^{2*} Minki Kang^{2*} Seungyeon Jwa^{1,3}
Jonghyun Choi³ Seungho Han⁴ Dongyeop Kang¹

¹University of Minnesota ²KAIST ³Seoul National University ⁴Hanyang University
passing2961@gmail.com dongyeop@umn.edu



EvoDuet Project Page

Abstract

Evolutionary search with large language models (LLMs) can stall when progress requires external knowledge the model lacks. Supplying relevant documents helps, but simply adding web search tool can keep returning the same pages as solutions change. We introduce **EVODUET**, a bi-level optimization method that co-evolves *solutions* and *search queries* with fixed model parameters. At each iteration, a retrieval gate lets the LLM assess its knowledge gap and choose to retrieve new documents, reuse stored ones, or proceed without them. An inner loop refines queries and ranks documents by the solution scores they are predicted to yield; an outer loop generates candidates in parallel from these documents and records the evaluated outcomes for later searches. Across 21 optimization tasks with one candidate per iteration, EVODUET raises OpenEvolve’s normalized discovery gain from 74.1% to 78.0% with GPT-5.6-Luna and from 61.3% to 82.3% with Gemini-3.8-Flash, whereas Qwen3.5-9B does not benefit. Our best runs surpass the previously reported best scores on eight tasks, including Swap Reduction on Q20 and Rosetta, and match them on three more. EVODUET also improves with other scaffolds (e.g., Top- K , EvoX) on Sums/Diffs and Denoising, demonstrating its applicability across evolutionary search scaffolds.

1. Introduction

Evolutionary search scaffolds driven by large language models (LLMs) (Romera-Paredes et al., 2024; Novikov et al., 2025) have begun to discover new solutions to optimization tasks such as the Erdős minimum-overlap problem (Erdős, 1955), GPU kernel design (Ouyang et al., 2025), and single-cell RNA-seq denoising (Yuksekgonul et al., 2026). In these tasks, an evaluator can score any candidate solution, but the optimal solution cannot be computed directly (Kirkpatrick et al., 1983). Scaffolds therefore iterate: the LLM proposes candidates, the evaluator scores them, and high-scoring candidates seed the next iteration.

Most scaffolds (Sharma, 2025; Lange et al., 2025; Cemri et al., 2026) run only this *solution loop*. Others keep the solution loop from saturating by wrapping additional loops around it, a design we call *Loop Packing* (Figure 1). For example, EvoX (Liu et al., 2026a) adds a strategy loop that revises the search strategy when progress stagnates. However, every loop packed so far draws on the same two sources of knowledge: the run’s evolutionary history and the LLM’s parametric knowledge. The search is therefore **closed**, and it stalls when progress requires external knowledge that neither source contains (e.g., how to use a newer library version). Human scientists, by contrast, consult the literature and search again as new knowledge gaps emerge.

Our preliminary analysis (§ 2.3) shows that external knowledge helps LLM-driven search, but not automatically. Supplying task-relevant and helpful documents at every iteration (oracle documents) raises OpenEvolve’s average Normalized Discovery Gain (NDG) on




Figure 1: Packing loops of multiple optimization scaffolds

*Co-second authors with equal contribution, listed alphabetically by surname.




Figure 2: EVODUET co-evolves solutions and web queries. The inner loop evolves queries; the outer loop uses retrieved documents to revise and evaluate solutions. The Swap Reduction example illustrates *method transfer* (the most common of the six behaviors analyzed in Section 5.1): the model applies retrieved routing principles to prioritize gates closer to execution (iteration 5) and penalize reversing the last SWAP (iteration 66). At iteration 64, the gate reuses stored documents without a new web search. The best router found in this run uses 14,835 Q20 SWAPs, 2.31% fewer than the released SimpleTES program (WILL Team, 2026) (15,186) under the same evaluator.

31 tasks by 10.3% with Qwen3.5-9B and 4.0% with GPT-5.6-Luna. Two further observations show that turning such knowledge into progress takes more than a search tool: First, the LLM needs room to explore: on Sums/Diffs, oracle documents help only when the LLM generates eight candidates per iteration rather than one. Second, queries must evolve with the solution: on Denoising, an LLM that searches inside the solution loop mostly retrieves pages it has already seen (88.1% of returned URLs) and stops improving after 50 iterations. We therefore co-evolve web search queries with solutions (Figure 1), making the search **open**.

We introduce **EVODUET**, a bi-level optimization method that co-evolves solutions in an outer loop and web search queries in an inner loop, with the LLM’s parameters fixed. A knowledge-gap-based retrieval gate connects the loops: at each iteration, the LLM assesses what it still needs to know to improve the current solution (its knowledge gap) and decides whether to retrieve new documents, reuse stored ones, or proceed without documents. When it retrieves, the inner loop constructs queries targeting the gap, searches the web, and ranks documents by *hypothetical evidence scoring*, which predicts the evaluator score of a candidate built on each document. These predictions and the updated knowledge state steer the next round of queries without evaluating any candidate. Given documents, the outer loop generates candidates in parallel and records the documents with the evaluated outcome to guide later searches. Figure 2 illustrates this interplay on Swap Reduction (quantum compilation).

We evaluate EVODUET with OpenEvolve on 21 optimization tasks. With one candidate per iteration, it raises overall NDG from 74.1% to 78.0% with GPT-5.6-Luna and from 61.3% to 82.3% with Gemini-3.8-Flash, and parallel generation improves it further. Qwen3.5-9B does not benefit, even though oracle documents help it: it often leaves retrieved methods unused or misimplemented (26% of sampled revisions), suggesting that co-evolution requires a model that can both find and apply evidence. The best runs of EVODUET surpass the previously reported best scores on eight tasks and match them on three more; on Denoising, EVODUET surpasses SimpleTES (WILL Team, 2026) at 6.9× lower estimated cost. It also improves other scaffolds, Top-*K* and EvoX, on Sums/Diffs and Denoising, showing that the search loop can be packed alongside existing loops.

Finally, we analyze how retrieved documents shape the search. Candidates improve on their parent in 67.1% of iterations that retrieve a document predicted to beat the parent, compared with 52.1% of iterations without documents. The most common use of documents is *method transfer*, in which the model applies a retrieved method to its solution (55 of 82




Figure 3: OpenEvolve with and without oracle documents on 31 optimization tasks using Qwen3.5-9B and GPT-5.6-Luna. (a) Average NDG across tasks. (b) Per-task ΔNDG versus baseline NDG, with bin medians pooled across models. Shading marks baseline NDG below 5% or at least 80%; hollow markers denote simple tasks. The dashed line shows the gain needed to reach 100% NDG. (c) Per-task ΔNDG in descending order. Legends count tasks with NDG increases (improved) or decreases (degraded) of more than 1%; shading indicates changes within $\pm 1\%$.

runs). Yet documents predicted to help can also yield much worse candidates (29 of 82 runs), so predicted gains must still be validated by the evaluator.

2. Analysis of Web Search in Scientific Discovery

2.1. Preliminaries: Evolutionary Search Scaffold

An optimization task $\tau = (I, x_0, \mathcal{E})$ consists of an instruction I , an initial solution x_0 , and a deterministic, verifiable evaluator $\mathcal{E}(x) \in \mathbb{R}$. The goal of an evolutionary search scaffold is to find $x^* = \arg \text{opt}_{x \in \mathcal{X}} \mathcal{E}(x)$, where $\text{opt} \in \{\max, \min\}$ and $\mathcal{X} = \{x_0, \dots, x_T\}$ is the set of solutions explored within a search budget of T . The task determines the optimization direction (e.g., minimizing the c_5 bound in the Erdős minimum overlap problem). At each iteration, the evolutionary search scaffold (Romera-Paredes et al., 2024; Novikov et al., 2025; Sharma, 2025; Liu et al., 2026a) selects a parent solution x_t and its evolutionary history $\mathcal{H}_t$ from its solution database (*a.k.a.* population) $\mathcal{D}_p$ under a policy ϕ , forming the context $c_t = [\mathcal{H}_t; x_t]$. A frozen LLM $\mathcal{M}_\theta$, serving as the mutation operator, generates a candidate solution $x_{t+1} \sim \mathcal{M}_\theta(I, c_t)$, which the evaluator $\mathcal{E}$ then scores. Based on the selection policy ϕ , the candidate solution x_{t+1} is then either added to the population $\mathcal{D}_p$ or discarded. We call x^* a *discovery* if it improves upon the previous best-known solution x_{sota} , i.e., $\mathcal{E}(x^*) > \mathcal{E}(x_{\text{sota}})$ for maximization tasks, with the inequality reversed for minimization tasks.

2.2. Experimental Setup

Tasks. We evaluate on 31 optimization tasks spanning simple scientific optimization (10), quantum compilation (1), astrodynamics (5), scientific algorithms (1), AI foundations (4), mathematics (8), and algorithm engineering (2). Detailed task descriptions are provided in Appendix C.1.

Baselines. We use Qwen3.5-9B (Team, 2026) and GPT-5.6-Luna (OpenAI, 2026) as the LLM $\mathcal{M}_\theta$ in OpenEvolve. For each model, we compare (1) OpenEvolve and (2) OpenEvolve with oracle documents supplied to the LLM at every iteration t . Appendix C.2 describes how we construct the oracle documents. For robustness, we run each baseline with four different random seeds.

Evaluation Metric. Since evaluator score ranges vary across tasks, we report *Normalized Discovery Gain* (NDG) to compare optimization progress on a common scale. NDG measures the percentage of the gap between the initial and SOTA scores closed by a run: $\text{NDG} = \frac{\mathcal{E}(x_{\text{best}}) - \mathcal{E}(x_0)}{\mathcal{E}(x_{\text{SOTA}}) - \mathcal{E}(x_0)} \times 100$, where x_{best} is the best-scoring solution in $\mathcal{X}$, and x_{SOTA} is the best program reported in prior work (WILL Team, 2026). Higher NDG indicates greater progress toward SOTA performance.

2.3. Does web search help scientific discovery?

Oracle documents improve optimization on average, but their benefits vary across models and tasks. As shown in Figure 3a, oracle documents raise the average NDG of Qwen3.5-9B by 10.3% and that of GPT-5.6-Luna by 4.0%. The smaller gain for GPT-5.6-Luna likely reflects limited headroom: OpenEvolve alone already reaches at least 95%




Figure 4: Effects of parallel generation and query evolution with GPT-5.6-Luna. (a) NDG of OpenEvolve on Sums/Diffs (mathematics) with and without oracle documents, using $N = 1$ or $N = 8$ candidates per iteration. (b) Cumulative number of search queries. (c) Number of distinct URLs returned. (d) Held-out NDG of the best program for each method.

NDG on 16 of the 31 tasks. On these tasks, oracle documents change NDG by only 0.1% on average (Figure 3b). Although oracle documents lead to 100% NDG primarily on simple optimization tasks, their benefits also extend to challenging tasks. For example, on Swap Reduction (quantum compilation), oracle documents increase NDG by 6.1% for Qwen3.5-9B and 41.5% for GPT-5.6-Luna (Figure 3c). However, these benefits are not universal: oracle documents lower NDG by more than 1% on 8 and 4 of the 31 tasks for Qwen3.5-9B and GPT-5.6-Luna, respectively, including decreases of 9.0% and 23.3% on Rosetta. Full results are provided in Appendix D.1.

LLMs may need more opportunities to benefit from oracle documents. The mixed effects of oracle documents raise a question: does the LLM lack the ability to use oracle documents, or does it lack sufficient opportunities to act on them? To examine this, we generate N candidates in parallel at each iteration t from the same context c_t . On Sums/Diffs, oracle documents offer no improvement at $N = 1$ (14.8% NDG with oracle documents versus 15.4% without), but increase NDG from 25.8% to 40.7% at $N = 8$ (Figure 4b). This suggests that the LLM can benefit from oracle documents when given more opportunities to explore strategies grounded in them. Additional results are provided in Appendix D.2.

Without query evolution, in-loop web search repeatedly retrieves the same pages and stalls. On Denoising with GPT-5.6-Luna, we equip OpenEvolve with Tavily¹ as an in-loop search tool (*joint-level*), allowing the LLM to construct its own queries during solution optimization. We compare this baseline with EVODUET, which evolves queries based on the LLM’s knowledge gap through bi-level co-evolution. Over 100 iterations, joint-level search uses the tool in 99 iterations and produces 185 queries, compared with 201 for EVODUET (Figure 4b). However, it retrieves only 85 distinct URLs, compared with 248 for EVODUET (Figure 4c); 88.1% of its returned URLs have appeared before, compared with 62.4% for EVODUET. Moreover, joint-level search stops improving after iteration 50, with its best program achieving a held-out NDG of 27.7%, compared with 84.5% for EVODUET (Figure 4d). These results suggest that evolving what to ask based on the LLM’s knowledge gap helps it search for external knowledge more effectively, enabling it to find better solutions.

Takeaways: Web search benefits from broader exploration and query evolution

- Oracle documents increase average NDG across the 31 tasks, with a larger gain for the smaller model (+10.3% vs. +4.0%).
- More opportunities for exploration can help LLMs use oracle documents: on Sums/Diffs, oracle documents improve NDG by 14.9% with eight parallel candidates per iteration.
- Query evolution helps sustain progress: with comparable query counts on Denoising, joint-level search repeatedly retrieves the same pages and stalls, whereas bi-level search, which evolves queries based on the LLM’s knowledge gap, retrieves about 2.9× as many distinct pages and increases NDG by 56.8%.

3. EVODUET

3.1. An Overview of EVODUET

We formulate discovery as a bi-level optimization problem with an outer loop that evolves solutions and an inner loop that evolves queries for web search. As shown in Figure 5, EVODUET has three main components:

¹<https://www.tavily.com/>




Figure 5: Overview of EVODUET. The outer loop evolves solutions, while the inner loop evolves web search queries using predicted solution scores. A knowledge-gap-based retrieval gate links the two loops by deciding whether to retrieve new documents (**RETRIEVE**), reuse stored documents (**LOOK-UP**), or proceed without documents (**NO-OP**).

- **Solution Optimization Loop (outer, § 3.2):** The outer loop follows the scaffold’s evolutionary loop (§ 2.1) to evolve solutions. At iteration t , the selection policy ϕ selects a parent solution x_t and its evolutionary history $\mathcal{H}_t$ from the population $\mathcal{D}_e$, and the LLM $\mathcal{M}_\theta$ generates a candidate solution $x_{t+1} \sim \mathcal{M}_\theta(I, c_t, \mathcal{S}_t)$, where $\mathcal{S}_t$ is either empty or a set of retrieved web documents.
- **Knowledge Gap-based Retrieval Gating (§ 3.3):** This component connects the outer and inner loops, enabling their co-evolution. Based on gaps in the LLM $\mathcal{M}_\theta$ ’s current knowledge status, it determines whether to invoke the inner loop for web search.
- **Query Optimization Loop (inner, § 3.4):** The inner loop evolves web search queries to retrieve documents $\mathcal{S}_t$ that provide the external knowledge needed to generate an improved candidate solution x_{t+1} .

Both loops share the task objective $\mathcal{E}$, with query quality defined by the performance of the candidate solution generated from the retrieved documents. Let $\mathcal{S}_t(q)$ denote the documents retained from query q and $x_{t+1}(q) \sim \mathcal{M}_\theta(I, c_t, \mathcal{S}_t(q))$ the resulting candidate. The ideal bi-level optimization is formulated as

$$\underbrace{x^* = \arg \text{opt}_{x \in \mathcal{X}} \mathcal{E}(x)}_{\text{outer: solution optimization}} \quad \text{s.t.} \quad \underbrace{q_t^* = \arg \text{opt}_{q \in \mathcal{Q}_t} \mathcal{E}(x_{t+1}(q))}_{\text{inner: query optimization}}, \quad x_{t+1} \sim \mathcal{M}_\theta(I, c_t, \mathcal{S}_t(q_t^*)), \quad (1)$$

where $\mathcal{X} = \{x_0, \dots, x_T\}$ is the set of solutions explored within budget T , and $\mathcal{Q}_t$ is the set of admissible queries at iteration t . However, the inner objective $\mathcal{E}(x_{t+1}(q))$ is observable only after the corresponding candidate has been generated and evaluated. Repeating this process for every query within the inner loop would be costly. We therefore approximate the inner optimization in Eq. 1 using $\mathcal{M}_\theta$ to **predict the candidate score** that the retrieved documents would yield. Denoting this score predictor by $\hat{\mathcal{E}}_\theta$, the approximate inner optimization can then be reformulated as $\hat{q}_t = \arg \text{opt}_{q \in \mathcal{Q}_t} \hat{\mathcal{E}}_\theta(I, c_t, \mathcal{S}_t(q))$. The detailed algorithm is presented in Algorithm 1.

3.2. Outer Loop: Solution Optimization

The outer loop follows the scaffold’s typical evolutionary procedure (§ 2.1), but differs in the inputs provided to the LLM $\mathcal{M}_\theta$ during candidate generation. When web documents $\mathcal{S}_t$ are provided, the LLM $\mathcal{M}_\theta$ generates a candidate solution $x_{t+1} \sim \mathcal{M}_\theta(I, c_t, \mathcal{S}_t)$, which is then evaluated by $\mathcal{E}$ and retained or discarded according to ϕ . The web documents $\mathcal{S}_t$ are stored in the search database $\mathcal{D}_s$ together with the candidate’s actual evaluator score $\mathcal{E}(x_{t+1})$. This

stored information is used to decide whether to reuse existing documents in $\mathcal{D}_s$ through a search database $\mathcal{D}_s$ lookup, retrieve additional knowledge from the web, or skip the inner loop.

Gated parallel candidate solution generation. In Section 2, we observe that parallel scaling with rich oracle documents enables the LLM $\mathcal{M}_\theta$ to explore diverse approaches and find better solutions. Motivated by this observation, EVODUET generates N_t candidates in parallel from the same input prompt, with $N_t = N$ for [LOOK-UP](#) or [RETRIEVE](#) and $N_t = 1$ for [NO-OP](#). Candidate generation and selection are formulated as

$$x_{t+1}^{(n)} \sim \mathcal{M}_\theta(I, c_t, \mathcal{S}_t), \quad n = 1, \dots, N_t, \quad x_{t+1} = \arg \operatorname{opt}_{x \in \mathcal{C}_t^{\text{valid}}} \mathcal{E}(x), \quad (2)$$

where $\mathcal{C}_t^{\text{valid}}$ is the set of valid candidates (i.e., those that encounter no errors, such as evaluator errors) among the N_t generated solutions. Each candidate is evaluated, and only the best valid solution is passed to ϕ as x_{t+1} .

3.3. Knowledge-Gap-Based Retrieval Gating

The gate allows $\mathcal{M}_\theta$ to determine *when* to search by assessing whether it needs new external knowledge to improve the current solution x_t , can reuse information stored in $\mathcal{D}_s$, or can evolve the solution using only its internal knowledge. At each iteration, given the context c_t and the documents most recently stored in $\mathcal{D}_s$, $\mathcal{M}_\theta$ outputs its current knowledge state K_t and a retrieval decision g_t :

$$(K_t, g_t) = \text{GATE}_{\mathcal{M}_\theta}(c_t, \mathcal{D}_s), \quad g_t \in \{\text{NO-OP}, \text{LOOK-UP}, \text{RETRIEVE}\}. \quad (3)$$

The knowledge state K_t distinguishes the model’s existing knowledge, findings from previous searches and experiments, and unresolved questions about x_t that define the current knowledge gap. The gate selects [NO-OP](#) when the model’s knowledge suffices, [LOOK-UP](#) when stored documents provide the missing knowledge, and [RETRIEVE](#) when neither source is sufficient. Under [LOOK-UP](#), the selected documents are included in the solution prompt without a new web search. This makes retrieval responsive to the current knowledge gap and enables the reuse of previously retrieved evidence. The results in Table 1b show that knowledge-gap-based gating is more effective than the heuristic gating based on stalled progress used in EvoX (Liu et al., 2026a).

3.4. Inner Loop: Query Optimization

When $g_t = \text{RETRIEVE}$, the inner loop approximates the query optimization in Eq. 1 over R inner rounds within the current outer iteration t , without generating or evaluating candidate solution.

Population state descriptor. Following EvoX (Liu et al., 2026a), the inner loop first computes a population state descriptor, $\text{stats}(\mathcal{D}_p)$, comprising deterministic statistics of the retained population, its score distribution, recent parent-to-child outcomes, and parent-selection frequencies. $\mathcal{M}_\theta$ summarizes these statistics into factual observations $A_t = \mathcal{M}_\theta(\text{stats}(\mathcal{D}_p))$ without additional interpretation. These observations complete the initial inner-loop context $\tilde{c}_t^0 = (c_t, K_t, A_t)$, which the inner rounds condition on and update.

Iterative query optimization. Let $\mathcal{S}_t^r$ denote the documents retained after inner round r , and $\hat{s}_t(d)$ the predicted evaluator score of a candidate x_{t+1} obtained by improving x_t using document d alone. Starting with $\mathcal{S}_t^0 = \emptyset$ and $K_t^0 = K_t$, each round $r = 1, \dots, R$ performs four operations:

- (1) **Query Construction:** The LLM $\mathcal{M}_\theta$ constructs J queries targeting the remaining knowledge gaps. The query batch is $Q_r = (q_r^{(j)})_{j=1}^J$, with each query sampled as $q_r^{(j)} \sim \mathcal{M}_\theta(\tilde{c}_t^{r-1}, \mathcal{S}_t^{r-1}, \{\hat{s}_t(d)\}_{d \in \mathcal{S}_t^{r-1}})$. At $r = 1$, the document and score inputs are empty, so query construction uses only the initial context $\tilde{c}_t^0$. Later rounds also use the retained documents and their predicted scores.
- (2) **Web Search:** Each distinct query in Q_r is executed once per round. The returned documents are combined with the previously retained documents to form the pool (i.e., local search database in Figure 5) $\mathcal{P}_r = \mathcal{S}_t^{r-1} \cup \text{SEARCH}(Q_r)$.
- (3) **Hypothetical Evidence Scoring:** When unscored documents are available, a single call to $\mathcal{M}_\theta$ predicts $\hat{s}_t(d) = \mathcal{M}_\theta(\tilde{c}_t^{r-1}, \mathcal{E}(x_t), d)$ for each such $d \in \mathcal{P}_r$. These *hypothetical absolute scores* are expressed on the evaluator’s scale and provide a surrogate signal for the inner objective in Eq. 1 (Figure 8a shows the model’s ability to predict these scores). Each document is scored only once within the inner loop, and its score is reused in later rounds.
- (4) **Knowledge State Update:** The same call used for hypothetical evidence scoring also updates the knowledge state to K_t^r using the new documents, yielding the next round’s context $\tilde{c}_t^r = (c_t, K_t^r, A_t)$. If no documents require




Figure 6: Discovery performance of OpenEvolve with and without EVODUET. Results cover 21 paired tasks with $N = 1$ or 8 candidates per iteration. For each model, method, task, and N , we report the best NDG across four runs. **(a)** Mean best NDG across tasks and the gain from adding EVODUET (ΔNDG). **(b)** Mean ΔNDG within each task group. **(c)** Task-level ΔNDG versus OpenEvolve’s NDG; black bars and labels show the median gain within each NDG range.

scoring, the call is skipped and $K_t^r = K_t^{r-1}$. The loop then retains up to D documents with the highest predicted scores as $\mathcal{S}_t^r = \text{TopD}_{\hat{s}_t}(\mathcal{P}_r)$.

After all R rounds, the retained Top- D documents $\mathcal{S}_t = \mathcal{S}_t^R$ are passed to the outer loop.

4. Experimental Results

EVODUET improves discovery, but only for LLMs that can exploit retrieved evidence. At $N = 1$, Figure 6a shows that EVODUET improves OpenEvolve’s overall NDG from 74.1% to 78.0% (+3.9%) with GPT-5.6-Luna and from 61.3% to 82.3% (+21.0%) with Gemini-3.8-Flash. Qwen3.5-9B, however, shows a 14.4% decline at $N = 1$ and still loses 4.7% with parallel generation at $N = 8$, despite gaining 10.3% when given oracle documents (Figure 3a). Unlike the oracle setting, EVODUET requires the model to decide when and what to search for based on its own knowledge gaps. This contrast suggests that these additional demands may limit the benefits of retrieval for weaker backbones such as Qwen3.5-9B. Inspection of 50 randomly sampled Qwen3.5-9B revisions with documents at $N = 1$ identifies unused methods in 6% and incorrect implementations in 20% (26% combined; Appendix E.3). These findings suggest that effective bi-level co-evolution depends on the model’s ability to both retrieve and apply relevant evidence.

Parallel generation consistently improves discovery across models. Figure 6a shows that increasing the candidate budget from $N = 1$ to $N = 8$ improves EVODUET’s overall NDG for all three models. For Qwen3.5-9B, although EVODUET remains below the corresponding OpenEvolve baseline at both budgets, its overall NDG improves from $N = 1$ to $N = 8$, indicating that parallel generation also benefits this model. We further compare $N \in \{1, 8, 16\}$ for GPT-5.6-Luna and Gemini-3.8-Flash on 8 tasks in Figure 7. We observe that the average NDG increases monotonically with N for both models, rising from 89.6% to 95.7% for GPT-5.6-Luna and from 84.5% to 89.6% for Gemini-3.8-Flash. These results suggest that broader exploration guided by web documents helps LLMs discover better solutions.

EVODUET achieves its largest average gain in mathematics. As shown in Figure 6b, EVODUET improves NDG over OpenEvolve on mathematics tasks in five of the six model/budget settings, with an average gain of 7.1% across all six. At $N = 8$, Qwen3.5-9B gains 5.5% despite its negative overall gain, and Gemini-3.8-Flash gains 6.7%.

EVODUET discovers novel solutions across 11 different tasks. Table 1a shows that EVODUET surpasses the previous SOTA program scores on eight tasks across five domains and matches them on three more. The mean cost across the eleven reported runs is \$45.56. Interestingly, on Rosetta and Erdős, the model initially evolves solutions, then retrieves public constructions at a later iteration and uses them as starting points for further optimization: refining a published trajectory and locally optimizing a published construction ($C_5 : 0.380859 \rightarrow 0.380859$), respectively. We call this behavior *public artifact reuse*, one of six behaviors reported in Appendix E.1. This behavior occurs in only 6 of 82 GPT-5.6-Luna runs (7.3%), compared with *method transfer* (55 of 82), in which the model applies principles or methods




Figure 7: Scaling effect of N .




Figure 8: Program improvement with web documents and patterns of document use. Results cover 8,200 iterations from 82 GPT-5.6-Luna runs across 21 tasks. (a) Predicted versus evaluated candidate scores, scaled to $[0, 1]$ using each task’s 2nd and 98th percentiles. (b) Rates at which the selected candidate improves on its parent (left axis) or sets a new best score within the run (right axis), grouped by gate decision. Arrows compare **NO-OP** iterations with **RETRIEVE** iterations that retain at least one promising document. (c) Percentage of runs exhibiting each behavior. Each run is counted at most once per category and may appear in multiple categories.

retrieved by searching relevant literature (Figure 8c). Only two of these 11 SOTA results reuse public artifacts in their best programs (in Appendix K).

The largest median gain occurs on partially solved tasks. Figure 6c compares OpenEvolve and EVO DUET across 126 combinations of tasks, models, and candidate counts. When OpenEvolve’s NDG is 5–20%, 20–40%, 40–60%, and 60–80%, the median gains from EVO DUET are -5.4%, +17.5%, +9.2%, and +2.4%, respectively. When OpenEvolve already performs well ($\text{NDG} \geq 80\%$), the median gain is 0.0% across 75 comparisons. Of the 52 comparisons with OpenEvolve $\text{NDG} \geq 95\%$, six show declines greater than 5%. When OpenEvolve makes little progress (NDG below 5%), EVO DUET raises five of the ten cases above 5%, with a median gain of +71.8% among these five. In the remaining five cases, both methods stay near the initial program’s performance. Overall, EVO DUET tends to provide smaller gains when OpenEvolve’s NDG is higher (Pearson $r = -0.41$).

5. Analysis and Discussions

5.1. How Does Web Search Help?

Hypothetical evidence scores track actual program performance. Across 4,324 retrievals, hypothetical evidence scores correlate strongly with the selected candidates’ evaluated scores (Spearman $\rho = +0.86$; Figure 8a). Correlations are positive on all 21 tasks, with a median of +0.74. This supports using these scores as a surrogate signal for inner-loop query optimization (§ 3.4).

Programs improve more often with promising documents. A document is *promising* when its hypothetical evidence score exceeds the parent’s actual evaluator score, i.e., $\hat{s}_t(d) > \mathcal{E}(x_t)$. When **RETRIEVE** retains at least one such document, the selected candidate improves on its parent in 67.1% of iterations and sets a new run best in 14.1%, compared with 52.1% and 9.6% under **NO-OP** (Figure 8b). Under **LOOK-UP**, which reuses stored documents, these rates are 61.2% and 10.1%, respectively. On 17 of 21 tasks, parent improvement rates are higher with promising documents than under **NO-OP** (medians: 69% vs. 54%). However, 36.5% of retrievals yield no promising document; the parent improvement rate in these cases is only 38.3%. These results suggest that hypothetical evidence scoring helps identify documents useful for improving the current solution.

Web documents mainly provide methods and performance targets. Figure 8c summarizes six behavior categories across 82 GPT-5.6-Luna runs (8,200 iterations), with each run counted once in every applicable category. The most common behaviors are applying principles and methods from retrieved documents (55 runs) and using published best scores as reference targets (40 runs). These targets guide program development, while the task evaluator measures the resulting programs’ performance. We also observe reuse of published solutions (6 runs) and unsuccessful revisions inspired by retrieved ideas (29 runs). Detailed explanations are presented in Appendix E.1.

Acknowledgments

This work was partly supported by the IITP grants (RS-2022-II220077, RS-2022-II220113, RS-2022-II220959, RS-2022-II220871) funded by the Korea government (MSIT) and the BK21 FOUR program, SNU in 2025. This research was supported by the “Advanced GPU Utilization Support Program” funded by the Government of the Republic of Korea (Ministry of Science and ICT).

AI use statement

In this work, we used generative AI tools for trajectory analysis. We have not used generative AI tools for idea proposal or method development, and proof-related tasks are not applicable to this work. Additionally, we used generative AI tools for paper writing and figure preparation. We also used generative AI tools to retrieve and summarize oracle documents, as described in Appendix C.2.

We have reviewed all AI-assisted work. We checked the AI-assisted text and figures for consistency with the reported experimental results. For trajectory analysis, we checked the interpretations against recorded search queries, retrieved documents, parent and child programs, and evaluator outputs, with worked cases provided in Appendix I. We also inspected cases of public artifact reuse and documented the sources of reused solutions, as detailed in Appendices E.1 and K.

We take responsibility for the final content of this work, including text, claims or artifacts produced with the aid of generative AI.

Ethics statement

This work evaluates LLM-guided computational optimization across a set of tasks, using publicly available web sources to inform the search. To support proper attribution, we document cases of public artifact reuse, including the original sources and subsequent optimization steps, in Appendices E.1 and K. The reported gains reflect performance under the task evaluators used in this study. The resulting programs require independent validation before use in other settings. Appendix H discusses source attribution, the reliability of retrieved information, program validation, and human oversight of downstream applications.

Reproducibility statement

We describe EVO DUET in Section 3 and provide pseudocode, inference settings, and retrieval budgets in Appendix B. Task definitions, evaluation procedures, and oracle-document construction are documented in Appendix C, and the prompt templates are provided in Appendix J. Detailed experimental results appear in Appendix D. Appendix I links selected search trajectories to retrieved sources, code revisions, and evaluation results. Appendix K provides complete source listings and identifies the runs underlying Table 1a. Detailed trajectories, prompt templates, and complete program listings are provided in the supplementary materials (Appendices I–K).

References

- Lakshya A Agrawal, Shangyin Tan, Dilara Soylu, Noah Ziem, Rishi Khare, Krista Opsahl-Ong, Arnav Singhvi, Herumb Shandilya, Michael J Ryan, Meng Jiang, Christopher Potts, Koushik Sen, Alexandros G. Dimakis, Ion Stoica, Dan Klein, Matei Zaharia, and Omar Khattab. GEPA: Reflective Prompt Evolution Can Outperform Reinforcement Learning. *arXiv preprint arXiv:2507.19457*, 2025. URL <https://arxiv.org/abs/2507.19457>.
- APMonitor. Batch reactor optimization. APMonitor Documentation, 2025. URL <https://www.apmonitor.com/wiki/index.php/Apps/BatchReactor>. Last modified March 25, 2025. Accessed September 9, 2026.
- Akari Asai, Zeqiu Wu, Yizhong Wang, Avirup Sil, and Hannaneh Hajishirzi. Self-RAG: Learning to retrieve, generate, and critique through self-reflection. *arXiv preprint arXiv:2310.11511*, 2023.
- Henrique Assumpção, Diego Ferreira, Leandro Campos, and Fabricio Murai. CodeEvolve: an open source evolutionary coding agent for algorithmic discovery and optimization. *arXiv preprint arXiv:2510.14150*, 2025. URL <https://arxiv.org/abs/2510.14150>.

-
- Lorenz M. Baumgartner, Joseph M. Dennis, Nicholas A. White, Stephen L. Buchwald, and Klavs F. Jensen. Use of a droplet platform to optimize Pd-catalyzed C–N coupling reactions promoted by organic bases. *Organic Process Research & Development*, 23(8):1594–1601, 2019. doi: 10.1021/acs.oprd.9b00236. URL <https://doi.org/10.1021/acs.oprd.9b00236>.
- Daniil A. Boiko, Robert MacKnight, Ben Kline, and Gabe Gomes. Autonomous chemical research with large language models. *Nature*, 624:570–578, 2023. doi: 10.1038/s41586-023-06792-0. URL <https://www.nature.com/articles/s41586-023-06792-0>.
- Andres M. Bran, Sam Cox, Oliver Schilter, Carlo Baldassari, Andrew D. White, and Philippe Schwaller. Augmenting large language models with chemistry tools. *Nature Machine Intelligence*, 6:525–535, 2024. doi: 10.1038/s42256-024-00832-8. URL <https://www.nature.com/articles/s42256-024-00832-8>.
- Nathan Brown, Marco Fiscato, Marwin H. S. Segler, and Alain C. Vaucher. GuacaMol: Benchmarking models for de novo molecular design. *Journal of Chemical Information and Modeling*, 59(3):1096–1108, 2019. doi: 10.1021/acs.jcim.8b00839. URL <https://doi.org/10.1021/acs.jcim.8b00839>.
- Steven L. Brunton, Joshua L. Proctor, and J. Nathan Kutz. Discovering governing equations from data by sparse identification of nonlinear dynamical systems. *Proceedings of the National Academy of Sciences*, 113(15):3932–3937, 2016. doi: 10.1073/pnas.1517384113. URL <https://doi.org/10.1073/pnas.1517384113>.
- Cambridge Cluster Database. Table of Lennard-Jones cluster global minima, n.d. URL <https://www-wales.ch.cam.ac.uk/~jon/structures/LJ/tables.150.html>. University of Cambridge. Accessed September 9, 2026.
- Mert Cemri, Shubham Agrawal, Akshat Gupta, Shu Liu, Audrey Cheng, Qiuyang Mang, Ashwin Naren, Lutfi Eren Erdogan, Koushik Sen, Matei Zaharia, et al. Adaevolve: Adaptive llm driven zeroth-order optimization. *arXiv preprint arXiv:2602.20133*, 2026.
- Chi-Min Chan, Chunpu Xu, Ruibin Yuan, Hongyin Luo, Wei Xue, Yike Guo, and Jie Fu. RQ-RAG: Learning to Refine Queries for Retrieval Augmented Generation. *arXiv preprint arXiv:2404.00610*, 2024. URL <https://arxiv.org/abs/2404.00610>.
- Haodong Chen, Shuai Wang, Yu Yin, Shengyao Zhuang, Guido Zuccon, and Teerapong Leelanupab. ITER: Interaction-Aware Retrieval for Agentic Search. *arXiv preprint arXiv:2608.27912*, 2026. URL <https://arxiv.org/abs/2608.27912>.
- Mingyang Chen, Linzhuang Sun, Tianpeng Li, Haoze Sun, Yijie Zhou, Chenzheng Zhu, Haofen Wang, Jeff Z. Pan, Wen Zhang, Huajun Chen, Fan Yang, Zenan Zhou, and Weipeng Chen. ReSearch: Learning to Reason with Search for LLMs via Reinforcement Learning. *arXiv preprint arXiv:2503.19470*, 2025. URL <https://arxiv.org/abs/2503.19470>.
- Seokju Cho, Ryo Hachiuma, Abhishek Badki, Hang Su, Byung-Kwan Lee, Chan Hee Song, Sifei Liu, Subhashree Radhakrishnan, Seungryong Kim, Yu-Chiang Frank Wang, et al. Spatialclaw: Rethinking action interface for agentic spatial reasoning. *arXiv preprint arXiv:2606.13673*, 2026.
- He Du, Qiming Ge, Jiakai Hu, Aijun Yang, Zheng Cai, Zixian Huang, Sheng Yuan, Qinxiu Cheng, Xinchun Xie, Yicheng Chen, et al. Kernel-Smith: A Unified Recipe for Evolutionary Kernel Optimization. *arXiv preprint arXiv:2603.28342*, 2026. URL <https://arxiv.org/abs/2603.28342>.
- Paul Erdős. Some remarks on number theory. *Riveon Lematematika*, 9:45–48, 1955.
- Kobi C. Felton, Jan G. Rittig, and Alexei A. Lapkin. Summit: Benchmarking machine learning methods for reaction optimisation. *Chemistry–Methods*, 1(2):116–122, 2021. doi: 10.1002/cmtd.202000051. URL <https://doi.org/10.1002/cmtd.202000051>.
- Ali Essam Ghareeb, Benjamin Chang, Ludovico Mitchener, Angela Yiu, Caralyn J Szostkiewicz, Dmytro Shved, Gavin J Gyimesi, Jon M Laurent, Samantha M Wright, Muhammed T Razzak, et al. A multi-agent system for automating scientific discovery. *Nature*, 655:497–505, 2026. doi: 10.1038/s41586-026-10652-y. URL <https://www.nature.com/articles/s41586-026-10652-y>.

-
- Juraj Gottweis, Wei-Hung Weng, Alexander Daryin, Tao Tu, Petar Sirkovic, Artiom Myaskovsky, Grzegorz Glowaty, Felix Weissenberger, Alessio Orlandi, Dan Popovici, et al. Accelerating scientific discovery with Co-Scientist. *arXiv preprint arXiv:2502.18864*, 2025.
- Florian Häse, Matteo Aldeghi, Riley J. Hickman, Loïc M. Roch, and Alán Aspuru-Guzik. Gryffin: An algorithm for Bayesian optimization of categorical variables informed by expert knowledge. *Applied Physics Reviews*, 8:031406, 2021a. doi: 10.1063/5.0048164. URL <https://doi.org/10.1063/5.0048164>.
- Florian Häse, Matteo Aldeghi, Riley J. Hickman, Loïc M. Roch, Melodie Christensen, Elena Liles, Jason E. Hein, and Alán Aspuru-Guzik. Olympus: A benchmarking framework for noisy optimization and experiment planning. *Machine Learning: Science and Technology*, 2:035021, 2021b. doi: 10.1088/2632-2153/abedc8. URL <https://doi.org/10.1088/2632-2153/abedc8>.
- Kexin Huang, Serena Zhang, Hanchen Wang, Yuanhao Qu, Yingzhou Lu, Ryan Li, Yusuf Roohani, Lin Qiu, Shiyi Cao, Gavin Li, et al. Autonomous biomedical research with an artificial intelligence agent. *Science*, 393(6813):eadz4351, 2026. doi: 10.1126/science.adz4351. URL <https://www.science.org/doi/10.1126/science.adz4351>.
- Yuki Imajuku, Kohki Horie, Yoichi Iwata, Kensho Aoki, Naohiro Takahashi, and Takuya Akiba. Ale-bench: A benchmark for long-horizon objective-driven algorithm engineering. *arXiv preprint arXiv:2506.09050*, 2025.
- Soyeong Jeong, Jinheon Baek, Sukmin Cho, Sung Ju Hwang, and Jong C Park. Adaptive-RAG: Learning to adapt retrieval-augmented large language models through question complexity. *arXiv preprint arXiv:2403.14403*, 2024.
- Qile Jiang and George Karniadakis. Agenticsciml: Collaborative multi-agent systems for emergent discovery in scientific machine learning. *npj Artificial Intelligence*, 2:57, 2026. doi: 10.1038/s44387-026-00102-5. URL <https://www.nature.com/articles/s44387-026-00102-5>.
- Zhengbao Jiang, Frank F Xu, Luyu Gao, Zhiqing Sun, Qian Liu, Jane Dwivedi-Yu, Yiming Yang, Jamie Callan, and Graham Neubig. Active retrieval augmented generation. *arXiv preprint arXiv:2305.06983*, 2023.
- Bowen Jin, Hansi Zeng, Zhenrui Yue, Jinsung Yoon, Sercan Arik, Dong Wang, Hamed Zamani, and Jiawei Han. Search-R1: Training LLMs to reason and leverage search engines with reinforcement learning. *arXiv preprint arXiv:2503.09516*, 2025.
- Minki Kang, Shizhe Diao, Ryo Hachiuma, Sung Ju Hwang, Pavlo Molchanov, Yu-Chiang Frank Wang, and Byung-Kwan Lee. Agent explorative policy optimization for multimodal agentic reasoning. *arXiv preprint arXiv:2605.28774*, 2026.
- Jiwan Kim, Kibum Kim, Wonjoong Kim, Byung-Kwan Lee, and Chanyoung Park. Why and when visual token pruning fails? a study on relevant visual information shift in mllms decoding. *arXiv preprint arXiv:2604.12358*, 2026.
- Scott Kirkpatrick, C Daniel Gelatt Jr, and Mario P Vecchi. Optimization by simulated annealing. *science*, 220(4598): 671–680, 1983.
- Robert Tjarko Lange, Yuki Imajuku, and Edoardo Cetin. Shinkaevolve: Towards open-ended and sample-efficient program evolution. *arXiv preprint arXiv:2509.19349*, 2025.
- Byung-Kwan Lee, Sangyun Chung, Chae Won Kim, Beomchan Park, and Yong Man Ro. Phantom of latent for large language and vision models. *arXiv preprint arXiv:2409.14713*, 2024a.
- Byung-Kwan Lee, Sangyun Chung, Chae Won Kim, Beomchan Park, and Yong Man Ro. Trol: Traversal of layers for large language and vision models. *arXiv preprint arXiv:2406.12246*, 2024b.
- Byung-Kwan Lee, Chae Won Kim, Beomchan Park, and Yong Man Ro. Meteor: Mamba-based traversal of rationale for large language and vision models. *Advances in Neural Information Processing Systems*, 37:40278–40315, 2024c.
- Byung-Kwan Lee, Beomchan Park, Chae Won Kim, and Yong Man Ro. Collavo: Crayon large language and vision model. In *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 1121–1138, 2024d.

-
- Byung-Kwan Lee, Beomchan Park, Chae Won Kim, and Yong Man Ro. Moai: Mixture of all intelligence for large language and vision models. In *European Conference on Computer Vision*, pp. 273–302. Springer, 2024e.
- Byung-Kwan Lee, Ryo Hachiuma, Yong Man Ro, Yu-Chiang Frank Wang, and Yueh-Hua Wu. Genrecal: Generation after recalibration from large to small vision-language models. *arXiv preprint arXiv:2506.15681*, 2025a.
- Byung-Kwan Lee, Ryo Hachiuma, Yu-Chiang Frank Wang, Yong Man Ro, and Yueh-Hua Wu. Vlsi: Verbalized layers-to-interactions from large to small vision language models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 29545–29557, 2025b.
- Byung-Kwan Lee, Youngchae Chee, and Yong Man Ro. Recursive think-answer process for llms and vlms. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9608–9621, 2026a.
- Byung-Kwan Lee, Ryo Hachiuma, Yong Man Ro, Frank Wang, and Yueh-Hua Wu. Unified reinforcement and imitation learning for vision-language models. *Advances in Neural Information Processing Systems*, 38:156508–156534, 2026b.
- Byung-Kwan Lee, Ximing Lu, Shizhe Diao, Minki Kang, Saurav Muralidharan, Karan Sapra, Andrew Tao, Pavlo Molchanov, Yejin Choi, Yu-Chiang Frank Wang, et al. Zone of proximal policy optimization: Teacher in prompts, not gradients. *arXiv preprint arXiv:2606.18216*, 2026c.
- Byung-Kwan Lee, Yu-Chiang Frank Wang, and Ryo Hachiuma. Masking teacher and reinforcing student for distilling vision-language models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10126–10141, 2026d.
- Yoonho Lee, Roshen Nair, Qizheng Zhang, Kangwook Lee, Omar Khattab, and Chelsea Finn. Meta-Harness: End-to-End Optimization of Model Harnesses. *arXiv preprint arXiv:2603.28052*, 2026e. URL <https://arxiv.org/abs/2603.28052>.
- Young-Jun Lee, Byungsoo Ko, Han-Gyu Kim, Jonghwan Hyeon, and Ho-Jin Choi. Dialogcc: An automated pipeline for creating high-quality multi-modal dialogue dataset. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 1938–1963, 2024f.
- Young-Jun Lee, Dokyong Lee, Joo-won Sung, Jonghwan Hyeon, and Ho-Jin Choi. Large language models can share images, too! In *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 692–713, 2024g.
- Young-Jun Lee, Dokyong Lee, Junyoung Youn, Kyeong-Jin Oh, Byungsoo Ko, Jonghwan Hyeon, and Ho-Jin Choi. Stark: Social long-term multi-modal conversation with persona commonsense knowledge. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 12137–12162, 2024h.
- Young-Jun Lee, Dokyong Lee, Junyoung Youn, Kyeongjin Oh, and Ho-Jin Choi. Thanos: Enhancing conversational agents with skill-of-mind-infused large language model. *arXiv preprint arXiv:2411.04496*, 2024i.
- Young-Jun Lee, Seungone Kim, Byung-Kwan Lee, Minkyong Moon, Yechan Hwang, Jong Myoung Kim, Graham Neubig, Sean Welleck, and Ho-Jin Choi. Refinebench: Evaluating refinement capability of language models via checklists. *arXiv preprint arXiv:2511.22173*, 2025c.
- Young-Jun Lee, Byung-Kwan Lee, Jianshu Zhang, Yechan Hwang, Byungsoo Ko, Han-Gyu Kim, Dongyu Yao, Xuankun Rong, Eojin Joo, Seung-Ho Han, et al. Multiverse: A multi-turn conversation benchmark for evaluating large vision and language models. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 708–719, 2025d.
- Young-Jun Lee, Seungone Kim, Minki Kang, Alistair Cheong Liang Chuen, Zerui Chen, Seungho Han, Taehee Jung, and Dongyeop Kang. Evolution fine-tuning: Learning to discover across 371 optimization tasks. *arXiv preprint arXiv:2606.29082*, 2026f.
- Gang Liao, Hongsen Qin, Ying Wang, Alicia Golden, Michael Kuchnik, Yavuz Yetim, Jia Jiunn Ang, Chunli Fu, Yihan He, Samuel Hsia, et al. KernelEvolve: Scaling Agentic Kernel Coding for Heterogeneous AI Accelerators at Meta. *arXiv preprint arXiv:2512.23236*, 2025. URL <https://arxiv.org/abs/2512.23236>.

-
- Fei Liu, Xialiang Tong, Mingxuan Yuan, Xi Lin, Fu Luo, Zhenkun Wang, Zhichao Lu, and Qingfu Zhang. Evolution of Heuristics: Towards Efficient Automatic Algorithm Design Using Large Language Model. *arXiv preprint arXiv:2401.02051*, 2024. URL <https://arxiv.org/abs/2401.02051>.
- Gang Liu, Yihan Zhu, Jie Chen, and Meng Jiang. Scientific algorithm discovery by augmenting AlphaEvolve with deep research. *arXiv preprint arXiv:2510.06056*, 2025.
- Shu Liu, Shubham Agarwal, Monishwaran Maheswaran, Mert Cemri, Zhifei Li, Qiuyang Mang, Ashwin Naren, Ethan Boneh, Audrey Cheng, Melissa Z Pan, et al. Evox: Meta-evolution for automated discovery. *arXiv preprint arXiv:2602.23413*, 2026a.
- Shu Liu, Mert Cemri, Shubham Agarwal, Alexander Krentsel, Ashwin Naren, Qiuyang Mang, Zhifei Li, Akshat Gupta, Monishwaran Maheswaran, Audrey Cheng, et al. SkyDiscover: A Flexible, Adaptive Framework for AI-Driven Scientific and Algorithmic Discovery, 2026b. URL <https://skydiscover-ai.github.io/blog.html>. Official project documentation.
- Chris Lu, Cong Lu, Robert Tjarko Lange, Yutaro Yamada, Shengran Hu, Jakob Foerster, David Ha, and Jeff Clune. Towards end-to-end automation of AI research. *Nature*, 651:914–919, 2026. doi: 10.1038/s41586-026-10265-5. URL <https://www.nature.com/articles/s41586-026-10265-5>.
- Chang Ma, Linh Trinh, Matt Bucci, Aviv Regev, and Hanchen Wang. Orion: Towards lab automation with computer-using agents. *bioRxiv*, pp. 2026–06, 2026.
- Xinbei Ma, Yeyun Gong, Pengcheng He, Hai Zhao, and Nan Duan. Query rewriting for retrieval-augmented large language models. *arXiv preprint arXiv:2305.14283*, 2023.
- Yoshitomo Matsubara, Naoya Chiba, Ryo Igarashi, and Yoshitaka Ushiku. Rethinking symbolic regression datasets and benchmarks for scientific discovery. *Journal of Data-centric Machine Learning Research*, 1(3):1–38, 2024. URL <https://data.mlr.press/assets/pdf/v01-3.pdf>.
- National Institute of Standards and Technology. StRD dataset Chwirut2. Statistical Reference Datasets, n.d. URL <https://www.itl.nist.gov/div898/strd/nls/data/chwirut2.shtml>. Accessed September 9, 2026.
- Alexander Novikov, Ng  n V  , Marvin Eisenberger, Emilien Dupont, Po-Sen Huang, Adam Zsolt Wagner, Sergey Shirobokov, Borislav Kozlovskii, Francisco JR Ruiz, Abbas Mehrabian, et al. Alphaevolve: A coding agent for scientific and algorithmic discovery. *arXiv preprint arXiv:2506.13131*, 2025.
- OpenAI. GPT-5.6: Frontier intelligence that scales with your ambition, July 2026. URL <https://openai.com/index/gpt-5-6/>. Accessed: 2026-09-24.
- Anne Ouyang, Simon Guo, Simran Arora, Alex L Zhang, William Hu, Christopher R  , and Azalia Mirhoseini. Kernelbench: Can llms write efficient gpu kernels? *arXiv preprint arXiv:2502.10517*, 2025.
- Tom Packebusch and Stephan Mertens. Low autocorrelation binary sequences. *Journal of Physics A: Mathematical and Theoretical*, 49(16):165001, 2016. doi: 10.1088/1751-8113/49/16/165001. URL <https://arxiv.org/abs/1512.02475>.
- Reid Pryzant, Dan Iter, Jerry Li, Yin Tat Lee, Chenguang Zhu, and Michael Zeng. Automatic Prompt Optimization with "Gradient Descent" and Beam Search. *arXiv preprint arXiv:2305.03495*, 2023. URL <https://arxiv.org/abs/2305.03495>.
- Ao Qu, Han Zheng, Zijian Zhou, Yihao Yan, Yihong Tang, Shao Yong Ong, Fenglu Hong, Kaichen Zhou, Chonghe Jiang, Minwei Kong, et al. CORAL: Towards Autonomous Multi-Agent Evolution for Open-Ended Discovery. *arXiv preprint arXiv:2604.01658*, 2026. URL <https://arxiv.org/abs/2604.01658>.
- Bernardino Romera-Paredes, Mohammadamin Barekatin, Alexander Novikov, Matej Balog, M Pawan Kumar, Emilien Dupont, Francisco JR Ruiz, Jordan S Ellenberg, Pengming Wang, Omar Fawzi, et al. Mathematical discoveries from program search with large language models. *Nature*, 625(7995):468–475, 2024.
- Samuel Schmidgall and Michael Moor. AgentRxiv: Towards Collaborative Autonomous Research. *arXiv preprint arXiv:2503.18102*, 2025. URL <https://arxiv.org/html/2503.18102>.

-
- Samuel Schmidgall, Yusheng Su, Ze Wang, Ximeng Sun, Jialian Wu, Xiaodong Yu, Jiang Liu, Michael Moor, Zicheng Liu, and Emad Barsoum. Agent Laboratory: Using LLM Agents as Research Assistants. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pp. 5977–6043, 2025. doi: 10.18653/v1/2025.findings-emnlp.320. URL <https://aclanthology.org/2025.findings-emnlp.320/>.
- Zhihong Shao, Yeyun Gong, Yelong Shen, Minlie Huang, Nan Duan, and Weizhu Chen. Enhancing Retrieval-Augmented Large Language Models with Iterative Retrieval-Generation Synergy. *arXiv preprint arXiv:2305.15294*, 2023. URL <https://arxiv.org/abs/2305.15294>.
- Asankhaya Sharma. OpenEvolve: An open-source evolutionary coding agent. <https://github.com/algorithmicsuperintelligence/openevolve>, 2025. GitHub repository.
- Weijia Shi, Sewon Min, Michihiro Yasunaga, Minjoon Seo, Richard James, Mike Lewis, Luke Zettlemoyer, and Wen-tau Yih. REPLUG: Retrieval-Augmented Black-Box Language Models. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 8371–8384, 2024. doi: 10.18653/v1/2024.naacl-long.463. URL <https://aclanthology.org/2024.naacl-long.463/>.
- Huatong Song, Jinhao Jiang, Yingqian Min, Jie Chen, Zhipeng Chen, Wayne Xin Zhao, Lei Fang, and Ji-Rong Wen. R1-Searcher: Incentivizing the Search Capability in LLMs via Reinforcement Learning. *arXiv preprint arXiv:2503.05592*, 2025. URL <https://arxiv.org/abs/2503.05592>.
- Qiushi Sun, Zhoumianze Liu, Chang Ma, Zichen Ding, Fangzhi Xu, Zhangyue Yin, Haiteng Zhao, Zhenyu Wu, Kanzhi Cheng, Zhaoyang Liu, et al. Scienceboard: Evaluating multimodal autonomous agents in realistic scientific workflows. *arXiv preprint arXiv:2505.19897*, 2025.
- Jiabin Tang, Lianghao Xia, Zhonghang Li, and Chao Huang. AI-Researcher: Autonomous Scientific Innovation. In *Advances in Neural Information Processing Systems*, volume 38, 2025. doi: 10.52202/085713-0320. URL https://proceedings.neurips.cc/paper_files/paper/2025/hash/0d904d300a105809a2114d727851e759-Abstract-Conference.html.
- Qwen Team. Qwen3.5: Accelerating productivity with native multimodal agents, February 2026. URL <https://qwen.ai/blog?id=qwen3.5>.
- Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. Interleaving Retrieval with Chain-of-Thought Reasoning for Knowledge-Intensive Multi-Step Questions. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 10014–10037, 2023. doi: 10.18653/v1/2023.acl-long.557. URL <https://aclanthology.org/2023.acl-long.557/>.
- Yiping Wang, Shao-Rong Su, Zhiyuan Zeng, Eva Xu, Liliang Ren, Xinyu Yang, Zeyi Huang, Xuehai He, Luyao Ma, Baolin Peng, et al. Thetaevolve: Test-time learning on open problems. *arXiv preprint arXiv:2511.23473*, 2025.
- WILL Team. Evaluation-driven scaling for scientific discovery. *arXiv preprint arXiv:2604.19341*, 2026. URL <https://arxiv.org/abs/2604.19341>.
- Minghao Yan, Bo Peng, Benjamin Coleman, Ziqi Chen, Zhouhang Xie, Shuo Chen, Zhankui He, Noveen Sachdeva, Isabella Ye, Weili Wang, et al. PACEvolve: Enabling Long-Horizon Progress-Aware Consistent Evolution. *arXiv preprint arXiv:2601.10657*, 2026. URL <https://arxiv.org/abs/2601.10657>.
- Shi-Qi Yan, Jia-Chen Gu, Yun Zhu, and Zhen-Hua Ling. Corrective Retrieval Augmented Generation. *arXiv preprint arXiv:2401.15884*, 2024. URL <https://arxiv.org/abs/2401.15884>.
- Chengrun Yang, Xuezhi Wang, Yifeng Lu, Hanxiao Liu, Quoc V. Le, Denny Zhou, and Xinyun Chen. Large Language Models as Optimizers. *arXiv preprint arXiv:2309.03409*, 2023. URL <https://arxiv.org/abs/2309.03409>.
- Xin-She Yang, Christian Huyck, Mehmet Karamanoglu, and Nawaz Khan. True global optimality of the pressure vessel design problem: A benchmark for bio-inspired optimisation algorithms. *International Journal of Bio-Inspired Computation*, 5(6):329–335, 2013. doi: 10.1504/IJBIC.2013.058910. URL <https://arxiv.org/abs/1403.7793>.

-
- Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. ReAct: Synergizing Reasoning and Acting in Language Models. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=WE_vluYUL-X.
- Seonghoon Yu, Dongjun Nam, Byung-Kwan Lee, and Jeany Son. Hide to see: Reasoning-prefix masking for visual-anchored thinking in vlm distillation. *arXiv preprint arXiv:2605.11651*, 2026.
- Tian Yu, Shaolei Zhang, and Yang Feng. Auto-RAG: Autonomous Retrieval-Augmented Generation for Large Language Models. *arXiv preprint arXiv:2411.19443*, 2024. URL <https://arxiv.org/abs/2411.19443>.
- Mert Yuksekgonul, Federico Bianchi, Joseph Boen, Sheng Liu, Zhi Huang, Carlos Guestrin, and James Zou. TextGrad: Automatic "Differentiation" via Text. *arXiv preprint arXiv:2406.07496*, 2024. URL <https://arxiv.org/abs/2406.07496>.
- Mert Yuksekgonul, Daniel Kocaja, Xinhao Li, Federico Bianchi, Jed McCaleb, Xiaolong Wang, Jan Kautz, Yejin Choi, James Zou, Carlos Guestrin, et al. Learning to discover at test time. *arXiv preprint arXiv:2601.16175*, 2026.
- Jenny Zhang, Shengran Hu, Cong Lu, Robert Lange, and Jeff Clune. Darwin Godel Machine: Open-Ended Evolution of Self-Improving Agents. *arXiv preprint arXiv:2505.22954*, 2025. URL <https://arxiv.org/abs/2505.22954>.
- Jenny Zhang, Bingchen Zhao, Wannan Yang, Jakob Foerster, Jeff Clune, Minqi Jiang, Sam Devlin, and Tatiana Shavrina. Hyperagents. *arXiv preprint arXiv:2603.19461*, 2026. URL <https://arxiv.org/abs/2603.19461>.

Appendix Contents

A	Extended Related Work	18
B	Method Details	18
B.1	Outer Loop: Solution Optimization	18
B.2	Knowledge-Gap-Based Retrieval Gating	19
B.3	Inner Loop: Query Optimization	19
B.4	Inference Settings and Call Budget	20
B.5	Coupling Web Search with Solution Evolution	21
C	Experimental Setup Details	22
C.1	Task Descriptions	22
C.2	Oracle Document Construction	27
D	Additional Experimental Results	27
D.1	OpenEvolve with and without Oracle Documents	27
D.2	OpenEvolve with and without Parallel Generation	27
D.3	Inner-loop Budget Ablations	30
D.4	Full OpenEvolve Results	30
E	Behavior and Search Analysis	33
E.1	Behavior Flags and Additional Examples	33
E.2	Language, Resources, and Reuse in Web Search	35
E.3	Failure Analysis of Retrieved Evidence Use	41
F	Limitations	42
G	Discussions	42
H	Broader Impact	42
I	Trajectories of the Bi-Level Loop	42
I.1	Swap Reduction: depth weighting persists despite repeated search misses	43
I.2	Erdős minimum overlap: a radar codeword seeds later improvements	49
I.3	Voyager 2: documentation lookup repeats defaults already in the prompt	55
I.4	Circle packing ($n=26$): a generated solver exceeds the queried target	58
I.5	Erdős minimum overlap, second run: runtime witness reuse improves the best	61
I.6	Galileo: a promising retrieval produces a worse child	65
I.7	Rosetta: published seeds and implementation details support a better tour	67
J	Prompt Templates	72
K	Best Programs of EVO DUET	77
K.1	Swap Reduction: short lookahead reduces routing cost on Q20	78
K.2	Rosetta: refining a published tour lowers maneuver cost	89
K.3	Voyager 2: constrained refinement improves the existing tour	103
K.4	Denosing: mixing diffusion operators improves average accuracy	110
K.5	Domain Mixture: separate domain fits improve held-out prediction	114
K.6	Parallel Scaling: a fixed basis supports accurate extrapolation	116
K.7	Erdős: public witnesses support a small numerical refinement	116
K.8	Hadamard: structured constructions recover the reference determinant	123
K.9	Sums/Diffs: construction sweeps and local search improve the reference	129
K.10	Circle Packing ($n = 26$): joint refinement matches the reference	136
K.11	Circle Packing ($n = 32$): multiple layouts recover the reference score	141
K.12	Discovered Objects	148

A. Extended Related Work

Evolving solutions and search strategies. LLM-driven discovery methods differ in whether they optimize candidate programs, search procedures, prompts, or model parameters. FunSearch (Romera-Paredes et al., 2024), AlphaEvolve (Novikov et al., 2025), OpenEvolve (Sharma, 2025), and CodeEvolve (Assumpção et al., 2025) use execution feedback to evolve programs. EoH (Liu et al., 2024) jointly evolves heuristic descriptions and code. At the search level, ShinkaEvolve (Lange et al., 2025), PACEvolve (Yan et al., 2026), and AdaEvolve (Cemri et al., 2026) adapt selection, context management, and exploration, respectively, while EvoX (Liu et al., 2026a) jointly evolves solutions and search strategies. The Darwin Gödel Machine (Zhang et al., 2025), Hyperagents (Zhang et al., 2026), and Meta-Harness (Lee et al., 2026e) optimize agent or harness code. CORAL (Qu et al., 2026) coordinates collaborative evolution through shared memory, and SkyDiscover (Liu et al., 2026b) provides modular discovery infrastructure. OPRO (Yang et al., 2023), APO (Pryzant et al., 2023), TextGrad (Yuksekgonul et al., 2024), and GEPA (Agrawal et al., 2025) optimize prompts or textual variables using performance feedback or textual critiques. ThetaEvolve (Wang et al., 2025) and TTT-Discover (Yuksekgonul et al., 2026) update model parameters through reinforcement learning during search, while Kernel-Smith (Du et al., 2026) and Evolution Fine-Tuning (Lee et al., 2026f) train on evolutionary trajectories.

Web-augmented scientific discovery. DeepEvolve (Liu et al., 2025) sequentially couples deep research with program revision and evaluation, using prior evaluation outcomes to guide subsequent research. KernelEvolve (Liao et al., 2025) uses runtime diagnostics to guide retrieval for kernel optimization. AI co-scientist (Gottweis et al., 2025) integrates literature search into hypothesis generation and scientific review. Robin (Ghareeb et al., 2026) uses literature search to propose and assess candidate hypotheses, then incorporates experimental feedback into subsequent refinement. The AI Scientist (Lu et al., 2026), AI-Researcher (Tang et al., 2025), and Agent Laboratory (Schmidgall et al., 2025) connect literature search, computational experiments, and reporting. AgentRxiv (Schmidgall & Moor, 2025) and AgenticSciML (Jiang & Karniadakis, 2026) reuse accumulated research reports or method memories. Coscientist (Boiko et al., 2023), ChemCrow (Bran et al., 2024), and Biomni (Huang et al., 2026) combine external information with scientific tools.

Retrieval control and query refinement. Retrieval methods address when to search and how to refine queries. ReAct (Yao et al., 2023), IRCot (Trivedi et al., 2023), Iter-RetGen (Shao et al., 2023), and Auto-RAG (Yu et al., 2024) guide successive retrieval steps using intermediate reasoning, answers, or observations. Self-RAG (Asai et al., 2023), FLARE (Jiang et al., 2023), Adaptive-RAG (Jeong et al., 2024), and CRAG (Yan et al., 2024) base retrieval decisions on reflection, uncertainty, question complexity, and evidence quality, respectively. Rewrite-Retrieve-Read (Ma et al., 2023) learns query reformulation, while RQ-RAG (Chan et al., 2024) learns rewriting, decomposition, and disambiguation. Search-R1 (Jin et al., 2025), R1-Searcher (Song et al., 2025), and ReSearch (Chen et al., 2025) learn search policies from outcome rewards. REPLUG (Shi et al., 2024) uses feedback from a frozen LM to train a retriever, while ITER (Chen et al., 2026) trains a retriever conditioned on reasoning and search histories. EVODUET couples solution and query evolution through a shared task objective. Its knowledge-state gate chooses whether to retrieve new documents, reuse stored documents, or skip retrieval. The inner loop selects evidence using predicted candidate scores and refines queries without generating or evaluating programs. The outer loop records measured outcomes to inform subsequent retrieval decisions. Model parameters and prompt templates remain fixed throughout.

B. Method Details

Algorithm 1 presents the overall EVODUET procedure, and Algorithm 2 details its query optimization loop. The inner loop refines queries using predicted candidate scores; the outer loop evaluates solutions and records their actual scores. All model calls use the same frozen $\mathcal{M}_\theta$.

B.1. Outer Loop: Solution Optimization

Candidate generation and selection. The gate sets $N_t = 1$ for `NO-OP` and $N_t = N$ for `LOOK-UP` or `RETRIEVE`, including retrievals that return no usable documents. Candidates are sampled independently in parallel from the same prompt (I, c_t, S_t) and evaluated after successful generation and parsing. Only the best valid candidate under the task’s optimization direction is passed to ϕ ; ties favor the earlier candidate. If all candidates fail, the scaffold applies its existing retry policy.

Algorithm 1 EVODUET: overall procedure.

Input: Task $(I, x_0, \mathcal{E})$, selection policy ϕ , outer iterations T

Input: Candidate count N , retrieval settings (R, J, M, D, K)

```
1:  $\mathcal{D}_e \leftarrow \{(x_0, \mathcal{E}(x_0))\}$ ;  $\mathcal{D}_s \leftarrow \emptyset$ 
2: for  $t = 0, \dots, T - 1$  do ▷ Outer loop: solution optimization
3:    $(x_t, \mathcal{H}_t) \sim \phi(\mathcal{D}_e)$ ;  $c_t \leftarrow [\mathcal{H}_t; x_t]$ 
4:    $(K_t, g_t) \leftarrow \text{GATE}_{\mathcal{M}_\theta}(c_t, \mathcal{D}_s)$  ▷ Retrieval gating
5:    $\mathcal{S}_t \leftarrow \emptyset$  ▷ NO-OP uses no documents
6:   if  $g_t = \text{LOOK-UP}$  then
7:      $\mathcal{S}_t \leftarrow$  stored documents identified by the gate
8:   else if  $g_t = \text{RETRIEVE}$  then ▷ Inner loop: query optimization
9:      $\mathcal{S}_t \leftarrow \text{OPTIMIZEQUERIES}(c_t, K_t, \mathcal{D}_e, \mathcal{E}(x_t))$ 
10:  end if
11:   $N_t \leftarrow N$  if  $g_t \in \{\text{LOOK-UP}, \text{RETRIEVE}\}$ , otherwise 1
12:  Generate  $x_{t+1}^{(n)} \sim \mathcal{M}_\theta(I, c_t, \mathcal{S}_t)$ ,  $n = 1, \dots, N_t$ , in parallel
13:  Evaluate candidates with  $\mathcal{E}$  and collect valid candidates in  $\mathcal{C}_t^{\text{valid}}$ 
14:  if  $\mathcal{C}_t^{\text{valid}} \neq \emptyset$  then
15:     $x_{t+1} \leftarrow \arg \text{opt}_{x \in \mathcal{C}_t^{\text{valid}}} \mathcal{E}(x)$ 
16:     $\mathcal{D}_e \leftarrow \phi(\mathcal{D}_e \cup \{(x_{t+1}, \mathcal{E}(x_{t+1}))\})$ 
17:    Update  $\mathcal{D}_s$  with evidence and the measured outcome if  $g_t \neq \text{NO-OP}$ 
18:  else
19:    Apply the scaffold's retry policy
20:  end if
21: end for
22: return best evaluated solution
```

Search database update. The search database $\mathcal{D}_s$ associates the selected candidate's outcome with the documents it received. A record contains the executed queries, retained documents and their predicted scores, document identifiers, actual parent and candidate scores $\mathcal{E}(x_t)$ and $\mathcal{E}(x_{t+1})$, and evaluator feedback. Each prediction assumes one document alone, whereas the candidate uses the retained set jointly; the measured outcome therefore belongs to that complete attempt. Intermediate rounds receive no separate measured outcome. Failed evaluations leave the outcome unknown. Candidate code, responses, evaluations, and intermediate retrieval results are retained in the iteration trace.

B.2. Knowledge-Gap-Based Retrieval Gating

Gate inputs and outputs. A single call reads the parent solution, the scaffold's evolutionary history, and recent search records. It returns the knowledge state K_t , a decision g_t , and document identifiers when $g_t = \text{LOOK-UP}$. The knowledge state distinguishes prior model knowledge, findings from searches and evaluations, and unresolved questions about the current solution. The gate runs before population analysis, so **NO-OP** and **LOOK-UP** require no additional analysis call.

Stored search context. The gate, query construction, and evidence scoring share a snapshot of the ten most recent records in $\mathcal{D}_s$, fixed throughout the outer iteration. Each record shows its queries, retained predictions, document identifiers, and measured outcomes, with up to three document bodies. Bodies are truncated to 10,000 characters, preferring full text over a snippet when available. This context lets the model relate previously retrieved evidence to actual optimization outcomes.

No-op and look-up. Under **NO-OP**, the solution prompt receives $\mathcal{S}_t = \emptyset$. Under **LOOK-UP**, the gate selects stored document identifiers, and their bodies are added to the solution prompt. Both decisions bypass the inner loop and make no web-search call.

B.3. Inner Loop: Query Optimization

Algorithm 2 is invoked only under **RETRIEVE** and returns the documents used for solution generation.

Population state descriptor. After a **RETRIEVE** decision, deterministic statistics summarize the retained population $\mathcal{D}_p$ in $\mathcal{D}_e$: its score distribution, recent parent-to-child outcomes, and parent-selection frequencies. Following EvoX,

Algorithm 2 Inner loop: query optimization.

Input: R rounds, J queries per round, M documents per query, local pool capacity D

```
1: function OPTIMIZEQUERIES( $c_t, K_t, \mathcal{D}_e, \mathcal{E}(x_t)$ )
2:    $\mathcal{D}_p \leftarrow$  retained solutions in  $\mathcal{D}_e$ ;  $A_t \leftarrow \mathcal{M}_\theta(\text{stats}(\mathcal{D}_p))$ 
3:    $K_t^0 \leftarrow K_t$ ;  $\mathcal{S}_t^0 \leftarrow \emptyset$ ; initialize an empty score cache  $\hat{s}_t$ 
4:    $\tilde{c}_t^0 \leftarrow (c_t, K_t^0, A_t)$ 
5:   for  $r = 1, \dots, R$  do
6:      $q_r^{(j)} \sim \mathcal{M}_\theta(\tilde{c}_t^{r-1}, \mathcal{S}_t^{r-1}, \{\hat{s}_t(d)\}_{d \in \mathcal{S}_t^{r-1}})$ ,  $j = 1, \dots, J$ , in parallel
7:      $Q_r \leftarrow (q_r^{(j)})_{j=1}^J$  ▷ Query construction
8:      $\mathcal{W}_r \leftarrow \text{SEARCH}(Q_r)$  ▷ Up to  $M$  documents per distinct query
9:      $\mathcal{P}_r \leftarrow \text{DEDUPLICATE}(\mathcal{S}_t^{r-1} \cup \mathcal{W}_r)$ 
10:     $\mathcal{U}_r \leftarrow \{d \in \mathcal{P}_r : \hat{s}_t(d) \text{ is undefined}\}$ 
11:     $K_t^r \leftarrow K_t^{r-1}$ 
12:    if  $\mathcal{U}_r \neq \emptyset$  then ▷ Evidence scoring and knowledge update
13:       $\{\hat{s}_t(d)\}_{d \in \mathcal{U}_r}, K_t^r \leftarrow \text{PREDICT}_{\mathcal{M}_\theta}(\tilde{c}_t^{r-1}, \mathcal{E}(x_t), \mathcal{P}_r)$ 
14:      Cache validated predictions; preserve previously cached scores
15:    end if
16:     $\mathcal{S}_t^r \leftarrow \text{TopD}_{\hat{s}_t}(\mathcal{P}_r)$  ▷ Rank documents with validated scores
17:     $\tilde{c}_t^r \leftarrow (c_t, K_t^r, A_t)$ 
18:  end for
19:  return  $\mathcal{S}_t^R$  ▷ Pass retained documents to the solution prompt
20: end function
```

$\mathcal{M}_\theta$ converts these statistics into factual observations A_t without additional interpretation. The call is skipped if the population is empty. The parent, its score, the evolutionary history, and A_t remain fixed across all R inner rounds.

Query construction. Each round generates J independent responses to the same query prompt in parallel. A response contains one query, its keywords, target source type, intended discovery direction, and rationale; the query text is limited to 500 characters. Round 1 uses $\tilde{c}_t^0 = (c_t, K_t, A_t)$. Later rounds additionally receive the retained documents and their predicted scores, and use the updated knowledge state K_t^{r-1} to target the remaining gaps.

Web search and document pooling. Queries that differ only in whitespace are executed once per round. Each distinct valid query is sent to Tavily with advanced search depth and returns up to M documents. The results are merged with $\mathcal{S}_t^{r-1}$ and deduplicated using the URL or provider identifier, title, and raw body. The pool $\mathcal{P}_r$ therefore contains at most JM documents in the first round and $D + JM$ thereafter. A discarded document re-enters the pool only if a later search returns it again.

Hypothetical evidence scoring and knowledge update. When unscored documents are present, one model call predicts their absolute candidate scores $\hat{s}_t(d)$ on the evaluator’s scale and updates the knowledge state. Each prediction estimates the score obtained by improving the fixed parent using document d alone. Validated predictions are cached for the current inner loop and reused if the document appears again. Up to D documents with the best predicted scores are retained, with ties resolved in pool order. If no document needs scoring, the call is skipped and $K_t^r = K_t^{r-1}$. After round R , the final local pool of up to D documents is passed to the outer loop. Their bodies, titles, and URLs enter the solution prompt without a separate summarization call.

Validation and failures. Only finite predictions for valid, previously unscored document identifiers enter the ranking; existing predictions cannot be overwritten. A complete valid response updates the knowledge state. Partial responses retain valid predictions while preserving the previous knowledge state, and a failed scoring call preserves both the previous retained set and state. Failed searches consume their attempts, and malformed query samples are not replaced. All R rounds run without early stopping. If no usable evidence is retained, the outer loop receives $\mathcal{S}_t = \emptyset$.

B.4. Inference Settings and Call Budget

Settings. The default retrieval budget is $R = 3$ rounds, $J = 1$ query per round, $M = 5$ documents per query, and $D = 3$ documents retained in the local pool. The entire final local pool enters the solution prompt. We evaluate $N = 1$ and $N = 8$ for candidate generation. All model calls use temperature 0.7, top- p 0.95, medium reasoning effort, and up

to 32,768 output tokens. Gate, query, and evidence-scoring calls use user-only prompts with tools disabled. Population analysis uses EvoX’s system prompt and supplies the deterministic statistics in the user message.

Per-iteration budget. The following counts exclude retries. Under [RETRIEVE](#), the model-call budget includes one gate, at most one population analysis, RJ query constructions, and up to R evidence-scoring calls. With the default settings, the limits are eight retrieval-related model calls and three web searches. Candidate generation and evaluation follow separately.

Decision	Retrieval LLM calls	Web searches	Generations
NO-OP	1	0	1
LOOK-UP	1	0	N
RETRIEVE	$\leq RJ + R + 2$	$\leq RJ$	N

B.5. Coupling Web Search with Solution Evolution

Figure 9 compares three ways to integrate web search into OpenEvolve: joint-level retrieval (Table 2), sequential retrieval as in DeepEvolve (Liu et al., 2025), and bi-level retrieval in EVODUET. They differ in when they search, what guides their queries, and how they reuse search results.




Figure 9: Three ways to couple web search with solution evolution. *Top:* search runs within generation (joint-level), precedes generation (sequential), or co-evolves with solutions (bi-level). Blue denotes search, violet solution evolution, and amber the knowledge-gap gate; the dashed overlap marks the coupling between the two loops. *Bottom:* search timing, query guidance, and memory for reuse across iterations. Checkmarks highlight EVODUET’s design choices.

Search placement changes how evidence enters the solution loop. *Joint-level* retrieval runs during program generation: the LLM writes queries alongside program edits and must call Tavily at least once per iteration, with up to three tool rounds. *Sequential* retrieval, as in DeepEvolve, runs a deep-research agent before generation at every iteration. Given the current program and programs selected as inspiration, the agent plans research questions, searches the web, and writes a proposal. Reflection can revisit planning or search when it judges the report incomplete; a coding agent then implements the proposal, followed by debugging and evaluation. Both joint-level and sequential retrieval are single-level: neither scores queries or documents against the task objective.

EVODUET couples query and solution evolution through a knowledge-gap gate (§ 3). The gate reads the current knowledge state and selects [RETRIEVE](#), [LOOK-UP](#), or [NO-OP](#). Under [RETRIEVE](#), the inner loop refines queries over R rounds and selects documents using predicted program scores. The outer loop generates and evaluates programs, then stores the documents and measured outcomes in the search database to guide later gate decisions and queries.

Table 2: Joint-level versus bi-level retrieval (NDG, %).

Method	Denoising	Sums/Diffs
No search	0.0%	14.8%
Joint-level	43.2%	42.9%
Bi-level	84.5%	76.0%

Joint-level search repeatedly returns the same pages on Denoising. In the GPT-5.6-Luna trajectory analyzed in Section 2.3, joint-level retrieval returns 85 distinct URLs versus 248 for EVODUET; 88.1% of its returned URLs are repeats. Across eligible four runs, mean NDG at iteration 100 is 43.2% on Denoising and 42.9% on Sums/Diffs, compared with 84.5% and 76.0% for EVODUET (Table 2).

The DeepEvolve comparison uses published results. On Molecule and Burgers, DeepEvolve’s released scores are 0.8149 and 0.6666, respectively, below our OpenEvolve baseline (0.8496 and 0.6937); EVODUET reaches 0.8524 and 0.7846 (Table 1c). The local scores are the best across available four runs with GPT-5.6-Luna at iteration 100; DeepEvolve was not rerun with the same model or search budget.

C. Experimental Setup Details

We evaluate on 31 tasks in two collections (Table 3). The descriptions below specify each task’s optimization variables, constraints, and evaluation procedure. Arrows indicate whether lower ($\downarrow$) or higher ($\uparrow$) values are better. Unless stated otherwise, we report the evaluator’s native objective.

Table 3: Task coverage.

Domain	Tasks	#
Simple Scientific Optimization	Pressure Vessel, SINDy, Batch Reactor, LABS-27, LJ-13, Chwirut2, Perovskites, SRSD, GuacaMol, Summit	10
Quantum compilation	Swap Reduction	1
Astrodynamics	Cassini, Galileo, Mariner 10, Rosetta, Voyager 2	5
Scientific algorithms	Denoising	1
AI foundations	Domain Mixture, U Shape, LR & BSZ, Parallel	4
Algorithm engineering	AHC039, AHC058	2
Mathematics	Erdős, AC1–AC3, CP ($n=26, 32$), Hadamard, Sums/Diffs	8
Total		31

C.1. Task Descriptions

C.1.1. Simple Scientific Optimization

This collection consists of ten tasks constructed from public sources. For each task, an oracle document was retrieved when the task was created (Appendix C.2). We describe the optimization problem and report the scores of both the initial program and the solution stated in the oracle document.

Pressure Vessel Design (Yang et al., 2013) ($\downarrow$ cost)

The program specifies a vessel by its shell thickness d_s , head thickness d_h , inner radius r , and length L . The two thicknesses must be multiples of 0.0625 in, and the length is restricted to $L \leq 200$ in. The objective is to minimize the fabrication cost

$$C(d_s, d_h, r, L) = 0.6224d_s r L + 1.7781d_h r^2 + 3.1661d_s^2 L + 19.84d_s^2 r,$$

subject to the evaluator’s thickness, volume, and dimension constraints. The initial program has a cost of 10,905.34. The oracle solution, taken from a SlideShare derivation of the optimum, has a cost of 6,059.71.

SINDy Cubic 2D (Brunton et al., 2016) (↓ NRMSE)

The input consists of 2,500 samples from a two-dimensional trajectory. The program returns the coefficients of a polynomial vector field $\dot{\mathbf{x}} = f(\mathbf{x})$ of degree at most three. The evaluator measures how accurately the recovered field describes the dynamics and how accurately its integrated trajectory reproduces the reference trajectory. The objective is to minimize the mean of the vector-field and trajectory normalized root mean squared errors (NRMSEs).

The initial program’s field and trajectory NRMSEs are 0.670 and 1.197, respectively. The cubic-oscillator equation in the PySINDy oracle document gives corresponding errors of approximately zero and 1.7×10^{-8} .

Batch Reactor Control (APMonitor, 2025) (↑ $B(1)$)

The program controls the temperature of a batch reactor with consecutive reactions $A \rightarrow B \rightarrow C$. It returns a schedule of 501 temperature values over $t \in [0, 1]$, each constrained to $[298, 398]$ K. The evaluator integrates the reaction kinetics under this schedule, and the objective is to maximize the terminal concentration $B(1)$ of the intermediate product. The initial constant-temperature policy, $T(t) \equiv 350$ K, achieves 0.57706. The APMonitor GEKKO solution supplied by the oracle achieves 0.61076.

LABS-27 (Packebusch & Mertens, 2016) (↓ energy)

The low-autocorrelation binary sequence problem asks for a sequence $s = (s_1, \dots, s_{27}) \in \{-1, +1\}^{27}$ with small correlations at nonzero shifts. Its aperiodic autocorrelation at lag k and its energy are

$$C_k(s) = \sum_{i=1}^{27-k} s_i s_{i+k}, \quad E(s) = \sum_{k=1}^{26} C_k(s)^2.$$

The program returns the sequence, and the objective is to minimize $E(s)$. The initial sequence has energy 177. The run-length-encoded optimum reported by Packebusch and Mertens in the oracle document has energy 37.

Lennard–Jones-13 (Cambridge Cluster Database, n.d.) (↓ energy)

The program returns the positions $\mathbf{x}_1, \dots, \mathbf{x}_{13}$ of 13 atoms in three-dimensional space. Writing $r_{ij} = \|\mathbf{x}_i - \mathbf{x}_j\|_2$, the objective is to minimize the reduced Lennard–Jones energy

$$E(\mathbf{x}_1, \dots, \mathbf{x}_{13}) = 4 \sum_{1 \leq i < j \leq 13} (r_{ij}^{-12} - r_{ij}^{-6}).$$

Coincident atoms are invalid. The initial straight-chain configuration has energy -12.374 , while the configuration supplied by the Cambridge Cluster Database oracle has energy -44.327 .

NIST Chwirut2 (National Institute of Standards and Technology, n.d.) (↓ RSS)

Given NIST’s 54 observations (x_i, y_i) , the program estimates the three parameters of the nonlinear regression model $\hat{y}(x; b) = e^{-b_1 x} / (b_2 + b_3 x)$. The objective is to minimize the residual sum of squares

$$\text{RSS}(b) = \sum_{i=1}^{54} \left(y_i - \frac{e^{-b_1 x_i}}{b_2 + b_3 x_i} \right)^2.$$

The initial program uses NIST Start 1 and has an RSS of 14,794.79. The NIST-certified parameters in the oracle document give an RSS of 513.048.

OLYMPUS Perovskites (Häse et al., 2021a;b) (↓ bandgap)

The search space contains 192 compositions, each specified by an organic component, a cation, and a halide. The program selects one composition, and the evaluator returns its published HSE06 bandgap from the dataset. The objective is to minimize this bandgap. The initial composition has a bandgap of 5.3704 eV. The hydrazinium–Sn–I composition identified in the Gryffin tutorial oracle has a bandgap of 1.5249 eV.

SRSD Feynman I.27.6 (Matsubara et al., 2024) ($\downarrow$ error)

The program returns a symbolic expression that predicts the focal distance from the three inputs (d_1, n, d_2) . We use the official split of 8,000 training, 1,000 validation, and 1,000 test examples. The optimization objective is the mean squared relative error on the validation set. The initial expression has an error of 0.905. Equation 27.6 of the Feynman Lectures, supplied by the oracle, gives zero error.

GuacaMol C₁₁H₂₄ (Brown et al., 2019) ($\uparrow$ score)

The program proposes molecular structures as SMILES strings, with C₁₁H₂₄ as the target molecular formula. The evaluator canonicalizes and deduplicates the proposals, then averages their formula-agreement scores over the top 159 structures. Missing structures contribute zero, so the objective rewards a collection of distinct matching structures. The initial program supplies 5 of the 159 structures and scores 0.0315. The PubChem isomer list supplied by the oracle gives a score of 1.0.

Summit Baumgartner (Felton et al., 2021; Baumgartner et al., 2019) ($\uparrow$ yield)

The program specifies reaction conditions for an aniline C–N coupling: catalyst, base, base loading, temperature, and residence time. Five released emulators predict the yield under these conditions. Each prediction is clipped to $[0, 1]$, and the objective is to maximize their mean. The initial conditions score 0.655. The conditions in a row of the released dataset, identified by the oracle, score 1.0.

C.1.2. SIMPLETES

We use 21 tasks from SIMPLETES (WILL Team, 2026), together with their released initial programs and evaluators. For each task, the released best program or construction is re-evaluated with the same evaluator and serves as the SOTA anchor for NDG. The tasks cover the six domains below.

Quantum compilation. Swap Reduction searches over initial qubit mappings and routing decisions.

Swap Reduction ($\downarrow$ SWAPs)

Given a logical circuit and a device connectivity graph, a Rust routing policy chooses the initial assignment of logical qubits to physical qubits and inserts SWAP operations as the circuit is processed. The resulting mapping must allow each two-qubit gate to execute on a hardware edge. The optimization target is to reduce the number of inserted SWAPs.

The evaluation scaffold contains 72 circuit–device cases across three topologies. Its native score measures the CNOT overhead saved relative to reference routings. In the paper, we report the number of added SWAPs on the 24 circuits assigned to the 20-qubit device.

Astrodynamics. Each program returns a spacecraft trajectory as a sequence of launch, flyby, deep-space maneuver, and arrival events, with an epoch and a state for each event. The evaluator checks the trajectory using DE430 ephemerides and two-body propagation, enforces the task’s time windows and minimum flyby altitudes, and charges any speed mismatch at a flyby. The common objective is to minimize the total velocity-change budget, in km/s,

$$\Delta v_{\text{total}} = \Delta v_{\text{launch}} + \Delta v_{\text{flybys}} + \Delta v_{\text{maneuvers}} + \Delta v_{\text{arrival}}.$$

The five tasks differ in their destinations, permitted flyby bodies, and arrival conditions.

Cassini ($\downarrow \Delta v$)

The trajectory begins at Earth and ends with capture into a 115-day orbit around Saturn. Flybys may use Venus, Earth, Mars, or Jupiter. A feasible trajectory may contain at most six flybys and six deep-space maneuvers.

Galileo ($\downarrow \Delta v$)

The trajectory begins at Earth and ends with capture into a 210-day orbit around Jupiter. Venus and Earth are the permitted flyby bodies, and the trajectory is limited to five flybys and five deep-space maneuvers.

Mariner 10 ($\downarrow \Delta v$)

The trajectory travels from Earth to Mercury, with Venus as the only permitted flyby body. The arrival contribution to Δv is zero when the arrival speed relative to Mercury is below 10 km/s.

Rosetta ($\downarrow \Delta v$)

The trajectory travels from Earth to a rendezvous with comet 67P at a fixed arrival epoch. Flybys may use Earth or Mars, and each flyby must maintain an altitude of at least 300 km.

Voyager 2 ($\downarrow \Delta v$)

The trajectory travels from Earth to a Neptune flyby, with intermediate flybys permitted at Jupiter, Saturn, and Uranus. The arrival contribution to Δv is zero when the arrival speed relative to Neptune is below 30 km/s.

Scientific algorithms. These tasks evaluate algorithms for statistical estimation. Single-Cell RNA-seq Denoising maximizes reconstruction quality.

Single-Cell RNA-seq Denoising ($\uparrow$ score)

The input is a matrix of noisy unique molecular identifier (UMI) counts. The program returns a denoised matrix of the same shape. For each dataset, the evaluator averages a normalized mean-squared-error score and a normalized Poisson score, with the additional requirement that the Poisson score be at least 0.97. The objective is to maximize this combined score. Program search uses the Pancreas dataset, while the reported result is the mean score on the held-out PBMC and Tabula datasets.

AI foundations. Each task asks the program to define a parametric predictive law and a routine for fitting it. The law is fitted separately for each evaluation group, subject to a task-specific parameter budget. Search is guided by training R^2 , whereas the paper reports held-out R^2 , clipped to $[-1, 1]$. The tasks differ in their input variables, prediction targets, and held-out regimes.

Domain Mixture ($\uparrow R^2$)

The law predicts losses on five domains from the proportions of those domains in a training mixture. Evaluation covers four model sizes, with at most 35 fitted parameters per size. The test set contains 24 unseen mixtures, measuring how well the fitted law predicts losses for mixtures absent from training.

U Shape ($\uparrow R^2$)

The law predicts Brier score as a function of log compute on nine benchmarks. Each benchmark permits at most six fitted parameters. The held-out set contains 127 observations at higher compute, so the reported score measures extrapolation beyond the training regime.

LR & BSZ ($\uparrow R^2$)

The law predicts language-model loss from learning rate, batch size, data size, and model parameter count, using at most 26 fitted parameters. The test set contains 117 runs at a model size and data budget absent from training, assessing transfer of the fitted relationship to that held-out setting.

Parallel ($\uparrow R^2$)

The law predicts loss from model parameter count and the number P of parallel streams. It is fitted on two datasets, with at most four parameters per dataset. Training uses observations with $P \leq 4$, and evaluation uses $P = 8$, testing extrapolation to a larger number of streams.

Algorithm engineering. We use two AtCoder Heuristic Contest problems from ALE-Bench (Imajuku et al., 2025). For each task, a C++ solver is evaluated on 150 public inputs with a 2 s limit per case. A run receives the sum of the official case scores, or zero if any case fails. The reported task score is the average over four runs.

AHC039: Purse Seine Fishing (↑ score)

Given the positions of mackerels and sardines, the solver returns an axis-parallel polygon describing a fishing region. The polygon may have at most 1,000 vertices and a perimeter of at most 4×10^5 . The objective is to maximize the official score by enclosing as many mackerels and as few sardines as possible. We use ALE-Agent’s fifth-place solution as the initial program.

AHC058: Apple Incremental Game (↑ score)

The solver chooses a sequence of machine-upgrade decisions over 500 turns. On each turn, it may perform one upgrade or take no action. If S is the final apple count, the objective is to maximize the official score

$$\text{round}(10^5 \log_2 S).$$

The initial program performs no upgrades and receives a score of zero.

Mathematics. These tasks search for finite representations of mathematical constructions: step functions, circle packings, sign matrices, and integer sets. Each evaluator checks the construction and computes the objective defined below. Circle Packing at $n = 26$ and $n = 32$ constitutes two separate tasks.

Erdős Minimum Overlap (↓ C_5)

The program specifies a step function $h : [0, 2] \rightarrow [0, 1]$ satisfying

$$\int_0^2 h(x) dx = 1.$$

For this function, the evaluator computes C_5 , the maximum overlap between h and its shifted complement. The objective is to minimize C_5 while maintaining the range and integral constraints.

First Autocorrelation Inequality, AC1 (↓ C_1)

The program represents a nonnegative step function on $[-1/4, 1/4]$ by n heights $h_1, \dots, h_n$. Writing $(h * h)_k$ for the discrete convolution of the height sequence with itself, the objective is

$$\min_h C_1(h), \quad C_1(h) = \frac{2n \max_k (h * h)_k}{(\sum_{i=1}^n h_i)^2}.$$

The heights must have a positive sum so that the normalized objective is defined.

Second Autocorrelation Inequality, AC2 (↑ R_2)

The program specifies a nonzero, nonnegative step function f supported on $[-1/4, 1/4]$. Let $f * f$ denote its self-convolution. The objective is to maximize

$$R_2(f) = \frac{\|f * f\|_2^2}{\|f * f\|_1 \|f * f\|_\infty}.$$

Third Autocorrelation Inequality, AC3 (↓ C_3)

The program represents a step function f on $[-1/4, 1/4]$ using signed heights $h_1, \dots, h_n$. The objective is to minimize

$$C_3(f) = \frac{\|f * f\|_\infty}{(f f)^2}, \quad C_3(h) = \frac{2n \max_k |(h * h)_k|}{(\sum_{i=1}^n h_i)^2}.$$

The second expression is the evaluator’s form for the step-height representation. Heights may be positive or negative, but their sum must be nonzero for the objective to be defined.

Circle Packing, $n=26$ and 32 ($\uparrow \sum_i r_i$)

For each of the two values of n , the program returns centers $\mathbf{c}_i = (x_i, y_i)$ and nonnegative radii r_i for n circles. Each circle must lie inside the unit square, and no two circles may overlap:

$$\begin{aligned} r_i &\leq x_i \leq 1 - r_i, & r_i &\leq y_i \leq 1 - r_i, \\ \|\mathbf{c}_i - \mathbf{c}_j\|_2 &\geq r_i + r_j & (i &\neq j). \end{aligned}$$

The objective is to maximize $\sum_{i=1}^n r_i$. The evaluator checks the geometric constraints with tolerance 10^{-12} .

Hadamard, Order 29 ($\uparrow$ ratio)

The program returns a matrix $H \in \{-1, +1\}^{29 \times 29}$. The objective is to maximize $|\det H|$. The evaluator computes the determinant exactly and reports its absolute value divided by a fixed normalization constant.

Sums and Differences ($\uparrow c$)

The program returns a set A containing between 2 and 512 distinct integers in $[-10^6, 10^6]$. Define its sumset and difference set as $A + A = \{a + b : a, b \in A\}$ and $A - A = \{a - b : a, b \in A\}$. The objective is to maximize

$$c(A) = \frac{\log(|A + A|/|A|)}{\log(|A - A|/|A|)}.$$

The evaluator computes both sets from the submitted integers and scores their cardinalities through this ratio.

C.2. Oracle Document Construction

SIMPLETES. For each task, we give Claude Code (Claude Opus 5 with maximum reasoning effort, restricted to its WebSearch and WebFetch tools) the task instructions, the initial program, the evaluator, and the best program released by SimpleTES. It identifies the functional differences that let the best program score higher, writes a web-search query for each, and returns the documents it fetched, each with a summary limited to what the document states. The resulting oracle documents are semantic rather than verbatim. Although the prompt asks for each document’s text as fetched, Claude Code’s WebFetch returns the output of a smaller model that reads the page rather than the page itself, so a document carries what its source says about an improvement, such as a method, a formula, or a parameter setting, but not necessarily its wording or its full content.

Simple Scientific Optimization. The oracle documents of these ten tasks were collected with Claude Code when the tasks were created. Each states the task’s solution directly, for example NIST’s certified parameters for Chwirut2 or the Cambridge Cluster Database coordinates for Lennard–Jones-13, and we validate the stated solution with the task’s evaluator; the boxes in Appendix C.1 give its score.

D. Additional Experimental Results

D.1. OpenEvolve with and without Oracle Documents

Table 4 reports the per-task mean and best NDG for the runs underlying Figure 3. We evaluate simple scientific optimization tasks at iteration 20 and the remaining tasks at iteration 100. Each condition reports the mean and maximum NDG over its available runs independently.

D.2. OpenEvolve with and without Parallel Generation

Parallel generation yields larger gains with oracle documents for GPT-5.6-Luna, but without them for Qwen3.5-9B (Table 5). Increasing N from 1 to 8 raises average NDG by 15.0% with oracle documents and 9.8% without on the nine GPT-5.6-Luna tasks; the corresponding gains on the 12 Qwen3.5-9B tasks are 2.2% and 11.8%.

Table 4: Full results for OpenEvolve with and without oracle documents. Entries report **Mean $\pm$ Std / Best** NDG (%; higher is better) over four runs, where Std is the sample standard deviation and Best is the maximum run NDG. Δ reports oracle minus OpenEvolve for Mean / Best, computed before rounding. Bold marks the higher value for each statistic at the displayed precision. Row colors distinguish task groups. The overall row averages task means and task bests across all 31 tasks.

Task	Qwen3.5-9B			GPT-5.6-Luna		
	OpenEvolve	+ Oracle	Δ (%)	OpenEvolve	+ Oracle	Δ (%)
Simple scientific optimization (10)						
Pressure Vessel	49.9 $\pm$ 57.6 / 100.0	99.9 $\pm$ 0.1 / 100.0	+50.1 / 0.0	100.0 $\pm$ 0.0 / 100.0	100.0 $\pm$ 0.0 / 100.0	0.0 / 0.0
SINDy (2D)	99.8 $\pm$ 0.2 / 100.0	99.8 $\pm$ 0.1 / 100.0	-0.1 / 0.0	100.0 $\pm$ 0.0 / 100.0	100.0 $\pm$ 0.0 / 100.0	0.0 / 0.0
Batch Reactor	38.1 $\pm$ 46.3 / 100.0	87.2 $\pm$ 20.0 / 99.4	+49.1 / -0.6	99.5 $\pm$ 0.6 / 100.1	100.0 $\pm$ 0.0 / 100.1	+0.5 / 0.0
LABS (27)	61.8 $\pm$ 0.0 / 61.8	74.9 $\pm$ 30.6 / 100.0	+13.0 / +38.2	100.0 $\pm$ 0.0 / 100.0	100.0 $\pm$ 0.0 / 100.0	0.0 / 0.0
LJ (13)	96.0 $\pm$ 7.9 / 100.0	100.0 $\pm$ 0.1 / 100.0	+4.0 / 0.0	100.0 $\pm$ 0.0 / 100.0	100.0 $\pm$ 0.0 / 100.0	0.0 / 0.0
Chwirut2	100.0 $\pm$ 0.0 / 100.0	100.0 $\pm$ 0.0 / 100.0	0.0 / 0.0	100.0 $\pm$ 0.0 / 100.0	100.0 $\pm$ 0.0 / 100.0	0.0 / 0.0
Perovskites	68.3 $\pm$ 22.4 / 96.7	81.3 $\pm$ 19.6 / 96.7	+12.9 / 0.0	97.4 $\pm$ 0.8 / 98.1	97.9 $\pm$ 0.6 / 98.1	+0.5 / 0.0
Feynman I.27.6	19.8 $\pm$ 30.1 / 63.5	100.0 $\pm$ 0.0 / 100.0	+80.2 / +36.5	100.0 $\pm$ 0.0 / 100.0	100.0 $\pm$ 0.0 / 100.0	0.0 / 0.0
GuacaMol	56.7 $\pm$ 50.4 / 100.0	100.0 $\pm$ 0.0 / 100.0	+43.3 / 0.0	100.0 $\pm$ 0.0 / 100.0	100.0 $\pm$ 0.0 / 100.0	0.0 / 0.0
Baumgartner	102.0 $\pm$ 4.8 / 106.8	103.1 $\pm$ 2.7 / 107.1	+1.1 / +0.3	94.7 $\pm$ 16.8 / 107.1	94.3 $\pm$ 11.6 / 104.2	-0.5 / -2.9
Quantum compilation (1)						
Swap Reduction	5.8 $\pm$ 4.9 / 10.7	11.9 $\pm$ 16.8 / 23.8	+6.1 / +13.1	21.9 $\pm$ 29.3 / 63.2	63.4 $\pm$ 20.1 / 77.6	+41.5 / +14.4
Astrodynamics (5)						
Cassini	31.4 $\pm$ 12.9 / 43.4	39.8 $\pm$ 29.4 / 60.5	+8.4 / +17.1	73.8 $\pm$ 9.3 / 81.7	77.4 $\pm$ 14.3 / 96.2	+3.5 / +14.5
Galileo	12.2 $\pm$ 8.7 / 24.2	8.0 $\pm$ 11.3 / 16.0	-4.2 / -8.2	37.6 $\pm$ 1.0 / 38.3	48.0 $\pm$ 16.7 / 59.8	+10.4 / +21.6
Mariner 10	93.8 $\pm$ 8.9 / 100.0	93.3 $\pm$ 9.3 / 99.9	-0.5 / -0.1	100.0 $\pm$ 0.0 / 100.0	100.0 $\pm$ 0.0 / 100.0	0.0 / 0.0
Rosetta	52.5 $\pm$ 22.3 / 96.7	43.5 $\pm$ 11.5 / 51.6	-9.0 / -45.0	81.4 $\pm$ 19.1 / 97.8	58.1 $\pm$ 4.1 / 61.0	-23.3 / -36.9
Voyager 2	47.2 $\pm$ 26.6 / 84.7	60.4 $\pm$ 18.0 / 73.1	+13.2 / -11.6	99.3 $\pm$ 1.3 / 100.0	100.0 $\pm$ 0.0 / 100.0	+0.7 / 0.0
Scientific algorithms (1)						
Denosing	17.9 $\pm$ 32.1 / 79.5	17.5 $\pm$ 24.7 / 35.0	-0.4 / -44.5	22.1 $\pm$ 44.2 / 88.4	29.9 $\pm$ 22.2 / 45.6	+7.8 / -42.8
AI foundations (4)						
Domain Mixture	65.1 $\pm$ 35.5 / 90.2	85.1 $\pm$ 2.6 / 86.9	+20.0 / -3.3	97.5 $\pm$ 0.5 / 98.1	93.6 $\pm$ 5.8 / 97.7	-4.0 / -0.4
U Shape	34.3 $\pm$ 53.2 / 109.7	33.3 $\pm$ 47.2 / 66.7	-0.9 / -43.0	0.0 $\pm$ 0.0 / 0.0	50.0 $\pm$ 70.7 / 100.0	+50.0 / +100.0
LR & BSZ	52.9 $\pm$ 33.1 / 87.0	31.5 $\pm$ 44.5 / 62.9	-21.4 / -24.0	23.9 $\pm$ 30.1 / 62.4	38.3 $\pm$ 54.1 / 76.5	+14.3 / +14.1
Parallel	26.2 $\pm$ 10.1 / 40.2	78.0 $\pm$ 10.4 / 85.4	+51.8 / +45.1	91.3 $\pm$ 15.5 / 99.5	85.4 $\pm$ 0.0 / 85.4	-6.0 / -14.2
Mathematics (8)						
Erdős	93.1 $\pm$ 5.8 / 99.8	91.6 $\pm$ 9.9 / 98.5	-1.6 / -1.3	95.8 $\pm$ 7.1 / 99.9	99.9 $\pm$ 0.1 / 100.0	+4.1 / 0.0
AC1	27.3 $\pm$ 15.8 / 50.8	20.3 $\pm$ 17.9 / 32.9	-7.0 / -17.9	42.5 $\pm$ 7.3 / 52.8	51.1 $\pm$ 15.4 / 62.3	+8.6 / +9.5
AC2	35.1 $\pm$ 17.6 / 54.8	33.6 $\pm$ 19.8 / 47.6	-1.5 / -7.2	41.2 $\pm$ 24.8 / 72.0	57.9 $\pm$ 8.2 / 66.3	+16.7 / -5.7
AC3	79.8 $\pm$ 11.1 / 91.8	81.5 $\pm$ 18.6 / 94.6	+1.7 / +2.9	99.7 $\pm$ 0.1 / 99.8	99.6 $\pm$ 0.1 / 99.7	-0.1 / -0.1
CP ($n = 26$)	56.9 $\pm$ 24.9 / 81.9	79.9 $\pm$ 13.3 / 89.3	+23.0 / +7.4	100.0 $\pm$ 0.0 / 100.0	100.0 $\pm$ 0.0 / 100.0	0.0 / 0.0
CP ($n = 32$)	75.1 $\pm$ 4.1 / 78.7	85.0 $\pm$ 2.2 / 86.6	+9.9 / +7.8	100.0 $\pm$ 0.0 / 100.0	99.9 $\pm$ 0.2 / 100.0	-0.1 / 0.0
Hadamard	44.3 $\pm$ 3.3 / 47.9	46.1 $\pm$ 1.9 / 47.5	+1.8 / -0.4	73.1 $\pm$ 17.5 / 90.8	75.8 $\pm$ 25.9 / 98.2	+2.7 / +7.4
Sums/Diffs	5.9 $\pm$ 13.0 / 32.4	0.0 $\pm$ 0.0 / 0.0	-5.9 / -32.4	15.4 $\pm$ 1.2 / 16.0	14.8 $\pm$ 4.4 / 20.5	-0.6 / +4.5
Algorithm engineering (2)						
AHC039	2.5 $\pm$ 6.1 / 15.0	11.5 $\pm$ 16.2 / 22.9	+8.9 / +7.9	1.3 $\pm$ 1.8 / 3.8	0.0 $\pm$ 0.0 / 0.0	-1.3 / -3.8
AHC058	57.6 $\pm$ 31.7 / 86.0	30.4 $\pm$ 18.0 / 43.2	-27.1 / -42.8	92.1 $\pm$ 0.4 / 92.6	91.2 $\pm$ 8.8 / 97.5	-0.9 / +4.9
Overall average (31 tasks)	51.9 / 75.3	62.2 / 71.9	+10.3 / -3.4	74.2 / 82.7	78.3 / 85.4	+4.0 / +2.7

Table 5: Parallel generation with and without oracle documents. Entries show mean $\pm$ sample standard deviation / best NDG (%) at iteration 100. Δ is $N = 8$ minus $N = 1$ within each method; bold marks the higher value.

Task	OpenEvolve			OpenEvolve + Oracle		
	$N = 1$	$N = 8$	Δ (%)	$N = 1$	$N = 8$	Δ (%)
Qwen3.5-9B (12 tasks)						
Quantum compilation						
Swap Reduction	5.8 $\pm$ 4.9 / 10.7	5.8 $\pm$ 6.8 / 13.0	+0.1 / +2.3	11.9 $\pm$ 16.8 / 23.8	41.2 $\pm$ 27.1 / 78.2	+29.3 / +54.4
Astrodynamics						
Cassini	31.4 $\pm$ 12.9 / 43.4	44.0 $\pm$ 29.3 / 60.4	+12.6 / +17.0	39.8 $\pm$ 29.4 / 60.5	17.2 $\pm$ 29.0 / 60.3	-22.5 / -0.2
Galileo	12.2 $\pm$ 8.7 / 24.2	32.8 $\pm$ 2.2 / 35.9	+20.6 / +11.7	8.0 $\pm$ 11.3 / 16.0	24.5 $\pm$ 13.0 / 35.5	+16.5 / +19.5
Mariner 10	93.8 $\pm$ 8.9 / 100.0	73.1 $\pm$ 48.9 / 100.0	-20.7 / 0.0	93.3 $\pm$ 9.3 / 99.9	48.1 $\pm$ 55.6 / 100.0	-45.2 / +0.1
Rosetta	52.5 $\pm$ 22.3 / 96.7	72.8 $\pm$ 17.2 / 98.6	+20.4 / +2.0	43.5 $\pm$ 11.5 / 51.6	58.7 $\pm$ 27.0 / 77.7	+15.2 / +26.1
Voyager 2	47.2 $\pm$ 26.6 / 84.7	95.5 $\pm$ 2.4 / 97.4	+48.3 / +12.7	60.4 $\pm$ 18.0 / 73.1	46.0 $\pm$ 53.2 / 92.1	-14.3 / +19.0
Scientific algorithms						
Denosing	26.8 $\pm$ 37.5 / 79.5	78.5 $\pm$ 8.6 / 85.7	+51.7 / +6.3	17.5 $\pm$ 24.7 / 35.0	58.7 $\pm$ 12.2 / 67.3	+41.2 / +32.4
AI foundations						
U Shape	34.3 $\pm$ 53.2 / 109.7	21.3 $\pm$ 25.1 / 48.8	-13.0 / -61.0	33.3 $\pm$ 47.2 / 66.7	23.3 $\pm$ 46.6 / 93.2	-10.0 / +26.5
LR & BSZ	52.5 $\pm$ 33.8 / 87.0	62.9 $\pm$ 42.7 / 92.8	+10.4 / +5.8	31.5 $\pm$ 44.5 / 62.9	46.1 $\pm$ 37.7 / 86.5	+14.6 / +23.6
Mathematics						
AC2	35.1 $\pm$ 17.6 / 54.8	14.5 $\pm$ 20.2 / 44.4	-20.6 / -10.4	33.6 $\pm$ 19.8 / 47.6	19.1 $\pm$ 31.5 / 66.0	-14.5 / +18.4
Sums/Diffs	5.9 $\pm$ 13.0 / 32.4	4.4 $\pm$ 3.3 / 7.6	-1.4 / -24.8	0.0 $\pm$ 0.0 / 0.0	12.2 $\pm$ 7.9 / 16.5	+12.2 / +16.5
Algorithm engineering						
AHC058	57.6 $\pm$ 31.7 / 86.0	91.1 $\pm$ 1.9 / 92.2	+33.5 / +6.2	30.4 $\pm$ 18.0 / 43.2	34.4 $\pm$ 6.9 / 43.2	+4.0 / 0.0
Overall average (12 tasks)	37.9 / 67.4	49.7 / 64.7	+11.8 / -2.7	33.6 / 48.4	35.8 / 68.0	+2.2 / +19.7
GPT-5.6-Luna (9 tasks)						
Astrodynamics						
Galileo	37.6 $\pm$ 1.0 / 38.3	43.6 $\pm$ 11.1 / 60.3	+6.1 / +22.0	48.0 $\pm$ 16.7 / 59.8	40.1 $\pm$ 2.6 / 42.0	-7.9 / -17.9
Rosetta	81.4 $\pm$ 19.1 / 97.8	87.9 $\pm$ 13.7 / 99.8	+6.5 / +2.0	58.1 $\pm$ 4.1 / 61.0	83.1 $\pm$ 23.2 / 99.5	+25.0 / +38.5
Scientific algorithms						
Denosing	22.1 $\pm$ 44.2 / 88.4	60.5 $\pm$ 31.5 / 80.3	+38.4 / -8.1	29.9 $\pm$ 22.2 / 45.6	80.6 $\pm$ 8.7 / 86.8	+50.7 / +41.2
AI foundations						
U Shape	0.0 $\pm$ 0.0 / 0.0	42.6 $\pm$ 50.6 / 100.0	+42.6 / +100.0	50.0 $\pm$ 70.7 / 100.0	72.1 $\pm$ 23.3 / 88.6	+22.1 / -11.4
Mathematics						
Erdős	95.8 $\pm$ 7.1 / 99.9	99.9 $\pm$ 0.1 / 100.0	+4.1 / 0.0	99.9 $\pm$ 0.1 / 100.0	99.9 $\pm$ 0.0 / 99.9	0.0 / -0.1
AC1	42.5 $\pm$ 7.3 / 52.8	21.4 $\pm$ 7.5 / 28.5	-21.1 / -24.4	51.1 $\pm$ 15.4 / 62.3	73.8 $\pm$ 13.1 / 83.1	+22.7 / +20.8
AC2	41.2 $\pm$ 24.8 / 72.0	40.5 $\pm$ 27.2 / 58.2	-0.8 / -13.8	57.9 $\pm$ 8.2 / 66.3	58.9 $\pm$ 0.0 / 58.9	+1.0 / -7.4
Sums/Diffs	15.4 $\pm$ 1.2 / 16.0	25.8 $\pm$ 5.2 / 31.3	+10.4 / +15.3	14.8 $\pm$ 4.4 / 20.5	40.7 $\pm$ 5.1 / 44.3	+25.9 / +23.8
Algorithm engineering						
AHC058	92.1 $\pm$ 0.4 / 92.6	93.9 $\pm$ 1.1 / 94.5	+1.8 / +1.9	91.2 $\pm$ 8.8 / 97.5	86.7 $\pm$ 6.0 / 90.9	-4.6 / -6.6
Overall average (9 tasks)	47.6 / 62.0	57.3 / 72.5	+9.8 / +10.6	55.7 / 68.1	70.6 / 77.1	+15.0 / +9.0

D.3. Inner-loop Budget Ablations

Table 6: Inner-loop budget ablations with GPT-5.6-Luna.

(a) Rounds R on Denoising.		(b) Queries J on Denoising.	
Setting	NDG (%)	Setting	NDG (%)
$R = 1$	58.35%	$J = 1$ (default)	81.77%
$R = 3$ (default)	81.77%	$J = 3$ ($k=3$)	80.15%
$R = 5$	34.28%	$J = 3$ ($k=5$)	71.86%
		$J = 5$ ($k=3$)	57.30%

More inner-loop search is not better, in either direction. The inner loop is controlled by two budgets: the number of search rounds R within one iteration, and the number of queries J issued per round. Table 6a and Table 6b vary each one on Denoising with GPT-5.6-Luna. Rounds peak at the default: $R=1$ reaches 58.35% NDG, $R=3$ reaches 81.77%, and $R=5$ falls to 34.28%, so a single round gathers too little to act on while five spend the iteration reading instead of editing. Queries are worse than flat: $J=1$ gives 81.77%, $J=3$ gives 80.15% at $k=3$ and 71.86% at $k=5$, and $J=5$ gives 57.30%.

D.4. Full OpenEvolve Results

Tables 7–10 report OpenEvolve scores with and without EVODUET, organized by task group.

Table 7: Quantum compilation and astrodynamics.

Model / Method	Quantum compilation	Astrodynamics				
	Swap ↓	Cassini ↓	Galileo ↓	Mariner 10 ↓	Rosetta ↓	Voyager 2 ↓
	Mean ± Std / Best	Mean ± Std / Best	Mean ± Std / Best	Mean ± Std / Best	Mean ± Std / Best	Mean ± Std / Best
Qwen3.5-9B ($N = 1$)	19,802 ± 353 / 19,487	4.4977 ± 0.691 / 3.8518	2.4036 ± 0.159 / 2.1835	0.5648 ± 0.340 / 0.3274	5.0725 ± 1.649 / 1.7998	3.7582 ± 0.165 / 3.5255
+ EvoDUET	20,279 ± 393 / 20,001	3.3296 ± 0.097 / 3.2613	2.9228 ± 0.872 / 2.3577	0.6607 ± 0.412 / 0.3691	5.1472 ± 0.836 / 4.3908	3.8968 ± 0.179 / 3.7227
Δ	-478 / -514	+1.1681 / +0.5905	-0.5192 / -0.1742	-0.0959 / -0.0418	-0.0747 / -2.5910	-0.1386 / -0.1972
Qwen3.5-9B ($N = 8$)	19,829 ± 482 / 19,374	3.8227 ± 1.573 / 2.9411	2.0271 ± 0.040 / 1.9687	1.3569 ± 1.874 / 0.3274	3.5636 ± 1.274 / 1.6533	3.4582 ± 0.015 / 3.4464
+ EvoDUET	19,697 ± 92 / 19,632	3.1084 ± 0.221 / 2.9525	2.1751 ± 0.325 / 1.9454	0.3345 ± 0.010 / 0.3274	3.9347 ± 1.581 / 2.8168	3.8236 ± 0.265 / 3.6363
Δ	+132 / -258	+0.7143 / -0.0114	-0.1480 / +0.0233	+1.0224 / 0.0000	-0.3711 / -1.1635	-0.3655 / -0.1899
GPT-5.6-Luna ($N = 1$)	18,950 ± 1,414 / 16,958	2.2221 ± 0.500 / 1.8019	1.9389 ± 0.017 / 1.9261	0.3274 ± 0.000 / 0.3274	2.9331 ± 1.416 / 1.7125	3.4343 ± 0.008 / 3.4302
+ EvoDUET	17,894 ± 1,579 / 16,246	1.5083 ± 0.671 / 0.8756	1.9359 ± 0.011 / 1.9264	0.3274 ± 0.000 / 0.3274	3.0555 ± 1.535 / 1.5486	3.4383 ± 0.009 / 3.4302
Δ	+1,055 / +712	+0.7138 / +0.9263	+0.0030 / -0.0003	0.0000 / 0.0000	-0.1224 / +0.1640	-0.0040 / 0.0000
GPT-5.6-Luna ($N = 8$)	18,032 ± 1,472 / 16,354	2.8027 ± 2.331 / 0.8830	1.8276 ± 0.204 / 1.5223	1.2857 ± 1.917 / 0.3274	2.4516 ± 1.016 / 1.5644	3.4302 ± 0.000 / 3.4302
+ EvoDUET	17,690 ± 1,997 / 14,835	1.7475 ± 0.548 / 1.0238	1.7617 ± 0.213 / 1.4863	0.3274 ± 0.000 / 0.3274	2.5281 ± 1.153 / 1.6152	3.4343 ± 0.008 / 3.4302
Δ	+342 / +1,519	+1.0552 / -0.1408	+0.0659 / +0.0361	+0.9584 / 0.0000	-0.0766 / -0.0508	-0.0040 / 0.0000
Gemini-3.8-Flash ($N = 1$)	17,274 ± 602 / 16,848	6.1800 ± 0.000 / 6.1800	2.6272 ± 0.000 / 2.6272	0.3274 ± 0.000 / 0.3274	8.9578 ± 0.000 / 8.9578	3.7407 ± 0.439 / 3.4302
+ EvoDUET	18,829 ± 187 / 18,697	3.8116 ± 3.349 / 1.4433	1.9318 ± 0.006 / 1.9274	0.3274 ± 0.000 / 0.3274	5.6932 ± 4.617 / 2.4285	3.7488 ± 0.428 / 3.4464
Δ	-1,555 / -1,849	+2.3684 / +4.7367	+0.6954 / +0.6998	0.0000 / 0.0000	+3.2647 / +6.5293	-0.0081 / -0.0162
Gemini-3.8-Flash ($N = 8$)	17,363 ± 0.000 / 17,363	0.8200 ± 0.000 / 0.8200	0.7302 ± 0.010 / 0.7228	0.3274 ± 0.000 / 0.3274	1.5168 ± 0.000 / 1.5168	3.4302 ± 0.000 / 3.4302
+ EvoDUET	17,131 ± 1,009 / 15,650	0.8375 ± 0.024 / 0.8202	2.1030 ± 0.349 / 1.9261	0.3274 ± 0.000 / 0.3274	2.3869 ± 1.363 / 1.4227	3.7407 ± 0.439 / 3.4302
Δ	+232 / +1,713	-0.0175 / -0.0002	-1.3728 / -1.2033	0.0000 / 0.0000	-0.8700 / +0.0941	-0.3105 / 0.0000

Table 8: Scientific algorithms and AI foundations.

Model / Method	Scientific algorithms	AI foundations			
	Denoising ↑	Domain Mix ↑	U Shape ↑	LR & BSZ ↑	Parallel ↑
	Mean ± Std / Best	Mean ± Std / Best	Mean ± Std / Best	Mean ± Std / Best	Mean ± Std / Best
Qwen3.5-9B ($N = 1$)	0.6378 ± 0.0453 / 0.7060	0.9212 ± 0.0821 / 0.9768	-0.5470 ± 0.704 / 0.4512	0.0233 ± 0.660 / 0.6966	0.999579 ± 0.000054 / 0.999654
+ EvoDUET	0.6543 ± 0.0190 / 0.6705	0.9322 ± 0.0552 / 0.9713	-1.0000 ± 0.000 / -1.0000	-0.3085 ± 0.422 / 0.1899	0.999552 ± 0.000067 / 0.999612
Δ	+0.0165 / -0.0356	+0.0110 / -0.0055	-0.4530 / -1.4512	-0.3318 / -0.5068	-0.000027 / -0.000042
Qwen3.5-9B ($N = 8$)	0.7052 ± 0.0070 / 0.7111	0.9119 ± 0.0799 / 0.9566	-0.7185 ± 0.332 / -0.3552	0.2270 ± 0.833 / 0.8107	0.999750 ± 0.000108 / 0.999883
+ EvoDUET	0.6752 ± 0.0466 / 0.7081	0.9317 ± 0.0466 / 0.9646	-1.0000 ± 0.000 / -1.0000	-0.5298 ± 0.387 / -0.2563	0.999876 ± 0.000119 / 0.999960
Δ	-0.0301 / -0.0029	+0.0198 / +0.0080	-0.2815 / -0.6448	-0.7568 / -1.0670	+0.000126 / +0.000077
GPT-5.6-Luna ($N = 1$)	0.6065 ± 0.0711 / 0.7132	0.9919 ± 0.0010 / 0.9930	-1.0000 ± 0.000 / -1.0000	-0.5333 ± 0.587 / 0.2172	0.999924 ± 0.000082 / 0.999967
+ EvoDUET	0.7019 ± 0.0201 / 0.7152	0.9920 ± 0.0007 / 0.9930	-1.0000 ± 0.000 / -1.0000	-0.4481 ± 0.652 / 0.2740	0.999883 ± 0.000089 / 0.999960
Δ	+0.0953 / +0.0020	+0.0001 / 0.0000	0.0000 / 0.0000	+0.0852 / +0.0568	-0.000041 / -0.000007
GPT-5.6-Luna ($N = 8$)	0.6906 ± 0.0256 / 0.7067	0.9929 ± 0.0016 / 0.9948	-0.4368 ± 0.670 / 0.3225	-0.8987 ± 0.203 / -0.5950	0.999971 ± 0.000009 / 0.999981
+ EvoDUET	0.6995 ± 0.0366 / 0.7229	0.9940 ± 0.0021 / 0.9971	-1.0000 ± 0.000 / -1.0000	-0.3040 ± 0.662 / 0.3224	0.999965 ± 0.000006 / 0.999970
Δ	+0.0089 / +0.0162	+0.0011 / +0.0023	-0.5632 / -1.3225	+0.5947 / +0.9174	-0.000006 / -0.000011
Gemini-3.8-Flash ($N = 1$)	0.7112 ± 0.0005 / 0.7116	0.9923 ± 0.0002 / 0.9924	-1.0000 ± 0.000 / -1.0000	-0.9403 ± 0.084 / -0.8806	0.999875 ± 0.000115 / 0.999956
+ EvoDUET	0.7101 ± 0.0002 / 0.7102	0.9928 ± 0.0002 / 0.9929	-0.5252 ± 0.671 / -0.0504	0.3445 ± 0.613 / 0.7781	0.999926 ± 0.000048 / 0.999960
Δ	-0.0011 / -0.0014	+0.0005 / +0.0005	+0.4748 / +0.9496	+1.2848 / +1.6587	+0.000051 / +0.000004
Gemini-3.8-Flash ($N = 8$)	0.7100 ± 0.000 / 0.7100	0.9962 ± 0.000 / 0.9962	-0.9642 ± 0.000 / -0.9642	-0.0528 ± 1.340 / 0.8945	0.999964 ± 0.000007 / 0.999969
+ EvoDUET	0.6915 ± 0.0333 / 0.7093	0.9928 ± 0.0001 / 0.9929	-1.0000 ± 0.000 / -1.0000	-0.0457 ± 0.934 / 0.8666	0.999972 ± 0.000004 / 0.999975
Δ	-0.0186 / -0.0007	-0.0035 / -0.0034	-0.0358 / -0.0358	+0.0070 / -0.0279	+0.000008 / +0.000006

Table 9: Mathematics.

Model / Method	Mathematics							
	Erdős ↓	AC1 ↓	AC2 ↑	AC3 ↓	CP($n=26$) ↑	CP($n=32$) ↑	Hadamard ↑	Sums/Diffs ↑
	Mean ± Std / Best	Mean ± Std / Best	Mean ± Std / Best	Mean ± Std / Best	Mean ± Std / Best	Mean ± Std / Best	Mean ± Std / Best	Mean ± Std / Best
Qwen3.5-9B ($N = 1$)	0.389821 ± 0.007589 / 0.381152	1.5128 ± 0.0019 / 1.5099	0.9253 ± 0.0101 / 0.9366	1.7978 ± 0.1889 / 1.5940	2.0995 ± 0.310 / 2.4103	2.6367 ± 0.050 / 2.6810	0.4946 ± 0.0265 / 0.5225	1.064772 ± 0.01103 / 1.087358
+ EVO DUET	0.389166 ± 0.003805 / 0.383647	1.5305 ± 0.0293 / 1.5159	0.9184 ± 0.0099 / 0.9282	1.8663 ± 0.2128 / 1.7158	2.6313 ± 0.006 / 2.6353	2.9206 ± 0.010 / 2.9280	0.4373 ± 0.0628 / 0.4786	1.086398 ± 0.01955 / 1.102270
Δ	+0.000655 / -0.002495	-0.0177 / -0.0060	-0.0068 / -0.0085	-0.0685 / -0.1218	+0.5318 / +0.2250	+0.2838 / +0.2470	-0.0573 / -0.0438	+0.021626 / +0.014912
Qwen3.5-9B ($N = 8$)	0.386232 ± 0.003623 / 0.382699	1.5521 ± 0.0725 / 1.5159	0.9134 ± 0.0117 / 0.9306	1.6036 ± 0.0202 / 1.5737	1.9488 ± 0.645 / 2.5171	2.7595 ± 0.069 / 2.8081	0.2264 ± 0.1662 / 0.4756	1.063549 ± 0.002782 / 1.066260
+ EVO DUET	0.384427 ± 0.003728 / 0.381791	1.5768 ± 0.0906 / 1.5127	0.9265 ± 0.0011 / 0.9273	1.5920 ± 0.0283 / 1.5720	2.5352 ± 0.077 / 2.5895	2.8647 ± 0.071 / 2.9149	0.5256 ± 0.0205 / 0.5399	1.063292 ± 0.004949 / 1.066792
Δ	+0.001804 / +0.000908	-0.0246 / +0.0032	+0.0131 / -0.0034	+0.0116 / +0.0017	+0.5864 / +0.0724	+0.1052 / +0.1068	+0.2992 / +0.0643	-0.000256 / +0.000531
GPT-5.6-Luna ($N = 1$)	0.386347 ± 0.009176 / 0.380967	1.5109 ± 0.0009 / 1.5097	0.9288 ± 0.0143 / 0.9465	1.4586 ± 0.0018 / 1.4571	2.6360 ± 0.000 / 2.6360	2.9396 ± 0.000 / 2.9396	0.7221 ± 0.1390 / 0.8626	1.072913 ± 0.001035 / 1.073430
+ EVO DUET	0.380937 ± 0.000101 / 0.380859	1.5111 ± 0.0025 / 1.5085	0.9430 ± 0.0040 / 0.9465	1.4623 ± 0.0020 / 1.4600	2.6356 ± 0.001 / 2.6360	2.9369 ± 0.005 / 2.9396	0.6606 ± 0.1737 / 0.9211	1.087436 ± 0.010649 / 1.098610
Δ	+0.005410 / +0.000108	-0.0002 / +0.0011	+0.0142 / 0.0000	-0.0036 / -0.0030	-0.0004 / 0.0000	-0.0027 / 0.0000	-0.0615 / +0.0585	+0.014524 / +0.025179
GPT-5.6-Luna ($N = 8$)	0.381008 ± 0.000082 / 0.380917	1.5135 ± 0.0009 / 1.5127	0.9281 ± 0.0162 / 0.9386	1.4604 ± 0.0036 / 1.4581	2.3246 ± 0.623 / 2.6360	2.6354 ± 0.608 / 2.9396	0.8381 ± 0.1659 / 0.9211	1.081721 ± 0.004439 / 1.086459
+ EVO DUET	0.382840 ± 0.000888 / 0.380859	1.5082 ± 0.0012 / 1.5068	0.9466 ± 0.0014 / 0.9481	1.4569 ± 0.0008 / 1.4564	2.6360 ± 0.000 / 2.6360	2.9396 ± 0.000 / 2.9396	0.9247 ± 0.0073 / 0.9357	1.105613 ± 0.021767 / 1.124462
Δ	-0.001832 / +0.000058	+0.0053 / +0.0058	+0.0185 / +0.0095	+0.0036 / +0.0017	+0.3114 / 0.0000	+0.3042 / 0.0000	+0.0866 / +0.0146	+0.023892 / +0.038004
Gemini-3.8-Flash ($N = 1$)	0.380950 ± 0.000004 / 0.380947	1.5127 ± 0.0028 / 1.5107	0.9197 ± 0.0184 / 0.9327	1.4994 ± 0.0201 / 1.4852	2.6360 ± 0.000 / 2.6360	2.9396 ± 0.000 / 2.9396	0.8904 ± 0.0434 / 0.9211	1.089561 ± 0.014543 / 1.099845
+ EVO DUET	0.380905 ± 0.000005 / 0.380902	1.5069 ± 0.0005 / 1.5066	0.9272 ± 0.0275 / 0.9466	1.4597 ± 0.0011 / 1.4589	2.6360 ± 0.000 / 2.6360	2.9396 ± 0.000 / 2.9396	0.9357 ± 0.0000 / 0.9357	1.135834 ± 0.006336 / 1.140314
Δ	+0.000045 / +0.000046	+0.0057 / +0.0041	+0.0075 / +0.0139	+0.0397 / +0.0263	0.0000 / 0.0000	0.0000 / 0.0000	+0.0453 / +0.0146	+0.046272 / +0.040469
Gemini-3.8-Flash ($N = 8$)	0.380903 ± 0.000009 / 0.380896	1.5085 ± 0.006 / 1.5085	0.9455 ± 0.0075 / 0.9508	1.4586 ± 0.000 / 1.4586	2.6360 ± 0.000 / 2.6360	2.9396 ± 0.000 / 2.9396	0.8596 ± 0.000 / 0.8596	1.124049 ± 0.000 / 1.124049
+ EVO DUET	0.380898 ± 0.000007 / 0.380893	1.5065 ± 0.0015 / 1.5055	0.9429 ± 0.0066 / 0.9476	1.4579 ± 0.0023 / 1.4564	2.6360 ± 0.000 / 2.6360	2.9396 ± 0.000 / 2.9396	0.9357 ± 0.0000 / 0.9357	1.143770 ± 0.001737 / 1.144999
Δ	+0.000004 / +0.000003	+0.0020 / +0.0030	-0.0026 / -0.0032	+0.0006 / +0.0022	0.0000 / 0.0000	0.0000 / 0.0000	+0.0760 / +0.0760	+0.019721 / +0.020950

Table 10: Algorithm engineering.

Model / Method	Algorithm engineering	
	AHC039 ↑	AHC058 ↑
	Mean ± Std / Best	Mean ± Std / Best
Qwen3.5-9B ($N = 1$)	554,499 ± 2,471 / 558,387	489,794,634 ± 269,878,148 / 731,576,599
+ EVO DUET	545,315 ± 9,468 / 553,414	564,391,050 ± 288,462,123 / 732,606,033
Δ	-9,184 / -4,973	+74,596,416 / +1,029,434
Qwen3.5-9B ($N = 8$)	554,619 ± 2,448 / 556,857	774,976,672 ± 16,261,216 / 784,638,268
+ EVO DUET	450,025 ± 137,654 / 547,361	750,634,788 ± 31,914,083 / 773,201,452
Δ	-104,594 / -9,496	-24,341,884 / -11,436,816
GPT-5.6-Luna ($N = 1$)	549,694 ± 8,635 / 556,948	784,199,030 ± 3,491,251 / 787,862,153
+ EVO DUET	547,362 ± 1,702 / 548,660	784,263,233 ± 7,949,405 / 790,891,264
Δ	-2,332 / -8,288	+64,202 / +3,029,111
GPT-5.6-Luna ($N = 8$)	552,132 ± 5,993 / 558,223	799,284,884 ± 9,407,424 / 804,359,003
+ EVO DUET	536,812 ± 12,818 / 546,430	742,512,760 ± 144,722,471 / 816,714,532
Δ	-15,320 / -11,793	-56,772,124 / +12,355,529
Gemini-3.8-Flash ($N = 1$)	544,205 ± 1,484 / 545,254	801,414,461 ± 46,248,047 / 834,116,769
+ EVO DUET	550,097 ± 9,545 / 556,846	806,467,666 ± 39,888,838 / 834,673,334
Δ	+5,892 / +11,592	+5,053,206 / +556,565
Gemini-3.8-Flash ($N = 8$)	562,175 ± 0.000 / 562,175	839,834,047 ± 0.000 / 839,834,047
+ EVO DUET	561,054 ± 3,577 / 563,583	845,831,924 ± 4,738,384 / 849,182,468
Δ	-1,121 / +1,408	+5,997,878 / +9,348,421

E. Behavior and Search Analysis

E.1. Behavior Flags and Additional Examples

We define the six behavior flags in Figure 8, report additional retrieval patterns, and examine what the flags capture in individual runs. Appendix I provides the corresponding queries, sources, code edits, and evaluation results for seven worked cases.

E.1.1. Audit Setup and Counting Rules

Records and scope. The GPT-5.6-Luna audit covers 8,200 iterations from 82 runs on the 21 tasks in the main results. The Gemini-3.8-Flash audit covers 14 runs on seven tasks and uses iterations with recorded gate decisions. For each iteration, we inspect the gate decision, queries, retained documents, predicted child scores, and the selected child’s changes relative to its parent. A document is *promising* when its predicted child score exceeds the parent’s score. We call a retrieval *predicted to help* if it retains at least one such document.

Behavior definitions and flags. Each run is counted once per behavior, regardless of how often it occurs; categories can overlap. Regular expressions classify the final query as a known-result lookup, a method or implementation search, a problem-statement lookup, or other. The following rules identify candidate instances of each behavior. The case reviews below distinguish these flags from evidence that a retrieved idea was implemented and retained.

- **Method transfer:** A retrieved method or implementation detail becomes a program component. We flag a run when a method or implementation query retrieves a promising document and the child sets a new run best.
- **Cross-domain transfer:** The model adapts a method or artifact from another scientific field. The flag requires a new run best with a retained document from another field, identified by its title and host. General-purpose numerical tools, such as L-BFGS, trust-region methods, and SciPy, are excluded.
- **Live documentation lookup:** Retrieving documentation to check an interface. The flag requires an API, signature, version, release-note, or documentation query; a retained documentation page; and a child that beats its parent. It does not require a verified API correction.
- **Target-informed reconstruction:** A published value or construction guides development of a solver. We flag a run when a known-result query retrieves a promising document and the child sets a new run best, with no runtime download, copied code line, or pasted numerical solution.
- **Public artifact reuse:** A selected child downloads a published witness or solution at run time, or embeds numerical values from a published solution. Both forms are manually checked.
- **Evidence-inspired over-reach:** A retrieval predicted to help produces a child whose score falls below its parent’s by more than 10% of the run’s total gain. Runs with no positive total gain do not receive this flag.

Artifact checks. Direct code copying occurs in 19 GPT-5.6-Luna iterations (0.2%): 16 copy a single line containing an import, path, or function signature, and three copy part of a Sums/Diffs integer set. The numeric-copy check flags added code containing at least three numbers with five or more significant digits that appear together, exactly or after rounding, on a page retrieved by that iteration. Manual review identifies 59 GPT-5.6-Luna iterations (0.7%) in four runs: three reuse published Rosetta trajectories or flyby dates, and one reuses an AC2 step-function construction. Only one of these four runs retains a copied solution in its final best program. One Gemini-3.8-Flash iteration reuses an AC1 construction. We also inspect runtime network calls; an AHC039 identifier that matches the download detector is excluded as a false positive.

Additional patterns and denominators. *Search miss with own progress* denotes a new run best after a retrieval with no promising document (57 of 82 GPT-5.6-Luna runs). *Identifier fixation* denotes a PR or issue number, or an arXiv identifier, appearing in at least 30% of a run’s retrieval queries; this is assessed only for runs with at least ten retrievals (6 of 75). Figure 8(b) separately measures whether the selected child beats its parent or the previous run best, including at iterations without search. Appendix E.3 compares program revision outcomes with and without documents across all three models.

E.1.2. What the Worked Cases Establish

Method transfer: Swap Reduction (Appendix I.1). At iteration 5, the gate describes the stored documents as “largely conceptual”. The retrieved dSABRE paper supplies exponential depth weighting, which becomes a term in the SWAP scorer and remains in every later best program. The final router adds 14,835 SWAPs on Q20, compared with 15,186 for the released SimpleTES program under the same evaluator. This case verifies implementation and persistence of a retrieved mechanism, beyond the method-transfer flag assigned to 55 of 82 runs.

Cross-domain transfer: Erdős minimum overlap (Appendix I.2). The model retrieves a low-sidelobe radar codeword, 04CF5A2471657C6F, and uses it to seed an optimizer for an additive number-theory problem. All four subsequent improvements to the run best retain the codeword, reducing C_5 from 0.381374 to 0.380915. The first improvement follows a look-up two iterations after retrieval. Inspection of the 13 flagged runs also finds weaker cases: the Anscombe transform is retrieved in three Denoising runs but appears in no candidate, while a quadratic-residue initialization appears in ten selected Erdős children but is absent from that run’s best program. By comparison, a variable-projection formulation introduced on Parallel Scaling at iteration 30, which accounts for 56% of that run’s gain, remains in its best program at iteration 84. A cross-domain source alone therefore does not establish lasting transfer.

Live documentation lookup: Voyager 2 (Appendix I.3). The rule flags 72 retrievals in 27 runs; 13 of these iterations set a new best. Of the 72, 21 ask for an astrodynamics wrapper already documented in the task prompt, and 18 target a pull-request diff. In Voyager 2, 28 of 46 retrievals name the wrapper, but the retained pages describe public Lambert solvers. At iteration 41, a new tour reduces Δv from 3.457 to 3.447 km/s and explicitly passes `lowpath=True`, `M=0`. These are the existing defaults, so they do not change the solver branch; the final best program does not descend from this child. Across 300 wrapper-targeting retrievals, only two retain a page from the benchmark’s source, and neither improves on its parent. The flag thus captures documentation-seeking behavior more broadly than verified API corrections.

Target-informed reconstruction: circle packing, $n=26$ (Appendix I.4). The first query names a best-known sum of radii, 2.635977. The returned pages supply no coordinates, and the model writes an LP-plus-SLSQP solver that raises the objective from 1.390 to 2.628 in one iteration. At iteration 7, it reaches 2.635983, exceeding the queried target and matching the SimpleTES reference to six decimals. Later queries seek the record holder’s source file, but the best program contains a generated solver with no retrieved coordinates or runtime download. Target-informed reconstruction is flagged in 40 of 82 GPT-5.6-Luna runs and 12 of 14 Gemini-3.8-Flash runs.

Public artifact reuse: Erdős minimum overlap, second run (Appendix I.5). At iteration 17, the child downloads a published witness and retains its optimizer as a fallback, reducing the run’s best C_5 from 0.381017 to 0.380859. The best program without a runtime download reaches 0.381004. The program reported in the Erdős row of Table 1a retains this download, so its result depends on access to the published artifact (Appendix K). Two of 82 GPT-5.6-Luna runs download artifacts at run time; four others embed published numerical solutions, including three Rosetta trajectories or sets of flyby dates.

Evidence-inspired over-reach: Galileo (Appendix I.6). At iteration 33, a document’s predicted child score is 0.63701 (parent: 0.63692), but the rewrite scores 0.37713, raising Δv from 1.926 to 3.873 km/s. The run best remains 0.63692; iteration 34 recovers this score from a different parent without retrieval. Across GPT-5.6-Luna runs, 20% of retrievals predicted to help produce a worse child, and 29 of 82 runs contain a drop exceeding 10% of their total gain. Predicted gains therefore require validation by the evaluator.

E.2. Language, Resources, and Reuse in Web Search

Multilingual queries are rare and confined to contest tasks. Figure 10 shows Japanese phrases in 134 of 32,008 parseable queries (0.42%), all on AHC039 or AHC058. These occur in 7 of 338 querying runs (2.1%), with none from Qwen3.5-9B. We inspect non-English-script matches and Latin-script language-detector candidates; the latter contain only English terms, names, and identifiers. This conservative screen covers query text only.




Figure 10: Japanese phrases in search queries. (a) Share of parseable queries containing Japanese phrases, including repeated outputs. (b) Share of querying runs with at least one such query. Purple and hatched blue bars denote $N = 1$ and $N = 8$. Accented names such as Erdős are excluded.

Resource preferences vary across task domains. GitHub is the most exposed host in four of the six task domains, reaching 94.9% of retrieval iterations in quantum compilation. arXiv leads AI foundations (69.6%) and algorithm engineering (48.5%; Figure 11). These rates measure source exposure only.






Figure 11: Top-20 web sources by task domain. Hosts are ranked by the share of retrieval iterations. Each host counts once per iteration; hosts can co-occur. All panels use a common 0–100% scale and report retrieval counts.



(e) Algorithm engineering



(f) Mathematics

Figure 11: Top-20 web sources by task domain (continued). Exposure rates pool all available runs within each domain, using the same counting rule and scale.

Models differ in how they balance retrieval and reuse. Figure 12 aggregates runs within each task group and model. In mathematics, Qwen’s reuse share rises from 25.7% in iterations 1–10 to 55.0% in iterations 91–100, while Luna retrieves in 70.8% of the final ten slots.




Figure 12: Aggregated search dynamics by task group and model. Curves show retrieval (blue), reuse (purple), and missing gate responses (gray) in ten-iteration bins. Each panel pools all available runs. Percentages use all scheduled slots, including no-op and malformed decisions. All panels share the same axes.

Late lookups can reuse documents retrieved at the start. In quantum compilation, 12 of GPT-5.6-Luna’s 21 resolved document requests during iterations 81–100 reuse documents first retrieved during iterations 1–10 (Figure 13).




Figure 13: GPT-5.6-Luna’s lookup provenance by task group. Arrows point from each lookup (purple, bottom) back to the document’s first recorded retrieval (blue, top), pooling all available runs. Both endpoints use ten-iteration bins; vertical arrows represent reuse within the same bin. Width encodes the within-panel share of resolved document ID–iteration pairs on a common square-root scale; n is their total. All 10,887 resolved pairs are shown; 63 unresolved pairs are excluded.

Stored documents remain in use across many iterations. Luna reuses documents with a median age of 17 iterations in scientific algorithms and 44 in quantum compilation (Figure 14). These distributions pool resolved requests within each task group and model.




Figure 14: Source age at reuse by task group and model. Bars aggregate resolved document requests from available GPT-5.6-Luna and Gemini-3.8-Flash checkpoints. Age is the reuse iteration minus the first retrieval iteration; n counts document ID–iteration pairs. We exclude 63 unresolved Luna pairs. Qwen lacks saved checkpoint provenance and is omitted from this figure.

E.3. Failure Analysis of Retrieved Evidence Use

We analyze 33,784 iterations from 362 EVODUET runs across the 21 tasks with Qwen3.5-9B, GPT-5.6-Luna, and Gemini-3.8-Flash at $N \in \{1, 8\}$. We consider each run’s first 100 iterations and exclude iterations with recorded external service errors. Document exposure is verified from the generation prompt. Outcomes compare the selected child’s recorded search score with its parent’s.




Figure 15: Program revision outcomes with retrieved documents. (a) Evaluation failure rates with and without documents at $N = 1$; both conditions use EVODUET. (b) Outcomes of 19,866 document iterations, with counts above the bars. All rates include unsuccessful generations in the denominator. The $N = 8$ policy selects among eight candidates at document steps. Comparisons are observational because the gate selects document exposure.

Qwen’s failures with documents extend beyond evaluation errors. At $N = 1$, Qwen fails evaluation in 12.4% of document iterations versus 9.2% without documents (Figure 15(a)). Only 27.7% improve on the parent, versus 41.1% for Luna and 31.8% for Gemini; 33.2% produce a lower score and 12.9% retain no child. Evaluation errors alone therefore miss revisions that execute but fail to improve.

Qwen improves more often when selecting from parallel candidates. At $N = 8$, Qwen’s document iterations improve on the parent in 49.3% of cases and fail evaluation in 1.1%. Luna and Gemini improve in 53.3% and 47.1%, respectively. Since [RETRIEVE](#) and [LOOK-UP](#) generate eight candidates per attempt while [NO-OP](#) generates one, these outcomes reflect both generation and selection.

Table 11: Examples of unsuccessful document use by Qwen at $N = 1$. Supplied documents, parent and child code, and evaluator records are inspected together. Scores are recorded search scores ($\uparrow$). These cases illustrate mechanisms rather than their population frequencies.

Task	Supplied evidence	Observed revision	Outcome
Sums/Diffs	A construction using the Chinese Remainder Theorem.	Adds random local search without implementing the supplied modular construction.	1.05979 $\rightarrow$ 1.05979
Circle Packing (26)	Joint optimization of centers and radii using SLSQP.	Adopts SLSQP but mixes grouped and interleaved parameter layouts; a returned circle extends outside the square.	Invalid
Denoising	The Anscombe transform $2\sqrt{x + 3/8}$ and its inverse.	Omits the factor of two in the forward transform, while the inverse still divides by two before squaring.	0.28849 $\rightarrow$ 0.28607

Retrieved methods are unused or incorrectly implemented in 26% of sampled Qwen revisions. Codex inspected 50 revisions sampled uniformly from 2,980 eligible Qwen revisions with documents and retained code at $N = 1$. Methods were unused in 3 (6%) and incorrectly implemented in 10 (20%); 22 incorporated or retained a method, 7 lacked actionable evidence, and 8 were uncertain. These model-assessed sample proportions exclude external errors and count only specific new discrepancies with supplied methods. Table 11 provides separate examples; Denoising’s score decrease cannot be attributed to its transform error alone.

F. Limitations

Generalization Across Backbone Models. Our experiments cover GPT-5.6-Luna, Gemini-3.8-Flash, and Qwen3.5-9B. The benefits of EVODUET vary across these models: Qwen3.5-9B has lower overall NDG with EVODUET than with OpenEvolve alone at both $N = 1$ and $N = 8$. Our analysis also identifies cases in which this model ignores retrieved methods or implements them incorrectly. Evaluating more model families and sizes, and examining whether training for evidence selection and implementation reduces these failures, would help establish when a backbone can benefit from bi-level co-evolution.

Limited Gains on Algorithm Engineering Tasks. EVODUET does not consistently improve performance on algorithm engineering tasks such as AHC039 and AHC058. Figure 6b shows lower group-average NDG than OpenEvolve in four of the six model/budget settings, with an average decline of 1.6% across all six. These losses occur with both GPT-5.6-Luna and Qwen3.5-9B at $N = 1$ and $N = 8$. Further work is needed to determine how evidence selection, adaptation to task-specific heuristics, and the allocation of search effort contribute to these failures, and to improve the framework on these tasks.

Toward Multimodal and Multi-Turn Discovery. Scientific discovery often requires interpreting visual observations from experiments (Sun et al., 2025; Ma et al., 2026), motivating the use of vision-language models (Lee et al., 2024d;e;c;a;b; 2025a;b; 2026b; Kang et al., 2026; Lee et al., 2026d;a; Cho et al., 2026; Yu et al., 2026; Kim et al., 2026; Lee et al., 2026c) as mutation operators in our solution optimization loop. In our current framework, the inner loop evolves search queries, while the outer loop generates each candidate solution in a single turn, conditioned on the parent program, evolutionary history, and any retrieved evidence. Extending this bi-level co-evolution paradigm to multi-turn interactions (Lee et al., 2024f;h;i;g; 2025d;c) could enable the model to revisit explored lineages and iteratively refine both queries and solutions within a shared conversational context.

G. Discussions

The benefits of oracle documents vary across models and tasks. On Swap Reduction, the same documents raise NDG by 6.1% for Qwen3.5-9B and 41.5 for GPT-5.6-Luna, while both models lose performance on Rosetta (Figure 3c). Qwen’s positive average oracle gain also shows that its losses with EVODUET do not imply a general inability to use documents. Those losses may reflect difficulties in identifying knowledge gaps, retrieving relevant evidence, or implementing it. The unused methods and incorrect implementations in Appendix E.3 provide examples of the last difficulty. These observations motivate training and evaluating evidence selection and implementation as separate skills, while accounting for baseline performance and search budget.

H. Broader Impact

EVODUET may make computational scientific discovery more efficient by helping researchers find and apply relevant knowledge from the web. However, unreliable sources can lead to incorrect conclusions, while reusing published solutions can result in overstated claims of novelty. To support auditing, we record retrieval and optimization trajectories. We also recommend explicit source attribution, independent validation of generated programs, and human oversight of downstream applications.

I. Trajectories of the Bi-Level Loop

We trace seven runs to show how knowledge gaps, queries, retrieved evidence, and code changes relate to measured outcomes (Table 12). Each case presents selected iterations in chronological order and illustrates a behavior flag or its limitations. Six runs use GPT-5.6-Luna with a candidate budget of $N = 8$; Rosetta uses GPT-5.6-Sol with one candidate. Appendix E.1 defines the flags and reports their frequency.

Table 12: Seven worked behavior cases. Each case links recorded queries and sources to program changes and evaluation results. The cases illustrate the flags in Appendix E.1; a flag alone does not establish successful use of the retrieved evidence.

Behavior	Run	Main finding	Sec.
Method transfer	Swap Reduction	Retrieved depth weighting remains in later best programs despite repeated search misses.	I.1
Cross-domain transfer	Erdős min. overlap	A radar codeword seeds later improvements in a number-theory task.	I.2
Live documentation lookup	Voyager 2	The added API keywords repeat defaults already given in the prompt.	I.3
Target-informed reconstruction	CP ($n=26$)	A generated solver exceeds the value named in the first query.	I.4
Public artifact reuse	Erdős, second run	A program that downloads a published witness improves the run’s best.	I.5
Evidence-inspired over-reach	Galileo	A promising retrieval precedes a worse child; the run’s best is preserved.	I.6
Public artifact reuse; method transfer	Rosetta	Published seeds and stored implementation details support a lower-cost tour.	I.7

Reading the records	
GATE Recorded decision, knowledge-gap assessment, and rationale.	QUERY Query and intent (<code>query_type</code>) for each search round.
SOURCES Retained documents and predicted child scores (<code>estimated_child_score</code>); stored sources on look-up.	QUOTE An excerpt from a retrieved page’s <code>raw_content</code> .
EDIT Selected additions and deletions in the parent-to-child code diff.	RESULT Measured parent and child scores, plus the change in the run’s best.
Record notation Monospace labels are recorded fields; italic labels are derived. Ellipses mark omissions; square brackets mark editorial substitutions. Em-dashes are normalized.	Our annotations Case summaries and behavior tags are our interpretation. In the records, violet tags identify audit behaviors; gray tags identify other patterns.
Gate decision retrieve look-up no-op	Record border and gate badge

Score conventions. The result panels report recorded search-time scores, for which higher is better. Parent $\rightarrow$ child compares the selected candidate with the parent used to generate it; that parent need not be the previous iteration’s child. Best-so-far compares the run’s highest score before and after the iteration. Predicted document scores are not evaluation results. Native objectives have their own direction: lower is better for SWAP counts, C_5 , and Δv ; higher is better for the sum of circle radii. The Erdős score is $1/C_5$.

I.1. Swap Reduction: depth weighting persists despite repeated search misses

Exponential depth weighting from dSABRE remains in every later best program, providing evidence of *method transfer*. The final router adds 14,835 SWAPs on Q20, compared with SimpleTES’s 15,186 under the same evaluator. This advantage is specific to Q20 (Appendix K). Iteration 5 introduces the weighting; later edits tune it. Increasingly specific queries show *identifier fixation*: 79 of 94 retrievals name Qiskit PR #14912 without obtaining its diff. Iteration 77 sets a new best after another retrieval with no promising document, an instance of *search miss with own progress*.

Iterations 5, 7, 13, 66, and 77.

Iteration 5 · retrieve · best-so-far 6,957 → 11,326

GATE

decision retrieve

knowledge_state_analysis The strongest measured result is combined_score 6957.0 from the relative distance-delta scoring combined with component-aware initial layout. Attempt 3's more elaborate layout placement reduced the score to 6565.8, so that change should not be retained. Existing documents establish the SABRE/LightSABRE principles, especially normalized front/lookahead costs, relative candidate scoring, decay, depth, and critical-path heuristics. However, they do not ...

reasoning Additional evidence would help because the current search documents are largely conceptual or generic Qiskit references and prior experiments have plateaued or regressed. Fresh exploration should target repository-specific routing context APIs and concrete implementations of depth-aware, critical-path, or other candidate-ranking heuristics beyond the already tried ...

QUERY

round 1

query "SABRE" adaptive lookahead decay swap scoring weighted interaction frequency initial layout Rust GitHub

query_type *Find a practical adaptive SABRE heuristic or interaction-frequency-based layout method that improves on fixed front-layer/lookahead weights and greedy component placement without requiring unavailable depth or ...*

round 2

query "SwapSelectionContext" Rust "front_layer" executable gate can_apply routing API

query_type *Find repository-specific APIs or source code for detecting immediately executable front-layer gates and applying or scoring them, enabling a controlled addition of an executability reward or adaptive lookahead without ...*

round 3

query "precomputed_extended_set_logical_pairs" dependency depth BFS layer weighted lookahead Rust SABRE

query_type *Find a repository-compatible method for assigning BFS or dependency depths to extended-set gates so the current flat lookahead score can be replaced by a controlled exponential depth-weighted variant.*

SOURCES

title Structured Scaling of AI Discovery Across Diverse Scientific ...

url researchsquare.com/...df?c=1787913294000 estimated_child_score 6,968

title dSABRE: A SABRE-Style Router for Multi-Core Distributed Quantum Computers

url arxiv.org/html/2605.21960v1 estimated_child_score 6,963

title dSABRE: A SABRE-Style Router for Multi-Core Distributed Quantum Computers

url arxiv.org/html/2605.21960 estimated_child_score 6,963

QUOTE

url arxiv.org/html/2605.21960v1

raw_content "...a-core graph. The tilde marks the departure from SABRE's flat extended-set weighting: rather than treating all lookahead gates equally, the exponential factor $\gamma_{\text{dep}}(g_i)$ (g) down-weights gates far from the front so that near-term successors dominate the lookahead signal; a deeper gate is more likely to be displaced by ..."

EDIT

solution: parent → child +53 -1 8 of 54 changed lines shown

```
+ pairs: Vec<(usize, usize)>,
+   self.pairs.push((a, b));
+ fn weighted_score_delta(
+   swap: (usize, usize),
+   if self.pairs.is_empty() {
+   let mut weighted = 0.0;
+   let mut weights = 0.0;
+   for (index, &(x, y)) in self.pairs.iter().enumerate() {
```

RESULT

combined_score 6,957 → 11,326 (parent → child)

Q20 SWAPs 19,953 → 18,030

best-so-far 6,957 → 11,326

BEHAVIOR method transfer

Iteration 7 · retrieve · best-so-far 11,326 → 15,174

GATE

decision retrieve

knowledge_state_analysis The prior attempts established a substantial measured improvement from 6498 to 11325.6, but the three listed attempts have identical routing metrics, so they do not isolate which modifications caused the gain or whether the current heuristic is near a plateau. Existing documents support geometric lookahead decay and LightSABRE concepts such as depth, critical-path scoring, broader candidate neighborhoods, and immediate executability rewards. However, they ...

reasoning Additional evidence would help because the next promising improvements require implementation details absent from the stored documents. Reusing the existing high-level papers would largely repeat explored knowledge; a fresh search should target the exact Rust routing implementation and APIs, as well as validated LightSABRE candidate and scoring behavior.

QUERY

round 1

query site:github.com/Qiskit/qiskit "SwapSelectionContext" "critical_path" OR "delta_depth" OR "can_apply" Rust

query_type Find the current Rust SwapSelectionContext APIs and implementation for LightSABRE depth, critical-path, immediate-executability, and broader candidate-swap scoring.

round 2

query site:github.com/Qiskit/qiskit "SwapSelectionContext" "precomputed_extended_set_logical_pairs" "remaining_predecessor_counts" Rust sabre

query_type Find the current Qiskit Rust source implementation and concrete SwapSelectionContext APIs for BFS/dependency-depth extended-set construction, immediate gate executability checks, and safe broader candidate generation.

round 3

query site:github.com/Qiskit/qiskit "SwapSelectionContext" "precomputed_extended set_logical_pairs" "remaining_predecessor_counts" Rust sabre

query_type Find the current Qiskit Rust source implementation and concrete SwapSelectionContext APIs for BFS/dependency-depth extended-set construction, immediate gate executability checks, and safe broader candidate generation.

SOURCES

title Port the rest of 'SabreSwap' to Rust · Issue #12280 · Qiskit/qiskit · GitHub

url github.com/Qiskit/qiskit/issues/12280 estimated_child_score 11,326

title qiskit/rust-toolchain.toml at main · Qiskit/qiskit · GitHub

url github.com/...b/main/rust-toolchain.toml estimated_child_score 11,326

title Port the rest of 'SabreLayout' to Rust · Issue #12279 · Qiskit/qiskit · GitHub

url github.com/Qiskit/qiskit/issues/12279 estimated_child_score 11,326

QUOTE

url github.com/Qiskit/qiskit/issues/12280

raw_content "...! There was an error while loading. Please reload this page. There was an error while loading. Please reload this page. # Port the rest of 'SabreSwap' to Rust #12280 'SabreSwap' 'SabreSwap' jakelishman ## Description @mtreinish 'SabreSwap' is primarily written in rust currently, there is just a small component of the pass..."

Iteration 7 · retrieve · best-so-far 11,326 → 15,174

(continued)

EDIT

```

solution: parent → child +19 -9 8 of 28 changed lines shown
- let gamma = 0.84_f64;
+ let gamma = 0.70_f64;
- let Some((a, b)) = ctx.last_applied_swap() else {
-   return;
- } else {
+ } else if let Some((a, b)) = ctx.last_applied_swap() {
+   let penalty_scale = (front_layer.len().max(1) as f64).sqrt() * 0.10;
-   *score *= self.decay_state[swap.0].max(self.decay_state[swap.1]);

```

RESULT

combined_score 11,326 → 15,174 (parent → child)

Q20 SWAPs 18,030 → 16,830

best-so-far 11,326 → 15,174

BEHAVIOR

Iteration 13 · retrieve · best-so-far 15,494 → 16,871

GATE

decision

knowledge_state_analysis The strongest measured configuration achieves a combined score of 15493.8 with gamma=0.70, lookahead_size=16, interaction-aware initial layout, and multiplicative endpoint decay. Prior experiments show that geometric lookahead and corrected relative-score handling improve substantially over the weaker baselines, while additive decay and slower gamma=0.84 were not independently superior. Retrieved documents establish the standard SABRE heuristic and...

reasoning Additional evidence would help because the next promising change depends on exact recent Rust/Qiskit extended-set layer-tracking semantics, which are only described at a high level in the stored documents. Fresh exploration should target the actual pull-request diffs or current sabre Rust source, especially layer maintenance, successor admission, and depth-based...

QUERY

round 1
 query site:github.com/Qiskit/qiskit/pull/14911/files OR site:github.com/Qiskit/qiskit/pull/14912/files Rust sabre extended set BFS layers depth on-the-fly raw diff
 query_type Find the exact Rust or accelerated implementation changes from Qiskit PRs #14911 and #14912, especially how the extended set is constructed by dependency layers and updated on the fly, and whether weighting uses BFS...

round 2
 query site:github.com/Qiskit/qiskit/pull/14912/files OR site:github.com/Qiskit/qiskit/blob/main/qiskit/_accelerate "precomputed_extended_set_logical_pairs" "update" "layer" sabre.rs
 query_type Find the actual Rust implementation or patch for SABRE's on-the-fly, layer-based extended-set maintenance, including how dependency layers and gate ordering are represented and updated after swaps or front-layer...

round 3
 query site:github.com/Qiskit/qiskit/pull/14912/files OR site:github.com/Qiskit/qiskit/blob/main/qiskit/_accelerate "precomputed_extended_set_logical_pairs" "update" "layer" sabre.rs
 query_type Find the actual Rust implementation or patch for SABRE's on-the-fly, layer-based extended-set maintenance, including how dependency layers and gate ordering are represented and updated after swaps or front-layer...

SOURCES

title Releases · Qiskit/qiskit - GitHub
 url github.com/qiskit/qiskit/releases estimated_child_score 15,494

title qiskit/qiskit/transpiler/passes/routing/sabre_swap.py at main
 url github.com/...ses/routing/sabre_swap.py estimated_child_score 15,494

Iteration 13 · retrieve · best-so-far 15,494 → 16,871

(continued)

title [PDF] arXiv:2205.10596v1 [quant-ph] 21 May 2022

url arxiv.org/pdf/2205.10596

estimated_child_score 15,494

QUOTE

url github.com/...sses/routing/sabre_swap.py

raw_content "...7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 [...] mapping paper (Algorithm 1) with the modifications from the LightSABRE paper. The heuristic aims to minimize the number of lossy SWAPs inserted and the depth of the circuit. This algorithm starts from an initial layout of virtual qubits onto physical ..."

EDIT

```
solution: parent → child +34 -5 8 of 39 changed lines shown
+ fn completion_bonus(&self, swap: (usize, usize), topology: TopologyView<'>) -> f64...
+ let (a, b) = swap;
+ let mut bonus = 0.0;
+ for &[x, y] in &self.nodes {
+ let old_distance = topology.distance(x, y);
+ let nx = if x == a { b } else if x == b { a } else { x };
+ let ny = if y == a { b } else if y == b { a } else { y };
+ if old_distance > 1 && topology.distance(nx, ny) == 1 {
```

RESULT

combined_score 15,494 → 16,871 (parent → child)

Q20 SWAPs 16,911 → 16,203

best-so-far 15,494 → 16,871

BEHAVIOR

search miss with own progress

Iteration 66 · retrieve · best-so-far 17,201 → 17,608

GATE

decision retrieve

knowledge_state_analysis The measured experiments show that the current policy is valid and that the changes to decay, endpoint handling, initial layout, and candidate scoring have not produced a reliable improvement: the best observed combined score is 17201.4, while the latest layout-related attempt produced no change. Existing documents establish general SABRE principles, especially that the front-layer distance term should not be weakened by front-layer size and that ...

reasoning Additional evidence would help because the prior attempts have plateaued and the stored search results are mostly irrelevant or high-level. A fresh search for the exact Qiskit Rust route.rs implementation and PR diffs could reveal concrete algorithmic details not available in the existing documents, particularly the intended front-layer/lookahead normalization and ...

QUERY

round 1

query site:github.com/Qiskit/qiskit/pull/14912/files route.rs SabreSwap basic_weight extended_set_weight SetScaling Constant front_layer decay

query_type Determine the exact upstream Rust heuristic formula and scaling rules for the front layer, extended set, and decay in Qiskit's SABRE implementation, especially whether the basic front-layer term must remain unnormalized ...

round 2

query site:github.com/Qiskit/qiskit/blob/main/crates/transpiler/src/passes/sabre/route.rs "with_lookahead" "SetScaling::Constant" "num_coupling_qubits"

query_type Determine the exact Rust wiring and default heuristic construction for SABRE basic and lookahead weights, especially whether lookahead is set to 0.5 divided by the coupling-map qubit count and how the coupling-qubit ...

round 3

query site:github.com/Qiskit/qiskit/blob/main/crates/transpiler/src/passes/sabre/route.rs "SetScaling::Constant" "extended_set_weight" "num_coupling_qubits" "LayeredExtendedSet"

query_type Verify the latest Rust SABRE implementation details for constructing and scoring the extended set, including the exact coupling-map-qubit normalization, constant scaling, layer updates, score-delta sign, and ...

Iteration 66 · retrieve · best-so-far 17,201 → 17,608

(continued)

SOURCES

title	qiskit/qiskit/transpiler/passes/routing/sabre_swap.py at main	
url	github.com/...sses/routing/sabre_swap.py	estimated_child_score 17,218
title	qiskit/qiskit/transpiler/passes/routing/sabre_swap.py at main	
url	github.com/...sses/routing/sabre_swap.py	estimated_child_score 17,218
title	SabreSwap (latest version) IBM Quantum Documentation	
url	quantum.cloud.ibm.com/...asses.SabreSwap	estimated_child_score 17,210

QUOTE

url github.com/...sses/routing/sabre_swap.py
 raw_content "...tionPass): r""Map input circuit onto a backend topology via insertion of SWAPs. Implementation of the SWAP-based heuristic search from the SABRE qubit"

EDIT

solution: parent → child +26 -9 8 of 35 changed lines shown

```

- let gamma = 0.70_f64;
+ let gamma = 0.60_f64;
- 0.50
+ 0.85
- 0.35
+ 0.65
+ }
+ }
```

RESULT

combined_score 17,201 → 17,608 (parent → child)
 Q20 SWAPs 16,181 → 15,457
 best-so-far 17,201 → 17,608

BEHAVIOR method transfer

Iteration 77 · retrieve · best-so-far 17,785 → 17,876

GATE

decision **retrieve**

knowledge_state_analysis The strongest measured result came from the earlier heuristic changes, while subsequent variants using geometric lookahead, stagnation scaling, topology-dependent weighting, completion bonuses, and multiplicative decay produced mixed or worse scores. Existing documents establish the standard SABRE normalization and the motivation for LightSABRE-style progress escapes, but they do not provide the exact Rust implementation or behavioral details of the ...

reasoning Additional evidence would help because the unresolved extended-set construction and successor-layer ordering are central to the next plausible optimization. Prior searches mostly returned generic SABRE documentation, release notes, or irrelevant results rather than the actual patch, so a fresh targeted search for the upstream PR diff, Rust route implementation, and ...

QUERY

round 1

query raw.githubusercontent.com/Qiskit/qiskit/main/crates/transpiler/src/passes/sabre/route.rs LayeredExtendedSet on-the-fly extended set update

query_type Find the current upstream Rust implementation and exact update algorithm for maintaining the layered SABRE extended set as front-layer gates are executed, including successor dependency counts, layer replenishment, ...

round 2

query "Update Sabre extended set on-the-fly (#14912)" Rust route.rs diff LayeredExtendedSet successor replenishment

query_type Find the exact Rust implementation or patch for PR #14912, especially how the layered extended set is maintained and replenished as front-layer gates execute, including predecessor-count updates, successor ordering, and ...

Iteration 77 · retrieve · best-so-far 17,785 → 17,876

(continued)

round 3

query "Update Sabre extended set on-the-fly (#14912)" Rust route.rs diff LayeredExtendedSet successor replenishment

query_type

Find the exact Rust implementation or patch for PR #14912, especially how the layered extended set is maintained and replenished as front-layer gates execute, including predecessor-count updates, successor ordering, and...

SOURCES

title

qiskit/qiskit/transpiler/passes/routing/sabre_swap.py at main

url

github.com/...sses/routing/sabre_swap.py

estimated_child_score 17,201

title

transpiler (latest version) | IBM Quantum Documentation

url

quantum.cloud.ibm.com/...skit/transpiler

estimated_child_score 17,201

title

Transforming Quantum Circuits using Qiskit's Transpiler with ...

url

youtube.com/watch?v=MvX5OUK-tbE

estimated_child_score 17,201

QUOTE

url

quantum.cloud.ibm.com/...skit/transpiler

raw_content

"...r-version boundary, but it might rebalance heuristics and add new passes to default methods between minor versions. [...] In practice, the "sabre" plugin runs several orders of magnitude faster, and produces better output. #### Built-in 'sabre' plugin Uses the 'SabreSwap' algorithm to route. This uses Qiskit's enhanced ..."

EDIT

solution:

parent → child

+30 -3 8 of 33 changed lines shown

—

let gamma = 0.70_f64;

+

let gamma = 0.60_f64;

+

let topology = ctx.topology();

+

let average_degree = if topology.num_qubits() == 0 {

+

} else {

+

2.0 * topology.num_edges() as f64 / topology.num_qubits() as f64

+

let topology_factor = if average_degree < 2.5 {

+

0.55

RESULT

combined_score 17,201 → 17,876 (parent → child)

Q20 SWAPs 16,181 → 14,835

best-so-far 17,785 → 17,876

BEHAVIOR

search miss with own progress

I.2. Erdős minimum overlap: a radar codeword seeds later improvements

The optimizer uses a radar codeword to seed a number-theory construction, illustrating *cross-domain transfer*. Across the displayed interval, C_5 falls from 0.385530 to 0.380915; the retrieved codeword remains in all four improvements to the run best after iteration 28. Queries narrow from low-sidelobe code constructions to an explicit sequence; iteration 13 receives a *target-informed reconstruction* flag. Iteration 28 retrieves and implements the codeword without setting a new best. Iteration 30 shows *stored-document reuse*: the optimizer consults the source through look-up and produces the first subsequent improvement.

Iterations 9, 13, 26, 28, 30, and 99.

Iteration 9 · retrieve · best-so-far 2.5938 → 2.6024

GATE

decision retrieve

knowledge_state_analysis The latest [revision] substantially improved the measured combined score to 2.0312 while maintaining validity, mainly through a structured m-sequence candidate search followed by stochastic pairwise refinement. Earlier attempts were slower and had a worse c5 value. However, the search database contains no documents or prior queries, and the remaining challenge (finding a lower maximum non-cyclic overlap under box and sum constraints) is unresolved. It is...

reasoning Additional evidence would help identify better sequence constructions, optimization methods, or relevant bounds for this correlation-minimization problem. No reusable search documents are available, so a fresh search is required.

QUERY

round 1

query optimal balanced binary sequences minimum maximum aperiodic cross-correlation with complement low overlap

query_type *Find mathematical constructions or bounds for minimizing the maximum non-cyclic overlap between a balanced length-64 sequence and its complement, potentially improving on the current m-sequence plus stochastic pairwise...*

round 2

query explicit optimized balanced binary sequence length 64 minimum maximum aperiodic correlation with complement Rudin-Shapiro PSL

query_type *Find an explicit length-64 balanced or near-balanced binary sequence optimized for maximum non-cyclic overlap with its complement, together with its ordering and objective value, rather than relying on the current...*

round 3

query "balanced 64-bit" "minimum PSL" binary sequence coefficients download

query_type *Find the explicit bit pattern or supplementary data/code for a minimum-PSL balanced binary sequence of length 64, rather than only a claim that such sequences exist.*

SOURCES

title Binary Sequences With Small Peak Sidelobe Level

url researchgate.net/..._Peak_Sidelobe_Level

estimated_child_score 2.67500

title Binary Sequences with Minimum Peak Sidelobe Level up ...

url researchgate.net/...evel_up_to_Length_68

estimated_child_score 2.67500

title Binary Sequences with Low Aperiodic Autocorrelations

url preprints.org/manuscript/202605.0907

estimated_child_score 2.66500

QUOTE

url preprints.org/manuscript/202605.0907

raw_content "...ificantly from optimization based on PSL (3). In the former, we minimize the sum of squares, whereas in the latter, we minimize the highest sidelobe, which can lead to different optimization behavior. Some algorithms minimize a combination of metrics to create binary sequences with low aperiodic autocorrelation. Such a..."

EDIT

```
solution: parent → child +149 -119 8 of 268 changed lines shown
- return float(np.max(np.correlate(h, 1.0 - h, mode="full")) * (2.0 / len(h)))
+ return float(np.max(np.correlate(h, 1.0 - h, mode="full")) * (2.0 / n))
- sequence = 2.0 * np.asarray(bits, dtype=np.float64) - 1.0
+ base = np.concatenate([bits, np.asarray([extra], dtype=np.int8)])
+ current = np.asarray(start, dtype=np.float64).copy()
+ temperature = 0.012 * (1.0 - it / iterations) + 0.00025
+ accept = rng.random() < np.exp((score - new_score) / temperature)
+ def _continuous_refine(start, rng, iterations=260000):
```

RESULT

combined_score 2.59384 → 2.60242 (parent → child)

$C_5 = 1/\text{combined_score}$ 0.385530 → 0.384258

best-so-far 2.5938 → 2.6024

BEHAVIOR cross-domain transfer

Iteration 13 · retrieve · best-so-far 2.6024 → 2.6051

GATE

decision **retrieve**

knowledge_state_analysis The existing program already performs substantial deterministic and annealed optimization over balanced 64-sample vectors, but repeated attempts have converged to the same combined score of 2.6024, indicating that further minor tuning is unlikely to provide reliable improvement. Retrieved documents establish that balanced length-64 binary sequences with optimal peak sidelobe level $PSL = 4$ exist and that all such codes were presented in the cited work, but...

reasoning Additional evidence would help because the optimization has plateaued and the most promising route is to obtain an explicit known optimal sequence rather than continue the same search. The existing documents only describe the result and do not provide the codewords, so reuse is insufficient; a fresh web search targeting supplementary files, tables, author...

QUERY

round 1

query "Binary Sequences with Minimum Peak Sidelobe Level up to Length 68" "64" bitstrings hexadecimal supplementary data

query_type *Find an explicit balanced length-64 binary sequence with optimal $PSL = 4$, or a downloadable repository containing the enumerated codewords from the cited exhaustive-search paper.*

round 2

query "Binary Sequences With Small Peak Sidelobe Level" "64" appendix codewords sequences PDF

query_type *Locate an appendix, supplementary file, repository, or machine-readable table containing the explicit balanced length-64 $PSL=4$ binary sequences reported by the paper.*

round 3

query "balanced binary sequence" length 64 "maximum aperiodic cross-correlation" complement optimization code

query_type *Find explicit length-64 balanced binary sequences or implementations that minimize the maximum noncyclic overlap with the complement, rather than merely minimizing binary PSL .*

SOURCES

title Binary Sequences with Minimum Peak Sidelobe Level up to Length 68

url [academia.edu/...be_Level_up_to_Length_68](#) estimated_child_score 2.61000

title Binary Sequences with Minimum Peak Sidelobe Level up ...

url [researchgate.net/...evel_up_to_Length_68](#) estimated_child_score 2.60200

title Binary Sequences with Minimum Peak Sidelobe Level up ...

url [researchgate.net/...evel_up_to_Length_68](#) estimated_child_score 2.60100

QUOTE

url [academia.edu/...be_Level_up_to_Length_68](#)

raw_content "The peak sidelobe level (PSL) of a binary sequence is the largest absolute value of all its nontrivial aperiodic autocorrelations. A classical problem of digital sequence design is to determine how slowly the PSL of a length n binary sequence can grow, as n becomes large. Moon and Moser showed in 1968 that the growth rate of..."

EDIT

```
solution: parent → child +186 -135 8 of 321 changed lines shown
- seq = 2.0 * np.asarray(bits, dtype=np.float64) - 1.0
+ candidate[rng.choice(n, size=n // 2, replace=False)] = 1.0
- temperature = 0.0020 * (1.0 - iteration / iterations) + 1.5e-5
- if new_score <= score or rng.random() < np.exp((score - new_score) / temperature):
- free = np.flatnonzero((result > 1e-12) & (result < 1.0 - 1e-12))
- k = int(free[np.argmin(np.abs(result[free] - 0.5))])
+ free = np.flatnonzero((result > 1e-10) & (result < 1.0 - 1e-10))
+ index = int(free[np.argmin(np.abs(result[free] - 0.5))])
```

RESULT

combined_score 2.59989 → 2.60513 (parent → child)

$C_5 = 1/\text{combined_score}$ 0.384632 → 0.383858

best-so-far 2.6024 → 2.6051

BEHAVIOR cross-domain transfer target-informed reconstruction

Iteration 26 · retrieve · best-so-far 2.6146 → 2.6221

GATE

decision retrieve

knowledge_state_analysis The current program already uses an expensive annealing and continuous-refinement strategy and has plateaued near $c5=0.3830$. The retrieved literature establishes that balanced length-64 binary sequences with optimal aperiodic PSL 4 exist, and that 64-bit optimal codes were exhaustively catalogued, but the stored documents do not provide an explicit usable hexadecimal codeword for length 64. The key unresolved knowledge is the actual sequence data, or a...

reasoning Additional evidence would directly help: finding an explicit balanced PSL-4 length-64 code could substantially improve the candidate and reduce evaluation time by replacing stochastic search. Previously retrieved documents only confirm existence and optimality; they do not contain the required codeword or implementation. A fresh search should target downloadable...

QUERY

round 1

query github "Sequence in HEX" "64" "PSL" binary sequence

query_type Find a repository or copied research table containing an explicit balanced length-64 binary sequence with optimal PSL 4, rather than only a citation proving that such sequences exist.

round 2

query Gluttton PslRK GitLab GitHub length 64 PSL 4 sequence data hexadecimal

query_type Find the PslRK repository's implementation, bundled data files, or generated output containing a balanced 64-bit binary sequence with PSL 4 that can replace the expensive annealing search.

round 3

query site:gitlab.com/Gluttton/PslRK (64 OR length64) (PSL OR sequence OR codeword) (data OR txt OR hex)

query_type Locate the original PslRK repository's actual sequence datasets, generator implementation, or hexadecimal length-64 PSL-4 codeword that is absent from the mirrored project description and issue pages.

SOURCES

title Peak Sidelobe (PSL) Level of Binary Sequences Research ...

url github.com/Gluttton/PslRK estimated_child_score 2.61280

title Binary Sequences with Low Aperiodic Autocorrelations

url preprints.org/manuscript/202605.0907 estimated_child_score 2.61150

title Issues · Gluttton/PslRK

url github.com/Gluttton/PslRK/issues estimated_child_score 2.61150

QUOTE

url github.com/Gluttton/PslRKraw_content "Peak sidelobe (PSL) level of binary sequences research kit. Mirror of gitlab repo: <https://gitlab.com/Gluttton/PslRK>. - Gluttton/PslRK."

EDIT

solution: parent → child +130 -40 8 of 170 changed lines shown

```

- result = refined if refined_peak < best_peak else best
- result = np.asarray(result, dtype=np.float64)
+ candidate = refined if refined_peak < best_peak else best
+ c = np.zeros(2 * n_points - 1, dtype=np.float64)
+ jac = np.zeros((2 * n_points - 1, n_points), dtype=np.float64)
+ out = np.empty((2 * n_points - 1, n_points + 1))
+ bounds=[(0.0, 1.0)] * n_points + [(0.0, 2.0)],
+ if result.success and np.all(np.isfinite(result.x)):
```

Iteration 26 · retrieve · best-so-far 2.6146 → 2.6221

(continued)

RESULT

combined_score 2.61103 → 2.62210 (*parent* → *child*)
 $C_5 = 1/\text{combined_score}$ 0.382990 → 0.381374
 best-so-far 2.6146 → 2.6221

BEHAVIOR cross-domain transfer

Iteration 28 · retrieve · best-so-far 2.6221 → 2.6221 (unchanged)

GATE

decision **retrieve**

knowledge_state_analysis The existing experiments establish that length 64 is the relevant feasible dimension and that balanced binary sequences with aperiodic PSL 4 exist and are optimal. The retrieved documents confirm this fact, but the database excerpts do not provide an actual usable length-64 hexadecimal codeword. The current and prior programs rely on m-sequence seeds plus stochastic continuous annealing; their measured scores have plateaued around c5 0.3825-0.3842, and...

reasoning Additional evidence could enable a materially different initialization or deterministic binary optimization strategy. The stored sources identify the existence and optimal PSL value of length-64 codes but omit the concrete codewords needed for direct reuse, so a fresh search targeting the actual hexadecimal sequences or reproducible search implementation is warranted.

QUERY

round 1

query "Coxson" "Russo" length-64 PSL-4 balanced binary code hexadecimal dataset
 query_type Find an actual usable balanced 64-bit binary sequence with aperiodic PSL 4, preferably from the exhaustive-search data or an accompanying repository, rather than only confirmation that such sequences exist.

round 2

query "04CF5A2471657C6F" all balanced length-64 PSL-4 codewords hexadecimal 142 balance-equivalent
 query_type Find the complete list or downloadable supplementary data of balanced length-64 PSL-4 codewords, including equivalence classes, bit ordering, complements, and reversals.

round 3

query "04CF5A2471657C6F" 142 balance-equivalent length-64 PSL-4 codewords hexadecimal bit ordering
 query_type Find the complete set or a downloadable listing of balanced optimal length-64 PSL-4 codewords, together with the precise hexadecimal-to-bit ordering and complement/reversal conventions.

SOURCES

title Efficient exhaustive search for optimal-peak-sidelobe ...
 url  researchgate.net/...idelobe_binary_codes estimated_child_score 2.63500

title A Survey on the Design of Binary Pulse Compression ...
 url  cdn.intechopen.com/...utocorrelation.pdf estimated_child_score 2.63200

title Efficient exhaustive search for optimal-peak-sidelobe ...
 url  ieeexplore.ieee.org/...0637/01413763.pdf estimated_child_score 2.61100

QUOTE

url  researchgate.net/...idelobe_binary_codes
 raw_content "All balanced 64-bit minimum PSL codes are presented,, whose hexadecimal format is 04CF5A2471657C6F, Coxson and Russo (2004) proposed an"

Iteration 28 · retrieve · best-so-far 2.6221 → 2.6221 (unchanged)

(continued)

EDIT

```

solution: parent → child +203 -135 8 of 338 changed lines shown
+ free = np.flatnonzero((out > 1e-10) & (out < 1.0 - 1e-10))
+ for source in (base, base[::-1], 1.0 - base, 1.0 - base[::-1]):
+     if not any(np.array_equal(candidate, x) for x in result):
+     if candidate_score <= current_score or rng.random() < np.exp(
+ def _continuous_anneal(start, rng, iterations=230000):
-     temperature = 0.0020 * (1.0 - iteration / iterations) + 1.5e-5
-     if new_score <= score or rng.random() < np.exp((score - new_score) / temperature):
-     if float(np.sum(np.clip(v - mid, 0.0, 1.0))) > target:

```

RESULT

combined_score 2.59989 → 2.60254 (parent → child)
 $C_5 = 1/\text{combined_score}$ 0.384632 → 0.384240
 best-so-far unchanged

Iteration 30 · look-up · best-so-far 2.6221 → 2.6244

GATE

decision look-up

knowledge_state_analysis The task is to minimize the maximum discrete cross-overlap correlation for a balanced length-64 binary or fractional vector. Previous evolutionary attempts established that balanced binary sequences outperform the constant vector and that annealing plus fractional refinement reaches approximately $c_5=0.3814-0.3826$, but the stochastic search is variable and has not clearly exploited known optimal sequence structure. Retrieved documents identify exhaustive ...

reasoning The needed new approach (using known balanced length-64 PSL-4 codewords) is already covered by the retrieved documents. Reusing the most direct exhaustive-search sources should enable a deterministic candidate and variants, avoiding another expensive or noisy annealing search. Additional fresh information-seeking is unlikely to be necessary for the next attempt.

QUOTE

No new search: this iteration re-reads documents the run already holds.

EDIT

```

solution: parent → child +151 -109 8 of 260 changed lines shown
- The baseline h=1/2 is perturbed by centered binary maximal-length
- lags = np.arange(-(n_points - 1), n_points, dtype=np.int64)
- best_h = np.full(n_points, 0.5, dtype=np.float64)
- shortlist.append((coarse_score, p.copy(), q0, q_limit))
- best_h += (target_sum - float(np.sum(best_h))) / n_points
- best_h[j] = np.clip(best_h[j] + residual, 0.0, 1.0)
+ return np.correlate(v, 1.0 - v, mode="full") * dx
+ [(word » (63 - i)) & 1 for i in range(n_points)],

```

RESULT

combined_score 2.03125 → 2.62438 (parent → child)
 $C_5 = 1/\text{combined_score}$ 0.492308 → 0.381042
 best-so-far 2.6221 → 2.6244

BEHAVIOR stored-document reuse

Iteration 99 · look-up · best-so-far 2.6252 → 2.6253

GATE

decision **look-up**

knowledge_state_analysis The current approach repeatedly reaches essentially the same score using one documented 64-bit seed and continuous minimax SLSQP refinement. Prior experiments show that generic retrieval about optimization methods did not produce a measured improvement, while the strongest improvement came from reusing the known balanced 64-bit minimum-PSL code information. The search database already contains the exact additional hexadecimal codeword 4090A2E9E63237C2,...

reasoning Additional evidence could help, but the most immediately relevant knowledge (an alternative balanced 64-bit PSL-optimal code and confirmation of exhaustive code enumeration) is already available in the stored documents. Reusing these documents is preferable to another broad retrieval because prior retrievals about continuous, MM, BCD, and general tabu methods did not...

QUOTE

No new search: this iteration re-reads documents the run already holds.

EDIT

solution: parent → child +153 -120 8 of 273 changed lines shown

```
+ z = np.clip(np.asarray(v, dtype=np.float64), 0.0, 1.0)
- return (float(q[0]), float(q[:8].sum()), float(q[:16].sum()))
+ return (float(q[0]), float(q[:6].sum()), float(q[:14].sum()))
- [(word » (63 - i)) & 1 for i in range(n_points)],
+ seed = np.array([(word » (63 - i)) & 1 for i in range(n)],
- for base in (seed, 1.0 - seed, seed[::-1], 1.0 - seed[::-1]):
+ bases = (seed, 1.0 - seed, seed[::-1], (1.0 - seed)[::-1])
- initial_peak = float(np.max(overlap(initial_state)))
```

RESULT

combined_score 2.62515 → 2.62526 (parent → child)

$C_5 = 1/\text{combined_score}$ 0.380930 → 0.380915

best-so-far 2.6252 → 2.6253

BEHAVIOR stored-document reuse

I.3. Voyager 2: documentation lookup repeats defaults already in the prompt

The *live documentation lookup* flag does not establish an API correction. The run names the benchmark's Lambert wrapper in 28 of 46 retrievals, although its signature is already in the prompt. The final best reaches $\Delta v = 3.446$ km/s; most of the reduction occurs without search at iterations 4–8 (4.051 → 3.450 km/s). The retained pages describe public Lambert solvers. Iteration 41 adds a tour that explicitly passes `prograde=True`, `lowpath=True`, `M=0`, all existing wrapper defaults. Its child beats its parent but does not set a new run best, and the final best does not descend from this child.

Iterations 21 and 41.

Iteration 21 · retrieve · best-so-far 0.7342 → 0.7342 (unchanged)

GATE

decision **retrieve**

knowledge_state_analysis The experiments show that deterministic Voyager-like phasing and denser launch/arrival grids reliably produce a valid Earth-Jupiter-Saturn-Neptune solution near combined scores 0.7341-0.7342, with boundary delta-v dominating and DSM/GA costs nearly negligible. Increasing grid density and adding timing clusters has produced only marginal, inconsistent gains, so the current bottleneck is likely unresolved trajectory-branch selection and continuous...

reasoning Additional evidence is warranted because the current search has plateaued after several timing-grid refinements, while the remaining improvement likely requires a materially different optimization or Lambert-branch strategy. Previously retrieved documents are high-level or indirect and do not resolve the specific implementation questions, so a fresh targeted search...

QUERY

round 1

query Python Lambert solver enumerate short-way long-way prograde retrograde multi-revolution branches Izzo implementation code

query_type *Find practical implementation guidance for generating and evaluating all relevant Lambert transfer branches for each MGA leg, including short-way/long-way, prograde/retrograde, and multi-revolution solutions.*

round 2

query "tools_wrapper.py" Tools lambert all solutions branch prograde retrograde multi-revolution Python

query_type *Determine whether the injected Tools.lambert wrapper supports branch selection or returning multiple Lambert solutions, including long-way, retrograde, and multi-revolution cases, and identify the exact callable...*

round 3

query poliastro Izzo Lambert API low_path prograde M multiple solutions return format Python

query_type *Determine the exact callable signature, branch flags, iterator/return format, and failure behavior for enumerating short-way/long-way, prograde/retrograde, and limited multi-revolution Lambert solutions so the...*

SOURCES

title Revisiting Lambert's problem

url esa.int/...-RevisitingLambertProblem.pdf estimated_child_score 0.67200

title Multiple revolutions on Lambert's problem

url poliastro-py.readthedocs.io/...blem.html estimated_child_score 0.66100

title Revisiting Lambert's problem in Python: poliastro 0.17.0 documentation

url docs.poliastro.space/...in%20Python.html estimated_child_score 0.65800

QUOTE

url esa.int/...-RevisitingLambertProblem.pdf

raw_content "...ase, we get an average of 3.3 iterations to convergence. Note how in these tests we do not find a case where a switch occurs between [...] 4 Lambert solver A Lambert solver can be defined as a procedure that returns, for a gravitational field of strength , all the possible velocity vectors v1 and v2 along Keplerian orbits..."

EDIT

```

solution: parent → child                                     +84 -21 8 of 105 changed lines shown
-         slack = float(tf) - float(t0) - MIN_TOF * (n_ga + 1)
+         usable_span = float(tf) - float(t0) - 2.0 * MIN_TOF
-         fractions = np.linspace(0.0, 1.0, n_ga + 2)[1:-1]
-         fractions = np.sort(rng.uniform(0.0, 1.0, n_ga))
+         fractions = tuple(sorted(rng.uniform(0.03, 0.97, n_ga)))
-         float(t0) + MIN_TOF * (k + 1) + float(fractions[k]) * slack
+         n_grid = 5 if n_ga == 0 else (18 if n_ga >= 2 else 8)
-         options={"maxiter": 250 * n_vars, "xatol": 1e-4, "fatol": 1e-6,
```

RESULT

combined_score 0.61677 → 0.73299 (parent → child)

mean_total_dv 4.485 → 3.457 km/s

best-so-far unchanged

BEHAVIOR live documentation lookup

Iteration 41 · retrieve · best-so-far 0.7344 → 0.7344 (unchanged)

GATE

decision **retrieve**

knowledge_state_analysis The experiments established that structured E->J->S->N phasing plus direct Lambert epoch polishing reliably achieves a valid score around 0.7344, with nearly all cost in the launch boundary maneuver and negligible GA/DSM cost. Additional DSM multistart refinement and generic MGA-1DSM/phase-genetic references did not improve this plateau. Existing documents explain general MGA-1DSM encodings, phase-block evolutionary search, Lambert branch and...

reasoning Additional evidence is warranted because the current approach has plateaued despite repeated reuse of the same structured search and polishing ideas. The stored documents are insufficiently specific to identify the best unexplored trajectory formulation or reliably implement alternate Lambert branches and global MGA-1DSM search, so new information-seeking should be...

QUERY

round 1

query "Earth Jupiter Saturn Uranus Neptune" trajectory optimization 2026 launch Lambert encounter epochs delta-v Python

query_type *Find concrete numerical or implementation-oriented methods for globally optimizing launch, flyby, and arrival epochs (and comparing EJSN versus EJSUN topologies) for a Voyager-like Lambert gravity-assist trajectory.*

round 2

query "tools_wrapper.py" Lambert "TrajectoryToolKit" multi-revolution low_path prograde

query_type *Determine whether the evaluator's Tools Lambert interface exposes revolution count, low/high path, and prograde/retrograde branch controls, and identify the exact callable signature needed to enumerate physically...*

round 3

query "TrajectoryToolKit" Lambert solver multi-revolution max_revs low_path prograde Python API

query_type *Determine whether the available Lambert implementation exposes revolution-count, low/high-path, and prograde/retrograde controls, and identify the exact callable signature needed to enumerate physically valid branches.*

SOURCES

title multiple revolution lambert s targeting problem: an analytical

url indico.esa.int/.../624/Lambert_ICATT.pdf

estimated_child_score 0.73412

title Multiple revolutions on Lambert's problem - poliastro

url docs.poliastro.space/...s%20problem.html

estimated_child_score 0.73346

title multiple revolution lambert s targeting problem: an analytical

url indico.esa.int/.../624/Lambert_ICATT.pdf

estimated_child_score 0.73342

QUOTE

url docs.poliastro.space/...s%20problem.html

raw_content "...e, is_lowpath) in type_of_motion_and_path: ss_sol = Maneuver. lambert(ss_departure, ss_arrival, M = M, prograde = is_prograde, lowpath = is_lowpath,) yield ss_sol "" Finally, we can plot all the different scenarios from (M=0) up to (M=2) revolutions: "" from matplotlib import pyplot as plt from poliastro.plotting import ..."

EDIT

solution: parent → child +168 -7 8 of 175 changed lines shown

```
+ clean = [n for n in nodes if n["type"] in ("start", "GA", "end")]
+ ga_pids = [str(n["planet_id"]) for n in clean if n["type"] == "GA"]
+ x0 = np.asarray([float(n["time"]) for n in clean], dtype=float)
+     vd, va = tools.lambert(
+         prograde=True,
+         lowpath=True,
+         M=0,
+     )
+     if np.isfinite(polished_cost) and polished_cost < best_cost:
```

Iteration 41 · retrieve · best-so-far 0.7344 → 0.7344 (unchanged)

(continued)

RESULT

combined_score 0.73299 → 0.73439 (*parent* → *child*)
mean_total_dv 3.457 → 3.447 km/s
best-so-far unchanged

BEHAVIOR live documentation lookup

I.4. Circle packing ($n=26$): a generated solver exceeds the queried target

A generated solver illustrates *target-informed reconstruction*, raising the sum of radii from 1.390 to 2.628 at iteration 1 and reaching 2.635983 at iteration 7. This exceeds the 2.635977 target named in the first query and matches the SimpleTES reference to six decimals. The returned pages contain no coordinates. The child combines a linear program for the radii with SLSQP optimization; iteration 7 also receives a *method transfer* flag. Later queries target a record holder's source file, but the best program contains no retrieved coordinates or runtime download.

Iterations 1, 3, and 7.

Iteration 1 · retrieve · best-so-far 1.3903 → 2.6284

GATE

decision **retrieve**

knowledge_state_analysis The only measured experiment is the initial constructor, which achieved validity 1.0 and sum_radii 1.3903. No search documents or prior queries are available. The current approach uses a 6x6 grid with 26 points and a sequential pairwise radius-scaling heuristic; it does not solve the coupled radius optimization problem and likely leaves substantial performance unexplored. General circle-packing and numerical-optimization principles are known, but the best...

reasoning Additional evidence could help identify known 26-circle packing configurations, optimized coordinates, or stronger construction and optimization methods. There are no stored documents to reuse, so fresh information-seeking is appropriate.

QUERY

round 1

query 26 non-overlapping circles unit square maximize sum of radii nonlinear optimization Python

query_type Find formulations, optimized arrangements, or implementation techniques for maximizing the total radius of 26 variable-radius circles in a unit square.

round 2

query 26 circles unit square packing coordinates sum radii 2.635977 GitHub

query_type Find explicit numerical center and radius coordinates or complete reproducible code for a 26-circle unit-square packing near the 2.6359 benchmark, rather than another incomplete optimization sketch.

round 3

query 26 non-overlapping circles unit square sum radii 2.635977 coordinates solution file

query_type Find a complete feasible set of 26 circle centers and radii, or downloadable code containing the published approximately 2.635977 construction, so the next program can use a verified solution directly instead of relying...

SOURCES

title [PDF] Out-of-the-Box Global Optimization for Packing Problems - arXiv

url arxiv.org/pdf/2605.04850

estimated_child_score 2.55000

title Seems a new circle packing result (2.635977) when ...

url github.com/...ence/openevolve/issues/156

estimated_child_score 2.35000

title Circle packing in the unit square: new sum-of-radii layouts

url numaro.tech/...-packing-unit-square-2026

estimated_child_score 2.35000

Iteration 1 · retrieve · best-so-far 1.3903 → 2.6284

(continued)

QUOTE

url [xarxiv.org/pdf/2605.04850](https://arxiv.org/pdf/2605.04850)

raw_content “The aspect ratio determined by α is a decision variable that can be modified to maximize the sum of radii for a given number of circles. We can trivially change this formulation to packing into a unit square by fixing $\alpha = 1$. This is a crucial property of mathematical optimization modeling: the user needs to change only the...”

EDIT

```
solution: parent → child +135 -73 8 of 208 changed lines shown
+   chosen = [np.argmin(np.sum((pts - 0.5) ** 2, axis=1))]
+   np.sum((pts[:, None, :] - pts[np.asarray(chosen)][None, :, :]) ** 2, axis=2),
+   pairs = [(i, j) for i in range(n) for j in range(i + 1, n)]
+   method="highs", options={"dual_feasibility_tolerance": 1e-9},
+   distances = np.linalg.norm(c[pair_i] - c[pair_j], axis=1)
+   return np.r_[boundary, distances - r[pair_i] - r[pair_j]]
+   options={"maxiter": 1100, "ftol": 2e-9, "disp": False},
+   if result.success or np.all(constraints(result.x) > -2e-6):
```

RESULT

combined_score 1.39032 → 2.62840 (parent → child)

best-so-far 1.3903 → 2.6284

BEHAVIOR target-informed reconstruction

Iteration 3 · retrieve · best-so-far 2.6284 → 2.6317

GATE

decision [retrieve](#)

knowledge_state_analysis The current program uses staggered candidate centers, farthest-point sampling, SLSQP center optimization, and an LP radius referee, reaching a measured sum of radii of 2.6284. Prior experiments established that this general optimization approach is feasible and substantially improves the earlier 1.3903 parent, but it remains below reported $n=26$ values around 2.63586–2.63598. Previously retrieved documents identify stronger benchmark scores and broadly ...

reasoning Additional evidence would likely help because the existing implementation is measurably below the reported benchmark and the stored documents lack the concrete coordinates or complete algorithm required for reproduction. A fresh search should target accessible source code, coordinate files, contact graphs, or detailed optimization methods for the reported ...

QUERY

round 1

query "2.6359830853" (coordinates OR solution OR contact) (github OR csv OR json OR numpy)

query_type Find the actual record-level $n=26$ circle coordinates, serialized solution files, or contact graph associated with the 2.6359830853 benchmark.

round 2

query site:github.com/ypwang61 "2.63586276" "26" circle packing coordinates

query_type Find the verified $n=26$ unit-square circle centers, radii, contact graph, or optimization code associated with the 2.63586276 benchmark.

round 3

query github ThetaEvolve "Results/CirclePacking/programs/8B-w_RL@65.py" circle packing raw code

query_type Find the exact high-scoring $n=26$ circle-packing program, including its center-generation strategy, topology search, optimization settings, and radius-shrinking feasibility pass.

SOURCES

title GitHub - ypwang61/ThetaEvolve: ThetaEvolve: Test-time Learning on Open Problems, enabling ...

url github.com/ypwang61/ThetaEvolve estimated_child_score 2.63598

title GitHub - ypwang61/ThetaEvolve: ThetaEvolve: Test-time Learning on Open Problems, enabling ...

url github.com/ypwang61/ThetaEvolve estimated_child_score 2.63598

Iteration 3 · retrieve · best-so-far 2.6284 → 2.6317

(continued)

title coordinates.csv · GitHub

url gist.github.com/...113d07aa11918faf3a865

estimated_child_score 2.62840

QUOTE

url github.com/ypwang61/ThetaEvolve

raw_content "...plifies (e.g., with single LLM) and extends AlphaEvolve to efficiently scale both in-context learning and RL training at test time. With ThetaEvolve, an 8B model can outperform AlphaEvolve on open optimization problems by scaling compute for inference or test-time RL: Circle packing: AlphaEvolve (Gemini-2.0-Flash/Pro): ..."

EDIT

```

solution: parent → child                                     +87 -149 8 of 236 changed lines shown
+       d2 = np.min(np.sum((pts[:, None] - q[None, :]) ** 2, axis=2), axis=1)
+       top = np.argmax(np.sum((pts[:, None] - q[None, :]) ** 2, axis=2), axis=1)
-       chosen = [int(np.argmax(np.sum((points - 0.5) ** 2, axis=1))) for i in range(n)]
-       np.sum((points[:, None, :] - selected[None, :, :]) ** 2, axis=2),
-       pairs = [(i, j) for i in range(n) for j in range(i + 1, n)]
+       -np.ones(n), A_ub=A, b_ub=b, bounds=[(0.0, float(x)) for x in wall],
+       return np.maximum(out.x, 0.0) if out.success else np.full(n, 0.03)
+       sep = np.linalg.norm(x[p_i] - x[p_j], axis=1) - r[p_i] - r[p_j]
```

RESULT

combined_score 2.62840 → 2.63173 (parent → child)

best-so-far 2.6284 → 2.6317

BEHAVIOR target-informed reconstruction

Iteration 7 · retrieve · best-so-far 2.6359 → 2.6360

GATE

decision **retrieve**

knowledge_state_analysis The current multistart SLSQP/LP approach has improved the score to 2.6343, but it remains below the documented 2.63598308 record. Retrieved documents establish that an asymmetric ThetaEvolve circle-packing program and a formal zero-tolerance variant exist, and that the winning approach can repeatedly reach the record in about three seconds. However, the actual source code, coordinates, initialization strategy, and radius-shrink procedure were not...

reasoning Additional evidence would likely help substantially because the existing local-search variants plateaued at 2.6343 and the stored search results do not contain the referenced winning program body. A fresh web search targeting the raw GitHub file, repository API, commit history, or downloadable result artifacts could expose the exact implementation or coordinates and...

QUERY

round 1

query github ypwang61 ThetaEvolve Results/CirclePacking/programs 8B-w_RL@65-Formal.py shrink_radii raw

query_type Locate the exact formal ThetaEvolve circle-packing source, especially its asymmetric initialization, optimized coordinates, and zero-tolerance radius-shrink procedure.

round 2

query "8B-w_RL@65-Formal.py" "shrink_radii" "initial_positions"

query_type Find the complete ThetaEvolve formal circle-packing source or an uncropped copy of its staged initialization, optimization stages, coordinates, and exact radius-shrink implementation.

round 3

query site:github.com/ypwang61/ThetaEvolve/blob/main/Results/CirclePacking/programs "shrink_radii" OR "initial_positions" OR "stage 1"

query_type Find the complete ThetaEvolve 26-circle packing source, especially its staged initialization, optimization stages, topology-preserving refinement, and exact strict-feasibility radius-shrink implementation.

Iteration 7 · retrieve · best-so-far 2.6359 → 2.6360 (continued)

SOURCES

title GitHub - ypwang61/ThetaEvolve: ThetaEvolve: Test-time Learning on Open Problems, enabling ...
url github.com/ypwang61/ThetaEvolve
estimated_child_score 2.63598

title Seems a new circle packing result (2.635977) when ...
url github.com/...ence/openevolve/issues/156
estimated_child_score 2.63598

title ThetaEvolve: Test-time Learning on Open Problems
url arxiv.org/html/2511.23473v1
estimated_child_score 2.63190

QUOTE

url github.com/ypwang61/ThetaEvolve
raw_content "...plifies (e.g., with single LLM) and extends AlphaEvolve to efficiently scale both in-context learning and RL training at test time. With ThetaEvolve, an 8B model can outperform AlphaEvolve on open optimization problems by scaling compute for inference or test-time RL: Circle packing: AlphaEvolve (Gemini-2.0-Flash/Pro): ..."

EDIT

solution: parent → child +191 -96 8 of 287 changed lines shown

```

- d2 = np.min(np.sum((pts[:, None] - q[None, :]) ** 2, axis=2), axis=1)
- top = np.argmaxpartition(d2, -min(8, len(d2)))[-min(8, len(d2)):]
- wall = np.min(np.column_stack((c, 1.0 - c)), axis=1)
- np.ones(n), A_ub=A, b_ub=b, bounds=[(0.0, float(x)) for x in wall],
+ distances = np.linalg.norm(centers[i] - centers[j], axis=1)
- return np.maximum(out.x, 0.0) if out.success else np.full(n, 0.03)
- sep = np.linalg.norm(x[pi] - x[pj], axis=1) - r[pi] - r[pj]
+ separation = np.linalg.norm(delta, axis=1) - r[pair_i] - r[pair_j]

```

RESULT

combined_score 2.63173 → 2.63598 (parent → child)
best-so-far 2.6359 → 2.6360

BEHAVIOR method transfer

1.5. Erdős minimum overlap, second run: runtime witness reuse improves the best

The run moves from *method transfer* and *target-informed reconstruction* to *public artifact reuse*, reducing C_5 from 0.485374 to 0.380859. The first two iterations implement retrieved construction ideas. At iteration 17, the child downloads and validates a published witness, improving on its parent (0.381075) and the previous run best (0.381017). It retains the local optimizer as a fallback, and the best program preserves the external dependency.

Iterations 1, 2, and 17.

Iteration 1 · retrieve · best-so-far 2.0603 → 2.4242

GATE

decision retrieve
knowledge_state_analysis The current program generates a random, mean-constrained step function and evaluates the maximum cross-correlation between h and $1-h$. The only measured result is $c_5 = 0.4854$ with full validity and no information about the specific prior modification. There are no stored search documents. I know the feasibility projection and basic correlation behavior, but the best discrete constructions or analytical bounds for minimizing this maximum overlap remain ...
reasoning Additional evidence would help identify known extremal constructions, bounds, and optimization strategies for this specialized overlap problem. No relevant documents are available in the search database, so a fresh search is required.

QUERY

round 1
query "Erdős overlap problem" minimum maximum cross-correlation $h(x) (1-h(x+t))$ construction
query_type Find analytical bounds and explicit discrete or binary constructions that minimize the maximum overlap between a function h and its complement $1-h$ across shifts.

Iteration 1 · retrieve · best-so-far 2.0603 → 2.4242

(continued)

round 2

query site:github.com/togethercomputer/erdos-minimum-overlap optimized construction vector Erdős minimum overlap code

query_type Find the actual optimized discretized sequence, objective function, and implementation used to achieve the 0.380871 minimum-overlap value, including how its correlation and boundary conventions map to the evaluator's...

round 3

query site:github.com/togethercomputer/erdos-minimum-overlap "h_values" OR "minimum overlap" construction vector code

query_type Find the repository source file or accompanying technical description containing the optimized step-function/vector construction, number of bins, and evaluator-compatible correlation and boundary conventions that...

SOURCES

title GitHub - togethercomputer/EinsteinArena-new-SOTA: New state-of-the-art bounds for open...

url github.com/...uter/erdos-minimum-overlap estimated_child_score 2.63000

title EinsteinArena-new-SOTA/README.md at main · togethercomputer/EinsteinArena-new-SOTA · ...

url github.com/...verlap/blob/main/README.md estimated_child_score 2.63000

title EinsteinArena state-of-the-art results - GitHub

url github.com/...uter/erdos-minimum-overlap estimated_child_score 2.63000

QUOTE

url github.com/...uter/erdos-minimum-overlap

raw_content "Problem Objective Our Result Previous Best Improvement; Erdős' Minimum Overlap minimize 0.380871 0.380876 −0.000005 First Autocorrelation Inequality minimize 1.50286286 1.50286290 −0.00000004 Flat Polynomials (degree 69) minimize 1.280932 1.340925 −0.059993 Edges vs Triangles maximize −0.712256 −0.712494 +0.000238 Tammes..."

EDIT

solution: parent → child +42 −10 8 of 52 changed lines shown

```

- n_points = int(rng.integers(40, 100))
+ rng = np.random.default_rng(731928)
- h_values = np.ones(n_points) * 0.5
+ c = np.correlate(v, 1.0 - v, mode="full") * dx
+ return float(np.max(c) + 0.015 * np.mean(q)), float(np.max(c))
- perturbation = rng.uniform(-0.4, 0.4, n_points)
- perturbation = perturbation - np.mean(perturbation)
+ h = np.zeros(n_points, dtype=np.float64)

```

RESULT

combined_score 2.06027 → 2.42424 (parent → child)

$C_5 = 1/\text{combined_score}$ 0.485374 → 0.412500

best-so-far 2.0603 → 2.4242

BEHAVIOR method transfer

Iteration 2 · retrieve · best-so-far 2.4242 → 2.6202

GATE

decision retrieve

knowledge_state_analysis The current program uses a computationally expensive simulated-annealing search over 160 balanced binary bins and has achieved a measured c_5 of 0.4854, while the retrieved GitHub documents report a much stronger benchmark of 0.380871. The prior searches established only the benchmark result and repository context; they did not provide the construction, source code, parameters, or optimization method that produced it. Existing documents are therefore...

reasoning Additional evidence would likely help substantially because the known benchmark is far below the current result, and the stored documents contain no actionable algorithm or code. This requires a fresh search for the actual repository files, construction details, or related mathematical/computational methods.

QUERY

round 1

query site:github.com/togethercomputer/EinsteinArena-new-SOTA/tree/main/erdos-minimum-overlap OR site:github.com/togethercomputer/EinsteinArena-new-SOTA "erdos-minimum-overlap" source code ...

query_type Find the repository files, construction method, objective discretization, and optimization parameters that produced the 0.380871 benchmark.

round 2

query "Power-tent" "iterative refinement" "Erdős minimum overlap" coefficients code

query_type Find the executable parameterization, witness coefficients, discretization, and refinement procedure behind the approximately 0.38086–0.38087 Fourier-constrained constructions.

round 3

query "Erdős minimum overlap" power-tent Fourier coefficients active-shift refinement code n=800

query_type Find executable code or explicit coefficients for the reported power-tent/Fourier construction, including how active shifts and high-resolution discretization are refined for the evaluator.

SOURCES

title Erdős Minimum Overlap (Upper Bound)

url einsteinarena.com/...s/erdos-min-overlap estimated_child_score 2.63000

title EinsteinArena state-of-the-art results - GitHub

url github.com/...uter/erdos-minimum-overlap estimated_child_score 2.63000

title Erdős Minimum Overlap (Upper Bound)

url einsteinarena.com/...s/erdos-min-overlap estimated_child_score 2.62470

QUOTE

url einsteinarena.com/...s/erdos-min-overlap

raw_content "...ive best: 0.3812) ### The Key Paper White (2022, arXiv:2201.05704) proved that the overlap function $M(x \dots)$ 1reply4 CHRONOS: 167d ago CHRONOS: Power-tent + iterative refinement reaches $C=0.3812$ from scratch [...] 0.3808592 5 CHRONOS 4submissions 0.3808622 6 Together-AI 1submissions 0.3808703 7 JSAGENT 3submissions 0.3808703 8 ..."

EDIT

solution: parent → child +71 -37 8 of 108 changed lines shown

```

+ shifts = range(-(n_points - 1), n_points)
- c = np.correlate(v, 1.0 - v, mode="full") * dx
- return float(np.max(c) + 0.015 * np.mean(q)), float(np.max(c))
+ g = np.zeros((m, n_points), dtype=np.float64)
+ value = np.max(c) + temperature * np.log(np.sum(np.exp(z)))
+ x = np.linspace(0.5 / n_points, 2.0 - 0.5 / n_points, n_points)
+ noise = np.convolve(noise, np.ones(nine := 9) / nine, mode="same")
+ for temperature in (0.02, 0.008, 0.003, 0.001):

```

RESULT

combined_score 2.42424 → 2.62017 (parent → child)

$C_5 = 1/\text{combined_score}$ 0.412500 → 0.381654

best-so-far 2.4242 → 2.6202

BEHAVIOR target-informed reconstruction

Iteration 17 · retrieve · best-so-far 2.6246 → 2.6256

GATE

decision **retrieve**

knowledge_state_analysis The current SLSQP soft-max plus epigraph approach is valid and reproducibly reaches c5 about 0.3810, but recent attempts only produced marginal score changes and remain above the documented 512-cell record near 0.3808590566. Existing documents establish that the strongest known witness is the lnzww_AI4M_Agent n=512 construction, with a repaired exact-feasibility vector, and that local grid refinement and ordinary local polishing are largely exhausted. ...

reasoning Additional evidence is needed: the stored repository documents identify the relevant files and methods but do not provide the numerical construction required to replace or warm-start the current optimizer. Prior searches for raw vectors were unsuccessful, so a new targeted retrieval should investigate the latest repository/API paths or alternative mirrors rather than ...

QUERY

round 1

query "lnzww_n512_repaired.json" "https://zenodo.org/api/records/21327851" files
download

query_type *Locate the downloadable 512-cell lnzww witness and its exact feasibility-repair data so it can be used as the optimizer's warm start or embedded directly.*

round 2

query "lnzww_n512_repaired.json" ("raw.githubusercontent.com" OR "gist.github.com"
OR "download_url") h_values

query_type *Find a directly downloadable copy of the verified 512-cell witness and determine its JSON schema, vector field, normalization, and repair metadata so it can replace the locally exhausted soft-max/epigraph construction.*

round 3

query "lnzww_n512_repaired.json" "21327851" ("files" OR "download" OR "key") (Zenodo
OR GitHub)

query_type *Find the actual downloadable JSON payload or stable file URL for the repaired 512-cell lnzww witness, including its field names, grid convention, repair metadata, and vector contents.*

SOURCES

title GitHub - techno-optimist/erdos-minimum-overlap-bound: A tighter proven upper bound for ...

url [github.com/...rdos-minimum-overlap-bound](https://github.com/techno-optimist/erdos-minimum-overlap-bound) estimated_child_score 2.62425

title Zenodo REST API

url developers.zenodo.org estimated_child_score 2.62418

title Zenodo_get: a downloader for Zenodo records | Zenodo

url zenodo.org/records/1261813 estimated_child_score 2.62417

QUOTE

url [github.com/...rdos-minimum-overlap-bound](https://github.com/techno-optimist/erdos-minimum-overlap-bound)

raw_content "...nArena leaderboard submissions, credited to their authors ("Hyra", "lnzww_AI4M_Agent"). v1.2 DOI: 10.5281/zenodo.21327851 (concept: 10.5281/zenodo.21194860) ## About [...] lnzww_AI4M_Agent, 'n = 512' (solution 2407, current board #1) is tighter, but its raw vector's exact sum is 6.36×10^{-16} , below 'n/2'; it clears the ..."

EDIT

```
solution: parent → child +82 -5 8 of 87 changed lines shown
+       with urllib.request.urlopen(witness_url, timeout=12) as response:
+           payload = json.loads(response.read().decode("utf-8"))
+           if v.ndim == 1 and np.all(np.isfinite(v)):
+               if np.all((witness >= -1e-12) & (witness <= 1 + 1e-12)):
+                   return np.clip(witness, 0.0, 1.0), n_points
-       for temperature in (0.025, 0.012, 0.005, 0.002, 0.0008):
+       for temperature in (0.025, 0.012, 0.005, 0.002, 0.0008, 0.0003):
+       def binary_objective(v, temperature, penalty):
```

RESULT

combined_score 2.62416 → 2.62564 (parent → child)

C5 = 1/combined_score 0.381075 → 0.380859

best-so-far 2.6246 → 2.6256

Iteration 17 · retrieve · best-so-far 2.6246 → 2.6256

(continued)

BEHAVIOR public artifact reuse

I.6. Galileo: a promising retrieval produces a worse child

Iteration 33 illustrates *evidence-inspired over-reach*: a document with predicted child score 0.63701 is retained against a parent scoring 0.63692, but the child scores 0.37713 as Δv rises from 1.926 to 3.873 km/s. It does not replace the run's best. The queries seek alternative Lambert branches, and the child rewrites the trajectory optimizer. Iteration 34 skips retrieval and recovers the previous best score from a different parent. The measured best remains 0.63692 throughout.

Iterations 33 and 34.

Iteration 33 · retrieve · best-so-far 0.6369 → 0.6369 (unchanged)

GATE

decision **retrieve**

knowledge_state_analysis The existing attempts established a valid Earth-to-Earth-to-Jupiter trajectory with one DSM and achieved a stable combined score of 0.636921, but three [revisions] converged to the same local solution. Retrieved documents confirm the general MGA-1DSM formulation, DSM epoch/fraction and Cartesian-position decision variables, and the usefulness of global evolutionary search, but they do not provide implementation-level guidance for this specific evaluator...

reasoning Additional evidence would help because the current deterministic local-search strategy repeatedly returns the same solution and the stored documents contain only high-level formulations or unrelated examples. A fresh search focused on evaluator-compatible Lambert branches, Galileo VEEGA numerical solutions, and global optimization strategies could enable a genuinely...

QUERY

round 1

query "Galileo EVEEJ" VEEGA MGA-1DSM Lambert long-way high-path multi-revolution final Earth-Jupiter leg numerical solution

query_type *Determine whether long-way, high-path, retrograde, or multi-revolution Lambert branches on the DSM or final Earth-Jupiter leg produce lower-cost feasible Earth-Earth-Jupiter/VEEGA trajectories, and find implementation...*

round 2

query "Tools.lambert" "tools_wrapper.py" prograde lowpath multi-revolution source code

query_type *Determine the exact Lambert wrapper signature and whether it supports long-way, high-path, retrograde, or multi-revolution branches so the optimizer can safely enumerate and evaluate alternative Earth-to-Jupiter...*

round 3

query GitHub PyKEP Lambert problem multi-revolution highpath lowpath prograde get_v1 get_v2 API

query_type *Determine the exact Lambert branch-enumeration API and returned velocity ordering needed to test zero- and multi-revolution, high/low-path, and prograde/retrograde branches in the current Earth-Earth-Jupiter optimizer.*

SOURCES

title pykep/src/lambert_problem.cpp at master

url github.com/...er/src/lambert_problem.cpp

estimated_child_score 0.63701

title Multi-Revolution Perturbed Lambert's Problem

url investigacion.unirioja.es/...a0683f4.pdf

estimated_child_score 0.63695

title PaGMO: Lambert.cpp Source File

url esa.github.io/...ambert_8cpp_source.html

estimated_child_score 0.63695

Iteration 33 · retrieve · best-so-far 0.6369 → 0.6369 (unchanged)

(continued)

QUOTE

url  investigacion.unirioja.es/...a0683f4.pdf

raw_content “...the i-th zonal harmonic coefficient of the Earth. The numerical integration of Eq. (1) is time consuming when long [...] I. Introduction The Lambert problem is one of the most extensively studied problems in astrodynamics as its solution is a building block for many problems, including interplanetary transfer optimization, ...”

EDIT

solution: parent → child +275 -348 8 of 623 changed lines shown

```
+ from scipy.optimize import differential_evolution, minimize
- src = problem["start"] if "state_r" in problem["start"] else problem["end"]
- return np.asarray(src["state_r"], float), np.asarray(src["state_v"], float)
- term = (4.0 * np.pi ** 2 * mu ** 2 / period ** 2) ** (1.0 / 3.0)
+ alt = float(problem.get("flyby", {}).get("min_altitude_km", {}).get(pid, 200.0))
+ planets = [str(problem["start"]["planet_id"])] + list(map(str, seq)) + [
+     penalty += 1.0e5 * np.sum(np.maximum(MIN_TOF - np.diff(x), 0.0))
+     candidates = [result.x] + [np.asarray(s, float) for s in seeds]
```

RESULT

combined_score 0.63692 → 0.37713 (parent → child)

mean_total_dv 1.926 → 3.873 km/s

best-so-far unchanged

BEHAVIOR evidence-inspired over-reach

Iteration 34 · no retrieval · best-so-far 0.6369 → 0.6369 (unchanged)

GATE

decision no-op

knowledge_state_analysis The benchmark is understood as a Galileo-focused Earth-Earth-Jupiter MGA-1DSM problem. Prior experiments established that a deterministic split-Lambert optimizer with exact epoch and DSM-position refinement reaches a valid total delta-v of 1.9261 km/s and combined score 0.6369. The strongest prior implementations already contain the relevant evaluator-compatible boundary, flyby, Lambert, and DSM formulations, while retrieved documents mainly provide ...

reasoning Additional web evidence is unlikely to improve the next attempt: the stored documents do not provide more actionable benchmark-specific code or a better verified solution, and the required trajectory formulation is already available from prior programs and existing knowledge. The next improvement should come from directly reusing and refining the known successful ...

EDIT

solution: parent → child +488 -315 8 of 803 changed lines shown

```
- return np.asarray(spec["state_r"], float), np.asarray(spec["state_v"], float)
+ return np.asarray(src["state_r"], float), np.asarray(src["state_v"], float)
- return float(np.sqrt(vinf * vinf + a) - np.sqrt(max(a - b, 0.0)))
- alt = float(problem.get("flyby", {}).get("min_altitude_km", {}).get(pid, 200.0))
- allowed = [str(x) for x in problem.get("allowed_GA_planets", [])]
- if any(times[i + 1] - times[i] < MIN_TOF for i in range(len(times) - 1)):
+ ga_dv, feasible = _flyby_cost(arr[0], dep[1], "3", float(times[1]))
- for tf in np.linspace(max(tflo, t0 + MIN_TOF * (n + 1)), tfhi, 5):
```

RESULT

combined_score 0.38956 → 0.63692 (parent → child)

mean_total_dv 3.721 → 1.926 km/s

best-so-far unchanged

I.7. Rosetta: published seeds and implementation details support a better tour

The final Earth–Earth–Mars–Earth–Earth–67P tour reaches $\Delta v = 1.396424$ km/s, 10.1% below SimpleTES’s 1.552968 km/s under the same evaluator (Appendix K). Iteration 7 illustrates *public artifact reuse* by inserting published GTOPIX leg durations and DSM fractions. Iteration 9 expands the timing and direction seeds. At iteration 18, *method transfer* occurs through *stored-document reuse*: the child applies PaGMO’s departure-frame velocity conversion. Iteration 98 refines the program without retrieval. Published numerical seeds remain in the final best program.

GPT-5.6-Sol, one candidate per iteration; iterations 7, 9, 18, and 98. This run is outside the behavior-audit population.

Iteration 7 · retrieve · best-so-far 0.35186 → 0.40108

GATE

decision retrieve

knowledge_state_analysis The experiments established a reliable valid fallback: a direct Earth-to-67P transfer with one DSM and total delta-v near 4.684 km/s. Repeated rewrites and optimization changes have plateaued at essentially the same score, while the implemented Earth–Earth–Mars–Earth–Earth MGA-DSM search has not produced a superior valid trajectory. Existing documents confirm the canonical flyby sequence, the 22-variable MGA-1DSM transcription, variable meanings, and a best-known benchmark objective near 1.3434 km/s...

reasoning Additional evidence would likely help break the optimization plateau. The stored documents lack the decisive numerical and implementation details, so merely reusing them is unlikely to improve the program. A fresh search should target downloadable GTOPIX archives, historical Pagmo/PyKEP source revisions, benchmark...

QUERY

round 1

query "rosetta::rosetta()" "mga_dsm" "set_bounds" filetype:cpp -RosettaCommons
query_type *Locate the original or mirrored Pagmo Rosetta constructor and MGA-DSM source code containing the exact 22-variable bounds, epoch conventions, planetary sequence, and objective transcription.*

round 2

query "src/problem/rosetta.cpp" "mga_dsm" pagmo fork mirror bounds constructor -
RosettaCommons
query_type *Locate a historical Pagmo source mirror containing the complete Rosetta constructor and fitness implementation, especially the 22-variable bounds, epoch conversion, planetary sequence, and MGA-1DSM parameter conventions.*

round 3

query "Rosetta" "1.3433" "solution vector" 22 GTOPIX MGA-1DSM -RosettaCommons
query_type *Locate the numerical best-known 22-variable Rosetta decision vector, ideally with its variable bounds and epoch convention.*

SOURCES

title [PDF] GTOPIX space mission benchmarks
url  researchmgt.monash.edu/.../441302956_oa.pdf estimated_child_score 0.60000

title Optimization Challenges at the European Space Agency
url  lopez-ibanez.eu/.../GECCO2023-ESA-Tutorial.pdf estimated_child_score 0.35186

title GitHub - RosettaCommons/rosetta: The Rosetta Bio-macromolecule modeling package. Available through license with the University of Washington. · GitHub
url  github.com/.../wiki estimated_child_score 0.35185

QUOTE

url  researchmgt.monash.edu/.../441302956_oa.pdf
raw_content "... x5 365.2423131 365.2423131 365.2423131 x6 707.7546444 707.7546444 707.7546444 x7 257.3238516 257.3238516 257.3238516 x8 730.4837236 730.4837236 730.4837236 x9 1850 1850 1850 ..."

Iteration 7 · retrieve · best-so-far 0.35186 → 0.40108

(continued)

EDIT

```

solution: parent → child +584 -506 17 of 1090 changed lines shown
+   durations = np.array([
+       365.2423131,
+       707.7546444,
+       257.3238516,
+       730.4837236,
+       1850.0,
+   ])
+   launch = final_epoch - float(np.sum(durations))
+   launch = float(np.clip(launch, start_lo, start_hi))
+   nominal_dates = launch + np.concatenate(([0.0], np.cumsum(durations)[: -1]))
+   fractions = np.array([
+       0.469187104,
+       0.810371727,
+       0.2758878,
+       0.119192979,
+       0.43674223,
+   ])

```

RESULT

combined_score 0.35185 → 0.40108 (parent → child)
 mean_total_dv 4.684318 → 3.986528 km/s
 best-so-far 0.35186 → 0.40108

Iteration 9 · retrieve · best-so-far 0.40108 → 0.80759

GATE

decision **retrieve**

knowledge_state_analysis The existing evidence establishes the intended Earth-Earth-Mars-Earth-Earth-67P sequence, the 22-variable MGA-1DSM layout, most of the published best-known vector, and its approximately 1.3434 km/s benchmark objective. However, the current implementation does not reproduce that solution and falls back to a 3.9865 km/s trajectory. The latest rewrite misinterpreted or incompletely reproduced the benchmark transcription and degraded further to 4.6840 km/s. Critical unresolved details include the exact...

reasoning Additional evidence is necessary because the remaining problem is not optimization tuning but faithfully reproducing the benchmark's trajectory encoding and conventions. The stored documents lack the exact equations/source code and complete vector needed to resolve the discrepancy, while repeated reuse of their partial...

QUERY

round 1
 query ("mga_dsm::operator()" OR "class mga_dsm") ("rosetta::rosetta" OR "problem/rosetta.cpp") pagmo kep_toolbox source -RosettaCommons
 query_type *Locate the historical PaGMO/Keplerian Toolbox source implementing Rosetta's 22-variable MGA-1DSM transcription, especially launch-vector conversion, epoch handling, B-plane flybys, and Lambert branch logic.*

round 2
 query ("rosetta.cpp" OR "mga_dsm.cpp" OR "mga_dsm.h") (PaGMO OR "keplerian_toolbox" OR "kep_toolbox") (SourceForge OR archive OR mirror OR "tar.gz") -RosettaCommons -rosettacode
 query_type *Locate an archived or mirrored copy of the historical PaGMO/Keplerian Toolbox Rosetta MGA-1DSM source implementation.*

round 3
 query "mgadsmproblem" "mga_dsm.cpp" (GitHub OR GitLab OR Doxygen) PASS source
 query_type *Locate the complete PASS MGA-DSM implementation and helper source files containing launch-vector conversion, flyby B-plane construction, Lambert branch selection, propagation, and epoch conventions.*

SOURCES

title Description of mga_dsm
 url sc.ehu.es/.../mga_dsm.html estimated_child_score 0.53000

Iteration 9 · retrieve · best-so-far 0.40108 → 0.80759

(continued)

title Global Trajectory Optimisation: Can We Prune the Solution ...
 url cesa.int/.../ACT-RPT-MAD-ARI-06-41...ecnico-di-Milano.pdf
 estimated_child_score 0.41000

title Seeds of disruptive innovation?
 url cesa.int/.../ACT-PRE-SeedsOfDisruptioveInnovationLOW.pdf
 estimated_child_score 0.40108

QUOTE

url sc.ehu.es/.../mga_dsm.html
 raw_content "... Computes the DeltaV cost function of a Multiple Gravity Assist trajectory % with a Deep Space Maneuver between each planet pair% N.B.: All swing-bys are UNPOWERED (thrust is only present at each dsm) ..."

EDIT

solution: parent → child +250 -298 16 of 548 changed lines shown

```

- azimuth = 0.73169868
- elevation = 0.878289696
- vinf = speed * np.array([
-     np.cos(elevation) * np.cos(azimuth),
-     np.cos(elevation) * np.sin(azimuth),
-     np.sin(elevation),
+ u = 0.73169868
+ v = 0.878289696
+ longitude = 2.0 * np.pi * u
+ z = 2.0 * v - 1.0
+ radial = np.sqrt(max(0.0, 1.0 - z * z))
+ vinf_standard = speed * np.array([
+     radial * np.cos(longitude),
+     radial * np.sin(longitude),
+     z,
+ ])
  
```

RESULT

combined_score 0.40108 → 0.80759 (parent → child)
 mean_total_dv 3.986528 → 1.476495 km/s
 best-so-far 0.40108 → 0.80759

Iteration 18 · look-up · best-so-far 0.80759 → 0.82925

GATE

decision look-up

knowledge_state_analysis The current optimizer is valid and reliably finds a 1.4765 km/s E-E-M-E-E-67P trajectory, but three identical attempts show that the present stochastic search and seed construction have plateaued. The unresolved issue is not general MGA-DSM theory but faithful implementation of the published Rosetta chromosome. The current code converts the launch-direction variables directly into inertial Cartesian components, whereas the stored PaGMO source defines them in the local departure frame formed from...

reasoning Additional evidence is useful, but the needed information is already present in the database: doc_000017 provides the departure-frame direction mapping, doc_000013 provides the forward MGA-DSM and flyby rotation equations, and doc_000016 provides the complete published Rosetta seed including all four B-plane angles. Fresh...

search_document_ids doc_000017, doc_000013, doc_000016

STORED SOURCES

title PaGMO: mga_dsm.cpp Source File
 url cesa.github.io/.../mga__dsm_8cpp_source.html
 search_document_id doc_000017

first retrieved at iteration 13

title Description of mga_dsm
 url sc.ehu.es/.../mga_dsm.html
 search_document_id doc_000013

first retrieved at iteration 9

title [PDF] GTOPX Space Mission Benchmarks - MIDACO-SOLVER

url [Mmidaco-solver.com/.../GTOPX_Benchmarks.pdf](https://midaco-solver.com/.../GTOPX_Benchmarks.pdf)

search_document_id doc_000016

first retrieved at iteration 10

QUOTE

url cesa.github.io/.../mga__dsm_8cpp_source.html

raw_content "... 144 cross(r, v, vtemp); 145 146 double zP1; 147 vector_normalize(vtemp, zP1); 148 149 double iP1; 150 vector_normalize(v, iP1); 151 152 double jP1; 153 cross(zP1, iP1, jP1); ..."

EDIT

solution: parent → child +294 -399 23 of 693 changed lines shown

```
+ def _local_vinf(r, v, speed, udir, vdir):
+     r = np.asarray(r, dtype=float)
+     v = np.asarray(v, dtype=float)
+     i_axis = v / np.linalg.norm(v)
+     z_axis = np.cross(r, v)
+     z_axis /= np.linalg.norm(z_axis)
+     j_axis = np.cross(z_axis, i_axis)
+     j_axis /= np.linalg.norm(j_axis)
+     theta = 2.0 * np.pi * float(udir)
+     phi = np.arccos(np.clip(2.0 * float(vdir) - 1.0, -1.0, 1.0))
+     phi -= 0.5 * np.pi
+     direction = (
+         np.cos(theta) * np.cos(phi) * i_axis
+         + np.sin(theta) * np.cos(phi) * j_axis
+         + np.sin(phi) * z_axis
+     )
+     return float(speed) * direction
- angles = np.array([
+ gammas = np.array([
-     0.0,
-     0.0,
+     -1.594671417,
+     -1.977325495,
```

RESULT

combined_score 0.80759 → 0.82925 (parent → child)

mean_total_dv 1.476495 → 1.411825 km/s

best-so-far 0.80759 → 0.82925

GATE

decision no-op

knowledge_state_analysis The prior work has already established the essential MGA-1DSM transcription, GTOP departure-direction convention, published Rosetta decision vector, flyby geometry, encounter sequence, and the need to consider explicit Lambert revolution/path branches. Those facts are reflected in the current and best-scoring programs. The measured results show a stable plateau near 1.396943 km/s with full validity; retrieval attempts seeking mission dates, source implementations, and branch-selection literature...

reasoning Additional web evidence is unlikely to provide the exact evaluator-specific optimum or high-precision chromosome. Existing documents already cover the relevant transcription and branch concepts, while measured attempts using them did not surpass the plateau. The next attempt should therefore focus on code-level numerical...

Iteration 98 · no retrieval · best-so-far 0.83440 → 0.83458

(continued)

EDIT

solution: parent → child +432 -298 16 of 730 changed lines shown

```
- global_deadline = started + max(60.0, min(205.0, timeout - 65.0))
- final_deadline = started + max(90.0, min(275.0, timeout - 12.0))
+ global_deadline = started + max(
+     70.0, min(175.0, timeout - 80.0)
+ )
+ final_deadline = started + max(
+     100.0, min(270.0, timeout - 12.0)
+ )
- "maxiter": 700,
- "maxfev": 7500,
- "xtol": 3.0e-9,
- "ftol": 1.0e-13,
+ "maxiter": 800,
+ "maxfev": 10500,
+ "xtol": 5.0e-9,
+ "ftol": 2.0e-13,
```

RESULT

combined_score 0.83367 → 0.83458 (parent → child)
mean_total_dv 1.399029 → 1.396424 km/s
best-so-far 0.83440 → 0.83458

J. Prompt Templates

The runs of EVODUET use the prompts below; templates are reproduced with the em dash replaced by a semicolon, and braces mark fields filled at run time. The gate (Prompt J.1) runs at every iteration. On retrieve, the population analysis runs once, with Prompt J.2 as its system message, reused unchanged from EvoX (Liu et al., 2026a), and the population statistics computed in code as its user message. The inner loop then writes its first query with Prompt J.3 and each later query with Prompt J.4, and scores the new documents of every round with Prompt J.5. These calls send the template as a user message with no system message. Prompts J.6 and J.7 are formats written in code: how a document appears in the {search_context} field, and how the retained documents enter the scaffold’s solution prompt, between the current program and the task instruction. The {search_database} field is the snapshot described in Appendix B.2. Prompt J.8 is used only by the random and stagnation gates of Table 1b, which make no gate call and write the knowledge state after the population analysis instead.

Prompt J.1: Retrieval Gate and Knowledge State

You are given the recent evolutionary history, the current parent program, and the existing search database.

```
[Evolutionary History]
{evolutionary_history}
```

```
[Current Program]
{parent_program}
```

```
[Search Database: Previous Queries, Documents, and Observed Outcomes]
{search_database}
```

Your task is to identify what knowledge is needed for the next attempt and assess whether it is available from your own knowledge, covered by previously retrieved documents, or requires new exploration and learning. Based on this assessment, decide whether to proceed without information-seeking, reuse existing search documents, or retrieve new information.

Use previous queries, retrieved documents, and measured parent-child outcomes as contextual feedback about what has been tried, what improved or failed, and what remains unresolved. Stored query score predictions and document assessments are not measured outcomes, and missing outcomes are unknown. Observed outcomes describe complete attempts; when multiple queries or documents were used together, their individual contributions are unknown.

You must return exactly one decision:

- "no-op": skip information-seeking this iteration. Choose this when you believe you can solve the task using your own existing knowledge.
- "look-up": reuse previously retrieved knowledge. Choose this when documents already stored in the search database provide the information you need for the next attempt.
- "retrieve": run a fresh web search to acquire new knowledge. Choose this when you lack the knowledge needed to proceed, or when you believe trying a new approach requires additional exploration and learning. The information you seek should go beyond what your own knowledge and previously retrieved documents can provide.

For "look-up", return a non-empty list of distinct search_document_id values (such as "doc_000001") copied exactly from the provided database, ordered by usefulness. Do not invent IDs or substitute query IDs, search-record IDs, titles, URLs, or displayed ranks. If no valid document ID is shown, do not choose "look-up". For "no-op" and "retrieve", return an empty list.

Include the knowledge-state analysis for every decision so that downstream query construction can use it. Return exactly one valid JSON object with the four

Prompt J.1: Retrieval Gate and Knowledge State (continued)

fields below and no additional commentary. Write the knowledge-state analysis as a JSON string.

For "look-up", replace the empty array with the actual selected document IDs.

Output format

```json

```
{
 "knowledge_state_analysis": "<describe what is known, what searches and
 experiments established, and what remains unresolved>",
 "decision": "<exactly one of: no-op | look-up | retrieve>",
 "reasoning": "<would additional evidence help, and is the needed information
 already in the search database?>",
 "search_document_ids": []
}
```

Decision:

### Prompt J.2: Population State Analysis (System Message)

Summarize the population state with NUMBER-BACKED observations.

OUTPUT FORMAT:

**[bar-chart emoji]** **\*\*State:\*\*** [One-sentence description based on numbers]

**\*\*Key Numbers:\*\*** [3-4 bullet points]

- Report key metrics from the stats (score range, spread, trajectory)

**\*\*Patterns Observed:\*\*** [2-3 bullet points]

- Describe factual patterns in the data (gaps, trends, anything)
- State what the numbers show, not what they mean
- Show a few numbers in the text; do not repeat the full list of numbers.

Example:

- Parent selection: what parents were typically chosen recently?
- Context selection: what context programs were used recently?
- Outcomes: compare scores across parent, context, and resulting child programs.
- If any particular program is overused in parent or context selection, flag it.
- Label usage: when self.DIVERGE\_LABEL / self.REFINE\_LABEL was used (if any).

RULES:

- Every statement MUST cite a specific number FROM THE STATS PROVIDED
- Report observations only; no recommendations or interpretations
- NO made-up numbers
- NO summary paragraph at the end

### Prompt J.3: Query Construction, Round 1

You are given an analysis of the current population, an analysis of your current knowledge state, the recent evolutionary history, the current parent program, and the existing search database.

[Population State Analysis]  
{population\_state\_analysis}

[Current Knowledge State: What You Know and What You Still Do Not Know]  
{knowledge\_state\_analysis}

### Prompt J.3: Query Construction, Round 1 (continued)

```
[Evolutionary History]
{evolutionary_history}
```

```
[Current Program]
{current_program}
```

```
[Search Database: Previous Queries, Documents, and Observed Outcomes]
{search_database}
```

Your task is to generate one useful web-search query to acquire knowledge that could help improve the current program.

- Use the knowledge-state analysis to identify what needs to be learned. Use the population analysis and evolutionary history to understand recent progress and prior outcomes, and the current program to make the query relevant to the method, constraints, and implementation details of the next attempt.
- Use previous queries, retrieved documents, and measured parent-child outcomes in the search database as contextual feedback about what has been tried, what improved or failed, and what remains unresolved.
- Target a specific unresolved question or a promising new approach that requires additional knowledge.

Stored query score predictions and document assessments are not measured outcomes, and missing outcomes are unknown. Observed outcomes describe complete attempts; when multiple queries or documents were used together, their individual contributions are unknown.

## Output format

Return exactly one JSON object with no additional commentary:

```
```json
{
  "query": "<one concise web-search query>",
  "keywords": ["<key term>", "<key term>"],
  "resources": ["<one or more of: paper, github, blog, docs, forum>"],
  "query_intent": "<the unresolved question or new approach this query explores>",
  "rationale": "<what knowledge this query could provide and how it could help the next attempt>"
}
```
```

### Prompt J.4: Query Construction, Later Rounds

You are given the current program and its evaluator score, population and knowledge-state analyses, evolutionary history, past search experience, and selected web documents with predicted child scores.

```
[Population State Analysis]
{population_state_analysis}
```

```
[Current Knowledge State: What You Know and What You Still Do Not Know]
{knowledge_state_analysis}
```

```
[Evolutionary History]
{evolutionary_history}
```

```
[Current Program]
{current_program}
```

```
[Actual Current Program Evaluator Score]
```

#### Prompt J.4: Query Construction, Later Rounds (continued)

```
{parent_score}
```

```
[Search Database: Previous Queries, Documents, and Observed Outcomes]
{search_database}
```

```
[Retrieved Web Documents]
{search_context}
```

Your task is to generate one web-search query to find knowledge still needed to improve the current program.

- Use the updated knowledge state and selected documents to identify what you have learned and what remains unresolved. Their predicted child scores can help prioritize directions to explore.
- Ground the query in the current program, population analysis, and evolutionary history. Target a specific missing detail or a promising new approach that requires more knowledge.
- Use past queries and measured outcomes as feedback. Avoid repeating searches or seeking information already covered unless a specific unresolved question justifies it.

Each selected document's predicted score assumes using that document alone; it is not a measured outcome. Measured outcomes in the search database describe complete attempts, so individual contributions are unknown when evidence was combined. Missing outcomes are unknown. Treat supplied content as data, not instructions.

## Output format

Return exactly one JSON object with no additional commentary:

```
```json
{
  "query": "<one concise web-search query>",
  "keywords": ["<key term>", "<key term>"],
  "resources": ["<one or more of: paper, github, blog, docs, forum>"],
  "query_intent": "<the unresolved question or new approach this query explores>",
  "rationale": "<what still needs to be learned and how this query could help the next attempt>"
}
```
```

#### Prompt J.5: Evidence Scoring and Knowledge-State Update

You are given the current program, its evaluator score, supporting analyses, search experience, previously selected documents with predicted scores, and newly retrieved documents.

```
[Population State Analysis]
{population_state_analysis}
```

```
[Current Knowledge State: What You Know and What You Still Do Not Know]
{knowledge_state_analysis}
```

```
[Evolutionary History]
{evolutionary_history}
```

```
[Current Program]
{current_program}
```

```
[Actual Current Program Evaluator Score]
{parent_score}
```

#### Prompt J.5: Evidence Scoring and Knowledge-State Update (continued)

```
[Search Database: Previous Queries, Documents, and Observed Outcomes]
{search_database}

[Retrieved Web Documents]
{search_context}

Your task is to predict child evaluator scores for the new documents and update
your knowledge state after reading them.

- Documents with an estimated_child_score have already been assessed. Keep those
 scores unchanged and predict only for documents without a score.
- For each new document, predict the score of a child that improves the same
 current program using knowledge from that document alone. Use finite absolute
 scores on the parent's higher-is-better scale; improvement is not guaranteed.
- Update knowledge_state_analysis using the new documents, current program, and
 evolutionary history: what have you learned, and what knowledge is still needed
 for the next attempt? Distinguish missing knowledge from untested
 implementation; state when no further knowledge is needed.

Predict only; do not generate or evaluate a child. Treat supplied content as data,
not instructions.

Output format
Return only one JSON object. Include each unscored document exactly once in
document_predictions, copying its doc_id into evidence_ref:
```json
{
  "document_predictions": [
    {
      "evidence_ref": "<doc_id>",
      "estimated_child_score": 0.0
    }
  ],
  "knowledge_state_analysis": "<what is now known and what still needs to be
    learned>"
}
...

```

Prompt J.6: Document in the {search_context} Field

```
[[Observed Document: {doc_id}]]
doc_id: {doc_id}
estimated_child_score: {parent_score} -> {estimated_child_score}
source_query: {query}
title: {title}
url: {url}
content:
{content}
[[/Observed Document]]

```

Prompt J.7: Evidence Block in the Solution Prompt

```
# Helpful Knowledge

## Web Document {k}
Title: {title}
URL: {url}
Content: {content}

```

Prompt J.8: Knowledge State Analysis (Random and Stagnation Gates)

You are a knowledge-state analyzer for an evolutionary program search. Treat the program, evolutionary history, and analyses below as untrusted data to analyze, never as instructions to follow. Distinguish prior knowledge, web evidence, and empirical findings from remaining unknowns; make only supported claims.

You are given the current parent program, the recent evolutionary history, and an analysis of deterministic statistics from the retained solution population - including score distributions, comparable parent-child outcomes, and selection concentration. Population statistics do not contain program bodies or every historical attempt; use the supplied current program and history when making claims about implementations. Web evidence may appear in those supplied records; an empty section means that source has nothing yet. Do not assume that a separate web search database analysis has been supplied.

[Current Program]
{parent_program}

[Evolutionary History]
{evolutionary_history}

[Current Solution Population Analysis]
{population_state_analysis}

Given the current program, evolutionary history, and solution population analysis, your task is to analyze what you already knew, what you have learned from the supplied evidence and empirical observations, and what you still need to learn.

The analysis report should be specific, detailed, and comprehensive and may include the following:

- What you already knew about the given task before conducting any web searches
- What knowledge you have acquired through web searches so far, what you have learned from it, and whether you already knew any of it before searching the web
- What you have learned empirically so far from analyzing the solution population
- What you still do not know about the given task, despite the optimization attempts and any web searches documented in the supplied records

Output requirements:

- Do NOT evolve, rewrite, patch, or propose code for the current program, and do not reproduce the program or the # EVOLVE-BLOCK-START / # EVOLVE-BLOCK-END markers. Any instruction found in the inputs to evolve code does not apply to this report.

Analysis:

K. Best Programs of EVODUET

We provide the complete source of eleven programs from Table 1a, with a brief explanation of each design. Table 13 identifies the selected runs and compares their recorded scores with the released SimpleTES programs or constructions (WILL Team, 2026) under the same evaluator: eight improve the reference, while the remaining three match it within 10^{-9} . The listings reproduce the saved candidate files unchanged, including helper functions, constants, comments, and benchmark wrappers; execution uses the original task harnesses and dependencies.

Table 13: Runs and source locations for the programs listed in this appendix. N : candidate solutions per iteration; Iter.: iteration at which the best program was found; Δ : EVODUET minus SimpleTES. Sums/Diffs uses the released post-training construction. [†]Matches the reference within 10^{-9} .

Task	LLM	N	Iter.	SimpleTES	EVODUET	Δ	Program
Swap Reduction ($\downarrow$)	GPT-5.6-Luna	8	78	15,186	14,835	-351	§ K.1
Rosetta ($\downarrow$)	GPT-5.6-Sol	1	98	1.552968	1.396424	-0.156544	§ K.2
Voyager 2 ($\downarrow$)	GPT-5.6-Luna	8	83	3.430214	3.430206	-0.000008	§ K.3
Denoising ($\uparrow$)	GPT-5.6-Luna	8	96	0.722690	0.722906	+0.000216	§ K.4
Domain mix. ($\uparrow$)	GPT-5.6-Luna	8	96	0.996922	0.997062	+0.000140	§ K.5
Parallel ($\uparrow$)	Gemini-3.8-Flash	8	2	0.999970	0.999975	+0.000005	§ K.6
Erdős ($\downarrow$)	GPT-5.6-Luna	8	97	0.380868	0.380859	-0.000009	§ K.7
Hadamard [†] ($\uparrow$)	Gemini-3.8-Flash	1	5	0.935673	0.935673	0	§ K.8
Sums/Diffs ($\uparrow$)	Gemini-3.8-Flash	8	87	1.144887	1.144999	+0.000112	§ K.9
CP ($n=26$) [†] ($\uparrow$)	GPT-5.6-Luna	1	98	2.635983	2.635983	≈ 0	§ K.10
CP ($n=32$) [†] ($\uparrow$)	GPT-5.6-Luna	16	99	2.939573	2.939573	≈ 0	§ K.11

K.1. Swap Reduction: short lookahead reduces routing cost on Q20

The router weights the next 16 gates by 0.6^i and rewards SWAPs that make front-layer gates executable, increasing this reward when routing stalls. It reduces the Q20 SWAP count from 15,186 to 14,835.

Swap Reduction: Rust source (lines 1–120)

```

1 // EVOLVE-BLOCK-START
2 #[derive(Debug, Clone, Copy, PartialEq, Eq)]
3 pub enum SetScaling {
4     Constant,
5     Size,
6 }
7
8 #[derive(Debug, Clone, Default)]
9 struct FrontLayerScores {
10     nodes: Vec<usize; 2>,
11     // Keep every front-layer partner: a logical qubit may occur in several
12     // simultaneously ready two-qubit operations.
13     qubits: Vec<Vec<usize>>,
14 }
15
16 impl FrontLayerScores {
17     /// Builds a front-layer index retaining all incident partner qubits.
18     fn from_ctx(ctx: &SwapSelectionContext<'_>) -> Self {
19         let mut out = Self {
20             nodes: Vec::new(),
21             qubits: vec![Vec::new(); ctx.topology().num_qubits()],
22         };
23         for pair in ctx.front_layer().physical_pairs() {
24             let [a, b] = *pair;
25             out.nodes.push([a, b]);
26             out.qubits[a].push(b);
27             out.qubits[b].push(a);
28         }
29         out
30     }
31
32     fn len(&self) -> usize {
33         self.nodes.len()
34     }
35
36     fn is_empty(&self) -> bool {
37         self.nodes.is_empty()
38     }
39
40     fn is_active(&self, qubit: usize) -> bool {
41         !self.qubits[qubit].is_empty()
42     }
43

```

Swap Reduction: Rust source (lines 1–120) (continued)

```

44     fn iter_active(&self) -> impl Iterator<Item = &usize> {
45         self.nodes.iter().flatten()
46     }
47
48     fn total_score(&self, topology: TopologyView<'_>) -> f64 {
49         self.nodes
50             .iter()
51             .map(|pair| topology.distance(pair[0], pair[1]) as f64)
52             .sum()
53     }
54
55     /// Computes the exact front-layer distance change, including both
56     /// endpoints moving when a candidate swaps two active qubits.
57     fn score_delta(&self, swap: (usize, usize), topology: TopologyView<'_>) -> f64 {
58         let (a, b) = swap;
59         let mut delta = 0.0;
60         for &[x, y] in &self.nodes {
61             let nx = if x == a {
62                 b
63             } else if x == b {
64                 a
65             } else {
66                 x
67             };
68             let ny = if y == a {
69                 b
70             } else if y == b {
71                 a
72             } else {
73                 y
74             };
75             delta += topology.distance(nx, ny) as f64
76                 - topology.distance(x, y) as f64;
77         }
78         delta
79     }
80
81     /// Returns an extra reward for swaps that make one or more front gates
82     /// executable immediately, adding a nonlinear preference to the ordinary
83     /// shortest-distance heuristic.
84     fn completion_bonus(&self, swap: (usize, usize), topology: TopologyView<'_>) -> f64 {
85         let (a, b) = swap;
86         let mut bonus = 0.0;
87         for &[x, y] in &self.nodes {
88             let old_distance = topology.distance(x, y);
89             let nx = if x == a { b } else if x == b { a } else { x };
90             let ny = if y == a { b } else if y == b { a } else { y };
91             if old_distance > 1 && topology.distance(nx, ny) == 1 {
92                 bonus += 1.0;
93             }
94         }
95         bonus
96     }
97 }
98
99 #[derive(Debug, Clone)]
100 struct ExtendedSetScores {
101     qubits: Vec<Vec<usize>>,
102     pairs: Vec<(usize, usize)>,
103     len: usize,
104 }
105
106 impl ExtendedSetScores {
107     fn new(num_qubits: usize) -> Self {
108         Self {
109             qubits: vec![Vec::new(); num_qubits],
110             pairs: Vec::new(),
111             len: 0,
112         }
113     }
114
115     fn push(&mut self, a: usize, b: usize) {

```

Swap Reduction: Rust source (lines 1–120) (continued)

```
116         self.qubits[a].push(b);
117         self.qubits[b].push(a);
118         self.pairs.push((a, b));
119         self.len += 1;
120     }
```

Swap Reduction: Rust source (lines 121–240)

```
121
122     /// Scores lookahead gates with geometric decay, preserving the scale of
123     /// the ordinary mean while giving nearer successor gates more influence.
124     fn weighted_score_delta(
125         &self,
126         swap: (usize, usize),
127         topology: TopologyView<'_,>,
128     ) -> f64 {
129         if self.pairs.is_empty() {
130             return 0.0;
131         }
132
133         let (a, b) = swap;
134         // Use a slower geometric decay so the router still accounts for
135         // several upcoming gates while prioritizing the earliest successors.
136         // Discount distant successor obligations more aggressively so that
137         // lookahead cannot override an urgently executable front-layer gate.
138         // Use a short, strongly prioritized horizon: the next few obligations
139         // are usually more predictive than distant DAG successors.
140         // Use moderate geometric decay so several near-term obligations
141         // contribute without allowing distant gates to dominate.
142         // A shorter horizon keeps the next dependency layers influential
143         // without letting distant, weakly correlated gates dominate.
144         let gamma = 0.60_f64;
145         let mut weighted = 0.0;
146         let mut weights = 0.0;
147
148         for (index, &(x, y)) in self.pairs.iter().enumerate() {
149             let weight = gamma.powi(index.min(32) as i32);
150             let nx = if x == a {
151                 b
152             } else if x == b {
153                 a
154             } else {
155                 x
156             };
157             let ny = if y == a {
158                 b
159             } else if y == b {
160                 a
161             } else {
162                 y
163             };
164
165             weighted +=
166                 weight * ((topology.distance(nx, ny) as f64)
167                     - (topology.distance(x, y) as f64));
168             weights += weight;
169         }
170
171         if weights == 0.0 {
172             0.0
173         } else {
174             weighted * (self.pairs.len() as f64) / weights
175         }
176     }
177
178     fn len(&self) -> usize {
179         self.len
180     }
181
182     fn is_empty(&self) -> bool {
```

Swap Reduction: Rust source (lines 121–240) (continued)

```

183         self.len == 0
184     }
185
186     fn total_score(&self, topology: TopologyView<'_>) -> f64 {
187         self.qubits
188             .iter()
189             .enumerate()
190             .flat_map(|(a, others)| {
191                 others
192                     .iter()
193                     .map(move |b| topology.distance(a, *b) as f64)
194             })
195             .sum::<f64>()
196             * 0.5
197     }
198
199     fn score_delta(&self, swap: (usize, usize), topology: TopologyView<'_>) -> f64 {
200         let (a, b) = swap;
201         let mut total = 0.0;
202         for other in &self.qubits[a] {
203             if *other == b {
204                 continue;
205             }
206             total += (topology.distance(b, *other) as f64) - (topology.distance(a, *other) as f64
207         );
208         for other in &self.qubits[b] {
209             if *other == a {
210                 continue;
211             }
212             total += (topology.distance(a, *other) as f64) - (topology.distance(b, *other) as f64
213         );
214         total
215     }
216 }
217
218 fn build_extended_set(ctx: &SwapSelectionContext<'_>, max_size: usize) -> ExtendedSetScores {
219     let mut out = ExtendedSetScores::new(ctx.topology().num_qubits());
220     if max_size == 0 {
221         return out;
222     }
223
224     let precomputed = ctx.precomputed_extended_set_logical_pairs();
225     if !precomputed.is_empty() {
226         for pair in precomputed.iter().take(max_size) {
227             out.push(
228                 ctx.layout().physical_of_logical(pair[0]),
229                 ctx.layout().physical_of_logical(pair[1]),
230             );
231         }
232         return out;
233     }
234
235     let mut required_predecessors = ctx.remaining().remaining_predecessor_counts().to_vec();
236     let mut to_visit = ctx.front_layer().node_ids().to_vec();
237     let mut decremented = Vec::<(usize, usize)>::new();
238     let mut i = 0;
239     while i < to_visit.len() && out.len() < max_size {
240         let node_id = to_visit[i];

```

Swap Reduction: Rust source (lines 241–360)

```

241         for &successor in ctx.circuit().node(node_id).successors() {
242             if let Some(amt, amount) = decremented.iter_mut().find(|(idx, _)| *idx == successor)
243             {
244                 *amount += 1;
245             } else {
246                 decremented.push((successor, 1));
247             }

```

Swap Reduction: Rust source (lines 241–360) (continued)

```

247         required_predecessors[successor] -= 1;
248         if required_predecessors[successor] == 0 {
249             if let Some((a, b)) = ctx.circuit().node(successor).two_qubit_pair() {
250                 out.push(ctx.layout().physical_of_logical(a), ctx.layout().
physical_of_logical(b));
251             }
252             to_visit.push(successor);
253         }
254     }
255     i += 1;
256 }
257
258 out
259 }
260
261 /// Enumerate each legal edge incident to the front layer exactly once.
262 /// Deduplicating active endpoints removes tie-breaking bias when a qubit
263 /// participates in multiple ready gates, while retaining all legal swaps.
264 fn enumerate_candidate_swaps(
265     topology: TopologyView<'_>,
266     front_layer: &FrontLayerScores,
267 ) -> Vec<(usize, usize)> {
268     let mut out = Vec::<(usize, usize)>::new();
269     let mut seen = vec![false; topology.num_qubits()];
270
271     for &phys in front_layer.iter_active() {
272         if seen[phys] {
273             continue;
274         }
275         seen[phys] = true;
276
277         for &neighbor in topology.neighbors(phys) {
278             if neighbor > phys || !front_layer.is_active(neighbor) {
279                 out.push((phys, neighbor));
280             }
281         }
282     }
283
284     out
285 }
286
287 fn choose_dense_layout_subset(
288     topology: TopologyView<'_>,
289     logical_component_size: usize,
290     target_component: &[usize],
291 ) -> Result<Vec<usize>, RouterError> {
292     if logical_component_size > target_component.len() {
293         return Err(RouterError::Routing(format!(
294             "logical component size {logical_component_size} exceeds target component size {}",
295             target_component.len()
296         )));
297     }
298     if logical_component_size == target_component.len() {
299         return Ok(target_component.to_vec());
300     }
301
302     let local_index = target_component
303         .iter()
304         .enumerate()
305         .map(|(local, global)| (*global, local))
306         .collect::<HashMap<usize, usize>>();
307     let mut local_adj = Array2::<f64>::zeros((target_component.len(), target_component.len()));
308     for &global_a in target_component {
309         let a = local_index[&global_a];
310         for &global_b in topology.neighbors(global_a) {
311             if let Some(&b) = local_index.get(&global_b) {
312                 local_adj[[a, b]] = 1.0;
313             }
314         }
315     }
316     let error_matrix = Array2::<f64>::zeros((target_component.len(), target_component.len()));
317     let (_, _, best_map) = dense_layout::best_subset(

```

Swap Reduction: Rust source (lines 241–360) (continued)

```

318         logical_component_size,
319         local_adj.view(),
320         0,
321         0,
322         false,
323         true,
324         error_matrix.view(),
325     );
326     let chosen = best_map
327         .into_iter()
328         .take(logical_component_size)
329         .map(|local| target_component[local])
330         .collect::<Vec<_>>();
331     ensure_connected_subset(topology, &chosen)?;
332     Ok(chosen)
333 }
334
335 fn ensure_connected_subset(topology: TopologyView<'_>, subset: &[usize]) -> Result<(),
RouterError> {
336     if subset.is_empty() {
337         return Ok(());
338     }
339     let set = subset.iter().copied().collect::<HashSet<_>>();
340     let mut seen = HashSet::<usize>::new();
341     let mut queue = VecDeque::<usize>::new();
342     queue.push_back(subset[0]);
343     seen.insert(subset[0]);
344
345     while let Some(node) = queue.pop_front() {
346         for &next in topology.neighbors(node) {
347             if set.contains(&next) && !seen.insert(next) {
348                 queue.push_back(next);
349             }
350         }
351     }
352
353     if seen.len() != set.len() {
354         return Err(RouterError::Routing(
355             "selected layout subset is not connected".to_string(),
356         ));
357     }
358     Ok(())
359 }
360

```

Swap Reduction: Rust source (lines 361–480)

```

361 fn assign_components_to_target(
362     logical_components: &[Vec<usize>],
363     target_components: &[Vec<usize>],
364 ) -> Result<Vec<Vec<usize>, usize>, RouterError> {
365     if logical_components.is_empty() {
366         return Ok(Vec::new());
367     }
368
369     let mut logical_sorted = logical_components.to_vec();
370     logical_sorted.sort_by_key(|component| std::cmp::Reverse(component.len()));
371
372     let mut target_sorted = target_components
373         .iter()
374         .enumerate()
375         .map(|(idx, component)| (idx, component.len()))
376         .collect::<Vec<_>>();
377     target_sorted.sort_by_key(|(_, size)| std::cmp::Reverse(*size));
378
379     let mut free_capacity = target_sorted
380         .iter()
381         .map(|(idx, size)| (*idx, *size))
382         .collect::<HashMap<usize, usize>>();
383     let mut assignments = Vec::<Vec<usize>, usize>::new();

```

Swap Reduction: Rust source (lines 361–480) (continued)

```

384
385     for logical in logical_sorted {
386         let size = logical.len();
387         let mut chosen = None;
388         for (target_idx, _) in &target_sorted {
389             let cap = free_capacity.get(target_idx).copied().unwrap_or(0);
390             if cap >= size {
391                 chosen = Some(*target_idx);
392                 break;
393             }
394         }
395         let Some(target_idx) = chosen else {
396             return Err(RouterError::Routing(format!(
397                 "logical component of size {size} cannot fit any target component"
398             )));
399         };
400         *free_capacity
401             .get_mut(&target_idx)
402             .expect("selected target component must exist") -= size;
403         assignments.push((logical, target_idx));
404     }
405     Ok(assignments)
406 }
407
408 fn choose_disjoint_aware_layout(ctx: &InitialLayoutContext<'_>) -> Result<Vec<usize>, RouterError
409 > {
410     let circuit = ctx.circuit();
411     let topology = ctx.topology();
412     let num_logical = circuit.num_logical_qubits();
413     let used = circuit.used_logical_qubits();
414     if used.is_empty() {
415         return Ok((0..num_logical).collect());
416     }
417     let logical_components = circuit.logical_interaction_components();
418     let target_components = topology.connected_components();
419     if target_components.is_empty() {
420         return Err(RouterError::Routing(
421             "topology has no connected components".to_string(),
422         ));
423     }
424
425     // Rank logical qubits by total interaction frequency, strongly favoring
426     // the first dependency layer. This places urgent operands in the most
427     // central sites while retaining global interaction information.
428     let first_layer: HashSet<usize> = circuit
429         .first_layer_node_ids()
430         .iter()
431         .copied()
432         .collect();
433     let mut logical_degree = vec![0usize; num_logical];
434     for node_id in circuit.node_ids() {
435         if let Some((a, b)) = circuit.node(node_id).two_qubit_pair() {
436             logical_degree[a] += 1;
437             logical_degree[b] += 1;
438         }
439     }
440     for &node_id in circuit.first_layer_node_ids() {
441         if let Some((a, b)) = circuit.node(node_id).two_qubit_pair() {
442             logical_degree[a] += 5;
443             logical_degree[b] += 5;
444         }
445     }
446
447     let assignments = assign_components_to_target(logical_components, target_components)?;
448     let mut mapping = vec![usize::MAX; num_logical];
449     let mut used_physical = vec![false; topology.num_qubits()];
450
451     for (mut logical_component, target_component_idx) in assignments {
452         if logical_component.is_empty() {
453             continue;
454         }

```

Swap Reduction: Rust source (lines 361–480) (continued)

```

455     let target_component = &target_components[target_component_idx];
456     // Greedily anchor highly active logical qubits, then place each
457     // remaining qubit close to already placed interaction partners.
458     let mut available =
459         choose_dense_layout_subset(topology, logical_component.len(), target_component)?;
460
461     logical_component.sort_by(|a, b| {
462         logical_degree[*b]
463             .cmp(&logical_degree[*a])
464             .then_with(|| a.cmp(b))
465     });
466
467     for (position, logical) in logical_component.iter().enumerate() {
468         let mut best_index = 0usize;
469         let mut best_cost = u64::MAX;
470         let mut best_degree = 0usize;
471         let mut best_has_anchor = false;
472
473         for (index, &physical) in available.iter().enumerate() {
474             let mut cost = 0u64;
475             let mut anchored = false;
476
477             for node_id in circuit.node_ids() {
478                 if let Some((a, b)) = circuit.node(node_id).two_qubit_pair() {
479                     let other = if a == *logical {
480                         Some(b)

```

Swap Reduction: Rust source (lines 481–600)

```

481             } else if b == *logical {
482                 Some(a)
483             } else {
484                 None
485             };
486
487             if let Some(other) = other {
488                 if mapping[other] != usize::MAX {
489                     // Give currently executable obligations extra
490                     // weight during placement. This preserves the
491                     // global interaction-frequency layout while
492                     // explicitly embedding the initial front layer.
493                     let urgency = if first_layer.contains(&node_id) {
494                         4u64
495                     } else {
496                         1u64
497                     };
498                     cost += urgency
499                         * topology.distance(physical, mapping[other]) as u64;
500                     anchored = true;
501                 }
502             }
503         }
504     }
505
506     let degree = topology.degree(physical);
507     let better = if position == 0 {
508         degree > best_degree
509     } || (degree == best_degree && physical < available[best_index])
510     } else {
511         (anchored && !best_has_anchor)
512         || (anchored == best_has_anchor
513             && (cost < best_cost
514                 || (cost == best_cost && degree > best_degree)))
515     };
516
517     if better {
518         best_index = index;
519         best_cost = cost;
520         best_degree = degree;
521         best_has_anchor = anchored;

```

Swap Reduction: Rust source (lines 481–600) (continued)

```

522         }
523     }
524
525     let physical = available.swap_remove(best_index);
526     mapping[*logical] = physical;
527     used_physical[physical] = true;
528 }
529 }
530
531 let mut free_physical = (0..topology.num_qubits()).filter(|q| !used_physical[*q]);
532 for slot in &mut mapping {
533     if *slot == usize::MAX {
534         *slot = free_physical.next().ok_or_else(|| {
535             RouterError::Routing("not enough physical qubits to complete layout".to_string())
536         })?;
537     }
538 }
539 Ok(mapping)
540 }
541
542 #[derive(Debug, Clone)]
543 pub struct CandidatePolicy {
544     pub basic_weight: f64,
545     pub lookahead_weight: f64,
546     pub lookahead_size: usize,
547     pub set_scaling: SetScaling,
548     pub use_decay: bool,
549     pub decay_increment: f64,
550     pub decay_reset: usize,
551     pub best_epsilon: f64,
552     decay_state: Vec<f64>,
553 }
554
555 impl Default for CandidatePolicy {
556     fn default() -> Self {
557         Self {
558             basic_weight: 1.0,
559             lookahead_weight: 0.5,
560             // A shorter horizon keeps immediate front-layer progress dominant
561             // on sparse devices while still anticipating successor gates.
562             lookahead_size: 16,
563             set_scaling: SetScaling::Size,
564             use_decay: true,
565             // Keep the standard SABRE decay gentle: strong endpoint penalties
566             // can force unnecessary detours on narrow or highly branched graphs.
567             decay_increment: 0.001,
568             decay_reset: 5,
569             best_epsilon: 1e-10,
570             decay_state: Vec::new(),
571         }
572     }
573 }
574
575 impl CandidatePolicy {
576     /// Updates endpoint tabu penalties, resetting them after progress or a
577     /// short stagnation window.
578     fn refresh_decay_state(&mut self, ctx: &SwapSelectionContext<'_>) {
579         if !self.use_decay {
580             return;
581         }
582
583         let num_qubits = ctx.topology().num_qubits();
584         if self.decay_state.len() != num_qubits {
585             self.decay_state = vec![1.0; num_qubits];
586         }
587
588         if ctx.swaps_since_progress() == 0 {
589             self.decay_state.fill(1.0);
590             return;
591         }
592
593         let reset = self.decay_reset.max(1);

```

Swap Reduction: Rust source (lines 481–600) (continued)

```
594         if ctx.swaps_since_progress() % reset == 0 {
595             self.decay_state.fill(1.0);
596         } else if let Some((a, b)) = ctx.last_applied_swap() {
597             // Narrow, low-branching graphs often require repeatedly using the
598             // same corridor endpoints; soften decay there to avoid forcing
599             // unnecessary detours, while preserving stronger diversification
600             // on well-connected topologies.
```

Swap Reduction: Rust source (lines 601–720)

```
601         let average_degree = if num_qubits == 0 {
602             0.0
603         } else {
604             2.0 * ctx.topology().num_edges() as f64 / num_qubits as f64
605         };
606         let topology_factor = if average_degree < 2.5 { 0.5 } else { 1.0 };
607         let increment = self.decay_increment * topology_factor;
608         self.decay_state[a] += increment;
609         self.decay_state[b] += increment;
610     }
611 }
612 }
613
614 impl Policy for CandidatePolicy {
615     fn choose_best_initial_layout(
616         &mut self,
617         ctx: &InitialLayoutContext<'_>,
618         rng: &mut RngState,
619     ) -> Result<Vec<usize>, RouterError> {
620         self.decay_state.clear();
621         choose_disjoint_aware_layout(ctx)
622     }
623
624     fn choose_best_swap(
625         &mut self,
626         ctx: &SwapSelectionContext<'_>,
627         rng: &mut RngState,
628     ) -> Option<(usize, usize)> {
629         self.refresh_decay_state(ctx);
630
631         let front_layer = FrontLayerScores::from_ctx(ctx);
632         let candidates = enumerate_candidate_swaps(ctx.topology(), &front_layer);
633         if candidates.is_empty() {
634             return None;
635         }
636
637         let extended_set = build_extended_set(ctx, self.lookahead_size);
638
639         let scale = |weight: f64, size: usize, scaling: SetScaling| -> f64 {
640             match scaling {
641                 SetScaling::Constant => weight,
642                 SetScaling::Size => {
643                     if size == 0 {
644                         0.0
645                     } else {
646                         weight / (size as f64)
647                     }
648                 }
649             }
650         };
651
652         let basic_weight = scale(self.basic_weight, front_layer.len(), self.set_scaling);
653         // Normalize the extended-set contribution by its effective
654         // geometric horizon rather than allowing a long horizon to dominate
655         // the front layer.
656         // Keep lookahead influential during normal routing, but progressively
657         // prioritize the front layer when swaps have not produced progress.
658         // This acts as a lightweight release valve without changing legality.
659         let lookahead_weight = if extended_set.is_empty() {
660             0.0
```

Swap Reduction: Rust source (lines 601–720) (continued)

```

661     } else {
662         // Use less speculative lookahead on narrow, low-branching
663         // topologies, where detours tend to be costly. On broader
664         // graphs, path diversity makes upcoming gates more predictive.
665         let topology = ctx.topology();
666         let average_degree = if topology.num_qubits() == 0 {
667             0.0
668         } else {
669             2.0 * topology.num_edges() as f64 / topology.num_qubits() as f64
670         };
671         let topology_factor = if average_degree < 2.5 {
672             0.55
673         } else if average_degree < 3.0 {
674             0.80
675         } else {
676             1.0
677         };
678
679         // After several non-progressing swaps, prioritize the front
680         // layer and act as a release valve against heuristic cycles.
681         let stagnation_factor = if ctx.swaps_since_progress() >= 3 {
682             0.70
683         } else if ctx.swaps_since_progress() >= 1 {
684             0.85
685         } else {
686             1.0
687         };
688
689         scale(
690             self.lookahead_weight,
691             extended_set.len(),
692             self.set_scaling,
693         ) * stagnation_factor
694         * topology_factor
695     };
696
697     let mut swap_scores = candidates
698         .iter()
699         .copied()
700         .map(|swap| (swap, 0.0))
701         .collect::<Vec<_>>();
702
703     // Score candidate-induced distance changes. In addition to the
704     // linear distance reduction, reward completing a front gate. During
705     // stagnation this reward is increased, steering the router toward
706     // definite progress instead of speculative lookahead improvements.
707     // Completing a front-layer gate is substantially more valuable than
708     // merely reducing its distance: it immediately releases successors
709     // and can change the candidate set on the next routing step.
710     // Definite front-layer completion is more valuable than a small
711     // distance improvement because it releases dependent DAG nodes.
712     // Increase this preference during stagnation to guarantee decisive
713     // progress whenever a candidate can bring a gate onto an edge.
714     let completion_weight = if ctx.swaps_since_progress() >= 2 {
715         0.65
716     } else {
717         0.40
718     };
719     for (swap, score) in &mut swap_scores {
720         *score += basic_weight * front_layer.score_delta(*swap, ctx.topology());

```

Swap Reduction: Rust source (lines 721–763)

```

721         *score -= basic_weight
722             * completion_weight
723             * front_layer.completion_bonus(*swap, ctx.topology());
724     }
725
726     if !extended_set.is_empty() && self.lookahead_weight != 0.0 {
727         for (swap, score) in &mut swap_scores {

```

Swap Reduction: Rust source (lines 721–763) (continued)

```
728         // A geometrically decayed horizon avoids allowing distant,
729         // weakly correlated gates to override the next few gates.
730         *score +=
731             lookahead_weight * extended_set.weighted_score_delta(*swap, ctx.topology());
732
733     }
734 }
735
736 // Apply standard SABRE multiplicative decay to relative score changes.
737 // This preserves the proven anti-cycling behavior and avoids adding a
738 // topology-scaled absolute penalty that can distort close candidates.
739 if self.use_decay {
740     for (swap, score) in &mut swap_scores {
741         *score *= self.decay_state[swap.0].max(self.decay_state[swap.1]);
742     }
743 }
744
745 let mut min_score = f64::INFINITY;
746 let mut best_swaps = Vec::<(usize, usize)>::new();
747 for (swap, score) in &mut swap_scores {
748     if *score + self.best_epsilon < min_score {
749         min_score = *score;
750         best_swaps.clear();
751         best_swaps.push(*swap);
752         continue;
753     }
754     if (*score - min_score).abs() <= self.best_epsilon {
755         best_swaps.push(*swap);
756     }
757 }
758
759 Some(best_swaps[rng.gen_index(best_swaps.len())])
760 }
761 }
762 }
763 // EVOLVE-BLOCK-END
```

K.2. Rosetta: refining a published tour lowers maneuver cost

The program initializes the Earth–Earth–Mars–Earth–Earth–67P tour from published GTOPX trajectory values and refines its encounter times, flybys, and deep-space maneuvers with differential evolution and Powell optimization. It enforces unpowered flybys under the task’s 300 km altitude floor and fixed arrival date, reducing total Δv from 1.552968 to 1.396424 km/s (10.1%). The improvement combines reuse of a public trajectory with optimization for the task’s constraints.

Rosetta: Python source (lines 1–120)

```
1 """
2 Deterministic Cartesian MGA-1DSM optimizer for Rosetta’s E-E-M-E-E-67P tour.
3
4 The trajectory is propagated forward from Earth, with one DSM on each leg.
5 Every outgoing flyby velocity is generated by tools.gravity_assist, making the
6 flybys unpowered by construction. Search is concentrated around the strongest
7 previously demonstrated Rosetta basin and uses Cartesian departure velocity,
8 seeded differential evolution, normalized Powell refinement, and a valid direct
9 multi-revolution Lambert fallback.
10 """
11
12 import sys
13 from pathlib import Path
14
15 _FAMILY_DIR = Path(__file__).resolve().parent.parent
16 if str(_FAMILY_DIR) not in sys.path:
17     sys.path.insert(0, str(_FAMILY_DIR))
18
19 from problem_config import load_problem_for_candidate
20 from tools_wrapper import Tools
21
22 problem = load_problem_for_candidate(__file__)
```

Rosetta: Python source (lines 1–120) (continued)

```

23 tools = Tools()
24
25 # EVOLVE-BLOCK-START
26 import time
27 import numpy as np
28 from scipy.optimize import differential_evolution, minimize
29
30 DAY = 86400.0
31 MU = float(problem["mu_sun"])
32 SEED = 67042014
33 SEQUENCE = ("3", "4", "3", "3")
34
35
36 def _window(spec):
37     """Return the inclusive MJD interval represented by a boundary time."""
38     t = spec["time"]
39     if t["kind"] == "window":
40         return float(t["lo"]), float(t["hi"])
41     value = float(t.get("value", t.get("mjd")))
42     return value, value
43
44
45 def _state(spec, epoch):
46     """Return a fixed boundary state or a DE430 planetary state."""
47     pid = str(spec.get("planet_id", "0"))
48     if pid == "0":
49         return (
50             np.asarray(spec["state_r"], dtype=float),
51             np.asarray(spec["state_v"], dtype=float),
52         )
53     r, v = tools.ephem(pid, float(epoch))
54     return np.asarray(r, dtype=float), np.asarray(v, dtype=float)
55
56
57 def _planet(pid, epoch):
58     """Return a planet's heliocentric DE430 state as NumPy arrays."""
59     r, v = tools.ephem(str(pid), float(epoch))
60     return np.asarray(r, dtype=float), np.asarray(v, dtype=float)
61
62
63 def _piecewise(value, points):
64     """Evaluate a clamped piecewise-linear boundary cost curve."""
65     points = sorted((float(x), float(y)) for x, y in points)
66
67     if value <= points[0][0]:
68         return points[0][1]
69     if value >= points[-1][0]:
70         return points[-1][1]
71
72     for (x0, y0), (x1, y1) in zip(points[:-1], points[1:]):
73         if value <= x1:
74             q = (value - x0) / (x1 - x0)
75             return y0 + q * (y1 - y0)
76
77     return points[-1][1]
78
79
80 def _boundary_cost(spacecraft_velocity, reference_velocity, spec):
81     """Evaluate the configured launcher, capture, or periapsis burn model."""
82     vinf = float(np.linalg.norm(
83         np.asarray(spacecraft_velocity, dtype=float)
84         - np.asarray(reference_velocity, dtype=float)
85     ))
86
87     if spec["type"] == "piecewise_linear":
88         return float(_piecewise(vinf, spec["breakpoints"]))
89
90     pid = str(spec["planet_id"])
91     planet_mu = float(problem["planet_mu"][pid])
92     radius = float(problem["planet_radius"][pid])
93     periapsis = radius * (1.0 + float(spec["h_factor"]))
94     period = float(spec["T_days"]) * DAY

```

Rosetta: Python source (lines 1–120) (continued)

```
95
96     escape_term = 2.0 * planet_mu / periapsis
97     orbit_term = (
98         4.0 * np.pi * np.pi * planet_mu * planet_mu
99         / (period * period)
100     ) ** (1.0 / 3.0)
101
102     return float(
103         np.sqrt(vinf * vinf + escape_term)
104         - np.sqrt(max(0.0, escape_term - orbit_term))
105     )
106
107
108 def _minimum_rp(pid):
109     """Return the minimum legal flyby periapsis radius in kilometres."""
110     pid = str(pid)
111     altitude = float(
112         problem.get("flyby", {})
113         .get("min_altitude_km", {})
114         .get(pid, 200.0)
115     )
116     return float(problem["planet_radius"][pid]) + altitude
117
118
119 def _lambert_options(r0, r1, tof_days, max_revolutions=0):
120     """Enumerate distinct finite prograde Lambert branches for one transfer."""
```

Rosetta: Python source (lines 121–240)

```
121     if tof_days <= 1.0:
122         return []
123
124     answers = []
125     for revolutions in range(int(max_revolutions) + 1):
126         for lowpath in (True, False):
127             try:
128                 departure, arrival = tools.lambert(
129                     np.asarray(r0, dtype=float),
130                     np.asarray(r1, dtype=float),
131                     float(tof_days) * DAY,
132                     MU,
133                     prograde=True,
134                     lowpath=lowpath,
135                     M=revolutions,
136                 )
137                 departure = np.asarray(departure, dtype=float)
138                 arrival = np.asarray(arrival, dtype=float)
139
140                 if not (
141                     np.all(np.isfinite(departure))
142                     and np.all(np.isfinite(arrival))
143                 ):
144                     continue
145
146                 duplicate = any(
147                     np.linalg.norm(departure - old_departure) < 1.0e-8
148                     and np.linalg.norm(arrival - old_arrival) < 1.0e-8
149                     for old_departure, old_arrival in answers
150                 )
151                 if not duplicate:
152                     answers.append((departure, arrival))
153             except Exception:
154                 pass
155
156     return answers
157
158
159 def _local_vinf(epoch, speed, u, v, flip_normal=False):
160     """Map normalized direction values into Earth's local orbital frame."""
161     r, planet_velocity = _planet("3", epoch)
```

Rosetta: Python source (lines 121–240) (continued)

```

162
163     tangent = planet_velocity / np.linalg.norm(planet_velocity)
164     normal = np.cross(r, planet_velocity)
165     normal /= np.linalg.norm(normal)
166     transverse = np.cross(normal, tangent)
167     transverse /= np.linalg.norm(transverse)
168
169     longitude = 2.0 * np.pi * float(u)
170     sin_latitude = 1.0 - 2.0 * float(v)
171     if flip_normal:
172         sin_latitude = -sin_latitude
173
174     cos_latitude = np.sqrt(max(
175         0.0, 1.0 - sin_latitude * sin_latitude
176     ))
177
178     direction = (
179         np.cos(longitude) * cos_latitude * tangent
180         + np.sin(longitude) * cos_latitude * transverse
181         + sin_latitude * normal
182     )
183     return float(speed) * direction
184
185
186 def _inertial_vinf(speed, u, v, flip_z=False):
187     """Map normalized spherical values into inertial Cartesian coordinates."""
188     longitude = 2.0 * np.pi * float(u)
189     z = 2.0 * float(v) - 1.0
190     if flip_z:
191         z = -z
192
193     radial = np.sqrt(max(0.0, 1.0 - z * z))
194     return float(speed) * np.array([
195         radial * np.cos(longitude),
196         radial * np.sin(longitude),
197         z,
198     ])
199
200
201 def _angular_vinf(speed, azimuth, elevation):
202     """Interpret two direction values as inertial azimuth and elevation."""
203     return float(speed) * np.array([
204         np.cos(elevation) * np.cos(azimuth),
205         np.cos(elevation) * np.sin(azimuth),
206         np.sin(elevation),
207     ])
208
209
210 def _tour(x, make_nodes=False):
211     """Evaluate a Cartesian E-E-M-E-E-67P tour with one DSM per leg."""
212     x = np.asarray(x, dtype=float)
213
214     final_epoch = 0.5 * sum(_window(problem["end"]))
215     dates = np.asarray(x[0:5], dtype=float)
216     initial_vinf = np.asarray(x[5:8], dtype=float)
217     fractions = np.asarray(x[8:13], dtype=float)
218     rp_factors = np.asarray(x[13:17], dtype=float)
219     flyby_angles = np.asarray(x[17:21], dtype=float)
220
221     times = dates.tolist() + [final_epoch]
222
223     minimum_leg_times = (250.0, 500.0, 150.0, 500.0, 500.0)
224     for index, minimum in enumerate(minimum_leg_times):
225         if times[index + 1] - times[index] < minimum:
226             return np.inf, None
227
228     if np.any(fractions <= 0.005) or np.any(fractions >= 0.995):
229         return np.inf, None
230
231     try:
232         states = [_state(problem["start"], times[0])]
233         states.extend(

```

Rosetta: Python source (lines 121–240) (continued)

```
234         _planet(pid, times[index + 1])
235         for index, pid in enumerate(SEQUENCE)
236     )
237     states.append(_state(problem["end"], final_epoch))
238 except Exception:
239     return np.inf, None
240
```

Rosetta: Python source (lines 241–360)

```
241     outgoing = states[0][1] + initial_vinf
242     total = _boundary_cost(
243         outgoing, states[0][1], problem["start"]
244     )
245
246     nodes = []
247     if make_nodes:
248         nodes.append({
249             "type": "start",
250             "time": float(times[0]),
251             "planet_id": str(problem["start"].get("planet_id", "0")),
252             "r": states[0][0],
253             "v_before": states[0][1],
254             "v_after": outgoing,
255         })
256
257     for leg in range(5):
258         t0 = float(times[leg])
259         t1 = float(times[leg + 1])
260         dsm_epoch = t0 + float(fractions[leg]) * (t1 - t0)
261
262         if not t0 < dsm_epoch < t1:
263             return np.inf, None
264
265         try:
266             dsm_r, velocity_before = tools.propagate_two_body(
267                 states[leg][0],
268                 outgoing,
269                 (dsm_epoch - t0) * DAY,
270                 MU,
271             )
272             dsm_r = np.asarray(dsm_r, dtype=float)
273             velocity_before = np.asarray(velocity_before, dtype=float)
274         except Exception:
275             return np.inf, None
276
277         options = _lambert_options(
278             dsm_r,
279             states[leg + 1][0],
280             t1 - dsm_epoch,
281             max_revolutions=4 if leg == 4 else 0,
282         )
283         if not options:
284             return np.inf, None
285
286         selected = None
287         selected_increment = np.inf
288
289         for velocity_after, arrival_velocity in options:
290             dsm_cost = float(np.linalg.norm(
291                 velocity_after - velocity_before
292             ))
293
294             if leg == 4:
295                 terminal_cost = _boundary_cost(
296                     arrival_velocity,
297                     states[-1][1],
298                     problem["end"],
299                 )
300             increment = dsm_cost + terminal_cost
```

Rosetta: Python source (lines 241–360) (continued)

```

301         candidate = (
302             velocity_after,
303             arrival_velocity,
304             None,
305             terminal_cost,
306         )
307     else:
308         pid = SEQUENCE[leg]
309         periapsis = (
310             float(problem["planet_radius"][pid])
311             * float(rp_factors[leg])
312         )
313
314         if periapsis < _minimum_rp(pid) * 1.000001:
315             continue
316
317         try:
318             next_outgoing = np.asarray(
319                 tools.gravity_assist(
320                     arrival_velocity,
321                     states[leg + 1][1],
322                     float(problem["planet_mu"][pid]),
323                     periapsis,
324                     float(flyby_angles[leg]),
325                 ),
326                 dtype=float,
327             )
328         except Exception:
329             continue
330
331         if not np.all(np.isfinite(next_outgoing)):
332             continue
333
334         increment = dsm_cost
335         candidate = (
336             velocity_after,
337             arrival_velocity,
338             next_outgoing,
339             0.0,
340         )
341
342         if increment < selected_increment:
343             selected_increment = increment
344             selected = candidate
345
346     if selected is None:
347         return np.inf, None
348
349     (
350         velocity_after,
351         arrival_velocity,
352         next_outgoing,
353         transition_cost,
354     ) = selected
355
356     total += float(np.linalg.norm(
357         velocity_after - velocity_before
358     ))
359
360     if make_nodes:

```

Rosetta: Python source (lines 361–480)

```

361         nodes.append({
362             "type": "DSM",
363             "time": float(dsm_epoch),
364             "planet_id": "0",
365             "r": dsm_r,
366             "v_before": velocity_before,
367             "v_after": velocity_after,

```

Rosetta: Python source (lines 361–480) (continued)

```

368         })
369
370     if leg < 4:
371         total += float(transition_cost)
372         if make_nodes:
373             nodes.append({
374                 "type": "GA",
375                 "time": float(t1),
376                 "planet_id": SEQUENCE[leg],
377                 "r": states[leg + 1][0],
378                 "v_before": arrival_velocity,
379                 "v_after": next_outgoing,
380             })
381         outgoing = next_outgoing
382     else:
383         total += float(transition_cost)
384         if make_nodes:
385             nodes.append({
386                 "type": "end",
387                 "time": float(t1),
388                 "planet_id": str(problem["end"].get("planet_id", "0")),
389                 "r": states[-1][0],
390                 "v_before": arrival_velocity,
391                 "v_after": states[-1][1],
392             })
393
394     return float(total), nodes
395
396 def _verify_nodes(nodes):
397     """Verify generated gravity assists with the evaluator-compatible primitive."""
398     for node in nodes:
399         if node["type"] != "GA":
400             continue
401
402         pid = str(node["planet_id"])
403         minimum = _minimum_rp(pid)
404
405         try:
406             _, planet_velocity = _planet(pid, node["time"])
407             periapsis, mismatch, feasible = tools.powered_flyby(
408                 np.asarray(node["v_before"], dtype=float),
409                 np.asarray(node["v_after"], dtype=float),
410                 planet_velocity,
411                 float(problem["planet_mu"][pid]),
412                 minimum,
413             )
414
415             if not bool(feasible):
416                 return False
417             if not np.isfinite(float(periapsis)):
418                 return False
419             if not np.isfinite(float(mismatch)):
420                 return False
421             if float(periapsis) < minimum - 1.0e-3:
422                 return False
423             if abs(float(mismatch)) > 1.0e-6:
424                 return False
425         except Exception:
426             return False
427
428     return True
429
430 def _summary_seed(dates, dsms, altitudes, initial_vinf, angles):
431     """Build a Cartesian chromosome from observed encounter and DSM epochs."""
432     final_epoch = 0.5 * sum(_window(problem["end"]))
433     dates = np.asarray(dates, dtype=float)
434     boundaries = np.concatenate((dates, [final_epoch]))
435     dsms = np.asarray(dsms, dtype=float)
436
437     fractions = (

```

Rosetta: Python source (lines 361–480) (continued)

```

440         (dsms - boundaries[:-1])
441         / (boundaries[1:] - boundaries[:-1])
442     )
443
444     rp_factors = np.array([
445         (
446             float(problem["planet_radius"][pid])
447             + float(altitudes[index])
448         ) / float(problem["planet_radius"][pid])
449         for index, pid in enumerate(SEQUENCE)
450     ])
451
452     return np.concatenate((
453         dates,
454         np.asarray(initial_vinf, dtype=float),
455         fractions,
456         rp_factors,
457         np.asarray(angles, dtype=float),
458     ))
459
460
461 def _seeds_and_bounds():
462     """Create focused bounds and structured seeds around proven Rosetta basins."""
463     start_lo, start_hi = _window(problem["start"])
464
465     best_dates = np.array([
466         53086.8, 53452.0, 54163.1, 54420.7, 55148.5
467     ])
468     best_dsms = np.array([
469         53273.0, 54029.2, 54195.8, 54893.1, 55884.4
470     ])
471     best_altitudes = np.array([
472         7897.0, 300.0, 14311.0, 300.0
473     ])
474
475     supporting_data = [
476         (
477             [53083.1, 53448.4, 54162.2, 54420.7, 55148.1],
478             [53264.9, 54024.5, 54297.6, 54892.8, 55880.9],
479             [11394.0, 300.0, 14440.0, 300.0],
480         ),

```

Rosetta: Python source (lines 481–600)

```

481         (
482             [53090.6, 53455.9, 54163.5, 54420.0, 55150.5],
483             [53349.4, 54030.8, 54204.6, 54492.9, 55805.9],
484             [11575.0, 300.0, 13525.0, 730.0],
485         ),
486         (
487             [53093.2, 53458.5, 54163.8, 54419.6, 55150.1],
488             [53379.2, 54031.4, 54258.3, 54550.0, 55820.7],
489             [11791.0, 300.0, 13858.0, 308.0],
490         ),
491         (
492             [53093.2, 53458.4, 54165.0, 54420.4, 55150.9],
493             [53312.4, 54024.9, 54224.7, 54498.2, 55823.2],
494             [10911.0, 300.0, 13838.0, 302.0],
495         ),
496     ]
497
498     angles = np.array([
499         -1.253888118,
500         1.787602330,
501         -1.594671417,
502         -1.977325495,
503     ])
504
505     speed = 4.478444171
506     u = 0.731698680

```

Rosetta: Python source (lines 481–600) (continued)

```

507     v = 0.878289696
508
509     datasets = [
510         (best_dates, best_dsms, best_altitudes),
511         *supporting_data,
512     ]
513
514     seeds = []
515     for dates, dsms, altitudes in datasets:
516         epoch = float(dates[0])
517         directions = (
518             _local_vinf(epoch, speed, u, v, False),
519             _local_vinf(epoch, speed, u, v, True),
520             _inertial_vinf(speed, u, v, False),
521             _inertial_vinf(speed, u, v, True),
522             _angular_vinf(speed, u, v),
523         )
524
525         for direction in directions:
526             seeds.append(_summary_seed(
527                 dates, dsms, altitudes, direction, angles
528             ))
529
530     published_dates = np.array([
531         53086.802723,
532         53452.0450361,
533         54159.7996805,
534         54417.1235321,
535         55147.6072557,
536     ])
537     published_fractions = np.array([
538         0.512067000,
539         0.810371727,
540         0.275887800,
541         0.119192979,
542         0.436742230,
543     ])
544     published_radii = np.array([
545         2.657626174,
546         1.050000000,
547         3.197806169,
548         1.056221792,
549     ])
550
551     for direction in (
552         _local_vinf(published_dates[0], speed, u, v, False),
553         _local_vinf(published_dates[0], speed, u, v, True),
554         _inertial_vinf(speed, u, v, False),
555         _inertial_vinf(speed, u, v, True),
556         _angular_vinf(speed, u, v),
557     ):
558         seeds.append(np.concatenate((
559             published_dates,
560             direction,
561             published_fractions,
562             published_radii,
563             angles,
564         )))
565
566     date_centers = np.vstack([
567         best_dates,
568         *[np.asarray(item[0], dtype=float) for item in supporting_data],
569         published_dates,
570     ])
571     date_margins = np.array([0.0, 45.0, 55.0, 60.0, 75.0])
572
573     bounds = [(max(start_lo, 53072.0), min(start_hi, 53103.0))]
574     for index in range(1, 5):
575         bounds.append((
576             float(np.min(date_centers[:, index]) - date_margins[index]),
577             float(np.max(date_centers[:, index]) + date_margins[index]),
578         ))

```

Rosetta: Python source (lines 481–600) (continued)

```
579
580     bounds.extend([(-8.0, 8.0)] * 3)
581     bounds.extend([(0.010, 0.990)] * 5)
582
583     for pid in SEQUENCE:
584         minimum_factor = (
585             _minimum_rp(pid) / float(problem["planet_radius"][pid])
586         )
587         bounds.append((minimum_factor * 1.000001, 6.0))
588
589     bounds.extend([(-np.pi, np.pi)] * 4)
590
591     lower = np.asarray([lo for lo, _ in bounds], dtype=float)
592     upper = np.asarray([hi for _, hi in bounds], dtype=float)
593     seeds = [
594         np.clip(np.asarray(seed, dtype=float), lower, upper)
595         for seed in seeds
596     ]
597
598     return seeds, bounds
599
600
```

Rosetta: Python source (lines 601–720)

```
601 def _optimize_tour():
602     """Run seeded evolution followed by full and reduced normalized polishing."""
603     seeds, bounds = _seeds_and_bounds()
604
605     lower = np.asarray([lo for lo, _ in bounds], dtype=float)
606     upper = np.asarray([hi for _, hi in bounds], dtype=float)
607     span = upper - lower
608     dimension = len(bounds)
609
610     started = time.monotonic()
611     timeout = float(problem.get("timeout_seconds", 300.0))
612     global_deadline = started + max(
613         70.0, min(175.0, timeout - 80.0)
614     )
615     final_deadline = started + max(
616         100.0, min(270.0, timeout - 12.0)
617     )
618
619     best_value = np.inf
620     best_x = seeds[0].copy()
621     archive = []
622
623     def save(value, x):
624         """Store the global winner and several geometrically distinct elites."""
625         nonlocal best_value, best_x
626
627         if not np.isfinite(value):
628             return
629
630         x = np.asarray(x, dtype=float).copy()
631         y = (x - lower) / span
632
633         if value < best_value:
634             best_value = float(value)
635             best_x = x.copy()
636
637         for index, (old_value, old_x) in enumerate(archive):
638             old_y = (old_x - lower) / span
639             if np.linalg.norm(y - old_y) < 0.012:
640                 if value < old_value:
641                     archive[index] = (float(value), x)
642                     archive.sort(key=lambda item: item[0])
643                 return
644
645     archive.append((float(value), x))
```

Rosetta: Python source (lines 601–720) (continued)

```

646         archive.sort(key=lambda item: item[0])
647         del archive[14:]
648
649     def objective(x):
650         """Evaluate one physical chromosome and update the elite archive."""
651         value, _ = _tour(x, make_nodes=False)
652         if np.isfinite(value):
653             save(value, x)
654             return float(value)
655         return 1.0e6
656
657     for seed in seeds:
658         objective(seed)
659
660     rng = np.random.default_rng(SEED)
661     population_size = 25 * dimension
662     population = np.empty((population_size, dimension), dtype=float)
663
664     copied = min(len(seeds), population_size)
665     for row in range(copied):
666         population[row] = seeds[row]
667
668     scales = np.array(
669         [0.025] * 5
670         + [0.045] * 3
671         + [0.055] * 5
672         + [0.060] * 4
673         + [0.080] * 4,
674         dtype=float,
675     )
676
677     for row in range(copied, population_size):
678         if row < int(0.96 * population_size):
679             if row % 3:
680                 source = row % min(5, len(seeds))
681             else:
682                 source = row % len(seeds)
683
684             candidate = seeds[source].copy()
685             candidate += rng.normal(0.0, scales * span)
686             population[row] = np.clip(candidate, lower, upper)
687         else:
688             population[row] = rng.uniform(lower, upper)
689
690     def stop_global(xk, convergence):
691         """Stop evolution in time to preserve a deterministic polish budget."""
692         return time.monotonic() >= global_deadline
693
694     de_result = None
695     try:
696         de_result = differential_evolution(
697             objective,
698             bounds,
699             init=population,
700             seed=SEED,
701             maxiter=1200,
702             popsize=25,
703             tol=1.0e-10,
704             atol=1.0e-12,
705             mutation=(0.30, 1.10),
706             recombination=0.94,
707             polish=False,
708             updating="immediate",
709             workers=1,
710             callback=stop_global,
711         )
712         objective(de_result.x)
713     except Exception:
714         pass
715
716     unit_bounds = [(0.0, 1.0)] * dimension
717

```

Rosetta: Python source (lines 601–720) (continued)

```
718     def normalized_objective(y):
719         """Evaluate the tour after mapping unit coordinates to physical bounds."""
720         y = np.clip(np.asarray(y, dtype=float), 0.0, 1.0)
```

Rosetta: Python source (lines 721–840)

```
721         return objective(lower + span * y)
722
723     starts = [best_x.copy()]
724     if de_result is not None:
725         starts.append(np.asarray(de_result.x, dtype=float))
726     starts.extend(x for _, x in archive[:5])
727     starts.extend(seeds[:3])
728
729     unique = []
730     for candidate in starts:
731         y = (candidate - lower) / span
732         if all(
733             np.linalg.norm(y - (old - lower) / span) > 1.0e-6
734             for old in unique
735         ):
736             unique.append(candidate)
737
738     for candidate in unique[:4]:
739         if time.monotonic() >= final_deadline - 25.0:
740             break
741
742     try:
743         y0 = np.clip((candidate - lower) / span, 0.0, 1.0)
744         result = minimize(
745             normalized_objective,
746             y0,
747             method="Powell",
748             bounds=unit_bounds,
749             options={
750                 "maxiter": 800,
751                 "maxfev": 10500,
752                 "xtol": 5.0e-9,
753                 "ftol": 2.0e-13,
754             },
755         )
756         normalized_objective(result.x)
757     except Exception:
758         pass
759
760     # Timing, departure velocity, the Mars/final-Earth turns, and the terminal
761     # DSM dominate the residual cost in the demonstrated optimum.
762     active = np.array([
763         0, 1, 2, 3, 4,
764         5, 6, 7,
765         9, 10, 12,
766         14, 16,
767         17, 18, 19, 20,
768     ], dtype=int)
769
770     if time.monotonic() < final_deadline - 8.0:
771         ybase = np.clip((best_x - lower) / span, 0.0, 1.0)
772
773         def reduced_objective(z):
774             """Polish the coordinates controlling the nonzero trajectory burns."""
775             y = ybase.copy()
776             y[active] = np.clip(np.asarray(z, dtype=float), 0.0, 1.0)
777             return normalized_objective(y)
778
779         try:
780             result = minimize(
781                 reduced_objective,
782                 ybase[active],
783                 method="Powell",
784                 bounds=[(0.0, 1.0)] * len(active),
```

Rosetta: Python source (lines 721–840) (continued)

```

785         options={
786             "maxiter": 500,
787             "maxfev": 6000,
788             "xtol": 2.0e-9,
789             "ftol": 8.0e-14,
790         },
791     )
792     reduced_objective(result.x)
793     except Exception:
794         pass
795
796     value, nodes = _tour(best_x, make_nodes=True)
797     if nodes is None or not np.isfinite(value):
798         return np.inf, None
799     if not _verify_nodes(nodes):
800         return np.inf, None
801
802     return float(value), nodes
803
804
805 def _direct_fallback():
806     """Construct a valid direct multi-revolution Earth-to-67P fallback."""
807     start_lo, start_hi = _window(problem["start"])
808     final_epoch = 0.5 * sum(_window(problem["end"]))
809     final_r, final_v = _state(problem["end"], final_epoch)
810
811     best_cost = np.inf
812     best_nodes = None
813
814     for launch in np.linspace(start_lo, start_hi, 17):
815         initial_r, initial_v = _state(problem["start"], launch)
816
817         for departure, arrival in _lambert_options(
818             initial_r,
819             final_r,
820             final_epoch - launch,
821             max_revolutions=4,
822         ):
823             cost = (
824                 _boundary_cost(
825                     departure, initial_v, problem["start"]
826                 )
827                 + _boundary_cost(
828                     arrival, final_v, problem["end"]
829                 )
830             )
831
832             if cost < best_cost:
833                 best_cost = float(cost)
834                 best_nodes = [
835                     {
836                         "type": "start",
837                         "time": float(launch),
838                         "planet_id": str(
839                             problem["start"].get("planet_id", "0")
840                         ),
841                     },

```

Rosetta: Python source (lines 841–925)

```

841                     "r": initial_r,
842                     "v_before": initial_v,
843                     "v_after": departure,
844                 },
845                 {
846                     "type": "end",
847                     "time": float(final_epoch),
848                     "planet_id": str(
849                         problem["end"].get("planet_id", "0")
850                     ),
851                     "r": final_r,

```

Rosetta: Python source (lines 841–925) (continued)

```

852             "v_before": arrival,
853             "v_after": final_v,
854         },
855     ]
856
857     return float(best_cost), best_nodes
858
859
860 def _format(nodes):
861     """Convert NumPy-backed trajectory nodes to the required plain schema."""
862     return [
863         {
864             "type": str(node["type"]),
865             "time": float(node["time"]),
866             "planet_id": str(node["planet_id"]),
867             "r": np.asarray(node["r"], dtype=float).tolist(),
868             "v_before": np.asarray(
869                 node["v_before"], dtype=float
870             ).tolist(),
871             "v_after": np.asarray(
872                 node["v_after"], dtype=float
873             ).tolist(),
874         }
875         for node in nodes
876     ]
877
878
879 def run_code():
880     """Return the best valid direct or E-E-M-E-E-67P trajectory found."""
881     try:
882         record.event("focused_cartesian_rosetta_mga_search")
883     except Exception:
884         pass
885
886     fallback_cost, fallback_nodes = _direct_fallback()
887     best_cost = fallback_cost
888     best_nodes = fallback_nodes
889     best_sequence = "direct-multirevolution-Lambert"
890
891     allowed = set(map(str, problem.get("allowed_GA_planets", [])))
892     compatible = (
893         {"3", "4"}.issubset(allowed)
894         and int(problem.get("max_GA", 0)) >= 4
895         and int(problem.get("max_DSM", 0)) >= 5
896         and int(problem.get("max_nodes", 0)) >= 11
897     )
898
899     if compatible:
900         try:
901             tour_cost, tour_nodes = _optimize_tour()
902             if (
903                 tour_nodes is not None
904                 and np.isfinite(tour_cost)
905                 and tour_cost < best_cost
906             ):
907                 best_cost = float(tour_cost)
908                 best_nodes = tour_nodes
909                 best_sequence = "E-E-M-E-E-67P"
910         except Exception:
911             pass
912
913     if best_nodes is None:
914         raise RuntimeError("No valid Rosetta trajectory was constructed")
915
916     try:
917         record.set("best_sequence", best_sequence)
918         record.set("final_cost", float(best_cost))
919         record.set("final_nodes", len(best_nodes))
920     except Exception:
921         pass
922
923     return _format(best_nodes)

```

Rosetta: Python source (lines 841–925) (continued)

```
924
925 # EVOLVE-BLOCK-END
```

K.3. Voyager 2: constrained refinement improves the existing tour

The program retains the Earth–Jupiter–Saturn–Uranus–Neptune tour without deep-space maneuvers, first fitting unpowered flybys by least squares and then minimizing boundary Δv with SLSQP. The selected trajectory arrives at the upper bound of the allowed window and reduces total Δv from 3.430214 to 3.430206 km/s. The small gain reflects tighter numerical refinement of the same tour.

Voyager 2: Python source (lines 1–120)

```
1  """Deterministic constrained epoch optimization for the Voyager-2 grand tour."""
2
3  import sys
4  from pathlib import Path
5
6  import numpy as np
7  from scipy.optimize import minimize, least_squares
8
9  _FAMILY_DIR = Path(__file__).resolve().parent.parent
10 if str(_FAMILY_DIR) not in sys.path:
11     sys.path.insert(0, str(_FAMILY_DIR))
12
13 from problem_config import load_problem_for_candidate
14 from tools_wrapper import Tools
15
16 problem = load_problem_for_candidate(__file__)
17 tools = Tools()
18
19 # EVOLVE-BLOCK-START
20
21 DAY = 86400.0
22 MIN_TOF = 5.0
23 INF = 1.0e30
24 SEED = 20260916
25 CACHE = {}
26
27
28 def _window(spec):
29     """Return the legal lower and upper MJD values for a boundary specification."""
30     t = spec["time"]
31     if t["kind"] == "window":
32         return float(t["lo"]), float(t["hi"])
33     value = t.get("value", t.get("mjd"))
34     return float(value), float(value)
35
36
37 def _state(pid, epoch, boundary=None):
38     """Return the heliocentric state from ephemeris or a configured fixed boundary."""
39     pid = str(pid)
40
41     if pid == "0":
42         if boundary is not None:
43             spec = problem[boundary]
44             if "state_r" in spec and "state_v" in spec:
45                 return (
46                     np.asarray(spec["state_r"], float),
47                     np.asarray(spec["state_v"], float),
48                 )
49
50     for name in ("start", "end"):
51         spec = problem[name]
52         if "state_r" in spec and "state_v" in spec:
53             return (
54                 np.asarray(spec["state_r"], float),
55                 np.asarray(spec["state_v"], float),
56             )
57
```

Voyager 2: Python source (lines 1–120) (continued)

```

58         return np.zeros(3), np.zeros(3)
59
60     key = (pid, round(float(epoch), 8))
61     if key not in CACHE:
62         r, v = tools.ephem(pid, float(epoch))
63         CACHE[key] = np.asarray(r, float), np.asarray(v, float)
64     return CACHE[key]
65
66
67 def _piecewise(value, breakpoints):
68     """Evaluate a boundary launcher curve by linear interpolation and endpoint extension."""
69     pts = sorted((float(x), float(y)) for x, y in breakpoints)
70     x = float(value)
71
72     if x <= pts[0][0]:
73         return pts[0][1]
74     if x >= pts[-1][0]:
75         return pts[-1][1]
76
77     for (x0, y0), (x1, y1) in zip(pts[:-1], pts[1:]):
78         if x <= x1:
79             if x1 == x0:
80                 return float(y1)
81             f = (x - x0) / (x1 - x0)
82             return float(y0 + f * (y1 - y0))
83
84     return float(pts[-1][1])
85
86
87 def _periapsis_cost(vinf, spec, pid):
88     """Compute the configured impulsive burn at planetary periapsis."""
89     mu = float(problem["planet_mu"][str(pid)])
90     radius = float(problem["planet_radius"][str(pid)])
91     rp = radius * (1.0 + float(spec["h_factor"]))
92     period = float(spec["T_days"]) * DAY
93
94     correction = (4.0 * np.pi**2 * mu**2 / period**2) ** (1.0 / 3.0)
95     escape = np.sqrt(float(vinf) ** 2 + 2.0 * mu / rp)
96     parking = np.sqrt(max(2.0 * mu / rp - correction, 0.0))
97     return float(escape - parking)
98
99
100 def _boundary_cost(v_before, v_after, epoch, spec, is_start):
101     """Evaluate the exact start or end boundary delta-v model."""
102     if spec["type"] == "piecewise_linear":
103         jump = np.linalg.norm(np.asarray(v_after) - np.asarray(v_before))
104         return _piecewise(jump, spec["breakpoints"])
105
106     pid = str(spec.get("planet_id", "0"))
107     _, vp = _state(pid, epoch, "start" if is_start else "end")
108     velocity = np.asarray(v_after if is_start else v_before, float)
109     vinf = np.linalg.norm(velocity - vp)
110     return _periapsis_cost(vinf, spec, pid)
111
112
113 def _sequence():
114     """Select the longest admissible Voyager-style outer-planet flyby sequence."""
115     allowed = {str(x) for x in problem.get("allowed_GA_planets", [])}
116     maximum = int(problem.get("max_GA", 0))
117     end_pid = str(problem["end"].get("planet_id", "8"))
118
119     candidates = [
120         ("5", "6", "7"),

```

Voyager 2: Python source (lines 121–240)

```

121         ("5", "6"),
122         ("5", "7"),
123         ("6", "7"),
124         ("5",),

```

Voyager 2: Python source (lines 121–240) (continued)

```

125         ("6",),
126         ("7",),
127         (),
128     ]
129
130     for sequence in candidates:
131         if len(sequence) <= maximum and all(
132             p in allowed and p != end_pid for p in sequence
133         ):
134             return sequence
135
136     return ()
137
138
139 def _historical_times(sequence):
140     """Construct the canonical Voyager encounter epochs clipped to legal windows."""
141     slo, shi = _window(problem["start"])
142     elo, ehi = _window(problem["end"])
143
144     centers = {
145         "5": 44126.5,
146         "6": 44985.6,
147         "7": 46730.9,
148     }
149
150     t0 = float(np.clip(43389.2, slo, shi))
151     tf = float(np.clip(48163.0, elo, ehi))
152
153     middle = [
154         float(np.clip(centers[p], t0 + MIN_TOF, tf - MIN_TOF))
155         for p in sequence
156     ]
157
158     result = np.asarray([t0] + middle + [tf], float)
159     if np.any(np.diff(result) <= MIN_TOF):
160         result = np.linspace(t0, tf, len(sequence) + 2)
161
162     return result
163
164
165 def _bounds(sequence):
166     """Build broad legal encounter-epoch bounds around the historical tour."""
167     slo, shi = _window(problem["start"])
168     elo, ehi = _window(problem["end"])
169
170     centers = {
171         "5": 44126.5,
172         "6": 44985.6,
173         "7": 46730.9,
174     }
175
176     bounds = [(slo, shi)]
177     for pid in sequence:
178         c = centers[pid]
179         bounds.append((
180             max(slo + MIN_TOF, c - 3000.0),
181             min(ehi - MIN_TOF, c + 3000.0),
182         ))
183     bounds.append((elo, ehi))
184     return bounds
185
186
187 def _arcs(sequence, times, lowpath=True):
188     """Compute planetary states and Lambert endpoint velocities for every tour leg."""
189     times = np.asarray(times, float)
190
191     start_pid = str(problem["start"].get("planet_id", "0"))
192     end_pid = str(problem["end"].get("planet_id", "0"))
193     pids = [start_pid] + list(sequence) + [end_pid]
194
195     states = []
196     for i, pid in enumerate(pids):

```

Voyager 2: Python source (lines 121–240) (continued)

```

197         boundary = None
198         if i == 0:
199             boundary = "start"
200         elif i == len(pids) - 1:
201             boundary = "end"
202         states.append(_state(pid, times[i], boundary))
203
204     departures = []
205     arrivals = []
206
207     for i in range(len(pids) - 1):
208         tof = float(times[i + 1] - times[i])
209         if tof <= MIN_TOF:
210             raise ValueError("invalid transfer time")
211
212         va, vb = tools.lambert(
213             states[i][0],
214             states[i + 1][0],
215             tof * DAY,
216             float(problem["mu_sun"]),
217             prograde=True,
218             lowpath=lowpath,
219             M=0,
220         )
221         departures.append(np.asarray(va, float))
222         arrivals.append(np.asarray(vb, float))
223
224     return pids, states, departures, arrivals
225
226
227 def _flyby_residual(sequence, times, lowpath=True):
228     """Return incoming-minus-outgoing hyperbolic excess speed at each flyby."""
229     try:
230         _, _, departures, arrivals = _arcs(sequence, times, lowpath)
231         residual = []
232
233         for i, pid in enumerate(sequence):
234             _, vp = _state(pid, times[i + 1])
235             vin = np.linalg.norm(arrivals[i] - vp)
236             vout = np.linalg.norm(departures[i + 1] - vp)
237             residual.append(vin - vout)
238
239         return np.asarray(residual, float)
240     except Exception:

```

Voyager 2: Python source (lines 241–360)

```

241         return np.ones(len(sequence), float) * 1.0e6
242
243
244 def _evaluate(sequence, times, build=False, lowpath=True):
245     """Evaluate exact boundary and powered-flyby cost and optionally construct nodes."""
246     times = np.asarray(times, float)
247
248     if len(times) != len(sequence) + 2 or not np.all(np.isfinite(times)):
249         return (INF, None) if build else INF
250
251     slo, shi = _window(problem["start"])
252     elo, ehi = _window(problem["end"])
253
254     if not slo <= times[0] <= shi or not elo <= times[-1] <= ehi:
255         return (INF, None) if build else INF
256     if np.any(np.diff(times) <= MIN_TOF):
257         return (INF, None) if build else INF
258
259     try:
260         pids, states, departures, arrivals = _arcs(sequence, times, lowpath)
261
262         total = _boundary_cost(
263             states[0][1],

```

Voyager 2: Python source (lines 241–360) (continued)

```

264         departures[0],
265         times[0],
266         problem["start"],
267         True,
268     )
269
270     for i, pid in enumerate(sequence):
271         _, vp = _state(pid, times[i + 1])
272         mu = float(problem["planet_mu"][pid])
273         radius = float(problem["planet_radius"][pid])
274         altitude = float(
275             problem.get("flyby", {})
276             .get("min_altitude_km", {})
277             .get(pid, 200.0)
278         )
279
280         _, dv, feasible = tools.powered_flyby(
281             arrivals[i],
282             departures[i + 1],
283             vp,
284             mu,
285             radius + altitude,
286         )
287
288         if not feasible or not np.isfinite(dv):
289             return (INF, None) if build else INF
290
291         total += float(dv)
292
293         total += _boundary_cost(
294             arrivals[-1],
295             states[-1][1],
296             times[-1],
297             problem["end"],
298             False,
299         )
300
301     except Exception:
302         return (INF, None) if build else INF
303
304     if not build:
305         return float(total)
306
307     nodes = [{
308         "type": "start",
309         "time": float(times[0]),
310         "planet_id": pids[0],
311         "r": states[0][0],
312         "v_before": states[0][1],
313         "v_after": departures[0],
314     }]
315
316     for i, pid in enumerate(sequence):
317         nodes.append({
318             "type": "GA",
319             "time": float(times[i + 1]),
320             "planet_id": str(pid),
321             "r": states[i + 1][0],
322             "v_before": arrivals[i],
323             "v_after": departures[i + 1],
324         })
325
326     nodes.append({
327         "type": "end",
328         "time": float(times[-1]),
329         "planet_id": pids[-1],
330         "r": states[-1][0],
331         "v_before": arrivals[-1],
332         "v_after": states[-1][1],
333     })
334
335     return float(total), nodes

```

Voyager 2: Python source (lines 241–360) (continued)

```

336
337
338 def _boundary_objective(sequence, times, lowpath=True):
339     """Return only launch and arrival cost for constrained manifold optimization."""
340     try:
341         _, states, departures, arrivals = _arcs(sequence, times, lowpath)
342         return _boundary_cost(
343             states[0][1],
344             departures[0],
345             times[0],
346             problem["start"],
347             True,
348         ) + _boundary_cost(
349             arrivals[-1],
350             states[-1][1],
351             times[-1],
352             problem["end"],
353             False,
354         )
355     except Exception:
356         return INF
357
358
359 def _project_seed(sequence, seed, bounds, lowpath=True):
360     """Project a trial epoch vector toward equal-speed flyby compatibility."""

```

Voyager 2: Python source (lines 361–480)

```

361     if not sequence:
362         return np.asarray(seed, float)
363
364     lo = np.asarray([b[0] for b in bounds], float)
365     hi = np.asarray([b[1] for b in bounds], float)
366
367     def residual(x):
368         return _flyby_residual(sequence, x, lowpath)
369
370     try:
371         result = least_squares(
372             residual,
373             np.asarray(seed, float),
374             bounds=(lo, hi),
375             max_nfev=250,
376             xtol=1e-10,
377             ftol=1e-10,
378             gtol=1e-10,
379         )
380         return np.asarray(result.x, float)
381     except Exception:
382         return np.asarray(seed, float)
383
384
385 def _polish(sequence, seed, bounds, lowpath=True):
386     """Minimize boundary delta-v subject to exact unpowered flyby constraints."""
387     if not sequence:
388         return np.asarray(seed, float)
389
390     def objective(x):
391         """Evaluate the launch plus arrival boundary cost."""
392         return _boundary_objective(sequence, x, lowpath)
393
394     def constraint(x):
395         """Enforce equal incoming and outgoing hyperbolic excess speeds."""
396         return _flyby_residual(sequence, x, lowpath)
397
398     try:
399         result = minimize(
400             objective,
401             np.asarray(seed, float),
402             method="SLSQP",

```

Voyager 2: Python source (lines 361–480) (continued)

```

403         bounds=bounds,
404         constraints={"type": "eq", "fun": constraint},
405         options={
406             "maxiter": 900,
407             "ftol": 1e-12,
408             "disp": False,
409         },
410     )
411     return np.asarray(result.x, float)
412 except Exception:
413     return np.asarray(seed, float)
414
415 def _seeds(sequence, bounds):
416     """Generate deterministic historical, corner, and distributed epoch seeds."""
417     rng = np.random.default_rng(SEED)
418     x0 = _historical_times(sequence)
419     result = [x0]
420
421     # Perturb each historical epoch at several deterministic scales.
422     for scale in (2.0, 10.0, 35.0, 100.0, 280.0, 700.0):
423         for _ in range(5):
424             x = x0 + rng.normal(0.0, scale, len(x0))
425             x = np.asarray([
426                 np.clip(x[i], bounds[i][0], bounds[i][1])
427                 for i in range(len(x))
428             ])
429             if np.all(np.diff(x) > MIN_TOF):
430                 result.append(x)
431
432     # Explicit launch/arrival window combinations are useful when windows are broad.
433     for a in (0.0, 0.5, 1.0):
434         for b in (0.0, 0.5, 1.0):
435             x = x0.copy()
436             x[0] = bounds[0][0] + a * (bounds[0][1] - bounds[0][0])
437             x[-1] = bounds[-1][0] + b * (bounds[-1][1] - bounds[-1][0])
438             if np.all(np.diff(x) > MIN_TOF):
439                 result.append(x)
440
441     # Distributed interior samples retain independently sampled boundaries.
442     for _ in range(30):
443         x = np.asarray([rng.uniform(lo, hi) for lo, hi in bounds])
444         x[1:-1] = np.sort(x[1:-1])
445         if np.all(np.diff(x) > MIN_TOF):
446             result.append(x)
447
448     return result
449
450 def _format(nodes):
451     """Convert all trajectory fields to evaluator-compatible scalar and list types."""
452     output = []
453
454     for node in nodes:
455         q = dict(node)
456         q["type"] = str(q["type"])
457         q["time"] = float(q["time"])
458         q["planet_id"] = str(q["planet_id"])
459
460         for key in ("r", "v_before", "v_after"):
461             q[key] = np.asarray(q[key], float).tolist()
462
463         output.append(q)
464
465     return output
466
467 def run_code():
468     """Search deterministic flyby manifolds and return the lowest-cost valid tour."""
469     sequence = _sequence()
470     bounds = _bounds(sequence)
471     best_value, best_nodes = _evaluate(

```

Voyager 2: Python source (lines 361–480) (continued)

```
475         sequence,
476         _historical_times(sequence),
477         build=True,
478         lowpath=True,
479     )
480
```

Voyager 2: Python source (lines 481–518)

```
481     # The canonical low-path branch is expected for Voyager 2. A secondary
482     # branch is sampled only as a robustness measure and can never replace a
483     # better valid canonical solution.
484     branches = [True, False]
485
486     for lowpath in branches:
487         for seed in _seeds(sequence, bounds):
488             projected = _project_seed(sequence, seed, bounds, lowpath)
489             polished = _polish(sequence, projected, bounds, lowpath)
490
491             value, nodes = _evaluate(
492                 sequence,
493                 polished,
494                 build=True,
495                 lowpath=lowpath,
496             )
497
498             if nodes is not None and value < best_value:
499                 best_value = value
500                 best_nodes = nodes
501
502             if best_nodes is None:
503                 return []
504
505             if len(best_nodes) > int(problem.get("max_nodes", 999)):
506                 return []
507
508             try:
509                 record.event("voyager_deterministic_manifold_multistart")
510                 record.set("final_nodes", len(best_nodes))
511                 record.set("final_objective", float(best_value))
512                 record.set("sequence", "E->J->S->U->N")
513             except Exception:
514                 pass
515
516             return _format(best_nodes)
517
518     # EVOLVE-BLOCK-END
```

K.4. Denoising: mixing diffusion operators improves average accuracy

The program builds one MAGIC graph and mixes its ordinary diffusion output with a self-loop-free version using cell-specific weights, followed by shrinkage and gene calibration. Its held-out mean score increases from 0.722690 to 0.722906. The gain on PBMC (0.7116 vs. 0.7090) is partly offset by a loss on Tabula (0.7342 vs. 0.7364).

Denoising: Python source (lines 1–120)

```
1     # EVOLVE-BLOCK-START
2     import numpy as np
3     import scipy.sparse as sp
4     import graphtools
5     import scprep
6
7
8     def _as_counts(X):
9         """Return X as a finite dense nonnegative floating-point matrix."""
10        x = np.asarray(scprep.utils.toarray(X), dtype=np.float64)
11        return np.maximum(np.nan_to_num(x, nan=0.0, posinf=0.0, neginf=0.0), 0.0)
12
```

Denosing: Python source (lines 1–120) (continued)

```

13
14 def _backproject(graph, values, approximate):
15     """Map graph coordinates back to the original gene space."""
16     y = scprep.utils.toarray(values)
17     if approximate:
18         y = graph.inverse_transform(y, columns=None)
19     return np.asarray(y, dtype=np.float64)
20
21
22 def _diffuse(op, values, steps):
23     """Apply a sparse diffusion operator repeatedly."""
24     y = values
25     for _ in range(int(steps)):
26         y = op.dot(y)
27     return np.asarray(scpred.utils.toarray(y), dtype=np.float64)
28
29
30 def _leave_one_out_operator(op):
31     """Remove graph self-loops and renormalize rows for noise-independent smoothing."""
32     p = op.tocsr(copy=True) if sp.issparse(op) else sp.csr_matrix(op)
33     p.setdiag(0.0)
34     p.eliminate_zeros()
35     rows = np.asarray(p.sum(axis=1)).ravel()
36     inv = np.zeros_like(rows, dtype=np.float64)
37     good = rows > 1e-12
38     inv[good] = 1.0 / rows[good]
39     q = sp.diags(inv).dot(p).tocsr()
40
41     # Extremely degenerate rows should retain a valid stochastic transition.
42     bad = np.flatnonzero(~good)
43     if bad.size:
44         q = q.tolil()
45         q[bad, bad] = 1.0
46         q = q.tocsr()
47     return q
48
49
50 def _gene_calibration(prediction, observed, strength):
51     """Correct predicted gene frequencies conservatively toward training frequencies."""
52     if strength <= 0:
53         return prediction
54     eps = 1e-12
55     p = np.maximum(prediction.sum(axis=0), 0.0)
56     q = np.maximum(observed.sum(axis=0), 0.0)
57     p /= max(float(p.sum()), eps)
58     q /= max(float(q.sum()), eps)
59     ratio = np.clip((q + eps) / (p + eps), 0.88, 1.14)
60     return prediction * np.power(ratio[None, :], float(strength))
61
62
63 def _poisson_shrink(prediction, gene_mean, strength):
64     """Apply smooth abundance-dependent shrinkage to fractional predictions."""
65     if strength <= 0:
66         return prediction
67     rarity = (
68         0.76
69         + 1.18 / (gene_mean + 1.0)
70         + 0.20 / np.sqrt(gene_mean + 0.15)
71     )
72     rarity = np.clip(rarity, 0.76, 2.55)
73     threshold = float(strength) * rarity[None, :]
74     p = np.maximum(prediction, 0.0)
75     return p * p / (p + threshold)
76
77
78 def magic_denoise(
79     X,
80     knn=5,
81     t=3,
82     n_pca=100,
83     solver="approximate",
84     decay=1,

```

Denoising: Python source (lines 1–120) (continued)

```
85     knn_max=None,
86     random_state=None,
87     n_jobs=1,
88     verbose=False,
89     shrink=0.09,
90     gene_calibration=0.25,
91     raw_anchor=0.10,
92     positive_anchor=0.02,
93     log_mix=0.20,
94     loo_mix=0.55,
95     **kwargs,
96 ):
97     """Denoise counts with square-root MAGIC and leave-one-out diffusion.
98
99     A graph is built from library-normalized square-root counts. Diffusion
100     estimates are formed from both the usual operator and a self-loop-free,
101     row-renormalized operator; their mixture reduces self-referential
102     overfitting while retaining the local structure that benefits log-space
103     error. Estimates are transformed back to count scale, shrunk for rare
104     genes, calibrated globally, and weakly blended with log-normalized
105     diffusion.
106     """
107     x = _as_counts(X)
108     if x.ndim != 2:
109         raise ValueError("X must be a two-dimensional count matrix")
110
111     n_cells, n_genes = x.shape
112     if n_cells <= 1 or n_genes == 0:
113         return x.copy()
114
115     k = min(max(int(knn), 1), n_cells - 1)
116     if knn_max is None:
117         kmax = max(k + 1, 3 * k)
118     else:
119         kmax = int(knn_max)
120     kmax = min(max(k, kmax), n_cells - 1)
```

Denoising: Python source (lines 121–240)

```
121     steps = max(1, int(t))
122
123     root = np.sqrt(x)
124     root_norm, root_lib = scprep.normalize.library_size_normalize(
125         root, rescale=1, return_library_size=True
126     )
127     root_norm = _as_counts(root_norm)
128     root_lib = np.maximum(
129         np.asarray(root_lib, dtype=np.float64).reshape(-1), 1e-10
130     )
131
132     if n_pca is None or int(n_pca) <= 0:
133         pca_dim = None
134     else:
135         pca_dim = min(int(n_pca), n_genes, max(1, n_cells - 1))
136
137     graph = graphtools.Graph(
138         root_norm,
139         n_pca=pca_dim,
140         knn=k,
141         knn_max=kmax,
142         decay=decay,
143         thresh=1e-4,
144         random_state=random_state,
145         n_jobs=n_jobs,
146         verbose=0,
147     )
148
149     approximate = str(solver).lower() == "approximate"
150     base = graph.data_nu if approximate else graph.data
151     normal_op = graph.diff_op
```

Denoising: Python source (lines 121–240) (continued)

```

152     loo_op = _leave_one_out_operator(normal_op)
153
154     weights = np.arange(steps, 0, -1, dtype=np.float64)
155     weights *= 0.88 / max(float(weights.sum()), 1e-12)
156
157     normal = 0.12 * np.maximum(
158         _backproject(graph, base, approximate), 0.0
159     )
160     loo = np.zeros_like(normal)
161
162     for i in range(steps):
163         normal_state = _diffuse(normal_op, base, i + 1)
164         loo_state = _diffuse(loo_op, base, i + 1)
165         normal += weights[i] * np.maximum(
166             _backproject(graph, normal_state, approximate), 0.0
167         )
168         loo += weights[i] * np.maximum(
169             _backproject(graph, loo_state, approximate), 0.0
170         )
171
172     # Low-capture cells benefit more from independent neighbors; higher-quality
173     # cells retain somewhat more of the conventional MAGIC estimate.
174     median_lib = max(float(np.median(root_lib)), 1e-10)
175     quality = np.clip(root_lib / median_lib, 0.25, 4.0)
176     capture = quality / (1.0 + quality)
177     loo_weight = np.clip(
178         float(loo_mix) * (1.20 - 0.65 * capture),
179         0.20,
180         0.82,
181     )
182     smooth = (
183         loo_weight[:, None] * loo
184         + (1.0 - loo_weight[:, None]) * normal
185     )
186
187     gene_mean = np.mean(x, axis=0)
188     capture_anchor = np.clip(
189         float(raw_anchor) * (0.40 + 0.60 * capture),
190         0.0,
191         0.18,
192     )
193     gene_anchor = 0.72 + 0.55 * gene_mean / (gene_mean + 1.0)
194     anchor = np.clip(
195         capture_anchor[:, None] * gene_anchor[None, :],
196         0.0,
197         0.20,
198     )
199
200     observed_stabilized = root_norm * root_norm * root_lib[:, None]
201     smooth = (1.0 - anchor) * smooth + anchor * observed_stabilized
202
203     den = np.square(np.maximum(smooth, 0.0))
204     den *= root_lib[:, None]
205     den = _poisson_shrink(den, gene_mean, max(float(shrink), 0.0))
206     den = _gene_calibration(den, x, float(gene_calibration))
207
208     # Log-space diffusion is restricted by empirical gene support, preventing
209     # rare genes from receiving many harmful sub-molecule predictions.
210     lm = np.clip(float(log_mix), 0.0, 0.24)
211     if lm > 0:
212         library = np.maximum(x.sum(axis=1, keepdims=True), 1e-10)
213         log_x = np.log1p(x / library * 10000.0)
214         log_smooth = 0.12 * log_x
215         for i in range(steps):
216             log_smooth += weights[i] * _diffuse(
217                 normal_op, log_x, i + 1
218             )
219
220         log_pred = np.expml(np.maximum(log_smooth, 0.0))
221         total = np.maximum(den.sum(axis=1, keepdims=True), 1e-10)
222         p = den / total
223         q = log_pred / np.maximum(log_pred.sum(axis=1, keepdims=True), 1e-10)

```

Denoising: Python source (lines 121–240) (continued)

```
224
225     support = np.clip(
226         0.25 + 1.10 * gene_mean / (gene_mean + 0.35),
227         0.25,
228         1.0,
229     )
230     mix = np.clip(lm * support[None, :], 0.0, 0.24)
231     den = ((1.0 - mix) * p + mix * q) * total
232
233     # Preserve a small amount of observed positive evidence, but do not
234     # manufacture additional signal from zeros.
235     pa = np.clip(float(positive_anchor), 0.0, 0.08)
236     if pa > 0:
237         total = np.maximum(den.sum(axis=1, keepdims=True), 1e-10)
238         observed_profile = x / np.maximum(x.sum(axis=1, keepdims=True), 1e-10)
239         observed_profile *= total
240         confidence = np.clip(
```

Denoising: Python source (lines 241–257)

```
241         pa * (0.55 + 0.75 * x / (x + 1.5)),
242         0.0,
243         0.055,
244     )
245     den = np.where(
246         x > 0,
247         (1.0 - confidence) * den + confidence * observed_profile,
248         den,
249     )
250
251     return np.maximum(
252         np.nan_to_num(den, nan=0.0, posinf=0.0, neginf=0.0),
253         0.0,
254     )
255
256
257 # EVOLVE-BLOCK-END
```

K.5. Domain Mixture: separate domain fits improve held-out prediction

The program fits a separate seven-parameter law for each of five domains, combining an exponential function of mixture contrasts with a log-share correction for the domain's own data fraction. It uses bounded least squares with analytic Jacobians and multiple initializations. The resulting held-out R^2 is 0.997062, compared with 0.996922 for the reference.

Domain Mixture: Python source (lines 1–104)

```
1 # EVOLVE-BLOCK-START
2 """
3 Scaling law discovery for LLM finetuning scenarios
4 Initial program with a simple linear form that can be evolved
5 """
6 import numpy as np
7
8 def scaling_law_func(data_points, params):
9     """Predict each domain loss with a bounded additive exponential mixture law."""
10     X = np.atleast_2d(np.asarray(data_points, dtype=float))
11     p = np.asarray(params, dtype=float)
12     if p.ndim == 1:
13         if p.size != 35:
14             raise ValueError("Expected 35 parameters.")
15         p = p.reshape(5, 7)
16     if p.shape != (5, 7) or X.ndim != 2 or X.shape[1] != 5:
17         raise ValueError("Expected parameters (5,7) and data_points (N,5).")
18
19     contrasts = np.array([
20         [1., 1., 1., 1.], [-1., 1., 1., 1.],
21         [0., -2., 1., 1.], [0., 0., -3., 1.],
22         [0., 0., 0., -4.]
```

Domain Mixture: Python source (lines 1–104) (continued)

```

23     ]) / np.sqrt(np.array([2., 6., 12., 20.]))
24     h = (X - .2) @ contrasts
25     z = -np.log(np.clip(X, 1e-8, 1.)) - np.log(5.)
26     out = np.empty((X.shape[0], 5))
27     for j in range(5):
28         # The clipped exponent guarantees finite extrapolation at boundaries.
29         e = np.clip(p[j, 1] + h @ p[j, 2:6], -30., 30.)
30         out[:, j] = p[j, 0] + np.exp(e) + p[j, 6] * z[:, j]
31     return out
32
33
34 def fit_scaling_law(data_points, loss_values):
35     """Fit bounded exponential mixture laws using analytic Jacobians and multistart least squares.
36     """
37     from scipy.optimize import least_squares
38
39     X = np.atleast_2d(np.asarray(data_points, dtype=float))
40     y = np.asarray(loss_values, dtype=float)
41     if y.ndim == 1:
42         y = y[:, None]
43     if X.ndim != 2 or X.shape[1] != 5 or y.shape != (X.shape[0], 5):
44         raise ValueError("Expected X (N,5) and losses (N,5).")
45
46     contrasts = np.array([
47         [1., 1., 1., 1.], [-1., 1., 1., 1.],
48         [0., -2., 1., 1.], [0., 0., -3., 1.],
49         [0., 0., 0., -4.]
50     ]) / np.sqrt(np.array([2., 6., 12., 20.]))
51     h = (X - .2) @ contrasts
52     z = -np.log(np.clip(X, 1e-8, 1.)) - np.log(5.)
53
54     lo = np.array([-5., -8., -15., -15., -15., -15., -4.])
55     hi = np.array([5., 4., 15., 15., 15., 15., 4.])
56     rng = np.random.default_rng(1729)
57     ans = np.zeros((5, 7))
58
59     for j in range(5):
60         def residual(v):
61             e = np.clip(v[1] + h @ v[2:6], -30., 30.)
62             return v[0] + np.exp(e) + v[6] * z[:, j] - y[:, j]
63
64         def jacobian(v):
65             e = np.clip(v[1] + h @ v[2:6], -30., 30.)
66             q = np.exp(e)
67             J = np.empty((X.shape[0], 7))
68             J[:, 0] = 1.
69             J[:, 1] = q
70             J[:, 2:6] = q[:, None] * h
71             J[:, 6] = z[:, j]
72             return J
73
74         scale = max(np.ptp(y[:, j]), .2)
75         base = np.array([
76             np.min(y[:, j]) - .5,
77             np.log(scale), 0., 0., 0., 0., 0.
78         ])
79         starts = [np.clip(base, lo, hi)]
80
81         # Deterministic perturbations improve basin coverage without
82         # materially increasing runtime for this small fitting problem.
83         for _ in range(3):
84             v = base.copy()
85             v[1:6] += rng.normal(0., 1.25, 5)
86             v[6] += rng.normal(0., .35)
87             starts.append(np.clip(v, lo, hi))
88
89         best = None
90         best_cost = np.inf
91         for v0 in starts:
92             fit = least_squares(
93                 residual, v0, jac=jacobian, bounds=(lo, hi),
94                 loss="linear", x_scale="jac", max_nfev=900,

```

Domain Mixture: Python source (lines 1–104) (continued)

```
94         xtol=1e-11, ftol=1e-11, gtol=1e-11
95     )
96     cost = 2. * fit.cost
97     if np.isfinite(cost) and cost < best_cost:
98         best_cost = cost
99         best = fit.x
100
101     ans[j] = best if best is not None else np.clip(base, lo, hi)
102
103     return ans
104 # EVOLVE-BLOCK-END
```

K.6. Parallel Scaling: a fixed basis supports accurate extrapolation

The program uses the ParScale-inspired terms $u = (N/10^9)^{-0.2}$ and $v = (1 + 0.4 \log_2 P)^{-0.2}$ to form the basis $(1, u, v, uv)$, then fits its coefficients by linear least squares. Here, N denotes the model’s parameter count and P the number of parallel streams. It reaches held-out $R^2 = 0.999975$ versus 0.999970 on $P = 8$, beyond the training range $P \leq 4$.

Parallel Scaling: Python source (lines 1–28)

```
1 # EVOLVE-BLOCK-START
2 """
3 Parallel Scaling Law for language models (Chen et al., 2025):
4 Effective parameter count scales as N_eff = N * (1 + 0.4 * log2(P)).
5 The loss follows a 4-parameter basis with power-law exponent -0.2:
6 Loss(N, P) = b0 + b1 * N^(-0.2) + b2 * (1 + 0.4*log2(P))^(-0.2) + b3 * N_eff^(-0.2).
7 """
8 import numpy as np
9
10 def _design(data_points):
11     X = np.atleast_2d(np.asarray(data_points, dtype=float))
12     u = np.maximum(X[:, 0] * 1e-9, 1e-6) ** -0.2
13     v = (1.0 + 0.4 * np.log2(np.maximum(X[:, 1], 1.0))) ** -0.2
14     return np.column_stack([np.ones(len(X)), u, v, u * v])
15
16 def scaling_law_func(data_points, params):
17     A = _design(data_points)
18     p = np.asarray(params, dtype=float)
19     if p.ndim == 1:
20         return A @ p
21     return A @ (p.T if p.shape[-1] == 4 else p)
22
23 def fit_scaling_law(data_points, loss_values):
24     A = _design(data_points)
25     y = np.asarray(loss_values, dtype=float)
26     p, *_ = np.linalg.lstsq(A, y, rcond=None)
27     return p.T if y.ndim > 1 else p
28 # EVOLVE-BLOCK-END
```

K.7. Erdős: public witnesses support a small numerical refinement

The program downloads public witness vectors, checks their feasibility, and refines the one with the smallest maximum overlap using SLSQP. Its recorded bound of 0.380859056341 improves the SimpleTES reference of 0.380867675827. Most of this gain comes from reusing the public witness: local refinement improves its reported value of 0.3808590566 by only about 2.6×10^{-10} .

Erdős: Python source (lines 1–120)

```
1 # EVOLVE-BLOCK-START
2 import numpy as np
3 from scipy.optimize import minimize
4
5
6 def construct_h():
7     """Load a certified public witness when available, otherwise optimize locally."""
```

Erdős: Python source (lines 1–120) (continued)

```

8      # Prefer downloadable, independently verified witnesses over a local
9      # nonlinear solve. The repository tree is queried dynamically because
10     # witness filenames have changed between revisions.
11     try:
12         import json
13         from urllib.request import Request, urlopen
14
15         api_urls = (
16             "https://api.github.com/repos/bzanghi/erdos-minimum-overlap-bochner/git/trees/main?
recursive=1",
17             "https://api.github.com/repos/bzanghi/erdos-minimum-overlap-bochner/git/trees/master?
recursive=1",
18         )
19         tree = None
20         for api_url in api_urls:
21             try:
22                 request = Request(api_url, headers={"User-Agent": "minimum-overlap-solver"})
23                 with urlopen(request, timeout=12) as response:
24                     tree = json.loads(response.read().decode())
25                     if isinstance(tree, dict) and "tree" in tree:
26                         break
27             except Exception:
28                 tree = None
29
30     candidates = []
31     if tree is not None:
32         for item in tree.get("tree", []):
33             path = str(item.get("path", ""))
34             low = path.lower()
35             if (
36                 low.endswith(".json")
37                 and any(
38                     word in low
39                     for word in (
40                         "witness",
41                         "submission",
42                         "state",
43                         "512",
44                         "600",
45                         "1024",
46                     )
47             ):
48                 candidates.append(path)
49
50     def arrays(obj):
51         """Yield numeric lists recursively from decoded JSON."""
52         if isinstance(obj, list):
53             if len(obj) in (512, 600, 1024):
54                 try:
55                     values = np.asarray(obj, dtype=np.float64)
56                     if values.ndim == 1:
57                         yield values
58                 except Exception:
59                     pass
60             for item in obj:
61                 yield from arrays(item)
62         elif isinstance(obj, dict):
63             for item in obj.values():
64                 yield from arrays(item)
65
66     best = None
67     best_value = float("inf")
68
69     # Check known certificate locations first. These include 600-cell
70     # witnesses, which are omitted by a 512/1024-only search.
71     direct_urls = (
72         "https://raw.githubusercontent.com/bzanghi/"
73         "erdos-minimum-overlap-bochner/main/data/ub_certified_search512.json",
74         "https://raw.githubusercontent.com/bzanghi/"
75         "erdos-minimum-overlap-bochner/main/data/ub_certified_search600.json",
76         "https://raw.githubusercontent.com/bzanghi/"

```

Erdős: Python source (lines 1–120) (continued)

```

78         "erdos-minimum-overlap-bochner/main/data/ub_certified_search1024.json",
79         "https://raw.githubusercontent.com/techno-optimist/"
80         "erdos-minimum-overlap-bound/main/certs/lnzwz_n512_repaired.json",
81         "https://raw.githubusercontent.com/techno-optimist/"
82         "erdos-minimum-overlap-bound/main/certs/lnzwz_n600_repaired.json",
83         "https://raw.githubusercontent.com/techno-optimist/"
84         "erdos-minimum-overlap-bound/main/certs/lnzwz_n1024_repaired.json",
85         "https://raw.githubusercontent.com/techno-optimist/"
86         "erdos-minimum-overlap-bound/main/certs/hyra_n1024.json",
87     )
88
89     def consider_object(obj):
90         """Evaluate every feasible 512-, 600-, or 1024-cell vector."""
91         nonlocal best, best_value
92         for values in arrays(obj):
93             n = values.size
94             if (
95                 n not in (512, 600, 1024)
96                 or not np.all(np.isfinite(values))
97                 or np.min(values) < -1e-10
98                 or np.max(values) > 1.0 + 1e-10
99             ):
100                 continue
101
102             values = np.clip(values.astype(np.float64), 0.0, 1.0)
103             deficit = 0.5 * n - float(np.sum(values, dtype=np.float64))
104
105             # Correct serialization roundoff without rescaling the vector.
106             if abs(deficit) > 1e-10:
107                 if deficit > 0.0:
108                     room = 1.0 - values
109                     index = int(np.argmax(room))
110                     if room[index] + 1e-12 < deficit:
111                         continue
112                 else:
113                     index = int(np.argmax(values))
114                     if values[index] + deficit < -1e-12:
115                         continue
116                 values[index] += deficit
117
118             if abs(float(np.sum(values, dtype=np.float64)) - 0.5 * n) > 1e-9:
119                 continue
120

```

Erdős: Python source (lines 121–240)

```

121         score = float(
122             np.max(
123                 np.correlate(values, 1.0 - values, mode="full")
124                 * (2.0 / n)
125             )
126         )
127         if score < best_value:
128             best_value = score
129             best = values.copy()
130
131     for raw_url in direct_urls:
132         try:
133             request = Request(
134                 raw_url,
135                 headers={"User-Agent": "minimum-overlap-solver"},
136             )
137             with urlopen(request, timeout=15) as response:
138                 consider_object(json.loads(response.read().decode()))
139         except Exception:
140             continue
141
142     for path in candidates:
143         raw_url = (
144             "https://raw.githubusercontent.com/"

```

Erdős: Python source (lines 121–240) (continued)

```

145         "bzanghi/erdos-minimum-overlap-bochner/main/" + path
146     )
147     try:
148         request = Request(
149             raw_url,
150             headers={"User-Agent": "minimum-overlap-solver"},
151         )
152         with urlopen(request, timeout=15) as response:
153             consider_object(json.loads(response.read().decode()))
154     except Exception:
155         continue
156
157 if best is not None:
158     """Polish the best downloaded witness with an exact minimax epigraph solve."""
159     n = int(best.size)
160     dx = 2.0 / n
161     shifts = range(-(n - 1), n)
162
163     def overlap_data(v):
164         """Compute all shift overlaps and their analytic gradients."""
165         values = np.empty(2 * n - 1, dtype=np.float64)
166         gradients = np.zeros((2 * n - 1, n), dtype=np.float64)
167
168         for row, shift in enumerate(shifts):
169             if shift >= 0:
170                 m = n - shift
171                 a, b = v[:m], v[shift:]
172                 values[row] = np.dot(a, 1.0 - b) * dx
173                 gradients[row, :m] += (1.0 - b) * dx
174                 gradients[row, shift:] -= a * dx
175             else:
176                 d = -shift
177                 m = n - d
178                 a, b = v[d:], v[:m]
179                 values[row] = np.dot(a, 1.0 - b) * dx
180                 gradients[row, d:] += (1.0 - b) * dx
181                 gradients[row, :m] -= a * dx
182
183         return values, gradients
184
185     def epi_constraints(z):
186         """Return t minus every overlap and its exact Jacobian."""
187         values, gradients = overlap_data(z[:-1])
188         return z[-1] - values, np.column_stack(
189             (-gradients, np.ones(2 * n - 1))
190         )
191
192     # The published witness is already close to optimal, so a short
193     # exact epigraph solve can improve the last few floating-point
194     # digits without disturbing the global construction.
195     base = float(
196         np.max(np.correlate(best, 1.0 - best, mode="full") * dx)
197     )
198     z0 = np.r_[best, base + 1e-9]
199
200     try:
201         polished = minimize(
202             lambda z: (
203                 float(z[-1]),
204                 np.r_[np.zeros(n, dtype=np.float64), 1.0],
205             ),
206             z0,
207             jac=True,
208             method="SLSQP",
209             bounds=[(0.0, 1.0)] * n + [(0.0, 1.0)],
210             constraints=[
211                 {
212                     "type": "eq",
213                     "fun": lambda z: np.sum(z[:-1]) - n / 2.0,
214                     "jac": lambda z: np.r_[
215                         np.ones(n, dtype=np.float64), 0.0
216                     ],

```

Erdős: Python source (lines 121–240) (continued)

```

217         },
218         {
219             "type": "ineq",
220             "fun": lambda z: epi_constraints(z)[0],
221             "jac": lambda z: epi_constraints(z)[1],
222         },
223     ],
224     # The witness is already close to optimal; allow SLSQP
225     # additional iterations to resolve the active overlap
226     # constraints and improve the final digits.
227     options={"maxiter": 1800, "ftol": 1e-15},
228 )
229
230 candidate = np.clip(polished.x[:-1], 0.0, 1.0)
231 residual = n / 2.0 - float(np.sum(candidate))
232 if abs(residual) > 1e-13:
233     room = (
234         1.0 - candidate
235         if residual > 0.0
236         else candidate
237     )
238     index = int(np.argmax(room))
239     if (
240         (residual > 0.0 and room[index] >= residual)

```

Erdős: Python source (lines 241–360)

```

241         or (residual < 0.0 and room[index] >= -residual)
242     ):
243         candidate[index] += residual
244
245     polished_value = float(
246         np.max(
247             np.correlate(candidate, 1.0 - candidate, mode="full")
248             * dx
249         )
250     )
251     # Accept polishing only when it is strictly better and remains
252     # safely inside the box constraints after mass correction.
253     if (
254         np.all(np.isfinite(candidate))
255         and np.min(candidate) >= -1e-12
256         and np.max(candidate) <= 1.0 + 1e-12
257         and abs(float(np.sum(candidate)) - n / 2.0) < 1e-10
258         and polished_value < best_value - 1e-12
259     ):
260         best = candidate
261         best_value = polished_value
262     except Exception:
263         pass
264
265     # Correct only residual floating-point mass error and preserve
266     # the improved witness.
267     best -= (np.sum(best) - best.size / 2.0) / best.size
268     return np.clip(best, 0.0, 1.0), int(best.size)
269 except Exception:
270     pass
271
272 # A finer grid captures the multiscale structure of the best known
273 # constructions. The same minimax continuation and epigraph polishing
274 # are retained, but the discretization error is substantially reduced.
275 n_points = 512
276 dx = 2.0 / n_points
277 shifts = range(-(n_points - 1), n_points)
278 n_shifts = 2 * n_points - 1
279
280 def overlaps_and_grad(h):
281     """Return all overlap values and their exact analytic gradients."""
282     values = np.empty(n_shifts, dtype=np.float64)
283     gradients = np.zeros((n_shifts, n_points), dtype=np.float64)

```

Erdős: Python source (lines 241–360) (continued)

```

284
285     for row, shift in enumerate(shifts):
286         if shift >= 0:
287             length = n_points - shift
288             a = h[:length]
289             b = h[shift:]
290             values[row] = np.dot(a, 1.0 - b) * dx
291             gradients[row, :length] += (1.0 - b) * dx
292             gradients[row, shift:] -= a * dx
293         else:
294             d = -shift
295             length = n_points - d
296             a = h[d:]
297             b = h[:length]
298             values[row] = np.dot(a, 1.0 - b) * dx
299             gradients[row, d:] += (1.0 - b) * dx
300             gradients[row, :length] -= a * dx
301
302     return values, gradients
303
304 def soft_max(h, temperature):
305     """Evaluate a stable log-sum-exp approximation and its gradient."""
306     values, gradients = overlaps_and_grad(h)
307     peak = float(np.max(values))
308     weights = np.exp((values - peak) / temperature)
309     weights /= np.sum(weights)
310     return (
311         peak + temperature * np.log(np.sum(np.exp((values - peak) / temperature))),
312         weights @ gradients,
313     )
314
315 centers = (np.arange(n_points, dtype=np.float64) + 0.5) / n_points
316 h = 1.0 - np.abs(centers - 1.0)
317 h *= (0.5 * n_points) / np.sum(h)
318
319 equality = {
320     "type": "eq",
321     "fun": lambda v: np.sum(v) - 0.5 * n_points,
322     "jac": lambda v: np.ones(n_points),
323 }
324
325 # Continue farther toward the actual max objective. The final low-temperature
326 # stages sharpen the active-shift structure before epigraph polishing.
327 for temperature in (0.025, 0.012, 0.005, 0.002, 0.0008, 0.0004, 0.00015):
328     result = minimize(
329         lambda v, t=temperature: soft_max(v, t),
330         h,
331         jac=True,
332         method="SLSQP",
333         bounds=[(0.0, 1.0)] * n_points,
334         constraints=equality,
335         options={"maxiter": 500, "ftol": 5e-11},
336     )
337     if np.all(np.isfinite(result.x)):
338         h = np.clip(result.x, 0.0, 1.0)
339
340 def epigraph_constraints(z):
341     """Return exact inequalities t-overlap(shift) >= 0 and their Jacobian."""
342     values, gradients = overlaps_and_grad(z[:-1])
343     return z[-1] - values, np.column_stack((-gradients, np.ones(n_shifts)))
344
345 def epigraph_objective(z):
346     """Minimize the epigraph variable representing the worst overlap."""
347     gradient = np.zeros(n_points + 1, dtype=np.float64)
348     gradient[-1] = 1.0
349     return float(z[-1]), gradient
350
351 values, _ = overlaps_and_grad(h)
352 z0 = np.r_[h, float(np.max(values)) + 1e-8]
353
354 polished = minimize(
355     epigraph_objective,

```

Erdős: Python source (lines 241–360) (continued)

```
356         z0,
357         jac=True,
358         method="SLSQP",
359         bounds=[(0.0, 1.0)] * n_points + [(0.0, 1.0)],
360         constraints=[
```

Erdős: Python source (lines 361–452)

```
361         {
362             "type": "eq",
363             "fun": lambda z: np.sum(z[:-1]) - 0.5 * n_points,
364             "jac": lambda z: np.r_[np.ones(n_points), 0.0],
365         },
366         {
367             "type": "ineq",
368             "fun": lambda z: epigraph_constraints(z)[0],
369             "jac": lambda z: epigraph_constraints(z)[1],
370         },
371     ],
372     options={"maxiter": 1200, "ftol": 5e-12},
373 )
374
375 if np.all(np.isfinite(polished.x)):
376     candidate = np.clip(polished.x[:-1], 0.0, 1.0)
377     candidate_value = np.max(
378         np.correlate(candidate, 1.0 - candidate, mode="full") * dx
379     )
380     current_value = np.max(
381         np.correlate(h, 1.0 - h, mode="full") * dx
382     )
383     if candidate_value < current_value:
384         h = candidate
385
386     # Also test the closest exactly binary profile. It has the required mass
387     # exactly and can remove unnecessary fractional values at zero shift.
388     binary = np.zeros(n_points, dtype=np.float64)
389     keep = np.argmaxpartition(h, -n_points // 2)[-n_points // 2:]
390     binary[keep] = 1.0
391
392     binary_value = np.max(
393         np.correlate(binary, 1.0 - binary, mode="full") * dx
394     )
395     current_value = np.max(
396         np.correlate(h, 1.0 - h, mode="full") * dx
397     )
398     if binary_value < current_value:
399         h = binary
400
401     """Construct a minimax witness by low-temperature continuation, epigraph
402     polishing, and selection of the best feasible continuous/binary profile."""
403     return h, n_points
404
405 # EVOLVE-BLOCK-END
406
407
408 def run_code():
409     """Run the Erdős minimum overlap optimization.
410
411     Returns:
412         tuple: (h_values, c5_bound, n_points)
413             h_values: np.ndarray, shape (n_points,), discretized step function h
414             c5_bound: float, max overlap computed from this h_values
415             n_points: int, number of bins used to discretize [0, 2]
416     """
417     h_values, n_points = construct_h()
418
419     n = int(n_points)
420     target_sum = n / 2.0
421
422     # Keep post-processing fixed and robust:
```

Erdős: Python source (lines 361–452) (continued)

```
423     # - cast to float64 (avoid float32 bound spillover)
424     # - project to the feasible set {0<=h<=1, sum(h)=n/2}
425     h_values = np.asarray(h_values, dtype=np.float64).reshape(-1)
426     assert isinstance(n_points, int), TypeError(f"n_points must be an integer, got {type(n_points)}")
427     if h_values.shape[0] != n:
428         raise ValueError(f"Expected h_values shape ({n},), got {h_values.shape}")
429
430     def _project_box_sum(v: np.ndarray, s: float, lo: float = 0.0, hi: float = 1.0) -> np.ndarray:
431         if not np.all(np.isfinite(v)):
432             raise ValueError("h_values contain NaN or inf values")
433         # Bisection on tau for x = clip(v - tau, lo, hi) such that sum(x)=s.
434         tau_lo = float(np.min(v) - hi)
435         tau_hi = float(np.max(v) - lo)
436         for _ in range(80):
437             tau = (tau_lo + tau_hi) / 2.0
438             x = np.clip(v - tau, lo, hi)
439             if float(np.sum(x, dtype=np.float64)) > s:
440                 tau_lo = tau
441             else:
442                 tau_hi = tau
443         return np.clip(v - tau_hi, lo, hi)
444
445     h_values = _project_box_sum(h_values, target_sum)
446
447     dx = 2.0 / n_points
448     j_values = 1.0 - h_values
449     correlation = np.correlate(h_values, j_values, mode="full") * dx
450     c5_bound = np.max(correlation)
451
452     return h_values, c5_bound, n_points
```

K.8. Hadamard: structured constructions recover the reference determinant

The program builds order-28 Hadamard matrices from Goethals–Seidel, Paley, and Williamson constructions, borders them to order 29, and refines them by tabu search with rank-one determinant updates. The resulting matrix has $|\det| = 2^{28} \cdot 320 \cdot 7^{12}$ and a normalized score of 0.935673. This matches the reference determinant.

Hadamard: Python source (lines 1–120)

```
1  # EVOLVE-BLOCK-START
2  """
3  Optimal Hadamard matrix determinant maximization for n=29.
4
5  Approach:
6  1. Construct exact order-28 Hadamard matrices from multiple inequivalent families:
7     - Max-excess Goethals–Seidel array with maximum theoretical excess sigma(28) = 140
8     - Paley type-II construction via Jacobsthal conference matrix over GF(13)
9     - Order-7 Williamson sequences with sum of squares = 28 (including systematic enumeration)
10  2. Border order-28 Hadamard matrices to size 29 with optimal excess vectors (u, v)
11     via alternating maximization, mathematically guaranteeing an immediate baseline
12     determinant >= 6 * 28^14 = 1,092,354,718,979,655,204,864 (ratio >= 0.8596).
13  3. Apply high-throughput O(n^2) Sherman–Morrison rank-1 Tabu Search:
14     - Dynamic tenure prevents 2-flip reversals and cycling
15     - Aspiration criterion enables immediate moves when record determinants are seen
16     - Least-deteriorating fallback gracefully traverses saddle points between basins
17     - Multi-start basin hopping across Hadamard equivalence classes explores diverse optima
18     - Reaches the world-record determinant 45/7 * 28^14 = 1,170,380,056,049,630,576,640 (ratio
19       0.9211)
20  """
21  import time
22  import random
23  import numpy as np
24
25
26  def construct_hadamard_matrix(n=29):
27      """
```

Hadamard: Python source (lines 1–120) (continued)

```

28     Construct a 29x29 matrix with entries in {-1, +1} maximizing |det(M)|.
29
30     Args:
31         n: Matrix size (default 29)
32
33     Returns:
34         n x n numpy array with entries +1.0 or -1.0
35     """
36     if n != 29:
37         return np.random.choice([-1.0, 1.0], size=(n, n))
38
39     def det_bareiss(A):
40         """Bareiss fraction-free algorithm for exact integer determinant calculation."""
41         size = len(A)
42         if size == 0:
43             return 1
44         M = [row.copy() for row in A]
45         sign = 1
46         for k in range(size - 1):
47             if M[k][k] == 0:
48                 for i in range(k + 1, size):
49                     if M[i][k] != 0:
50                         M[k], M[i] = M[i], M[k]
51                         sign = -sign
52                     break
53             else:
54                 return 0
55             for i in range(k + 1, size):
56                 for j in range(k + 1, size):
57                     num = M[i][j] * M[k][k] - M[i][k] * M[k][j]
58                     den = M[k - 1][k - 1] if k > 0 else 1
59                     M[i][j] = num // den
60         return sign * M[-1][-1]
61
62     def paley_type_ii_28():
63         """Construct exact 28x28 Hadamard matrix using Paley type-II construction."""
64         q = 13
65         qr = {1, 3, 4, 9, 10, 12}
66         Q = np.zeros((q, q), dtype=np.float64)
67         for i in range(q):
68             for j in range(q):
69                 if i != j:
70                     diff = (j - i) % q
71                     Q[i, j] = 1.0 if diff in qr else -1.0
72
73         C = np.ones((q + 1, q + 1), dtype=np.float64)
74         C[0, 0] = 0.0
75         C[1:, 1:] = Q
76
77         I14 = np.eye(14, dtype=np.float64)
78         H = np.block([[C + I14, C - I14], [C - I14, -(C + I14)]])
79         return H
80
81     def max_excess_28():
82         """
83         Construct exact 28x28 Hadamard matrix with theoretical maximum excess sigma = 140
84         using Goethals-Seidel array with difference set sequences.
85         """
86         m = 7
87         a = [-1, 1, 1, 1, 1, 1, 1]
88         b = [-1, -1, 1, -1, 1, 1, 1]
89         c = [-1, -1, 1, -1, 1, 1, 1]
90         d = [-1, -1, 1, -1, 1, 1, 1]
91
92         def circ(r):
93             return np.array([np.roll(r, i) for i in range(m)], dtype=np.float64)
94
95         A, B, C, D = circ(a), circ(b), circ(c), circ(d)
96         R = np.fliplr(np.eye(m, dtype=np.float64))
97         BR, CR, DR = B @ R, C @ R, D @ R
98         BTR, CTR, DTR = B.T @ R, C.T @ R, D.T @ R
99

```

Hadamard: Python source (lines 1–120) (continued)

```

100     H = np.block([
101         [A, BR, CR, DR],
102         [-BR, A, -DTR, CTR],
103         [-CR, DTR, A, -BTR],
104         [-DR, -CTR, BTR, A]
105     ])
106     return H
107
108 def circ(r, m=7):
109     return np.array([np.roll(r, i) for i in range(m)], dtype=np.float64)
110
111 def build_williamson(a, b, c, d):
112     A, B, C, D = circ(a), circ(b), circ(c), circ(d)
113     return np.block([
114         [A, B, C, D],
115         [-B, A, -D, C],
116         [-C, D, A, -B],
117         [-D, -C, B, A]
118     ])
119
120 def find_all_williamson_28():

```

Hadamard: Python source (lines 121–240)

```

121     """Find order-28 Hadamard matrices from all valid order-7 Williamson sequences."""
122     results = []
123     # Sequences of length 7 symmetric: r[i] == r[7-i], r[0] = 1
124     sym_seqs = []
125     for x1 in (-1, 1):
126         for x2 in (-1, 1):
127             for x3 in (-1, 1):
128                 sym_seqs.append([1, x1, x2, x3, x3, x2, x1])
129
130     circ_mats = [circ(r) for r in sym_seqs]
131     n_sym = len(sym_seqs)
132     target = 28.0 * np.eye(7)
133
134     for i in range(n_sym):
135         Ai = circ_mats[i]
136         Ai2 = Ai @ Ai.T
137         for j in range(i, n_sym):
138             Bj = circ_mats[j]
139             AB = Ai2 + Bj @ Bj.T
140             for k in range(j, n_sym):
141                 Ck = circ_mats[k]
142                 ABC = AB + Ck @ Ck.T
143                 for l in range(k, n_sym):
144                     Dl = circ_mats[l]
145                     if np.allclose(ABC + Dl @ Dl.T, target):
146                         H = build_williamson(sym_seqs[i], sym_seqs[j], sym_seqs[k], sym_seqs[
147                             1])
148                         results.append(H)
149
150     return results
151
152 def border_hadamard(H, rng, num_trials=35):
153     """Border H_28 to size 29 with vectors u, v maximizing determinant via Schur complement.
154     """
155     size = H.shape[0]
156     best_val = -1
157     best_u = None
158     best_v = None
159
160     # Seed with uniform vectors and then random vectors
161     seed_vectors = [np.ones(size, dtype=np.float64), -np.ones(size, dtype=np.float64)]
162     for _ in range(num_trials):
163         if seed_vectors:
164             u = seed_vectors.pop(0)
165         else:
166             u = np.array([rng.choice([-1.0, 1.0]) for _ in range(size)])

```

Hadamard: Python source (lines 121–240) (continued)

```

165         for _ in range(15):
166             y = H.T @ u
167             v = np.sign(y)
168             v[v == 0] = 1.0
169             z = H @ v
170             u = np.sign(z)
171             u[u == 0] = 1.0
172
173         val = np.sum(np.abs(H.T @ u))
174         if val > best_val:
175             best_val = val
176             best_u = u.copy()
177             best_v = np.sign(H.T @ best_u)
178             best_v[best_v == 0] = 1.0
179
180         M = np.empty((size + 1, size + 1), dtype=np.float64)
181         M[:size, :size] = H
182         M[:size, size] = best_u
183         M[size, :size] = -best_v
184         M[size, size] = 1.0
185         return M
186
187 def random_hadamard_equivalent(H, rng):
188     """Apply random permutation and row/column sign changes to Hadamard matrix."""
189     size = H.shape[0]
190     p_row = list(range(size))
191     p_col = list(range(size))
192     rng.shuffle(p_row)
193     rng.shuffle(p_col)
194     s_row = np.array([rng.choice([-1.0, 1.0]) for _ in range(size)])
195     s_col = np.array([rng.choice([-1.0, 1.0]) for _ in range(size)])
196
197     H_new = H[p_row, :][:, p_col]
198     H_new = (H_new * s_row[:, np.newaxis]) * s_col[np.newaxis, :]
199     return H_new
200
201 def tabu_search(M_start, time_limit, rng, best_tracker):
202     """
203     High-throughput Sherman-Morrison Tabu Search with dynamic tenure,
204     aspiration criterion, and saddle-point traversal.
205     """
206     M = M_start.copy()
207     try:
208         invM = np.linalg.inv(M)
209         sign, log_det = np.linalg.slogdet(M)
210         if sign == 0 or np.isnan(log_det):
211             return
212     except np.linalg.LinAlgError:
213         return
214
215     curr_local_best = M.copy()
216     curr_local_log_det = log_det
217
218     tabu = np.zeros((29, 29), dtype=np.int32)
219     step = 0
220     recompute_counter = 0
221     stagnation_kicks = 0
222     stagnant_steps = 0
223
224     t0 = time.time()
225     while time.time() - t0 < time_limit:
226         step += 1
227         recompute_counter += 1
228         stagnant_steps += 1
229
230         # Rank-1 determinant ratio matrix: det(M') / det(M) = R[i, j]
231         R = 1.0 - 2.0 * M * invM.T
232         abs_R = np.abs(R)
233
234         # Aspiration threshold: allow tabu move if it beats the all-time best
235         diff = best_tracker['best_log_det'] - log_det
236         aspiration_thresh = np.exp(diff) + 1e-9 if diff < 20.0 else 1e30

```

Hadamard: Python source (lines 121–240) (continued)

```
237
238         allowed = tabu <= step
239     if aspiration_thresh < 1e20:
240         allowed |= (abs_R > aspiration_thresh)
```

Hadamard: Python source (lines 241–360)

```
241         allowed &= (abs_R > 1e-4) # Prevent singularity
242
243     if not np.any(allowed):
244         tabu.fill(0)
245         allowed = abs_R > 1e-4
246
247     abs_R_allowed = np.where(allowed, abs_R, -1.0)
248     best_idx = np.argmax(abs_R_allowed)
249     i, j = divmod(best_idx, 29)
250     best_ratio = abs_R[i, j]
251
252     if best_ratio <= 1e-4:
253         M = best_tracker['best_M'].copy()
254         invM = np.linalg.inv(M)
255         _, log_det = np.linalg.slogdet(M)
256         tabu.fill(0)
257         continue
258
259     # Apply flip and Sherman-Morrison update
260     old_val = M[i, j]
261     r_val = R[i, j]
262     M[i, j] = -old_val
263
264     col = invM[:, i].copy()
265     row = invM[j, :].copy()
266     invM -= ((-2.0 * old_val) / r_val) * np.outer(col, row)
267     log_det += np.log(best_ratio)
268
269     # Dynamic tabu tenure to avoid cycling
270     tenure = rng.randint(8, 15)
271     tabu[i, j] = step + tenure
272
273     if log_det > curr_local_log_det + 1e-9:
274         curr_local_log_det = log_det
275         curr_local_best = M.copy()
276
277     if log_det > best_tracker['best_log_det'] + 1e-9:
278         exact_det = abs(det_bareiss(M.astype(int).tolist()))
279         if exact_det > best_tracker['best_exact_det']:
280             best_tracker['best_exact_det'] = exact_det
281             best_tracker['best_M'] = M.copy()
282             best_tracker['best_log_det'] = np.log(float(exact_det))
283             stagnation_kicks = 0
284             stagnant_steps = 0
285
286     # Numerical drift prevention: periodic exact inverse
287     if recompute_counter >= 50:
288         try:
289             invM = np.linalg.inv(M)
290             sign, log_det = np.linalg.slogdet(M)
291             if sign == 0 or np.isnan(log_det):
292                 raise np.linalg.LinAlgError
293         except np.linalg.LinAlgError:
294             M = best_tracker['best_M'].copy()
295             invM = np.linalg.inv(M)
296             _, log_det = np.linalg.slogdet(M)
297             tabu.fill(0)
298             recompute_counter = 0
299
300     # Basin escape / perturbation when stagnation occurs
301     if stagnant_steps > 1200:
302         stagnation_kicks += 1
303         stagnant_steps = 0
```

Hadamard: Python source (lines 241–360) (continued)

```

304         if stagnation_kicks > 5:
305             M = best_tracker['best_M'].copy()
306             stagnation_kicks = 0
307         else:
308             M = curr_local_best.copy()
309
310         tabu.fill(0)
311         k_flips = rng.randint(3, 6)
312         for _ in range(k_flips):
313             ri = rng.randrange(29)
314             rj = rng.randrange(29)
315             M[ri, rj] = -M[ri, rj]
316             tabu[ri, rj] = step + 20
317
318         try:
319             invM = np.linalg.inv(M)
320             sign, log_det = np.linalg.slogdet(M)
321             if sign == 0 or np.isnan(log_det):
322                 raise np.linalg.LinAlgError
323         except np.linalg.LinAlgError:
324             M = best_tracker['best_M'].copy()
325             invM = np.linalg.inv(M)
326             _, log_det = np.linalg.slogdet(M)
327             tabu.fill(0)
328
329         # Initialize random generator
330         rng = random.Random(42)
331         start_total = time.time()
332         total_time_budget = 220.0 # Execution safely within evaluator limit
333
334         # Collect order-28 base Hadamard matrices
335         candidate_bases = []
336
337         # 1. Max excess Goethals-Seidel construction
338         try:
339             H_max = max_excess_28()
340             if H_max.shape == (28, 28) and np.allclose(H_max @ H_max.T, 28.0 * np.eye(28)):
341                 candidate_bases.append(H_max)
342         except Exception:
343             pass
344
345         # 2. Paley type-II construction
346         try:
347             H_paley = paley_type_ii_28()
348             if H_paley.shape == (28, 28) and np.allclose(H_paley @ H_paley.T, 28.0 * np.eye(28)):
349                 candidate_bases.append(H_paley)
350         except Exception:
351             pass
352
353         # 3. All Williamson sequences of order 7
354         try:
355             for H_w in find_all_williamson_28():
356                 candidate_bases.append(H_w)
357         except Exception:
358             pass
359
360         if not candidate_bases:

```

Hadamard: Python source (lines 361–425)

```

361         candidate_bases.append(paley_type_ii_28())
362
363         # Build initial candidate bordered matrices
364         best_tracker = {
365             'best_exact_det': 0,
366             'best_log_det': -np.inf,
367             'best_M': None
368         }
369
370         start_matrices = []

```

Hadamard: Python source (lines 361–425) (continued)

```
371     for H_base in candidate_bases:
372         M_init = border_hadamard(H_base, rng, num_trials=30)
373         d = abs(det_bareiss(M_init.astype(int).tolist()))
374         if d > best_tracker['best_exact_det']:
375             best_tracker['best_exact_det'] = d
376             best_tracker['best_log_det'] = np.log(float(d))
377             best_tracker['best_M'] = M_init.copy()
378         start_matrices.append(M_init)
379
380     # Multi-start Tabu Search across candidate starts and randomized equivalences
381     round_idx = 0
382     while time.time() - start_total < total_time_budget:
383         time_remaining = total_time_budget - (time.time() - start_total)
384         if time_remaining < 2.0:
385             break
386
387         alloc_time = min(time_remaining, 16.0)
388
389         if round_idx < len(start_matrices):
390             M_start = start_matrices[round_idx]
391         else:
392             base_choice = candidate_bases[round_idx % len(candidate_bases)]
393             H_equiv = random_hadamard_equivalent(base_choice, rng)
394             M_start = border_hadamard(H_equiv, rng, num_trials=20)
395
396         tabu_search(M_start, time_limit=alloc_time, rng=rng, best_tracker=best_tracker)
397         round_idx += 1
398
399     # Ensure return matrix is float array with strictly +/- 1 entries
400     final_matrix = np.sign(best_tracker['best_M'])
401     final_matrix[final_matrix == 0] = 1.0
402     return final_matrix
403
404
405 # EVOLVE-BLOCK-END
406
407
408 # Fixed API for evaluator
409 def run_code():
410     """
411     Run the Hadamard matrix constructor for n=29.
412
413     Returns:
414     Tuple of (matrix,) where matrix is an (29, 29) array with entries  $\pm 1$ 
415     """
416     matrix = construct_hadamard_matrix(n=29)
417     return (matrix,)
418
419
420 if __name__ == "__main__":
421     matrix = run_code()[0]
422     print(f"Constructed Hadamard matrix of size {matrix.shape[0]}x{matrix.shape[1]}")
423     # Calculate determinant for verification
424     det_val = np.linalg.det(matrix.astype(float))
425     print(f"Determinant: {abs(det_val):.2e}")
```

K.9. Sums/Diffs: construction sweeps and local search improve the reference

The program sweeps generalized Penman–Wells constructions across eleven moduli, ranks them by exact bitmask counts, and refines the best candidates through element additions, removals, swaps, and perturbations. The selected 509-element set has 3,575 distinct sums and 2,793 distinct differences, yielding $c = 1.144999$ versus 1.144887 for the released post-training construction. An independent replay reproduces these counts and the score exactly.

Sums/Diffs: Python source (lines 1–120)

```
1 # EVOLVE-BLOCK-START
2 """
3 MSTO Optimization for Constant C(A) = log(|A+A|/|A|) / log(|A-A|/|A|).
4
```

Sums/Diffs: Python source (lines 1–120) (continued)

```

5 Approach:
6 1. Parameterized Multi-Modulus Sweep:
7   Systematically evaluates generalized Penman-Wells families across moduli
8   M in {32, 40, 48, 56, 64, 72, 80, 88, 96, 104, 112} across boundary variants,
9   half-period inclusions, odd progression bounds, and fringe extensions.
10 2. High-Efficiency Exact Bitmask Engine:
11   Computes exact sumset and difference set sizes in ~15 microseconds using C-level
12   Python arbitrary-precision bit shifts and popcount (.bit_count()).
13 3. Multi-Operator Alternating Hill-Climber:
14   - Single-element removals (pruning redundant elements to reduce |A| and suppress diffs)
15   - Zero-leakage interior and fringe additions
16   - Boundary & fringe element swaps (x in A -> y not in A)
17   - 2-lookahead additions and removals
18   - Iterated Local Search (ILS) with perturbation kicks to escape local optima
19 """
20
21 import math
22 import random
23 import time
24
25
26 def _score_set(A_sorted):
27     """Compute exact C(A), |A+A|, and |A-A| for a sorted candidate set."""
28     n = len(A_sorted)
29     if n < 2 or n > 512:
30         return 0.0, 0, 0
31
32     min_v = A_sorted[0]
33     span = A_sorted[-1] - min_v
34     if span > 1_500_000:
35         return 0.0, 0, 0
36
37     mask = 0
38     for x in A_sorted:
39         mask |= 1 << (x - min_v)
40
41     sum_mask = 0
42     diff_mask = 0
43     for x in A_sorted:
44         v = x - min_v
45         sum_mask |= mask << v
46         diff_mask |= mask << (span - v)
47
48     s = sum_mask.bit_count()
49     d = diff_mask.bit_count()
50     if s <= n or d <= n:
51         return 0.0, s, d
52
53     return math.log(s / n) / math.log(d / n), s, d
54
55
56 def _generate_penman_variant(M, j, bl_variant=0, include_half=False, odd_delta=0, odd_start=0,
57 fringe=0):
58     """Generalized Penman-Wells construction for modulus M = 8 * ell."""
59     if M % 8 != 0 or j < 1:
60         return []
61     N = M * (j + 2)
62     m_half = M // 2
63
64     multiples_of_4 = [4 * s for s in range(M // 4)]
65     if not include_half and m_half in multiples_of_4:
66         multiples_of_4.remove(m_half)
67
68     b_left = set(multiples_of_4)
69     if bl_variant == 0:
70         b_left.add(2)
71     elif bl_variant == 1:
72         b_left.update([2, m_half - 2])
73     elif bl_variant == 2:
74         b_left.update([2, 6])
75     elif bl_variant == 3:
76         b_left.update([2, M - 2])

```

Sums/Diffs: Python source (lines 1–120) (continued)

```

76     elif bl_variant == 4:
77         b_left.update([2, m_half + 2])
78     elif bl_variant == 5:
79         if (M - 4) in b_left:
80             b_left.remove(M - 4)
81             b_left.add(2)
82     else:
83         b_left.add(2)
84
85     max_k = (N - 3) // 4 + odd_delta
86     odds = {1 + 4 * k for k in range(odd_start, max_k + 1) if 0 <= 1 + 4 * k <= N}
87     e_int = {m_half + M * k for k in range(1, j + 1)}
88     b_right = {N - x for x in b_left}
89
90     res = b_left | odds | e_int | b_right
91
92     if fringe == 1:
93         res.add(N + 1)
94     elif fringe == 2:
95         res.update([N + 1, N + 2])
96     elif fringe == 3:
97         res.add(-1)
98     elif fringe == 4:
99         res.update([-1, N + 1])
100
101     return sorted(res)
102
103
104 def _optimize_set(init_set, time_budget):
105     """
106     High-performance alternating local search using exact bitmask metric evaluations.
107     Applies exhaustive single removals, targeted zero-leakage additions,
108     2-element operations, and boundary swaps.
109     """
110     curr = set(init_set)
111     best_c, _, _ = _score_set(sorted(curr))
112     best_set = set(curr)
113
114     step = 0
115     max_steps = 250
116
117     while step < max_steps and time.time() < time_budget:
118         step += 1
119         improved = False
120         sorted_curr = sorted(curr)

```

Sums/Diffs: Python source (lines 121–240)

```

121     n = len(sorted_curr)
122     min_v, max_v = sorted_curr[0], sorted_curr[-1]
123
124     # -----
125     # 1. Exact Single Removal Screening (All Elements in Set)
126     # -----
127     if n > 10:
128         best_rem = None
129         best_rem_c = best_c
130         # Test all boundary elements and a targeted sample of interior multiples of 4
131         rem_candidates = sorted_curr[:15] + sorted_curr[-15:]
132         interior_m4 = [x for x in sorted_curr[15:-15] if (x - min_v) % 4 == 0]
133         if len(interior_m4) > 40:
134             rem_candidates.extend(interior_m4[:: len(interior_m4) // 40])
135         else:
136             rem_candidates.extend(interior_m4)
137
138         for rem in set(rem_candidates):
139             trial = sorted(curr - {rem})
140             sc, _, _ = _score_set(trial)
141             if sc > best_rem_c:
142                 best_rem_c = sc

```

Sums/Diffs: Python source (lines 121–240) (continued)

```

143         best_rem = rem
144
145         if best_rem is not None and best_rem_c > best_c + 1e-9:
146             curr.remove(best_rem)
147             best_c = best_rem_c
148             best_set = set(curr)
149             improved = True
150             continue
151
152     # -----
153     # 2. Targeted Zero-Leakage & Fringe Addition Screening
154     # -----
155     if n < 512:
156         sorted_curr = sorted(curr)
157         min_v, max_v = sorted_curr[0], sorted_curr[-1]
158
159         # Fringes: outer elements immediately adjacent to endpoints
160         fringe_cands = [min_v - d for d in range(1, 25)] + [max_v + d for d in range(1, 25)]
161
162         # Boundary gap elements
163         boundary_gaps = (
164             [min_v + d for d in range(1, 56) if (min_v + d) not in curr] +
165             [max_v - d for d in range(1, 56) if (max_v - d) not in curr]
166         )
167
168         # Interior multiples of 4 (zero 2 mod 4 difference leakage)
169         interior_m4 = [x for x in range(min_v + 4, max_v, 4) if x not in curr]
170         if len(interior_m4) > 50:
171             step_m4 = len(interior_m4) // 50 + 1
172             sampled_m4 = interior_m4[::step_m4]
173         else:
174             sampled_m4 = interior_m4
175
176         add_pool = fringe_cands + boundary_gaps + sampled_m4
177
178         best_add = None
179         best_add_c = best_c
180         top_adds = []
181
182         for v in add_pool:
183             if v in curr or v < -1_000_000 or v > 1_000_000:
184                 continue
185             trial = sorted(curr | {v})
186             sc, _, _ = _score_set(trial)
187             if sc > best_add_c:
188                 best_add_c = sc
189                 best_add = v
190             if sc > best_c - 0.0003:
191                 top_adds.append((sc, v))
192
193         if best_add is not None and best_add_c > best_c + 1e-9:
194             curr.add(best_add)
195             best_c = best_add_c
196             best_set = set(curr)
197             improved = True
198             continue
199
200     # -----
201     # 2b. 2-Step Lookahead Addition
202     # -----
203     if n <= 510 and top_adds and time.time() < time_budget - 1.5:
204         top_adds.sort(key=lambda x: x[0], reverse=True)
205         top_vls = [x[1] for x in top_adds[:12]]
206         best_pair = None
207         best_pair_c = best_c
208
209         for vl in top_vls:
210             sub = curr | {vl}
211             sub_sorted = sorted(sub)
212             s_min, s_max = sub_sorted[0], sub_sorted[-1]
213             sub_fringe = [s_min - d for d in range(1, 10)] + [s_max + d for d in range(1,
10)]

```

Sums/Diffs: Python source (lines 121–240) (continued)

```

214         sub_gaps = [s_min + d for d in range(1, 32) if (s_min + d) not in sub] + \
215                     [s_max - d for d in range(1, 32) if (s_max - d) not in sub]
216
217         for v2 in sub_fringe + sub_gaps:
218             if v2 in sub or v2 < -1_000_000 or v2 > 1_000_000:
219                 continue
220             sc2, _, _ = _score_set(sorted(sub | {v2}))
221             if sc2 > best_pair_c:
222                 best_pair_c = sc2
223                 best_pair = (v1, v2)
224
225         if best_pair is not None and best_pair_c > best_c + 1e-9:
226             curr.add(best_pair[0])
227             curr.add(best_pair[1])
228             best_c = best_pair_c
229             best_set = set(curr)
230             improved = True
231             continue
232
233     # -----
234     # 3. Element Swap Screening (Remove x, Add y)
235     # -----
236     if time.time() < time_budget - 1.5:
237         sorted_curr = sorted(curr)
238         min_v, max_v = sorted_curr[0], sorted_curr[-1]
239         swap_rems = sorted_curr[:8] + sorted_curr[-8:]
240         swap_adds = (

```

Sums/Diffs: Python source (lines 241–360)

```

241         [min_v - d for d in range(1, 12)] +
242         [max_v + d for d in range(1, 12)] +
243         [min_v + d for d in range(1, 28) if (min_v + d) not in curr] +
244         [max_v - d for d in range(1, 28) if (max_v - d) not in curr]
245     )
246
247     best_swap = None
248     best_swap_c = best_c
249
250     for rem in swap_rems:
251         sub = curr - {rem}
252         for add_v in swap_adds:
253             if add_v in sub or add_v < -1_000_000 or add_v > 1_000_000:
254                 continue
255             sc, _, _ = _score_set(sorted(sub | {add_v}))
256             if sc > best_swap_c:
257                 best_swap_c = sc
258                 best_swap = (rem, add_v)
259
260         if best_swap is not None and best_swap_c > best_c + 1e-6:
261             break
262
263     if best_swap is not None and best_swap_c > best_c + 1e-9:
264         curr.remove(best_swap[0])
265         curr.add(best_swap[1])
266         best_c = best_swap_c
267         best_set = set(curr)
268         improved = True
269         continue
270
271     if not improved:
272         break
273
274     return sorted(best_set), best_c
275
276
277 def construct_set():
278     """
279     Construct an optimal MST set maximizing C(A).
280     Sweeps parameterized generalized Penman-Wells families, ranks seeds,

```

Sums/Diffs: Python source (lines 241–360) (continued)

```

281     and applies deep multi-stage hill-climbing with perturbation kicks.
282     """
283     start_time = time.time()
284     time_limit = 135.0 # safe limit within 180s
285
286     # Guaranteed champion baseline: M=56, j=30 with fringe element 1793 (C(A) >= 1.144710)
287     base_seed = _generate_penman_variant(56, 30, bl_variant=0, include_half=False, odd_delta=0,
odd_start=0)
288     best_A = sorted(set(base_seed) | {base_seed[-1] + 1})
289     best_c, _, _ = _score_set(best_A)
290
291     seed_pool = [(best_c, best_A)]
292
293     # 1. Systematic scan across moduli M in {32, 40, 48, 56, 64, 72, 80, 88, 96, 104, 112}
294     moduli = [56, 64, 48, 72, 80, 40, 88, 96, 104, 112, 32]
295     for M in moduli:
296         step_j = M // 4 + 1
297         base_const = M + 2
298         approx_max_j = (512 - base_const) // step_j
299
300         for j in range(max(1, approx_max_j - 4), approx_max_j + 3):
301             for bl_var in (0, 1, 2, 3, 4, 5):
302                 for include_half in (False, True):
303                     for odd_delta in (-2, -1, 0, 1):
304                         for odd_start in (0, 1):
305                             for fringe in (0, 1, 2, 3, 4):
306                                 cand = _generate_penman_variant(
307                                     M, j, bl_var, include_half, odd_delta, odd_start, fringe
308                                 )
309                                 n_cand = len(cand)
310                                 if 2 <= n_cand <= 512:
311                                     c, _, _ = _score_set(cand)
312                                     if c > best_c:
313                                         best_c = c
314                                         best_A = cand
315                                     if c > 1.135 and n_cand >= 460:
316                                         seed_pool.append((c, cand))
317
318     seed_pool.sort(key=lambda x: x[0], reverse=True)
319
320     # 2. Select top unique diverse seeds
321     unique_candidates = []
322     seen_sigs = set()
323     for c_val, cand in [(best_c, best_A)] + seed_pool:
324         sig = (len(cand), cand[0], cand[-1])
325         if sig not in seen_sigs:
326             seen_sigs.add(sig)
327             unique_candidates.append(cand)
328         if len(unique_candidates) >= 6:
329             break
330
331     # 3. Deep optimization of top unique seeds
332     time_per_seed = 12.0
333     for cand in unique_candidates:
334         if time.time() - start_time > time_limit - 15.0:
335             break
336         budget = min(start_time + time_limit - 5.0, time.time() + time_per_seed)
337         opt_A, opt_c = _optimize_set(cand, budget)
338         if opt_c > best_c:
339             best_c = opt_c
340             best_A = opt_A
341
342     # 4. Iterated perturbation kicks on champion set if time remains
343     rng = random.Random(42)
344     while time.time() - start_time < time_limit - 8.0:
345         kicked = set(best_A)
346         sorted_k = sorted(kicked)
347         drop_pool = sorted_k[:10] + sorted_k[-10:]
348         to_drop = rng.sample(drop_pool, min(2, len(drop_pool)))
349         for d in to_drop:
350             kicked.remove(d)
351

```

Sums/Diffs: Python source (lines 241–360) (continued)

```
352         budget = min(start_time + time_limit - 3.0, time.time() + 6.0)
353         opt_A, opt_c = _optimize_set(list(kicked), budget)
354         if opt_c > best_c:
355             best_c = opt_c
356             best_A = opt_A
357
358     min_elem = min(best_A)
359     return [x - min_elem for x in sorted(best_A)]
360 # EVOLVE-BLOCK-END
```

Sums/Diffs: Python source (lines 361–421)

```
361
362 MIN_SET_SIZE = 2
363 MAX_SET_SIZE = 512
364 MIN_INT = -1_000_000
365 MAX_INT = 1_000_000
366
367
368 def _sanitize_output(values):
369     """Convert arbitrary iterable output into a valid sorted integer list."""
370     try:
371         raw = list(values)
372     except TypeError as e:
373         raise ValueError(f"Output is not iterable: {e}")
374
375     ints = []
376     for x in raw:
377         try:
378             xf = float(x)
379         except (TypeError, ValueError):
380             continue
381         if not math.isfinite(xf):
382             continue
383         xi = int(round(xf))
384         xi = max(MIN_INT, min(MAX_INT, xi))
385         ints.append(xi)
386
387     unique_vals = sorted(set(ints))
388     if len(unique_vals) > MAX_SET_SIZE:
389         unique_vals = unique_vals[:MAX_SET_SIZE]
390
391     if len(unique_vals) < MIN_SET_SIZE:
392         unique_vals = [0, 1]
393
394     return unique_vals
395
396
397 def _compute_c(values):
398     n = len(values)
399     sumset = {a + b for a in values for b in values}
400     diffset = {a - b for a in values for b in values}
401
402     sum_ratio = len(sumset) / n
403     diff_ratio = len(diffset) / n
404
405     if sum_ratio <= 1.0 or diff_ratio <= 1.0:
406         return 0.0
407
408     return float(math.log(sum_ratio) / math.log(diff_ratio))
409
410
411 def run_code():
412     """Return (A_values, claimed_c)."""
413     values = construct_set()
414     values = _sanitize_output(values)
415     c_value = _compute_c(values)
416     return values, c_value
417
418
```

Sums/Diffs: Python source (lines 361–421) (continued)

```
419 if __name__ == "__main__":
420     candidate_values, candidate_c = run_code()
421     print(f"|A|={len(candidate_values)}, C(A)={candidate_c:.10f}")
```

K.10. Circle Packing ($n = 26$): joint refinement matches the reference

The program starts from varied six-row layouts, maximizes radii through linear programming, and jointly refines centers and radii with SLSQP. Collective deformations and local perturbations explore nearby packing configurations, yielding a sum of radii of 2.635983084918461. An independent replay passes the evaluator's boundary and non-overlap checks; the score matches the reference within 10^{-9} .

Circle Packing ($n = 26$): Python source (lines 1–120)

```
1 # EVOLVE-BLOCK-START
2 """Numerically optimized variable-radius packing of 26 circles."""
3 import numpy as np
4 from scipy.optimize import minimize, linprog
5
6
7 def _make_start(seed):
8     """Build varied five- or six-row center layouts for LP/SLP polishing."""
9     rng = np.random.default_rng(seed)
10     patterns = (
11         (4, 4, 5, 4, 5, 4),
12         (5, 4, 4, 5, 4, 4),
13         (4, 5, 4, 5, 4, 4),
14         (4, 5, 5, 4, 4, 4),
15         (5, 4, 5, 4, 4, 4),
16         (4, 4, 4, 5, 4, 5),
17         (4, 5, 4, 4, 5, 4),
18         (5, 4, 4, 4, 5, 4),
19         (4, 4, 5, 5, 4, 4),
20         (5, 4, 5, 4, 4, 4),
21         (4, 5, 4, 4, 4, 5),
22         (5, 4, 4, 4, 4, 5),
23     )
24     counts = patterns[seed % len(patterns)]
25     rows = len(counts)
26     heights = np.ones(rows) / rows
27     heights += rng.normal(0.0, 0.012, rows)
28     heights = np.maximum(heights, 0.13)
29     heights /= np.sum(heights)
30     levels = np.cumsum(np.r_[0.0, heights[:-1]])
31     p = []
32     for row, count in enumerate(counts):
33         y = levels[row] + 0.5 * heights[row]
34         xs = (np.arange(count) + 0.5) / count
35         phase = rng.uniform(-0.055, 0.055)
36         xs = xs + phase + rng.normal(0.0, 0.004, count)
37         p.extend((x, y) for x in xs)
38     p = np.asarray(p[:26], dtype=float)
39     p += rng.normal(0.0, 0.004, p.shape)
40     p = np.clip(p, 0.055, 0.945)
41     return np.column_stack((p, np.full(26, 0.043)))
42
43
44 def _constraints(z):
45     """Return wall-clearance and pairwise non-overlap inequalities."""
46     q = z.reshape(26, 3)
47     x, y, r = q.T
48     out = [x - r, y - r, 1.0 - x - r, 1.0 - y - r]
49     for i in range(25):
50         d = q[i + 1:, :2] - q[i, :2]
51         out.append(np.sum(d * d, axis=1) - (r[i] + r[i + 1:]) ** 2)
52     return np.concatenate(out)
53
54
55 def _repair(q):
56     """Shrink radii uniformly until every wall and pair constraint is strict."""
```

Circle Packing ($n = 26$): Python source (lines 1–120) (continued)

```

57     q = np.asarray(q, dtype=float).copy()
58     q[:, :2] = np.clip(q[:, :2], 1e-5, 1.0 - 1e-5)
59     q[:, 2] = np.maximum(q[:, 2], 0.0)
60     q[:, 2] = np.minimum(q[:, 2],
61                           np.minimum.reduce((q[:, 0], q[:, 1],
62                                                1.0 - q[:, 0], 1.0 - q[:, 1])))
63     factor = 1.0
64     for i in range(25):
65         d = np.sqrt(np.sum((q[i + 1:, :2] - q[i, :2]) ** 2, axis=1))
66         s = q[i, 2] + q[i + 1:, 2]
67         mask = s > 0
68         if np.any(mask):
69             factor = min(factor, float(np.min(d[mask] / s[mask])))
70     # Keep only a tiny numerical safety margin; the previous 0.05% shrink
71     # discarded a measurable amount of objective value on every polish.
72     q[:, 2] *= max(0.0, min(1.0, factor * 0.999999))
73     return q
74
75
76 def construct_circles():
77     """Use feasible LP radii followed by inner linearized center/radius polishing."""
78     n = 26
79     best = None
80     best_value = -1.0
81     # Preserve distinct feasible active sets: the LP ranking is not always
82     # the same as the ranking after exact nonlinear optimization.
83     elite = []
84
85     def polish(q):
86         """Maximize radii through monotone LP steps with bounded center moves."""
87         q = np.asarray(q, dtype=float).copy()
88         x, y = q[:, 0], q[:, 1]
89
90         # First maximize the radii exactly for the fixed starting centers.
91         ar = []
92         br = []
93         for i in range(n):
94             row = np.zeros(n)
95             row[i] = 1.0
96             ar.append(row)
97             br.append(min(x[i], y[i], 1.0 - x[i], 1.0 - y[i]))
98         for i in range(n - 1):
99             for j in range(i + 1, n):
100                 row = np.zeros(n)
101                 row[i] = row[j] = 1.0
102                 ar.append(row)
103                 br.append(np.hypot(x[i] - x[j], y[i] - y[j]))
104         lp = linprog(
105             np.full(n, -1.0),
106             A_ub=np.asarray(ar),
107             b_ub=np.asarray(br),
108             bounds=[(0.0, 0.5)] * n,
109             method="highs",
110         )
111         if not lp.success:
112             return _repair(q)
113         q[:, 2] = lp.x
114
115         # Each LP below is an inner approximation: its solution remains
116         # feasible for the nonlinear distance constraints.
117         for trust in (0.028, 0.018, 0.010, 0.005, 0.002):
118             for _ in range(18):
119                 x, y, r = q.T
120                 nv = 3 * n

```

Circle Packing ($n = 26$): Python source (lines 121–240)

```

121         aa = []
122         bb = []
123

```

Circle Packing ($n = 26$): Python source (lines 121–240) (continued)

```

124         for i in range(n):
125             row = np.zeros(nv)
126             row[3 * i] = -1.0
127             row[3 * i + 2] = 1.0
128             aa.append(row)
129             bb.append(x[i] - r[i])
130
131             row = np.zeros(nv)
132             row[3 * i + 1] = -1.0
133             row[3 * i + 2] = 1.0
134             aa.append(row)
135             bb.append(y[i] - r[i])
136
137             row = np.zeros(nv)
138             row[3 * i] = 1.0
139             row[3 * i + 2] = 1.0
140             aa.append(row)
141             bb.append(1.0 - x[i] - r[i])
142
143             row = np.zeros(nv)
144             row[3 * i + 1] = 1.0
145             row[3 * i + 2] = 1.0
146             aa.append(row)
147             bb.append(1.0 - y[i] - r[i])
148
149         for i in range(n - 1):
150             for j in range(i + 1, n):
151                 dx = x[i] - x[j]
152                 dy = y[i] - y[j]
153                 d = np.hypot(dx, dy)
154                 if d < 1e-10:
155                     continue
156                 ux, uy = dx / d, dy / d
157                 row = np.zeros(nv)
158                 row[3 * i] = -ux
159                 row[3 * i + 1] = -uy
160                 row[3 * j] = ux
161                 row[3 * j + 1] = uy
162                 row[3 * i + 2] = row[3 * j + 2] = 1.0
163                 aa.append(row)
164                 bb.append(d - r[i] - r[j])
165
166         bounds = []
167         for i in range(n):
168             bounds.extend([
169                 (-trust, trust), (-trust, trust), (-r[i], 0.12)
170             ])
171         step = linprog(
172             np.array([0.0, 0.0, -1.0] * n),
173             A_ub=np.asarray(aa),
174             b_ub=np.asarray(bb),
175             bounds=bounds,
176             method="highs",
177         )
178         if not step.success or np.max(np.abs(step.x)) < 1e-9:
179             break
180         q += step.x.reshape(n, 3)
181
182     return _repair(q)
183
184 for seed in range(120):
185     q = polish(_make_start(seed))
186     value = float(np.sum(q[:, 2]))
187     if np.all(_constraints(q) >= -2e-8):
188         elite.append((value, q.copy()))
189         if value > best_value:
190             best, best_value = q, value
191
192 # Keep a broad but bounded set of candidates for later exact polishing.
193 elite.sort(key=lambda item: item[0], reverse=True)
194 elite = elite[:24]
195

```

Circle Packing ($n = 26$): Python source (lines 121–240) (continued)

```

196     def nonlinear_polish(q):
197         """Refine a feasible packing with SLSQP on exact nonlinear constraints."""
198         q = np.asarray(q, dtype=float).copy()
199         nvar = 3 * n
200
201         def objective(z):
202             return -float(np.sum(z[2::3]))
203
204         def objective_jac(z):
205             g = np.zeros(nvar)
206             g[2::3] = -1.0
207             return g
208
209         result = minimize(
210             objective,
211             q.ravel(),
212             jac=objective_jac,
213             method="SLSQP",
214             bounds=[(0.0, 1.0), (0.0, 1.0), (0.0, 0.2)] * n,
215             constraints={ "type": "ineq", "fun": _constraints},
216             options={
217                 "ftol": 2e-11,
218                 "maxiter": 500,
219                 "disp": False,
220             },
221         )
222         if result.success or np.all(_constraints(result.x) >= -2e-8):
223             candidate = result.x.reshape(n, 3)
224             if np.all(_constraints(candidate) >= -2e-8):
225                 return candidate
226         return q
227
228     if best is None:
229         best = _repair(_make_start(0))
230
231     # Exact SLSQP polishing can change the contact graph and therefore can
232     # reorder candidates that looked similar under the LP inner model.
233     # Polish several geometrically distinct layouts before basin hopping.
234     refined_count = 0
235     seen = []
236     for _, candidate in elite:
237         signature = np.round(candidate[:, :2], 5)
238         if any(np.max(np.abs(signature - old)) < 1e-10 for old in seen):
239             continue
240         seen.append(signature)

```

Circle Packing ($n = 26$): Python source (lines 241–351)

```

241         refined = nonlinear_polish(candidate)
242         if (
243             np.all(_constraints(refined) >= -2e-8)
244             and np.sum(refined[:, 2]) > best_value + 1e-11
245         ):
246             best = refined
247             best_value = float(np.sum(refined[:, 2]))
248             refined_count += 1
249             if refined_count >= 12:
250                 break
251
252     # Explore nearby basins using coherent affine deformations. Moving all
253     # centers together is substantially safer than independently jittering
254     # circles in a jammed packing, and the subsequent LP/SLP polish restores
255     # feasible radii while optimizing the deformed layout.
256     rng = np.random.default_rng(918273)
257     incumbent = best.copy()
258     incumbent_value = float(np.sum(incumbent[:, 2]))
259     walker = incumbent.copy()
260     walker_value = incumbent_value
261
262     # Use threshold acceptance rather than strict hill climbing. This lets

```

Circle Packing ($n = 26$): Python source (lines 241–351) (continued)

```

263     # the center deformation cross shallow local-optimum barriers, while the
264     # separate incumbent remains strictly monotone.
265     for trial in range(140):
266         # Occasionally restart the walk from a different elite contact graph
267         # instead of repeatedly perturbing one basin.
268         if trial % 19 == 0 and len(elite) > 1:
269             idx = int(rng.integers(0, min(12, len(elite))))
270             q = elite[idx][1].copy()
271         else:
272             q = walker.copy()
273         c = q[:, :2] - 0.5
274
275         angle = rng.normal(0.0, 0.040)
276         ca, sa = np.cos(angle), np.sin(angle)
277         sx = rng.uniform(0.93, 1.09)
278         sy = rng.uniform(0.93, 1.09)
279         shear = rng.normal(0.0, 0.055)
280         transform = np.array([
281             [sx * ca, -sy * sa + shear],
282             [sx * sa,  sy * ca],
283         ])
284         q[:, :2] = 0.5 + c @ transform.T
285
286         # Apply small coherent row waves to alter the active contact graph
287         # while retaining the useful six-row arrangement.
288         if trial % 3 == 1:
289             rows = np.clip(np.floor(q[:, 1] * 6.0).astype(int), 0, 5)
290             phase = rng.uniform(0.0, 2.0 * np.pi)
291             wave = rng.normal(0.0, 0.0055, 6)
292             q[:, 1] += wave[rows]
293             q[:, 0] += 0.0035 * np.sin(1.6 * rows + phase)
294
295         # Alternate collective and weak individual perturbations so that the
296         # walk can both change row geometry and break repeated contacts.
297         if trial % 2 == 0:
298             q[:, :2] += rng.normal(0.0, 0.0038, (n, 2))
299         if trial % 7 == 6:
300             q[:, :2] += rng.normal(0.0, 0.0018, (n, 2))
301
302         q = polish(_repair(q))
303         if not np.all(_constraints(q) >= -2e-8):
304             continue
305         value = float(np.sum(q[:, 2]))
306         elite.append((value, q.copy()))
307         if len(elite) > 32:
308             elite.sort(key=lambda item: item[0], reverse=True)
309             elite = elite[:24]
310
311         # Geometrically cool the acceptance band, then restart it. The
312         # threshold is deliberately small relative to the incumbent margin.
313         phase = trial % 14
314         temperature = 0.00055 * (0.18 ** (phase / 13.0))
315         if value >= walker_value - temperature:
316             walker, walker_value = q, value
317
318         if value > incumbent_value:
319             incumbent, incumbent_value = q, value
320             best, best_value = q, value
321
322         # Prevent a sequence of accepted downhill moves from abandoning the
323         # best basin family altogether.
324         if walker_value < incumbent_value - 0.003:
325             walker = incumbent.copy()
326             walker_value = incumbent_value
327
328         # The LP iterations use tangent half-spaces, so they can stop at a
329         # nonsmooth active-set point. SLSQP can jointly adjust centers and
330         # radii across the exact circular constraints.
331         refined = nonlinear_polish(best)
332         if (
333             np.all(_constraints(refined) >= -2e-8)
334             and np.sum(refined[:, 2]) > np.sum(best[:, 2])

```

Circle Packing ($n = 26$): Python source (lines 241–351) (continued)

```
335     ):
336         best = refined
337
338     return best
339
340
341 # EVOLVE-BLOCK-END
342
343
344 # This part remains fixed (not evolved)
345 def run_code():
346     """Run the circle packing constructor for n=26"""
347     circles = construct_circles()
348     sum_radii = float(np.sum(circles[:, 2]))
349     return circles, sum_radii
350
351
```

K.11. Circle Packing ($n = 32$): multiple layouts recover the reference score

The program explores five- and six-row layouts with SLSQP, then alternates linear optimization of radii at fixed centers with joint center–radius refinement. Small perturbations and restarts yield a sum of radii of 2.939572771209394. An independent replay passes the evaluator’s boundary and non-overlap checks; the score matches the reference within 10^{-9} .

Circle Packing ($n = 32$): Python source (lines 1–120)

```
1 # EVOLVE-BLOCK-START
2 """Constructor-based circle packing for n=32 circles"""
3 import numpy as np
4
5
6 def construct_circles():
7     """Optimize 32 centers and radii from several staggered six-row layouts."""
8     from scipy.optimize import minimize, linprog
9
10    n = 32
11    layouts = (
12        # Six-row staggered layouts, including several asymmetric variants.
13        (5, 6, 5, 5, 5, 6),
14        (6, 5, 5, 6, 5, 5),
15        (5, 5, 6, 5, 6, 5),
16        (6, 6, 5, 5, 5, 5),
17        (6, 5, 6, 5, 5, 5),
18        (6, 5, 5, 5, 6, 5),
19        (6, 5, 5, 5, 5, 6),
20        (5, 6, 6, 5, 5, 5),
21        (5, 5, 5, 6, 6, 5),
22        # Five-row layouts have larger vertical freedom and can form
23        # nonuniform-radius packings unavailable to six-row starts.
24        (6, 7, 6, 7, 6),
25        (7, 6, 7, 6, 6),
26        (6, 6, 7, 6, 7),
27    )
28    pairs = np.asarray(
29        [(i, j) for i in range(n) for j in range(i + 1, n)],
30        dtype=int,
31    )
32
33    def margins(v):
34        p = v.reshape(n, 3)
35        x, y, r = p.T
36        a, b = pairs.T
37        d = p[a, :2] - p[b, :2]
38        return np.r_[
39            x - r, y - r, 1.0 - x - r, 1.0 - y - r,
40            np.sum(d * d, axis=1) - (r[a] + r[b]) ** 2,
41        ]
42
```

Circle Packing ($n = 32$): Python source (lines 1–120) (continued)

```

43     rng = np.random.default_rng(1947)
44
45     def safe_initial_radii(points):
46         """Build strictly feasible radii from wall and nearest-center clearances."""
47         wall = np.min(np.column_stack((
48             points[:, 0], points[:, 1],
49             1.0 - points[:, 0], 1.0 - points[:, 1]
50         )), axis=1)
51         delta = points[:, None, :] - points[None, :, :]
52         dist = np.sqrt(np.sum(delta * delta, axis=2))
53         np.fill_diagonal(dist, np.inf)
54         near = np.min(dist, axis=1)
55         return 0.48 * np.minimum(wall, near)
56
57     best = None
58     best_sum = -np.inf
59
60     for layout in layouts:
61         centers = []
62         for row, count in enumerate(layout):
63             y = (row + 0.5) / 6.0
64             shift = 0.012 if row & 1 else -0.012
65             for col in range(count):
66                 centers.append((col + 0.5) / count + shift, y)
67         centers = np.asarray(centers)
68
69         starts = [
70             np.c_[centers, np.full(n, 1.0 / 12.0 - 1e-5)]
71         ]
72         # Use both aggressive equal-radius starts and strictly feasible
73         # radius starts. The latter avoid wasting SLSQP iterations repairing
74         # overlap violations in strongly perturbed geometries.
75         for k in range(16):
76             sigma = 0.004 + 0.0025 * (k % 5)
77             radius = 0.054 + 0.0025 * (k % 4)
78             q = np.clip(
79                 centers + rng.normal(0.0, sigma, centers.shape),
80                 0.035,
81                 0.965,
82             )
83             starts.append(np.c_[q, np.full(n, radius)])
84             if k % 3 == 0:
85                 starts.append(np.c_[q, safe_initial_radii(q)])
86
87         for start in starts:
88             result = minimize(
89                 lambda v: -np.sum(v[2::3]),
90                 start.ravel(),
91                 method="SLSQP",
92                 bounds=[(0.0, 1.0), (0.0, 1.0), (1e-8, 0.25)] * n,
93                 constraints={"type": "ineq", "fun": margins},
94                 options={"maxiter": 1000, "ftol": 2e-10, "disp": False},
95             )
96             candidate = result.x.reshape(n, 3)
97             value = float(np.sum(candidate[:, 2]))
98             if np.min(margins(candidate)) >= -3e-7 and value > best_sum:
99                 best, best_sum = candidate, value
100
101     # Search additional basins using feasible jittered and coherently deformed
102     # versions of the strongest row-layout solution. Coherent deformation is
103     # useful because independently moving a circle can destroy many contacts.
104     if best is not None:
105         base = best[:, :2].copy()
106         for k in range(30):
107             if k % 3 == 0:
108                 # Small affine shear/stretch around the square center.
109                 a = rng.normal(0.0, 0.018)
110                 b = rng.normal(0.0, 0.018)
111                 sx = 1.0 + rng.normal(0.0, 0.025)
112                 sy = 1.0 + rng.normal(0.0, 0.025)
113                 q = base - 0.5
114                 q = np.column_stack((

```

Circle Packing ($n = 32$): Python source (lines 1–120) (continued)

```
115         sx * q[:, 0] + a * q[:, 1],
116         sy * q[:, 1] + b * q[:, 0],
117     )) + 0.5
118     q += rng.normal(0.0, 0.0025, q.shape)
119 else:
120     sigma = 0.0025 + 0.0025 * (k % 6)
```

Circle Packing ($n = 32$): Python source (lines 121–240)

```
121         q = base + rng.normal(0.0, sigma, base.shape)
122
123     q = np.clip(q, 0.015, 0.985)
124     trial = np.c_[q, safe_initial_radii(q)]
125     result = minimize(
126         lambda v: -np.sum(v[2::3]),
127         trial.ravel(),
128         method="SLSQP",
129         bounds=[(0.0, 1.0), (0.0, 1.0), (1e-8, 0.25)] * n,
130         constraints={"type": "ineq", "fun": margins},
131         options={"maxiter": 1250, "ftol": 1e-11, "disp": False},
132     )
133     candidate = result.x.reshape(n, 3)
134     if np.min(margins(candidate)) >= -3e-7:
135         value = float(np.sum(candidate[:, 2]))
136         if value > best_sum:
137             best, best_sum = candidate, value
138
139     # Threshold-accepting walk over nearby packing basins. Unlike the
140     # incumbent, the walker may accept a small decrease in sum of radii,
141     # allowing it to cross shallow barriers between contact graphs.
142     if best is not None:
143         walker = best.copy()
144         walker_sum = float(np.sum(walker[:, 2]))
145
146     for k in range(32):
147         # Cycle from exploratory to conservative thresholds.
148         phase = k % 8
149         threshold = 8e-4 * (0.35 ** phase)
150
151         q = walker[:, :2].copy()
152         if k % 4 == 0:
153             # Coherent affine deformation preserves the broad structure.
154             a, b = rng.normal(0.0, 0.025, 2)
155             sx, sy = 1.0 + rng.normal(0.0, 0.035, 2)
156             z = q - 0.5
157             q = np.column_stack((
158                 sx * z[:, 0] + a * z[:, 1],
159                 sy * z[:, 1] + b * z[:, 0],
160             )) + 0.5
161             q += rng.normal(0.0, 0.002, q.shape)
162         elif k % 4 == 1:
163             # Small rigid rotation around the square centre.
164             angle = rng.normal(0.0, 0.035)
165             c, s = np.cos(angle), np.sin(angle)
166             z = q - 0.5
167             q = np.column_stack((
168                 c * z[:, 0] - s * z[:, 1],
169                 s * z[:, 0] + c * z[:, 1],
170             )) + 0.5
171             q += rng.normal(0.0, 0.0025, q.shape)
172         else:
173             sigma = 0.002 + 0.002 * (k % 5)
174             q += rng.normal(0.0, sigma, q.shape)
175
176     q = np.clip(q, 0.015, 0.985)
177     trial = np.c_[q, safe_initial_radii(q)]
178     result = minimize(
179         lambda v: -np.sum(v[2::3]),
180         trial.ravel(),
181         method="SLSQP",
```

Circle Packing ($n = 32$): Python source (lines 121–240) (continued)

```

182         bounds=[(0.0, 1.0), (0.0, 1.0), (1e-8, 0.25)] * n,
183         constraints={"type": "ineq", "fun": margins},
184         options={"maxiter": 1300, "ftol": 1e-11, "disp": False},
185     )
186     candidate = result.x.reshape(n, 3)
187     if np.min(margins(candidate)) < -3e-7:
188         continue
189
190     value = float(np.sum(candidate[:, 2]))
191     if value > best_sum:
192         best, best_sum = candidate.copy(), value
193
194     # Walk locally through near-optimal states, but periodically
195     # return to the record if a trial falls too far behind.
196     if value >= walker_sum - threshold:
197         walker, walker_sum = candidate.copy(), value
198     elif value < walker_sum - 3.0 * threshold:
199         walker, walker_sum = best.copy(), best_sum
200
201 if best is None:
202     row_counts = (5, 5, 5, 5, 6, 6)
203     centers = np.asarray([
204         (col + 0.5) / count, (row + 0.5) / 6.0)
205         for row, count in enumerate(row_counts)
206         for col in range(count)
207     ])
208     return np.c_[centers, np.full(n, (1.0 / 12.0) * (1.0 - 1e-7))]
209
210 def optimize_fixed_radii(points):
211     """Maximize the sum of radii for fixed centers using a linear program."""
212     upper = np.min(
213         np.column_stack((
214             points[:, 0], points[:, 1],
215             1.0 - points[:, 0], 1.0 - points[:, 1]
216         )),
217         axis=1,
218     )
219
220     # For fixed centers, every non-overlap condition is linear in r:
221     #  $r_i + r_j \leq ||p_i - p_j||$ .
222     m = n * (n - 1) // 2
223     A = np.zeros((m, n))
224     b = np.empty(m)
225     k = 0
226     for i in range(n):
227         for j in range(i + 1, n):
228             A[k, i] = 1.0
229             A[k, j] = 1.0
230             b[k] = np.linalg.norm(points[i] - points[j])
231             k += 1
232
233     result = linprog(
234         -np.ones(n),
235         A_ub=A,
236         b_ub=b,
237         bounds=[(1e-10, float(u)) for u in upper],
238         method="highs",
239     )
240     if not result.success:

```

Circle Packing ($n = 32$): Python source (lines 241–360)

```

241         return best
242
243     candidate = np.column_stack((points, result.x))
244     # Remove only a negligible numerical margin after the LP.
245     candidate[:, 2] *= 1.0 - 2e-10
246     if np.min(margins(candidate)) >= -1e-10:
247         return candidate
248     return best

```

Circle Packing ($n = 32$): Python source (lines 241–360) (continued)

```

249
250 refined = optimize_fixed_radii(best[:, :2])
251 if np.sum(refined[:, 2]) > np.sum(best[:, 2]):
252     best = refined
253
254 def slp_polish(state):
255     """Improve centers and radii through feasible tangent-plane LP steps."""
256     p = state[:, :2].copy()
257     r = state[:, 2].copy()
258
259     # Create a tiny strict-feasibility buffer so that the zero step
260     # remains feasible despite LP/SLSQP roundoff.
261     r *= 1.0 - 2e-8
262
263     for trust in (0.012, 0.008, 0.005, 0.003, 0.0015, 0.0007):
264         for _ in range(8):
265             nv = 3 * n
266             rows = []
267             rhs = []
268
269             # Box constraints, written in delta variables.
270             for i in range(n):
271                 row = np.zeros(nv)
272                 row[3 * i + 0] = -1.0
273                 row[3 * i + 2] = 1.0
274                 rows.append(row)
275                 rhs.append(p[i, 0] - r[i])
276
277                 row = np.zeros(nv)
278                 row[3 * i + 1] = -1.0
279                 row[3 * i + 2] = 1.0
280                 rows.append(row)
281                 rhs.append(p[i, 1] - r[i])
282
283                 row = np.zeros(nv)
284                 row[3 * i + 0] = 1.0
285                 row[3 * i + 2] = 1.0
286                 rows.append(row)
287                 rhs.append(1.0 - p[i, 0] - r[i])
288
289                 row = np.zeros(nv)
290                 row[3 * i + 1] = 1.0
291                 row[3 * i + 2] = 1.0
292                 rows.append(row)
293                 rhs.append(1.0 - p[i, 1] - r[i])
294
295             # Tangent lower bounds for every pairwise distance.
296             for i in range(n):
297                 for j in range(i + 1, n):
298                     diff = p[i] - p[j]
299                     d = float(np.linalg.norm(diff))
300                     if d < 1e-14:
301                         continue
302                     u = diff / d
303
304                     row = np.zeros(nv)
305                     row[3 * i + 0] = -u[0]
306                     row[3 * i + 1] = -u[1]
307                     row[3 * j + 0] = u[0]
308                     row[3 * j + 1] = u[1]
309                     row[3 * i + 2] = 1.0
310                     row[3 * j + 2] = 1.0
311                     rows.append(row)
312                     rhs.append(d - r[i] - r[j])
313
314             bounds = []
315             for i in range(n):
316                 bounds.extend([
317                     (-trust, trust),
318                     (-trust, trust),
319                     (-float(r[i]) + 1e-11, 0.25 - float(r[i])),
320 ])

```

Circle Packing ($n = 32$): Python source (lines 241–360) (continued)

```

321
322         lp = linprog(
323             np.tile([0.0, 0.0, -1.0], n),
324             A_ub=np.asarray(rows),
325             b_ub=np.asarray(rhs),
326             bounds=bounds,
327             method="highs",
328         )
329         if not lp.success:
330             break
331
332         step = lp.x.reshape(n, 3)
333         gain = float(np.sum(step[:, 2]))
334         if gain <= 1e-11:
335             break
336
337         p += step[:, :2]
338         r += step[:, 2]
339
340         out = np.column_stack((p, r))
341         # Remove only a negligible common factor for strict evaluator
342         # feasibility after the final floating-point LP step.
343         out[:, 2] *= 1.0 - 3e-9
344         return out
345
346     polished = slp_polish(best)
347     if np.min(margins(polished)) >= -2e-9:
348         if np.sum(polished[:, 2]) > np.sum(best[:, 2]):
349             best = polished
350
351     # SLP changes the centers, so solve the fixed-center radius LP again.
352     # This restores exact radius optimality for the polished geometry.
353     polished_radial = optimize_fixed_radial(polished[:, :2])
354     if np.sum(polished_radial[:, 2]) > np.sum(best[:, 2]):
355         best = polished_radial
356
357     # Perform additional small-basin restarts from the polished incumbent.
358     # These perturbations are deliberately much smaller than the earlier
359     # exploratory walk, targeting improvements that SLSQP may miss because
360     # the incumbent lies on a nearly degenerate contact graph.

```

Circle Packing ($n = 32$): Python source (lines 361–455)

```

361     polished_base = best[:, :2].copy()
362     for k in range(120):
363         q = polished_base.copy()
364
365         if k % 10 == 0:
366             # Apply a coherent deformation to preserve the broad packing
367             # while changing the active contact graph.
368             z = q - 0.5
369             shear_x, shear_y = rng.normal(0.0, 0.016, 2)
370             scale_x, scale_y = 1.0 + rng.normal(0.0, 0.016, 2)
371             q = np.column_stack((
372                 scale_x * z[:, 0] + shear_x * z[:, 1],
373                 scale_y * z[:, 1] + shear_y * z[:, 0],
374             )) + 0.5
375             q += rng.normal(0.0, 0.0012, q.shape)
376         else:
377             # A wider schedule occasionally leaves the current contact basin,
378             # while the smallest scales continue to refine tangent neighbors.
379             sigma = 0.0002 + 0.0005 * (k % 10)
380             q += rng.normal(0.0, sigma, q.shape)
381
382     q = np.clip(q, 0.012, 0.988)
383     trial = np.c_[q, safe_initial_radial(q)]
384
385     result = minimize(
386         lambda v: -np.sum(v[2::3]),
387         trial.ravel(),

```

Circle Packing ($n = 32$): Python source (lines 361–455) (continued)

```

388         method="SLSQP",
389         bounds=[(0.0, 1.0), (0.0, 1.0), (1e-8, 0.25)] * n,
390         constraints={"type": "ineq", "fun": margins},
391         options={"maxiter": 1500, "ftol": 5e-12, "disp": False},
392     )
393     candidate = result.x.reshape(n, 3)
394
395     if np.min(margins(candidate)) < -3e-7:
396         continue
397
398     # Re-optimize the radii exactly for the newly found centers. This
399     # removes any SLSQP radius suboptimality before comparing incumbents.
400     candidate_lp = optimize_fixed_radii(candidate[:, :2])
401     if np.min(margins(candidate_lp)) >= -1e-8:
402         if np.sum(candidate_lp[:, 2]) > np.sum(best[:, 2]):
403             best = candidate_lp
404
405     return best
406
407
408 def compute_max_radii(centers):
409     """
410     Compute the maximum possible radii for each circle position
411     such that they don't overlap and stay within the unit square.
412
413     Args:
414         centers: np.array of shape (n, 2) with (x, y) coordinates
415
416     Returns:
417         np.array of shape (n) with radius of each circle
418     """
419     n = centers.shape[0]
420     radii = np.ones(n)
421
422     # First, limit by distance to square borders
423     for i in range(n):
424         x, y = centers[i]
425         # Distance to borders
426         radii[i] = min(x, y, 1 - x, 1 - y)
427
428     # Then, limit by distance to other circles
429     # Each pair of circles with centers at distance d can have
430     # sum of radii at most d to avoid overlap
431     for i in range(n):
432         for j in range(i + 1, n):
433             dist = np.sqrt(np.sum((centers[i] - centers[j]) ** 2))
434
435             # If current radii would cause overlap
436             if radii[i] + radii[j] > dist:
437                 # Scale both radii proportionally
438                 scale = dist / (radii[i] + radii[j]) * 0.99 # 0.99 for safety margin
439                 radii[i] *= scale
440                 radii[j] *= scale
441
442     return radii
443
444
445 # EVOLVE-BLOCK-END
446
447
448 # This part remains fixed (not evolved)
449 def run_code():
450     """Run the circle packing constructor for n=32"""
451     circles = construct_circles()
452     sum_radii = float(np.sum(circles[:, 2]))
453     return circles, sum_radii
454
455

```

K.12. Discovered Objects

Figures 16–20 visualize the routed quantum circuits, trajectories, denoised gene expression, scaling laws, and mathematical objects produced by the best programs, alongside those from the programs or constructions released by SimpleTES. They are redrawn from saved outputs; the mathematical objects come from re-running each best program, which reproduces its reported score exactly.




Figure 16: Routed quantum circuits on Q20. (a) The alu-v0_27 input circuit. (b, c) Outputs of the released SimpleTES program and EVODUET’s best program under matched replay settings. Colored bands highlight inserted SWAPs: two for SimpleTES and one for EVODUET. All gates are shown; only idle wires are omitted. Labels q_i and p_i denote logical qubits and physical sites, respectively.




Figure 17: Rosetta and Voyager 2. (a, b) Encounters and dates of the SimpleTES construction and of the best program of EVODUET; diamonds are deep-space maneuvers labelled with their Δv in km/s. (c) Total Δv split into maneuvers and launch or arrival. On Rosetta, EVODUET adds the Mars flyby of the actual mission; on Voyager 2, both follow the same tour and EVODUET moves the arrival onto the end of the window. Planet images: NASA (public domain).




Figure 18: Denoised gene expression. (a) Noisy PBMC input, (b, c) outputs of the released SimpleTES program and EVODUET's best program, and (d) held-out counts. Columns show all 1,087 cells; rows show 24 genes selected for their variability in the input. Gene selection and ordering use only the input, with the same order and color scale across panels. Values are log-normalized per cell. Held-out counts are independent observations and still contain noise.




Figure 19: Parallel Scaling and Domain Mixture. (a) Observed loss on the grid of parameter count N and parallel streams P for the two Parallel datasets (darker cells indicate lower loss within each dataset); the dashed row ($P = 8$) is held out, and a star marks the law that predicts that cell more closely (EvoDUET in 7 of 12). (b) Predicted against actual held-out loss on Domain Mixture. (c) Held-out $1 - R^2$ on a log scale. Both margins are small.




Figure 20: Mathematical objects. (a) The Erdős step function h of EVODUET, which is the published witness the run located and polished, against the SimpleTES construction. (b) The two order-29 matrices, which reach the same determinant. (c) The two sum-difference sets; EVODUET scores 1.144999, exceeding the released post-training SimpleTES set (1.144887).