

RECOMMEND P.C.B. LAYOUT
TOP VIEW

MATERIALS

- HOUSING : P.B.T (UL 94V-0).
- TERMINAL : LEADED BRASS.
- SHELL : STEEL.

SPECIFICATION

- CURRENT RATING : 5 AMP. MAX.
- DIELECTRIC WITHSTANDING VOLTAGE : 1000V AC R.M.S. FOR ONE MINUTE.
- INSULATION RESISTANCE : 1000M OHMS MIN. AT 500V DC.
- OPERATING TEMPERATURE : -55°C TO +105°C.

ORDER INFORMATION :

DB4 - ** - * * M * T * G - R

SERIES CODE

NUMBER OF POSITION

WIRE WRAP LENGTH OPTIONS

- 10.00mm/0.394"
- 13.00mm/0.512"
- 17.50mm/0.689"
- 9.50mm/0.374"
- 12.20mm/0.480"

MOUNTING OPTIONS

REF. DRAW NO. C400-0004

STANDARD : A : MOUNTING HOLE

ENVIRONMENTAL PROTECTION CODE (RoHS)

GOLD PLATING ON SOLDER TAIL

CONTACT PLATING OPTIONS

- GOLD FLASH
- .000010" GOLD
- .000015" GOLD
- .000030" GOLD


TIN PLATING ON SHELL

HOUSING COLOR OPTIONS

- BLACK
- WHITE (STANDARD)

MALE

Number of Position	Dimensions			
	A	B	C	D
09	30.81[1.213]	24.99[.984]	16.92[.666]	19.28[.759]
15	39.14[1.541]	33.32[1.312]	25.25[.994]	27.51[1.083]
25	53.04[2.088]	47.04[1.852]	38.96[1.534]	41.30[1.626]
37	69.32[2.729]	63.50[2.500]	55.42[2.182]	57.71[2.272]

TOLERANCE	DRAWER	 WWW.ASTRON.COM.TW
.0=±.38 [.015]	CHECK	
.00=±.25 [.010]	APP'D	
.000=±.XXX	PRODUCT SPEC.	
.0000=±.	C404-0002	NAME D-SUB WIRE WRAP MACHINED PIN TYPE MALE
ANG.=±3'	405-0003	
UNITS : mm [inch]	SHEET 1 OF 1	DRAW NO. CDB4-XX-XXMXTXG-R
SCALE NONE	SIZE A4	REV. D 18002

L±0.50[.020]
WIRE WRAP LENGTH
1 10.00[.394]
2 13.00[.512]
3 17.50[.689]
4 9.50[.374]
5 12.20[.480]