

# R and Tidyverse

SYS 6018 | Spring 2022

Rintro.pdf

## Contents

<b>1</b>	<b>Technical Requirements</b>	<b>2</b>
<b>2</b>	<b>Introduction to R</b>	<b>2</b>
2.1	Getting Help . . . . .	2
2.2	RStudio . . . . .	2
2.3	Using R Packages . . . . .	2
2.4	RMarkdown . . . . .	3
2.5	Graphics with the <code>ggplot2</code> package . . . . .	3
2.6	Data Transformation with the <code>dplyr</code> package . . . . .	3
2.7	Groupwise operations . . . . .	5
2.8	Data Importing . . . . .	6
2.9	Tidy Data with the <code>tidyr</code> package . . . . .	7
2.10	Loops . . . . .	8

---

# 1 Technical Requirements

- Working and updated version of R and RStudio
  - Update packages as well
- Install R packages: `tidyverse` and `nycflights13`
- Course Webpage: <https://mdporter.github.io/SYS6018>

## 2 Introduction to R

### 2.1 Getting Help

- A good source of basic data analysis using R is found in the free book [R for Data Science](#).
- Web search, especially *stackoverflow.com* and *stats.stackexchange.com*
- Troubleshooting/Debugging.
  - Check one line of code at a time.
  - Use scripts
  - Make sure it works in plain R before incorporating into Rmd

### 2.2 RStudio

- Install R and RStudio
- Make use of *Projects* in RStudio

### 2.3 Using R Packages

It takes two steps to use the functions and data in an R package

1. Install the package
  - i.e., download the package to your computer
  - this only needs to be done one time
  - `install.packages()`
2. Load the package
  - i.e., tell R to look for the package functions and/or data
  - this needs to be done every time R is started (and you want to use the package)
  - `library()`

#### 2.3.1 Note on `tidyverse` package

- The `tidyverse` package <https://www.tidyverse.org/packages/> is really just a wrapper to load several related R packages
  - `ggplot2` for graphics
  - `dplyr` for data manipulation
  - `tidyr` for getting data into tidy form
  - `readr` for loading in data
  - `tibble` for improved data frames
  - `purrr` for functional programming

- `stringr` for string manipulation
- `forcats` for categorical/factor data
- This provides a nice shortcut to load all of these packages with `library(tidyverse)` instead of each separately:

```
#- the hard way
library(ggplot2)
library(dplyr)
library(tidyr)
library(readr)
library(tibble)
library(purrr)
library(stringr)
library(forcats)
```

```
#- the easy way
library(tidyverse)
```

## 2.4 RMarkdown

- Homework will be submitted in Rmd and (html) format
- When you *knit* a Rmd, it:
  1. starts a new instance of R (clean environment)
  2. in the current directory
- Any data or code must first be put into the Rmd file
  - The Rmd won't know about anything in another script or in your R environment
  - Any `source()` or data paths are relative to the current directory of the Rmd
- A homework template will be provided for each homework
  - This will automatically apply a custom format if you have the R6018 package installed

## 2.5 Graphics with the `ggplot2` package

The `ggplot2` package is an approach to creating graphics for data analysis.

- See <https://ggplot2.tidyverse.org/>
- Keep the `ggplot2` cheatsheet handy

## 2.6 Data Transformation with the `dplyr` package

- See <https://dplyr.tidyverse.org/>
- Keep the `dplyr` cheatsheet handy

### 2.6.1 single table verbs

1. `filter()`: find/keep certain rows
  - alternative to `base::subset()`
  - `slice()` to keep by row number

- helper functions: `between()`: numeric values in a range
2. `arrange()`: reorder rows
    - alternative to `base::order()`
    - helper functions: `desc()` to use descending order
  3. `select()`: find/keep certain columns
    - helper functions: `starts_with()`, `ends_with()`, `matches()`, `contains()`, `?select`
  4. `mutate()`: add/create new variables
    - alternative to `base::transform()`
    - `transmute()`: only return new variables
  5. `summarize()`: produce summary statistics
    - don't confuse with `summary()`
    - most useful when data is *grouped*

### 2.6.2 Chaining/Pipes

- Multiple operations can be chained together with the *pipe* operator, `%>%`, (pronounced as *then*). Technically, it performs `x %>% f(y) -> f(x, y)`. This lets you focus on the verbs, or actions you are performing.

```
x = c(1:5, NA)
x %>% mean(na.rm=TRUE)
#> [1] 3
mean(x, na.rm=TRUE)
#> [1] 3
```

#### Your Turn #1

1. Load the `nycflights13` package, which contains airline on-time data for all flights departing NYC in 2013. Also includes useful 'metadata' on airlines, airports, weather, and planes.
2. Load the `tidyverse` package
3. Using the `flights` data,
  - find all flights that were less than 1000 miles (`distance`)
  - Keep only the columns: `dep_delay`, `arr_delay`, `origin`, `dest`, `air_time`, and `distance`
  - Add the Z-score for departure delays
  - Convert the departure and arrival delays into hours
  - Calculate the average flight speed (in mph)
  - order by average flight speed (fastest to slowest)
  - return the first 12 rows

### 2.6.3 Other useful `dplyr` functions

- `distinct()`: retain unique/distinct rows
- `slice_sample()`: select random rows
- `slice_min/slice_max()`: select rows with smallest/highest values
- `mutate()/add_column()` add new column in particular position
- `coalesce(x, y)` replaces the NA in `x` with `y`

```
x = c(1, 2, NA, 5, 5, NA)
coalesce(x, 0)      # replace NA with 0
#> [1] 1 2 0 5 5 0
```

## 2.7 Groupwise operations

### 2.7.1 Split - Apply - Combine

The dplyr operations are more powerful when they can be used with grouping variables. Split - Apply - Combine.




Image from Hadley Wickham UseR tutorial June 2014 <http://www.dropbox.com/sh/i8qnlwmuieicxc/AAAgT9tIKoIm7WZKIyK25lh6a>

### 2.7.2 group\_by()

First use the `group_by()` function to group the data (determines how to split), then apply function(s) to each group using the `summarise()` function. Note: grouping should be applied on discrete variables (categorical, factor, or maybe integer valued columns).

```
flights %>%
  group_by(origin, dest) %>% # group by both origin and dest
  summarize(max_delay = max(arr_delay, na.rm=TRUE),
```

```

    avg.delay = mean(arr_delay, na.rm=TRUE),
    min.delay = min(arr_delay, na.rm=TRUE),
    count = n() )      # n() gives the group count
#> Warning in max(arr_delay, na.rm = TRUE): no non-missing arguments to max;
#> returning -Inf
#> Warning in min(arr_delay, na.rm = TRUE): no non-missing arguments to min;
#> returning Inf
#> # A tibble: 224 x 6
#>   origin dest   max.delay avg.delay min.delay count
#>   <chr>  <chr>     <dbl>    <dbl>    <dbl> <int>
#> 1 EWR    ALB       328     14.4      -34    439
#> 2 EWR    ANC        39     -2.5      -47     8
#> 3 EWR    ATL       796     13.2      -39   5022
#> 4 EWR    AUS       349    -0.474     -59   968
#> 5 EWR    AVL       228      8.80     -26   265
#> 6 EWR    BDL       266      7.05     -43   443
#> # ... with 218 more rows

```

- `count(...)` is a shortcut for `group_by(...) %>% summarize(n=n())`
- `ungroup()` removes the grouping

### 2.7.3 Grouped Mutate and Filter

- When data is *grouped*, `mutate()` and `filter()` operate on each group independently

```

#- proportion of carrier at each dest
flights %>%
  count(dest, carrier) %>%
  group_by(dest) %>%      # group by dest
  mutate(total=sum(n), p=n/sum(n)) %>% # grouped mutate sum(n) is by group
  arrange(desc(total), -p)      # arrange by most freq dest and prop
#> # A tibble: 314 x 5
#>   dest carrier      n total      p
#>   <chr> <chr>   <int> <int>    <dbl>
#> 1 ORD   UA      6984 17283 0.404
#> 2 ORD   AA      6059 17283 0.351
#> 3 ORD   MQ      2276 17283 0.132
#> 4 ORD   9E      1056 17283 0.0611
#> 5 ORD   B6       905 17283 0.0524
#> 6 ORD   EV        2 17283 0.000116
#> # ... with 308 more rows

```

## 2.8 Data Importing

### 2.8.1 readr package

- See <https://readr.tidyverse.org/>
- Keep the [data import cheatsheet](#) handy

```

## Load data from course website
library(tidyverse)

#: specify path to url
data.dir = 'https://mdporter.github.io/SYS6018/data/'
url = file.path(data.dir, 'crashes16.csv') # the crashes 16 data set

```

```

#: load directly from web
crashes = read_csv(url)
crashes
#> # A tibble: 456 x 2
#>   mile   time
#>   <dbl> <dbl>
#> 1    87  6.62
#> 2   118  6.70
#> 3   120  0.0549
#> 4    90  0.206
#> 5   124.  0.726
#> 6   118  3.88
#> # ... with 450 more rows

## Download data first, then load into R

#: specify path to url
data.dir = 'https://mdporter.github.io/SYS6018/data/'
url = file.path(data.dir, 'crashes16.csv') # the crashes 16 data set

#: download file
save.path = "data/crashes16.csv" # can be relative path!
download.file(url, save.path)

#: load data from hard drive
library(tidyverse)
crashes = read_csv(save.path)

```

## 2.8.2 readxl package

- See <https://readxl.tidyverse.org/> for importing excel files

## 2.9 Tidy Data with the tidyr package

- <https://tidyr.tidyverse.org/>
- Keep the [tidy data cheatsheet](#) handy.

### 2.9.1 Why Tidy Data?

- Tidy data (in form of a data frame) is usually the best form for analysis
  - some exceptions are for modeling (e.g., matrix manipulations and algorithms)
- For presentation of data (e.g., in tables), non-tidy form can often do better
- the functions in `tidyr` usually allow us to covert from non-tidy to tidy for analysis and also from tidy to non-tidy for presentation

### 2.9.2 Main tidyr functions

---

function	description
<code>pivot_wider()</code> / <code>spread()</code>	Spreads a pair of key:value columns into a set of tidy columns
<code>pivot_longer()</code> / <code>gather()</code>	Gather takes multiple columns and collapses into key-value pairs, duplicating all other columns as needed. You use <code>pivot_longer()</code> / <code>gather()</code> when you notice that you have columns that are not variables

---

function	description
<code>separate()</code>	turns a single character column into multiple columns
<code>unite()</code>	paste together multiple columns into one (reverse of <code>separate()</code> )

### ## Converting to longer format for grouped summaries and plotting


```
delays_long = flights %>%
  select(year, month, day, dep_delay, arr_delay) %>%
  pivot_longer(cols = c(dep_delay, arr_delay), names_to="type", values_to="delay") %>%
  mutate(type = ifelse(type == "dep_delay", "departure", "arrival"))
```

### #: average delays of each type

```
delays_long %>%
  group_by(type) %>%
  summarize(avg_delay = mean(delay, na.rm=TRUE))
#> # A tibble: 2 x 2
#>   type      avg_delay
#>   <chr>      <dbl>
#> 1 arrival         6.90
#> 2 departure      12.6
```

### #: plot histogram

```
delays_long %>%
  ggplot(aes(delay, fill=type)) +
  geom_density(alpha = .5)
```



## 2.10 Loops

We will make good use of iteration in this course. Suppose we want to compare the performance of two models over multiple subsets of a data set.

```
#: simulate fake data
set.seed(2022)
data = tibble(x = runif(100), y = rnorm(100))
```



```
#: fake model output
model_1 <- function(x) rnorm(length(x), mean = -.5, sd = 1)
model_2 <- function(x) rnorm(length(x), mean = .5, sd = 2)
```

We can consider using a for loop

```
n_subsets = 5

set.seed(876)
output = vector("list", n_subsets) # initiate empty list
for(i in 1:n_subsets){

  #: sub-sample data (25 samples)
  data_sub = dplyr::slice_sample(data, n = 25)

  #: get output from the models
  yhat_1 = model_1(data_sub$x)
  yhat_2 = model_2(data_sub$x)

  #: score models (using MSE)
  perf_1 = mean( (yhat_1 - data_sub$y)^2 )
  perf_2 = mean( (yhat_2 - data_sub$y)^2 )

  #: save results
  output[[i]] = tibble(perf_1, perf_2, iter = i)
}

#: convert to tibble and summarize
bind_rows(output) %>%
  summarize(avg.diff = mean(perf_1 - perf_2), n=n())
#> # A tibble: 1 x 2
#>   avg.diff      n
#>   <dbl> <int>
#> 1   -1.51     5
```