

3.7

Managing State

© 2021 Robin Hillyard



Northeastern
University

Continuing our discussion of mutability

- Whether we like it or not, applications typically have *state*.
- Remember how we defined push and pop in the Mill class (3.4 Mutable vs. Immutable)?
- We will continue that theme here.

Problem with Random Number Generation

- Random numbers (for testing)
 - are usually generated by a PRNG (pseudo-random-number-generator), e.g. *java.util.Random*
 - But, by definition, such a PRNG is **non-idempotent** and therefore **non-referentially-transparent**;
 - That's to say:
`random.getNext != random.getNext`
 - and this is anathema to functional programming.
 - In the first week, I referred to the “evils” of mutable state for testing purposes.

Problem with PRNGs continued

- Is there anything we can do about this?
 - Or, are we forever going to be limited by this lack of referential transparency?
- Let's think about the root cause of the problem?
 - It's that a mutable object can change its state without a referrer knowing about it—the referrer is *in the dark*:
 - There are two ways this can happen:
 - the mutable object *spontaneously* mutates (e.g. the system clock or a remote web service);
 - the mutable object is referenced in another thread and is updated there (e.g. draws the next random number);
 - In a testing framework, there are no guarantees about the order of execution of tests—therefore another test may draw a random number.

Carry your protection with you

- Maybe tortoises used to protect themselves by hiding under a rock—then they found it more convenient to carry the rock around with them on their backs ?!
- BTW, I don't believe this of course!



What if we carry our state with us?

- Let's define the following trait:

```
trait RNG[A] {  
  def next: RNG[A]  
  def value: A  
}
```

- It has two properties: its (random) value and the next RNG in the series...
 - ... from which, of course, we can get another random value.
- What we've defined is like the old concept of a “one-time pad” used for setting an encryption key.
 - We only ever call *value* on an instance of *RNG* *once* (it always yields the same result because it's immutable)!
 - To get the next value in the series we invoke `next.value`

Using it in practice

- Here we test in a Spec file:

```
behavior of "RNG"
it should "allow predictable sequential usage" in {
  val r0 = LongRNG(0L)
  val r1 = r0.next
  r1.value shouldBe -4962768465676381896L
  val r2 = r1.next
  r2.value shouldBe 4804307197456638271L
  val r3 = r2.next
  r3.value shouldBe -1034601897293430941L
}
```

- Still, that's not super-useful. For practical purposes, we will need either:
 - a (mutable) *LazyList* of random values, batches of which can be consumed in different places; *Or*
 - an (immutable) *LazyList* of random values that can be consumed in one place.

Streamer

- I call the first of these a *Streamer* (a general concept):

```
/**
 * This class is based on a mutable LazyList.
 * Its purpose is like a one-time-pad: each value is yielded by the Streamer once and once only.
 *
 * @param s the LazyList
 * @tparam X the underlying type and the type of the result
 */
case class Streamer[X] (private var s: LazyList[X]) extends (()=>X) {

  apply() // We need to skip over the first value

  /**
   * This method mutates this Streamer by resetting the value of s to its tail and returning its head.
   * @return the head of the Stream
   */
  override def apply(): X = s match {
    case x #:: tail => s = tail; x
  }

  def take(n: Int): Seq[X] = {
    @tailrec def inner(xs: Seq[X], i: Int): Seq[X] = if (i==0) xs else inner(xs :+ this(), i-1)
    inner(Seq.empty, n)
  }
}

=====

behavior of "take"
it should "work with random number generator" in {
  val target = Streamer(RNG.values(LongRNG(0L)))
  target.take(4) shouldBe Seq(-4962768465676381896L, 4804307197456638271L, -1034601897293430941L, 7848011421992302230L)
}
```


LazyList of Random

- The second is simply an (immutable) *LazyList* of random numbers, generated from an *RNG[T]* instance:

```
trait RNG[T] {  
  /**  
   * @return the next random state in the pseudo-random series  
   */  
  def next: RNG[T]  
  
  /**  
   * @return the value of this random state (renamed from value)  
   */  
  def get: T  
  
  /**  
   * @return a lazy list of T values  
   */  
  def toLazyList: LazyList[T]  
}
```

Guess what?

- You're going to implement the second of these in an assignment.