

MATH473 HW4

Jiasen Zhang

1 Problem 1

Suppose we are computing $w * x * y$, according to commutativity and associativity of convolution, we have:

$$w * x * y = w * y * x = (w * y) * x = w * (y * x)$$

Because

$$(w * y) * x = (M_y w) * x = M_x M_y w$$

$$w * (y * x) = M_{x*y} w$$

We have

$$w * x * y = M_x M_y w = M_{x*y} w$$

$$\Rightarrow M_x M_y = M_{x*y}$$

2 Problem 2

I set the parameter of penalty term $\rho = 1$ with which the result performs best, then try different values of λ , compute SNR and MSE and list them in a table. From Table 1 we can see $\lambda = 0.0001$ corresponds to the largest SNR and smallest MSE. The result with $\lambda = 0.0001$ is the best.

λ	SNR	MSE
0.01	4.6000	6.70e-5
0.001	15.0521	6.00e-6
0.0001	28.9612	2.46e-7
0.00001	28.6852	2.63e-7
0.000001	19.4412	2.21e-6

Table 1: λ vs. SNR and MSE

Plot the result with $\lambda = 0.0001$ below. As shown in Figure 1, with a large SNR, the computed x_0 is almost the same as the ground truth X .




Figure 1: Result with $\lambda = 0.0001$

3 Matlab Code

3.1 Problem 2

```
1 clear all;clc;
2
3 tic
4 % simulate a blurred and noisy image J
5 n = 5;
6 sigma = 1;
7 psf = fspecial('gauss',[n n],sigma); % Gaussian PSF
8 load PartPhantomEg.mat X;
9 [nr,nc] = size(X);
10 P = zeros(nr,nc);
11 P(1:n,1:n) = psf; % zero pad psf
12 ctr = [ceil(n/2) ceil(n/2)]; % center of psf
13 S = fft2(circshift(P,l-ctr)); % eigenvalues of the BCCB matrix A
14 J = ifft2(S.*fft2(X));
15 J = real(J); % blurred
16
17 % get B by adding random noise
18 c = 0.01;
19 E = randn(size(J));
20 E = E/norm(E,'fro');
21 B = J + c*E*norm(J,'fro');
22
23 % initialization
24 x0 = zeros(nr,nc); % to be solved
25 w = zeros(nr,nc);
26 lambda = zeros(nr,nc);
27
28 % parameters
29 lambda0 = 0.0001; % to be tuned
30 rho = 1;
31 tol = 1e-6; % tolerance
32
33 % ADMM iteration
34 for k=1:1000000
35     % old x0 and w
36     xold=x0;
37     wold=w;
38
39     % update new x0
40     %x0 = ifft2( fft2(conj(S).*B+rho*w-lambda)./(S.*conj(S)+rho) );
41     x0 = ifft2( (conj(S).*fft2(B)+rho*fft2(w-lambda/rho))./(S.*conj(S)+rho) );
42     %x0=real(x0);
43
44     % update new w with new x0
45     w = sign(x0+lambda/rho).*max(0,abs(x0+lambda/rho)-lambda0/rho);
46     %w = real(w);
47
48     % update lambda with new w and new x0
49     lambda = lambda + rho*(x0-w);
50
51     % stopping criteria
52     dx = max(max(abs(x0-xold)));
53     dw = max(max(abs(w-wold)));
54     d = max(dw,dx);
55     if mod(k,500)==0
56         fprintf('%d %e\n',k,d);
57     end
58     if d<tol
59         break;
```

```

60     end
61 end
62 %x0=real(x0);
63
64 % compute MSE and SNR
65 mse = sum(sum((x0-X).^2))/(nr*nc);
66 p = sum(sum(X.^2))/(nr*nc);
67 snr = 10*log10(p/mse);
68 fprintf('MSE = %f \n',mse);
69 fprintf('SNR = %f \n',snr);
70
71 % plot
72 subplot(1,3,1);
73 imagesc(X);axis image;colormap(gray);
74 title('Original image X');
75 subplot(1,3,2);
76 imagesc(B);axis image;colormap(gray);
77 title('Blurred image B');
78 subplot(1,3,3);
79 imagesc(x0);axis image;colormap(gray);
80 title('Approximated image x_0');
81 toc

```