

Data Science for Economists

Lecture 5: Loops in R

Drew Van Kuiken

University of North Carolina | ECON 370

Table of contents

1. [Introduction](#)
2. [Loops](#)
3. [The Apply Family](#)
4. [Vectorization](#)

Introduction

Agenda

This class will cover loops in R and their quirks

While loops are fundamental to programming, they are slow in R and should be avoided when possible.

There is a nice family of functions called the apply family that can condense loops into better looking code.

- However, they are still ultimately loops and are just as slow as standard loops.

When in doubt, make sure your code is vectorized when possible!

Drew's thoughts: iiii don't know? Loops are not necessarily slow. They can be fast.

They're also easier than putting stuff in a matrix and less error prone.

Overall: develop your own intuitions about when to vectorize vs when to use loops. Move towards vectorization, especially when you're learning.


Loops

Motivation: For loop

At times we would look to do the same task multiple times that only change a single variable in each iteration.

This can be done with a for loop.

With for loops, you need something to "loop over" and an index that indicates the iteration you're on.



Our First Loop

```
sum_val = 0
for(i in 1:10){
  sum_val = sum_val + i
}
sum_val
```

```
## [1] 55
```

```
sum(1:10)
```

```
## [1] 55
```

```
11*10/2
```

```
## [1] 55
```

Note: for sequence of integers, $\text{Sum} = n(a+l)/2 = 10*(1+10)/2$

Two Approaches to Loops

There are two approaches to loops, and more specifically, what to loop over.

1. Loop over objects in a vector, list, data.frame, etc.
2. Loop over indexes for that vector, list, data.frame, etc.

For ease of understanding *what* is being looped over, 1. is usually best.

- However, it requires keeping track of indexes in another variable.

For ease of storing variables, 2. is usually easier.

- However, what exactly is being looped over can be obscured.

Neither is always better than another and at some point comes down to preference.

Two Approaches: An Example

```
Nsim          = 100          #set number of simulations/draws
norm_draws    = rnorm(Nsim)  #draw  $N(0,1)$  random variables
out1          = rep(0,Nsim)  #initialize output 1: MORE ON THIS LATER
out2          = rep(0,Nsim)  #initialize output 2: MORE ON THIS LATER
n             = 1            #initialize counter

for(draw in norm_draws){
  out1[n] = draw^2            #square the draw and store it
  n       = n + 1            #advance the counter
} #NOTE THAT A COUNTER IS NEEDED

for(i in 1:Nsim){
  out2[i] = norm_draws[i]^2  #square the ith draw and store it
} #notice no counter needed

all.equal(out1,out2) #test to see if these approaches are the same

## [1] TRUE
```

More Examples: Advanced Sums

Suppose we wanted to calculate

$$\sum_{a=1}^{20} \sum_{b=1}^{15} \frac{e^{\sqrt{a}} \log(a^5)}{5 + \cos(a) \sin(b)}$$

```
val = 0
for(a in 1:20){
  for(b in 1:15){
    val = val + (exp(sqrt(a))*log(a^5))/(5+cos(a)*sin(b))
  }
}
val
```

```
## [1] 25922.81
```

The loop works, but it is not needed in R!

- Will return to this at the end of the lecture.

Preallocation

Many times you'll want to use a loop to "fill up" a matrix or vector.

It is best practice to "preallocate" this object to the correct size before filling it.

There are a few reasons for this, but it ultimately comes down to speed:

- Changing the size of the object inside the loop each iteration makes it much slower than they already are in R!

Preallocation: Example

```
N          = 1000000
my_vec     = c(0)
my_vec_pre = rep(0,N)

for(i in 1:N){
  my_vec[i] = i^2
}

for(i in 1:length(my_vec_pre)){
  my_vec_pre[i] = i^2
}
```

Both run! But let's look at the speed.

Preallocation: Comparing Speed


```
mbm = microbenchmark(  
  "no_preal"={  
    my_vec      = c(0)  
    for(i in 1:N){  
      my_vec[i] = i^2  
    },  
  "preal"={  
    my_vec_pre = rep(0,N)  
    for(i in 1:length(my_vec_pre)){  
      my_vec_pre[i] = i^2  
    },times=1000)  
)  
mbm
```

```
## Unit: milliseconds  
##      expr      min       lq      mean     median        uq  
## no_preal 29.230398 33.371610 37.326908 36.693882 39.136462 253.  
## preal   7.515862  8.042438  8.973442  8.390997  9.075575  72.
```

Bottom line: Preallocate objects whenever possible!

While loops

- For loops are not the only types of loops in R!
- Another type is while loops.
- Instead of looping through objects or indexes, we continue to do so as long as a condition is no longer met.
- This can be really useful for some of the things we will use later on.
- Can be dangerous though: infinite loop!
 - Not so much in RStudio, though.



Our First While Loop

```
val = 0
n   = 1
while(n < 31){
    val = val + n
    n   = n + 1
}
val
```

```
## [1] 465
```

```
30*31/2
```

```
## [1] 465
```

The while loop continues to increase *n* by one and add it to `val` until *n*

Econ Application: English Auction

Art and other valuable objects are often sold in an ascending auction where bidders start at a low price and bidders continue to increase the price until only one bidder remains.

We can "simulate" these auctions using while loops.

Suppose there are N bidders and each bidder i has a "valuation" v_i that represents how much she values the object.

As well, suppose there is some fixed amount Δ that bidders must increase the price by each round (no more and no less) and bidders continue to alternate until only one bidder remains. Also suppose that the initial price $p_0 = \Delta$.

So each round t , if a bidder is willing to bid, the price increases to $p_t = p_{t-1} + \Delta$.

Bidder i is willing to bid if $v_i \geq p_t$ or $v_i \geq p_{t-1} + \Delta$.

Let's go to R.

Another Application: An Easy Fix

In math, a fixed point, x^* , of a function f is defined as a value where $f(x^*) = x^*$.

- So a fixed point is a point where when we apply the function to it, we get the same value back!

While loops can be used to calculate these when they exist.

The idea is to keep applying the function over and over again until the value is "close enough"

So $x_{n+1} = f(x_n)$. If $|x_{n+1} - x_n|$ is "small," we stop.

If not, replace x_n with x_{n+1} , and continue.

- So $x_{n+2} = f(x_{n+1})$ and then compare x_{n+2} and x_{n+1} .

We will use the function $f(x) = \sqrt{x}$.

$\sqrt{1} = 1$ and $\sqrt{0} = 0$. So these are our candidate fixed points.

However, we will only get to one of them no matter which starting value we choose.

Calculating Fixed Points

```
eps    = .Machine$double.eps #set tolerance
x_n    = 5000                 #starting guess
x_np1  = sqrt(x_n)           #apply function

while(abs(x_n - x_np1) > eps){
  x_n    = x_np1             #update guess
  x_np1  = sqrt(x_n)         #apply function
}
x_np1
```

```
## [1] 1
```

```
x_n    = 0.00001             #starting guess
x_np1  = sqrt(x_n)           #apply function

while(abs(x_n - x_np1) > eps){
  x_n    = x_np1             #update guess
  x_np1  = sqrt(x_n)         #apply function
}
x_np1
```

```
## [1] 1
```

Implementing Fail-Safes

When writing while loops, it is often good practice to implement a fail-safe so the loop doesn't run for forever.

This could be because the code isn't converging as quickly as we'd like or because the code will never converge because you wrote it wrong.

I did not need one above because that question has really good convergence (and I trust my code 😊).

To implement a fail-safe, we need to create a new variable and use some properties we talked about last lecture.

Ideas?

We want it to stop when $|x_{n+1} - x_n| < \varepsilon$ **or** $n > \bar{N}$ where \bar{N} is some number of iterations we set.

So what is the "while condition?" Hint: DeMorgan's Law!

Implementing a Fail-Safe

```
x_n    = 50000          #starting guess
x_np1  = sqrt(x_n)      #apply function
n      = 1
MaxIt  = 100000
```

```
while(abs(x_n - x_np1) > eps & n < MaxIt){
    x_n    = x_np1      #update guess
    x_np1  = sqrt(x_n)  #apply function
    n      = n + 1      #increase counter
}
```

```
#check to see why loop stopped
if(abs(x_n - x_np1) > eps){
    stop("Did not find fixed point!")
} else{
    print(c(x_np1,n))
}
```

```
## [1] 1 55
```

Fail-Safes (Fixed Points)

Fixed points don't always exist, and even when they do, we're not always able to find them via the iterative procedure I described.

That's where these fail safes can come into play.

Consider the function $f(x) = 2x$. f has a fixed point (and only one fixed point), but however, we are not guaranteed to ever find it via the iterative procedure.

Therefore, the fail safe needs to be triggered so our loop doesn't go on forever.

Necessary Fail-Safes

```
x_n    = 0.0001 #starting guess
x_np1  = 2*x_n  #apply function
n      = 1      #initialize counter
MaxIt  = 1000   #fix max iterations

while(abs(x_n - x_np1) > eps & n < MaxIt){
    x_n    = x_np1      #update guess
    x_np1  = 2*x_n      #apply function
    n      = n + 1      #increase counter
}

if(abs(x_n - x_np1) > eps){
    stop("Did not find fixed point!")
} else{
    print(c(x_np1,n))
}
```

```
## Error in eval(expr, envir, enclos): Did not find fixed point!
```

Repeat Loops

In R, there is a third kind of loop: the repeat loop.

The repeat loop will continue to do something until you manually break

These are slightly different than while loops; however, while loops can be modified to have their behavior quite easily.

I would mostly recommend avoiding repeat loops.

Repeat Loops

```
val = 0
n   = 1
repeat{
  val = val + n
  n   = n + 1
  if(val > 30) break
}
print(c(val, n))
```

```
## [1] 36  9
```

```
val = 0
n   = 1
while(TRUE){
  val = val + n
  n   = n + 1
  if(val > 30) break
}
print(c(val, n))
```

```
## [1] 36  9
```


The Apply Family of Functions

The Apply Family

In R, there are a family of functions called the apply family.

They can be used to write loops in a much more compact format.

The idea is to have some vector-like object that you would do something in a vector-like manner, and then "apply" some function to each element of the object.

If you'd like to see more about the apply family, I would recommend following this [tutorial](#) for more.

The Apply Function

The first one we will look at is the apply function.

It takes three arguments:

1. an array (matrix, vector, etc.)
2. a "margin" (which dimension to apply over)
3. a function

It takes the array and then applies the function over the dimension that margins argument.

Apply: An Example

```
rand_mat = matrix(rnorm(3*2),ncol=3)
rand_mat
```

```
##           [,1]      [,2]      [,3]
## [1,]  1.1837459  0.7296892 0.0007641864
## [2,] -0.7715014 -0.5870856 2.2144653193
```

```
apply(rand_mat,1,sum)
```

```
## [1] 1.9141993 0.8558783
```

```
apply(rand_mat,2,sum)
```

```
## [1] 0.4122445 0.1426036 2.2152295
```

- MARGIN = 1, the sum function is applied to each row.
 - So we are summing across columns
- MARGIN = 2, the sum function is applied to each column.
 - So we are summing across rows.

Apply's Connection to Loops

It might not be entirely obvious apply's connection to loops.

When MARGIN = 1, this is what apply is doing:

```
out = rep(0,nrow(rand_mat))
for(i in 1:nrow(rand_mat)){
  out[i] = sum(rand_mat[i,])
}
out
```

```
## [1] 1.9141993 0.8558783
```

Likewise, when MARGIN = 2, this is what apply is doing:

```
out = rep(0,ncol(rand_mat))
for(i in 1:ncol(rand_mat)){
  out[i] = sum(rand_mat[,i])
}
out
```

```
## [1] 0.4122445 0.1426036 2.2152295
```

Beyond Apply

As seen above, apply can simplify loops and results in much cleaner code.

- Though, is it more readable?

While the apply function is useful, it has its limitations.

1. It can only be used on array-like objects.
2. It will only return a vector or array.

There are other functions that can be used on a wider class of objects and non-arrays.

- lapply: returns a list the same length as the object
- sapply: returns the "most simple" version of the output of lapply that is a vector, matrix, or data frame.
 - I know, this sounds ambiguous because it is!
- vapply: the same as sapply, but an output type must be specified.
 - Generally, safer to use.
- tapply
 - I have never used this one. Just know it exists.

x-apply Examples

```
my_list = list(a = 1:10, beta = exp(-3:3), logic = c(TRUE,FALSE,FA
my_list
```

```
## $a
## [1] 1 2 3 4 5 6 7 8 9 10
##
## $beta
## [1] 0.04978707 0.13533528 0.36787944 1.00000000 2.71828183
## [7] 20.08553692
##
## $logic
## [1] TRUE FALSE FALSE TRUE
```

```
lapply(my_list, mean)
```

```
## $a
## [1] 5.5
##
## $beta
## [1] 4.535125
##
## $logic
## [1] 0.5
```

x-apply Examples (Cont.)

```
sapply(my_list, mean)
```

```
##          a          beta        logic  
## 5.500000 4.535125 0.500000
```

```
lapply(my_list, quantile, probs = (1:3)/4)
```

```
## $a  
## 25% 50% 75%  
## 3.25 5.50 7.75  
##  
## $beta  
##          25%          50%          75%  
## 0.2516074 1.0000000 5.0536690  
##  
## $logic  
## 25% 50% 75%  
## 0.0 0.5 1.0
```


x-apply Examples (Cont.)

```
sapply(my_list, quantile)
```

##		a	beta	logic
## 0%	1.00	0.04978707	0.0	
## 25%	3.25	0.25160736	0.0	
## 50%	5.50	1.00000000	0.5	
## 75%	7.75	5.05366896	1.0	
## 100%	10.00	20.08553692	1.0	

x-apply Examples (Cont.)

By default, `sapply` will apply functions to columns (across rows) of data. `MARGIN = 2` in the `apply` function.

Note, there is no `MARGIN` argument for `sapply`, `lapply`, or `vapply`.

```
data(mtcars)
sapply(mtcars, summary)
```

```
##           mpg      cyl      disp      hp      drat      wt      q
## Min.      10.40000  4.0000   71.1000   52.0000  2.760000  1.51300  14.50
## 1st Qu.   15.42500  4.0000  120.8250   96.5000  3.080000  2.58125  16.89
## Median    19.20000  6.0000  196.3000  123.0000  3.695000  3.32500  17.71
## Mean      20.09062  6.1875  230.7219  146.6875  3.596563  3.21725  17.84
## 3rd Qu.   22.80000  8.0000  326.0000  180.0000  3.920000  3.61000  18.90
## Max.      33.90000  8.0000  472.0000  335.0000  4.930000  5.42400  22.90
##           am      gear      carb
## Min.      0.00000  3.0000  1.0000
## 1st Qu.    0.00000  3.0000  2.0000
## Median    0.00000  4.0000  2.0000
## Mean      0.40625  3.6875  2.8125
## 3rd Qu.    1.00000  4.0000  4.0000
## Max.      1.00000  5.0000  8.0000
```

Vectorization

To Loop or Not To Loop

Generally in R, you want to avoid loops at all costs. This is because they

Developing your programming style in R requires learning when to use l

```
mbm = microbenchmark(  
  "loop"={  
    N = 100000      #set size of vector  
    out = rep(0, N) #preallocate vector  
    for(i in 1:N){  
      out[i] = i^2  #fill in vector with square of index  
    }},  
  "vectorized"={  
    N = 100000      #set size of vector  
    out = 1:N       #preallocate vector  
    out = out^2      #square each index  
  },times=1000)  
mbm  
  
## Unit: microseconds  
##      expr      min       lq      mean    median      uq  
##      loop 7119.313 7807.3000 10539.793 8412.680 9873.459 14986  
##  vectorized 272.527  727.9515  1252.171  770.984  882.128 10332
```

Returning To Advanced Sums

Earlier, we wanted to calculate the following sum:

$$\sum_{a=1}^{20} \sum_{b=1}^{15} \frac{e^{\sqrt{a}} \log(a^5)}{5 + \cos(a) \sin(b)}$$

While we used a loop, it was not necessary. If we expand out every combination, then, we can use vectorized operations.

```
aANDb = expand.grid(a=1:20,b=1:15)
a      = aANDb$a
b      = aANDb$b
sum((exp(sqrt(a))*log(a^5))/(5+cos(a)*sin(b)))
```

```
## [1] 25922.81
```

Benchmarking These Sums

```
mbm = microbenchmark(  
  "loop"={  
    val = 0  
    for(a in 1:20){  
      for(b in 1:15){  
        val = val + (exp(sqrt(a))*log(a^5))/(5+cos(a)*sin(b))  
      }  
    }  
  },  
  "vectorized"={  
    aANdb = expand.grid(a=1:20,b=1:15)  
    a      = aANdb$a  
    b      = aANdb$b  
    sum((exp(sqrt(a))*log(a^5))/(5+cos(a)*sin(b)))  
  },times=1000)  
mbm
```

```
## Unit: microseconds
```

##	expr	min	lq	mean	median	uq
##	loop	5971.643	6595.8195	12901.8845	7383.849	10190.610
##	vectorized	112.349	132.3815	325.7309	179.524	205.061

```
mean(mbm[mbm$expr=="loop","time"])/mean(mbm[mbm$expr=="vectorized"
```

```
## [1] 39.60903
```

When Must We Use Loops?

Sometimes, the use of a loop cannot be avoided. This might be for the following reasons:

1. Calculations depend on previous calculations.
2. The size of an "inner loop" changes based on the values of the "outer loop".
3. Too difficult to do the "prep-work" mentally for the vectorized operation.

Calculations That Depend on Ot

An $AR(1)$ Time Series is a perfect example of an economic application absolutely necessary.

An $AR(1)$ model says that today's value of y , called y_t , depends on yesterday's value scaled by some value ρ , plus some constant δ , plus some error term ε_t .


In math, that is

$$y_t = \delta + \rho y_{t-1} + \varepsilon_t$$

```
rho      = 0.5
delta    = 2
N        = 1000
AR1_ts   = rep(0,N)
AR1_ts[1] = delta + rho*(delta/(1-rho)) + rnorm(1)
for(i in 2:N){
  AR1_ts[i] = delta + rho*AR1_ts[i-1] + rnorm(1)
}
```

Note: I did not use t as the loop variable because of the function `t()`. I cause a namespace conflict.

AR(1) Plot



Inner Loop Dependency

Sometimes when loops are nested (like our advanced sums), the inner loop values depend on the values of the outer loop.

In this case, loops cannot be entirely avoided.

- Though, they can be minimized.

Consider a slight modification of the advanced sum we saw earlier

$$\sum_{a=1}^{20} \sum_{b=1}^a \frac{e^{\sqrt{a}} \log(a^5)}{5 + \cos(a) \sin(b)}$$

Instead of looping b from 1 to 15 , now the max value of b depends on the value of a .

In this case, a loop cannot be avoided.

- At least, without making a specialized grid which will be very tedious.

Dependent Loops

```
val = 0
for(a in 1:20){
  for(b in 1:a){
    val = val + (exp(sqrt(a))*log(a^5))/(5+cos(a)*sin(b))
  }
}
val
```

```
## [1] 27100
```

With some thinking and brute force, the loops might be able to be eliminated.

However, if the speed of your code matters, it is worth spending the time

In Conclusion

Loops are very valuable to understand conceptually, but should be avoided when implementing code in R.

There are variations on loops called while loops that can be very useful for certain things.

There are a family of functions called the apply family which condense loops into compact syntax. However, they are still loops at heart (and just as slow).

For further experience, use `swirl` for loops and the apply functions.

For further reading, please see [this link](#). It was very helpful when making

Next lecture(s): Miscellaneous
