



Deep kNN for Medical Image Classification


Jia-Xin Zhuang¹, Jiabin Cai¹, Ruixuan Wang¹, Jianguo Zhang², Wei-Shi Zheng¹

¹School of Data and Computer Science, Sun Yat-sen University, China

²Department of Computer Science and Engineering,
Southern University of Science and Technology, China.

MICCAI 2020


Motivation




Data imbalance is common in medical diagnosis.

Motivation


kNN only use a few neighboring data.



Data imbalance is common in medical diagnosis.





Motivation



Data imbalance is common in medical diagnosis.

kNN only use a few neighboring data.




Task irrelevant feature will degrade the performance of kNN.



Related work

- ▶ Feature learning for kNN:
 - ▶ Traditional metric learning methods: Neighborhood Component Analysis, Large Margin Nearest Neighbor methods.
 - ▶ Pretrained Model as feature extractor, such as VGG, ResNet.
 - ▶ Triplet based methods.
- ▶ Alleviate data imbalance:
 - ▶ Oversampling, augmentation.
 - ▶ Transfer learning, ensemble model.
 - ▶ Class Weighting (cost sensitive learning), instance weighting.



Framework of deep kNN (training)



Framework of deep kNN (training)



Framework of deep kNN (training)




Search $K + M$ nearest neighbors

Triplet: (Anchor, Positive, Negative)

Different class

Same class




Search $K + M$ nearest neighbors

Triplet: (Anchor, Positive, Negative)

Different class

Same class

Generate triplets for \mathbf{x}_i :



Search $K + M$ nearest neighbors

Triplet: (Anchor, Positive, Negative)

Different class

Same class

x_1 $x_{1,1}^+$ $x_{1,2}^+$... $x_{1,K}^+$ $x_{1,1}^-$ $x_{1,2}^-$... $x_{1,M}^-$

x_2 $x_{2,1}^+$ $x_{2,2}^+$... $x_{2,K}^+$ $x_{2,1}^-$ $x_{2,2}^-$... $x_{2,M}^-$

⋮

x_i $x_{i,1}^+$ $x_{i,2}^+$... $x_{i,K}^+$

⋮

x_N

Generate triplets for \mathbf{x}_i :


- ▶ K nearest neighbors $\{\mathbf{x}_{i,k}^+\}$ of the same class.

Search $K + M$ nearest neighbors

Triplet: (Anchor, Positive, Negative)

Different class

Same class



x_1 $x_{1,1}^+$ $x_{1,2}^+$... $x_{1,K}^+$ $x_{1,1}^-$ $x_{1,2}^-$... $x_{1,M}^-$

x_2 $x_{2,1}^+$ $x_{2,2}^+$... $x_{2,K}^+$ $x_{2,1}^-$ $x_{2,2}^-$... $x_{2,M}^-$

⋮

x_i $x_{i,1}^+$ $x_{i,2}^+$... $x_{i,K}^+$ $x_{i,1}^-$ $x_{i,2}^-$... $x_{i,M}^-$

⋮

x_N

Generate triplets for \mathbf{x}_i :

- ▶ K nearest neighbors $\{\mathbf{x}_{i,k}^+\}$ of the same class.
- ▶ M nearest neighbors $\{\mathbf{x}_{i,m}^-\}$ from all other classes.

Search $K + M$ nearest neighbors

Triplet: (Anchor, Positive, Negative)

Diagram illustrating the triplet structure:

- Anchor (green) and Positive (green) are connected by a double-headed arrow labeled "Same class".
- Anchor (green) and Negative (red) are connected by a double-headed arrow labeled "Different class".


$K \cdot M$ Triplets:

| |
|-------------------------------|
| $(x_i, x_{i,1}^+, x_{i,1}^-)$ |
| $(x_i, x_{i,1}^+, x_{i,2}^-)$ |
| \vdots |
| $(x_i, x_{i,1}^+, x_{i,M}^-)$ |
| $(x_i, x_{i,2}^+, x_{i,1}^-)$ |
| \vdots |
| $(x_i, x_{i,K}^+, x_{i,M}^-)$ |


Generate triplets for \mathbf{x}_i :

- ▶ K nearest neighbors $\{\mathbf{x}_{i,k}^+\}$ of the same class.
- ▶ M nearest neighbors $\{\mathbf{x}_{i,m}^-\}$ from all other classes.
- ▶ K and M neighbors are used to generate $K \cdot M$ triplets.


Framework of deep kNN (inference)




Framework of deep kNN (inference)




Framework of deep kNN (inference)




Framework of deep kNN (inference)



Framework of deep kNN (inference)



Framework of deep kNN (inference)



Experiments on baseline

Deep kNN outperforms baselines

Experiments on baseline

**Deep kNN outperforms baselines
particularly on small classes with a large margin**

| Datasets | Skin-7 | | | Pneumonia | | | SD-198 | | |
|-------------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| Methods | Acc | MCR | RS | Acc | MCR | RS | Acc | MCR | RS |
| kNN (VGG19, $K_p = 5$) | 70.72 | 30.77 | 10.34 | 55.42 | 55.71 | 44.97 | 15.12 | 13.28 | 4.17 |
| kNN (ResNet50, $K_p = 5$) | 74.41 | 37.53 | 34.48 | 55.52 | 54.66 | 39.65 | 19.11 | 17.45 | 12.50 |
| Triplet(ResNet50, $K_p = 5$) | 84.29 | 68.31 | 67.34 | 70.00 | 68.73 | 66.32 | 60.17 | 60.02 | 47.21 |
| deep kNN (ours, $K_p = 5$) | 89.1 | 78.9 | 77.3 | 71.1 | 69.4 | 69.0 | 65.1 | 64.3 | 48.3 |
| Weighted-CE(ResNet50) | 88.02 | 80.21 | 76.60 | 71.12 | 69.11 | 70.05 | 61.90 | 62.40 | 47.67 |
| deep kNN* (ours, $K_p = 5$) | 90.3 | 81.0 | 80.4 | 71.6 | 71.1 | 70.9 | 66.4 | 66.4 | 51.5 |

Advantages of deep kNN

Works with Multilayer perceptron structure

| Methods | kNN-basic | NCA | LMNN | MLP+triplets | MLP+CE | MLP+deep-kNN |
|---------|-----------|-------|-------|--------------|--------|--------------|
| Acc | 64.53 | 75.06 | 81.85 | 77.13 | 78.85 | 85.09 |
| MCR | 34.49 | 36.39 | 61.78 | 62.22 | 63.11 | 66.08 |
| RS | 10.34 | 27.59 | 62.07 | 63.43 | 64.21 | 67.30 |



Advantages of deep kNN

Works with Multilayer perceptron structure

| Methods | kNN-basic | NCA | LMNN | MLP+triplets | MLP+CE | MLP+deep-kNN |
|---------|-----------|-------|-------|--------------|--------|--------------|
| Acc | 64.53 | 75.06 | 81.85 | 77.13 | 78.85 | 85.09 |
| MCR | 34.49 | 36.39 | 61.78 | 62.22 | 63.11 | 66.08 |
| RS | 10.34 | 27.59 | 62.07 | 63.43 | 64.21 | 67.30 |

Advantages of Deep kNN



Faster than traditional triplet loss.



Left: ResNet50 on SD-198; Right: DenseNet121 on Skin-7.

Advantages of Deep kNN

Faster than traditional triplet loss.



Left: ResNet50 on SD-198; Right: DenseNet121 on Skin-7.

Advantages of Deep kNN

Flexibility with Different Architecture

| Models | VGG19 | | ResNet50 | | Dense121 | | SE-ResNet50 | |
|--------|-------|--------------------------------|----------|--------------------------------|----------|--------------------------------|-------------|--------------------------------|
| | kNN | deep kNN | kNN | deep kNN | kNN | deep kNN | kNN | deep kNN |
| Acc | 59.16 | 61.51 ^{+2.35↑} | 60.17 | 65.12 ^{+4.95↑} | 60.54 | 64.02 ^{+3.48↑} | 61.85 | 62.79 ^{+0.94↑} |
| MCR | 56.33 | 61.93 ^{+5.60↑} | 57.35 | 64.34 ^{+6.99↑} | 60.12 | 65.11 ^{+4.99↑} | 59.32 | 62.27 ^{+4.99↑} |
| RS | 43.12 | 45.43 ^{+2.89↑} | 46.01 | 48.31 ^{+2.30↑} | 50.42 | 52.21 ^{+1.79↑} | 50.01 | 53.12 ^{+3.11↑} |

Advantages of Deep kNN

Flexibility with Different Architecture

| Models | VGG19 | | ResNet50 | | Dense121 | | SE-ResNet50 | |
|--------|-------|--------------------------------|----------|--------------------------------|----------|--------------------------------|-------------|--------------------------------|
| | kNN | deep kNN | kNN | deep kNN | kNN | deep kNN | kNN | deep kNN |
| Acc | 59.16 | 61.51 _{+2.35↑} | 60.17 | 65.12 _{+4.95↑} | 60.54 | 64.02 _{+3.48↑} | 61.85 | 62.79 _{+0.94↑} |
| MCR | 56.33 | 61.93 _{+5.60↑} | 57.35 | 64.34 _{+6.99↑} | 60.12 | 65.11 _{+4.99↑} | 59.32 | 62.27 _{+4.99↑} |
| RS | 43.12 | 45.43 _{+2.89↑} | 46.01 | 48.31 _{+2.30↑} | 50.42 | 52.21 _{+1.79↑} | 50.01 | 53.12 _{+3.11↑} |

Advantages of Deep kNN

Flexibility with Different Architecture

| Models | VGG19 | | ResNet50 | | Dense121 | | SE-ResNet50 | |
|--------|-------|--------------------------------|----------|--------------------------------|----------|--------------------------------|-------------|--------------------------------|
| | kNN | deep kNN | kNN | deep kNN | kNN | deep kNN | kNN | deep kNN |
| Acc | 59.16 | 61.51 _{+2.35↑} | 60.17 | 65.12 _{+4.95↑} | 60.54 | 64.02 _{+3.48↑} | 61.85 | 62.79 _{+0.94↑} |
| MCR | 56.33 | 61.93 _{+5.60↑} | 57.35 | 64.34 _{+6.99↑} | 60.12 | 65.11 _{+4.99↑} | 59.32 | 62.27 _{+4.99↑} |
| RS | 43.12 | 45.43 _{+2.89↑} | 46.01 | 48.31 _{+2.30↑} | 50.42 | 52.21 _{+1.79↑} | 50.01 | 53.12 _{+3.11↑} |

Advantages of Deep kNN

Flexibility with Different Architecture

| Models | VGG19 | | ResNet50 | | Dense121 | | SE-ResNet50 | |
|--------|-------|--------------------------------|----------|--------------------------------|----------|--------------------------------|-------------|--------------------------------|
| | kNN | deep kNN | kNN | deep kNN | kNN | deep kNN | kNN | deep kNN |
| Acc | 59.16 | 61.51 ^{+2.35↑} | 60.17 | 65.12 ^{+4.95↑} | 60.54 | 64.02 ^{+3.48↑} | 61.85 | 62.79 ^{+0.94↑} |
| MCR | 56.33 | 61.93 ^{+5.60↑} | 57.35 | 64.34 ^{+6.99↑} | 60.12 | 65.11 ^{+4.99↑} | 59.32 | 62.27 ^{+4.99↑} |
| RS | 43.12 | 45.43 ^{+2.89↑} | 46.01 | 48.31 ^{+2.30↑} | 50.42 | 52.21 ^{+1.79↑} | 50.01 | 53.12 ^{+3.11↑} |

Acknowledgement

Thanks for watching.



This work is supported in part by the National Key Research and Development Program (grant No. 2018YFC1315402), the Guangdong Key Research and Development Program (grant No. 2019B020228001), the National Natural Science Foundation of China (grant No. U1811461), and the Guangzhou Science and Technology Program (grant No. 201904010260).