

Sea-Bird Electronics, Inc.

1808 136th Place NE, Bellevue, Washington 98005 USA Website: http://www.seabird.com

FAX: (425) 643-9954

104 mA

Tel: (425) 643-9866 Email: seabird@seabird.com

SBE 5M MINI SUBMERSIBLE PUMP CONFIGURATION SHEET

Serial Number:	<u>1491</u>					
Job Number:	<u>66476R</u>					
Customer:	NOAA/PMEI	<u>L</u>				
Delivery Date:	<u>1/13/2012</u>					
Single Bulkhead Connector.						
Pressure Case: 10,500 meters (titanium)						
Maxon Motor Type:						
P/N 801605, Motor PN 20130 (Pulsed Duty 6 VDC, 2000 RPM MAX)						
P/N 801606, Motor PN 20127 (Continuous Duty 9 VDC, 2000 RPM MAX)						✓
Vin 15V valtage	o coroco CO.	7 000	VDC	Current	10 5 m	
Vin 15V voltage	across GZ.	7.900	VDC	Current	10.5 mA	
Vin 9V voltage	across C2:	7.982	VDC	Current	10.6 mA	
Vin 6V voltage	across C2:	5.776	VDC	Current	9.52 mA	

Pump submerged test, no load, Vin 12VDC Average current draw in water: