PO Box 518 620 Applegate St. Philomath, OR 97370



(541) 929-5650 Fax (541) 929-5277 www.wetlabs.com

## **FLNTU Characterization Sheet**

Date: February 25, 2016 S/N: FLNTUS-1075

## **Chlorophyll Scale Factor**

Chlorophyll concentration expressed in µg/l can be derived using the equation:

CHL ( $\mu$ g/I) = Scale Factor x (Output - Dark Counts)

Dark Counts	Analog		Digital	
	0.089	V	61	counts
Scale Factor (SF)	21	μg/l/V	0.0251	μg/l/count
Maximum Output	4.98	V	4121	counts
Resolution	0.6	mV	1.0	counts
Ambient temperature during calibration	22.3	°C		

## Nephelometric Turbidity Unit (NTU) Scale Factor

Turbidity units expressed in NTU can be derived using the equation:

NTU = Scale Factor x (Output - Dark Counts)

	Analog		Digital	
Dark Counts	0.076	V	51	counts
NTU Solution Value	0.95	V	769	counts
Scale Factor (SF)	174	NTU/V	0.2109	NTU/count
Maximum Output	4.98	V	4121	counts
Resolution	0.6	mV	1.0	counts
Ambient temperature during calibration	22.3	°C		

## **Definition of terms:**

Dark Counts: Signal output of the meter in clean water with black tape over detector.

NTU Solution Value: Signal output of the turbidity sensor when measuring a sample of interest.

**SF (CHL)**: Determined using the following equation:  $SF = x \div (\text{output - dark counts})$ , where x is the concentration of the solution used during instrument characterization. SF is used to derive instrument output concentration from the raw signal output of the fluorometer.

**SF (NTU)**: Scale factor is determined using the following equation:  $SF = xx \div (Output - Dark counts)$ , where xx is the value of a Formazin concentration. For example:  $12.2 \div (2011 - 50) = 0.0062$ .

Maximum Output: Maximum signal output the fluorometer is capable of.

Resolution: standard deviation of 1 minute of collected data.

FLNTUS-1075 fIntuchar Revision H 10/2/07