## Sea-Bird Electronics, Inc.

## 13431 NE 20th Street, Bellevue, WA 98005-2010 USA

Phone: (+1) 425-643-9866 Fax (+1) 425-643-9954 Email: seabird@seabird.com

SENSOR SERIAL NUMBER: 0507 CALIBRATION DATE: 05-Oct-16

SBE 39 RTC CALIBRATION DATA ITS-90 TEMPERATURE SCALE

## **COEFFICIENTS:**

rtca0 = 9.999765e-001 rtca1 = 1.608726e-006 rtca2 = -3.667277e-008

RTC	COMPUTED	RESIDUAL
FREQUENCY (Hz)	FREQUENCY (Hz)	(PPM)
0.9999740	0.9999740	-0.0
0.9999780	0.9999780	0.0
0.9999830	0.9999829	-0.1
0.9999870	0.9999870	-0.0
0.9999900	0.9999901	0.1
0.9999920	0.9999923	0.3
0.9999940	0.9999937	-0.3
0.9999940	0.9999941	0.1
0.9999940	0.9999936	-0.4
0.9999920	0.9999923	0.3
0.9999900	0.9999900	0.0
	FREQUENCY (Hz) 0.9999740 0.9999780 0.9999830 0.9999870 0.9999900 0.9999940 0.9999940 0.9999940 0.9999920	FREQUENCY (Hz) 0.9999740 0.9999780 0.9999780 0.9999830 0.9999870 0.99999870 0.9999900 0.9999900 0.9999900 0.9999920 0.9999940 0.9999940 0.9999940 0.9999940 0.9999923 0.9999940 0.9999920 0.9999936 0.9999920 0.9999923

t = temperature (°C)

RTC frequency =  $rtca0 + rtca1 * t + rtca2 * t^2$ 

Residual (PPM) = (Computed RTC frequency - Measured RTC frequency) \* 1e6

