## Sea-Bird Electronics, Inc.

## 13431 NE 20th Street, Bellevue, WA 98005-2010 USA

Phone: (+1) 425-643-9866 Fax (+1) 425-643-9954 Email: seabird@seabird.com

SENSOR SERIAL NUMBER: 3770 CALIBRATION DATE: 04-Mar-15

SBE 37 PRESSURE CALIBRATION DATA

FSR: 1450 psia S/N 6036

## **COEFFICIENTS:**

PA0	=	7.866619e-001	PTCA0 = -1.515528e+002
PA1	=	6.905437e-002	PTCA1 = 4.843444e-001
PA2	=	-3.692928e-009	PTCA2 = 2.656836e-004
			PTCB0 = 2.477262e+001
			DTCR11 0750000_003

PTCB2 = 0.000000e+000

	PRESSU	THERMAL CO	THERMAL CORRECTION			
PRESSURE	INST	TEMP	COMPUTED	ERROR	TEMP	INST
PSIA	OUTPUT	ITS90	PRESSURE	%FS	ITS90	OUTPUT
14.75	61.8	23.2	14.75	-0.00	32.50	86.37
315.02	4406.4	23.2	314.99	-0.00	29.00	84.83
615.02	8749.4	23.1	614.98	-0.00	24.00	82.62
915.03	13094.7	23.1	914.98	-0.00	18.50	79.50
1214.98	17441.8	23.1	1214.98	-0.00	15.00	77.60
1464.98	21066.0	23.0	1464.97	-0.00	4.50	72.69
1214.99	17442.3	23.1	1215.01	0.00	1.00	71.05
914.99	13095.3	23.0	915.03	0.00		
614.99	8750.0	23.0	615.02	0.00	TEMP (ITS90)	SPAN (mV)
314.98	4406.9	23.0	315.03	0.00	-5.00	24.78
14.75	61.6	23.0	14.74	-0.00	35.00	24.73

 $x = pressure output - PTCA0 - PTCA1 * t - PTCA2 * t^2$   $n = x * PTCB0 / (PTCB0 + PTCB1 * t + PTCB2 * t^2)$  $pressure (psia) = PA0 + PA1 * n + PA2 * n^2$ 

