

CARMANAH M550 LIGHT

METOCEAN GPS

FCOM_V1

DRAFT

WRENCH TIGHTEN
ALL SHACKLES

7/8" SAS -**NYLON NUT?**
.5 METER 1" CHAIN
7/8" SAS -**NYLON NUT?**

INDUCTIVE BREAKOUT

BELOW SOCKET,
PAWLER STOPPER.

PAWLER
CTD, DO 4330, FLUOROMETER

27.5 METERS 3/8" WIRE ROPE
SOFT JACKETED PAWLER WIRE

HYDROSHOCK
PAWLER STOPPER

SWAGED WIRE TERMINATION
5/8" SAS

.5 METER 1/2" CHAIN

WRENCH TIGHTEN
ALL SHACKLES

5/8" SAS
3 TON SWIVEL
5/8" SAS
5/8" SAS
8242 ACOUSTIC RELEASE


5/8" SAS

.5 METER 1/2" CHAIN

3/4" SAS

15 METER 1" STUD CHAIN

POSSIBLE SWITCH IF DOME CAN BE FABRICATED/PURCASED



1680# ANCHOR W/ STEEL DOME

3/4" SAS NUT WELDED TO PIN

7 METER 1/2" CHAIN

3/4"SLING LINK
3/4"SAS

1 METER 1/2" CHAIN

3/4"SAS

7/8" SAS

3400# ANCHOR dry wt.
1900# ANCHOR wet wt.

DEPTH 36 METERS
WITH LENGTHS AS SHOWN
SCOPE: 1.50:1



NOAA-PMEL-EDD
7600 Sandpoint Way NE
Seattle, Wa. 98115
(206) 526-6149

MOORING:
21BSITAEFPR-14A/FCOM_V1_B14

LOCATION:
BERING

DRAWN BY:
MIKE CRAIG

DATE:
25 MAY 2021

APPROVED BY:

DATE: