

ICE DETECTION HYDROPHONE
CARMANAH M550 LIGHT

VAISALA(wxt510)
METOCEAN GPS

36" FLOAT EST. ~600# BUOYANCY

WRENCH TIGHTEN
ALL SHACKLES

3/4" SAS W/NYLON NUT
3/4" SAS W/NYLON NUT
3 LINKS 3/4" CHAIN
7/8" SAS W/NYLON NUT

INDUCTIVE BREAKOUT

BELOW SOCKET,
PRAWLER STOPPER.

PRAWLER
CTD, DO 4330, FLUOROMETER

27.5 METERS 3/8" WIRE ROPE
SOFT JACKETED PRAWLER WIRE

HYDROSHOCK
PRAWLER STOPPER

SWAGED WIRE TERMINATION
5/8" SAS

.5 METER 1/2" CHAIN

WRENCH TIGHTEN
ALL SHACKLES

5/8" SAS
3 TON SWIVEL
5/8" SAS
5/8" SAS
8242 ACOUSTIC RELEASE

5/8" SAS

.5 METER 1/2" CHAIN

3/4" SAS

15 METER 1" STUD CHAIN

3/4" SAS NUT WELDED TO PIN

7 METER 1/2" CHAIN

3/4"SLING LINK
3/4"SAS

1 METER 1/2" CHAIN

3/4"SAS

7/8" SAS

3400# ANCHOR dry wt.
1900# ANCHOR wet wt.

DEPTH 36 METERS
WITH LENGTHS AS SHOWN
SCOPE: 1.50:1



NOAA-PMEL-EDD
7600 Sandpoint Way NE
Seattle, Wa. 98115
(206) 526-6149

MOORING: 22BSITAEFPR-14A/FCOM_V2_B14

LOCATION: BERING

DRAWN BY: MIKE CRAIG

DATE: 12 AUGUST 2022

APPROVED BY:

DATE: