Sea-Bird Electronics, Inc.

13431 NE 20th Street, Bellevue, WA 98005-2010 USA

Phone: (+1) 425-643-9866 Fax (+1) 425-643-9954 Email: seabird@seabird.com

SENSOR SERIAL NUMBER: 3767 CALIBRATION DATE: 04-Mar-15

SBE 37 PRESSURE CALIBRATION DATA

FSR: 1450 psia S/N 5756

COEFFICIENTS:

PA0 = 8.019693e-001 PTCA0 = -1.728584e+002
PA1 = 6.919261e-002 PTCA1 = 4.996848e-001
PA2 = -3.970452e-009 PTCA2 = -1.562682e-005
PTCB0 = 2.469425e+001
PTCB1 = -5.500000e-004

PTCB2 = 0.000000e+000

PRESSURE SPAN CALIBRATION THERMAL CORRECTION **PRESSURE INST TEMP COMPUTED INST ERROR TEMP** PSIA OUTPUT ITS90 **PRESSURE** OUTPUT %FS ITS90 14.75 14.75 0.00 32.50 61.89 40.2 23.2 315.02 4378.6 23.3 315.01 -0.00 29.00 60.38 615.02 8715.1 23.2 614.99 -0.00 24.00 57.96 915.03 13054.0 23.2 914.98 -0.00 18.50 55.05 1214.98 17395.0 23.2 1214.97 -0.00 15.00 53.12 -0.00 1464.98 21014.4 23.2 1464.98 4.50 48.03 1214.99 17395.6 23.1 1215.01 0.00 1.00 46.36 914.99 13054.6 23.1 915.02 0.00 TEMP (ITS90) SPAN (mV) 614.99 8715.5 23.1 615.02 0.00 -5.00 24.70 314.98 4378.7 23.1 315.02 0.00 14.75 39.9 23.1 14.73 -0.00 35.00 24.68

 $x = pressure output - PTCA0 - PTCA1 * t - PTCA2 * t^2$ $n = x * PTCB0 / (PTCB0 + PTCB1 * t + PTCB2 * t^2)$ $pressure (psia) = PA0 + PA1 * n + PA2 * n^2$

