F	MILLER	1 100/11				1	HURSD		17 FE 320		ZONE +9			
TII	ME POSITION (Lat. and Long	PRESEN WEATHE	IT IR	AL (W.W.) DIF		EA WAVE	SW SW	ELL WA	₹	SEA LEVEL	TEM	PERATUR OC		
01	166°32,0'h		2					(F		SEA	BUL			
02	MOORED AS BE	DRE RIS	12	136		-			2.	8 984.	23.	81.7		
03	MOORED AS BE	DRE R.S	2			2-	-	1	2.		02.2			
04	MODRED AS BEE	DRE R	2			2-		-	2.8	981.6	3.6	1.9		
05	MOGRED AN BER	RE R.S	12	141		2-	~ /~	+	2.8	980,0	3.0	2.0		
06	MODRED AS BOR	RE R.S	2	134		2-3			2.	978.0	2.8	1.8		
07	MORED AS REPO	RE RS	2	096		2-3	4-	-	2.7		2.7	1.8		
08						18-3	+	-	2.7	974.6	2.5	1.7		
09	MODED AS BERN	R/3	2	170	18-2	S 202	,+-	+-	No		ļ			
11 11 11 R/S 2 100 6 0.5 Scs 971.6 3.6 2.9														
11 11 11 CL 1 130 8-19 5 970.0 4.0 3.0														
12 967.1 4.6 3.6														
13														
14	11 11	CL, R	1	130	28	3-4	+	+		-				
15	\ \(\(\)	CLIL	2	121	19	2-3	1	-	-	963.2	4.5	3.2		
16	14	CL	3	130	12			1	 	962.1	4.9	3.5		
17		در	3	180	8	0-1	-	1	+-	960.4	5.5	4.2		
8	166 -21.20	CL	3	160	18	0-1	-	 	+-	959.3	5.5	4.8		
9	50-58.92	Nostly CL	10	150	21		222	/		959.1	6.3	4.8		
0	166°16.9'W	-BAPC	10	127	24	2-12	030	2-5		959.5	5.0	3.5		
1 /	540 13.6'N 1660 5.8'W	Pc	O	166	30	2-4	200	2-5	2.4	958.1	7.3	5.0		
2 /	54 · 17.6/21 169 · 14.1/21 24 · 23.3/N	Pc	10	170	32	4-6	000	2-4		954.3		3.3		
3 /	45030.31.1	CL RE	10	174	34	6-10			2.8	760.7	3.4	3.2		
MARK	65018.41	CL,R	10	165	26	6-10			10.1	163.1	32	3.2		
	_	In Port	Dw		Herbo				2-8	964.2	3.0	3.0		
	1800	u/w ç			teh_		han	·						
							00/							
	- 													
	· · · · · · · · · · · · · · · · · · ·													
														

DECK	LOG	 WEATHER	OBSERVATION	SHEET

NO	AA SHIP	DE	ECK L	OG - W	/EATHE	R OBSI	ERVAT	ION SHI	EET		O ADMIT	NISTRATI
	Mulca					DAY		DATE		TIME Z	ONE	
	MILLER	FREEMY	<u> </u>			FR	DAY	18F	EB2000			
ТІМ	POSITION	PRESENT	___	T								
	(Lat. and Long.)	WEATHER	VISIBILITY	`	IND	SEA WAVE HEIGHT	SWEL	L WAVES	WATER EMP.	EVEL	TEMPE	ERATURE OC
01	54036.9 N	-	× N	DIR. (True)	SPEED (Kts.)	SEA	DIR.	HEIGHT	SEA W	SEA LEVEL PRESSURE (mb)	DRY	WET
02	54036.9'N 54046.7'N 1640 50.5'N	CI	1/0	175	27	6-10			1.6	966,8	 	3.0
03	1640 39,4 1M	PC PC	10	157	19	5-8			1.7	967.9	4-3	3.0
04	164.22 N	12	10	157	29	6-10			1.4	966.2	3.8	
)5	55011.7 N	CL	9	150	28	6-10			1.8	966.8	3.9	3.7
6	163 55.5 (1)	CL	10	120	20	5-8		/	1.7	968.6	51	4.1
7	35 44 E S	CL	10	120	18	5-6	/	-	1.5	968.3	4.6	4.1
8 9	163° 58.2' W	a	10	150	21	5-6	/		1.6	9686	4,5	4./
7 0	56° 8.3'N	cı	10	142	26	5-6			1.1	969.1	4.0 52	3.8
1	164 0.2'W	CL	10	147	21	5-6	07%	, 3	0.7	969.9	3.3	3-2
	560 29.5 N	CL	10	140	18	5-6	870	10	0.8	4	3.5	3.3
3	164°02,2'N	CL	10	120	21	5-6	090	6	-0. 8	970-5	3.6	3.1
4	164.05.0.M	CL	10	115	17	5-6		6	-0.4	970.5	3.5	3,1
,	56°52.6'N 164° 02, 7'W	در	10	110	18	5-6	090	6	-0.9		3.0	2.2
,	66 52.4 N 16404.4 W	CL	10	120	15	5-6	100	6			ه.3	21
	56' 52.6'N 164' 03.2'W	CL	10	131	18	6-8	100	8			3.7	2.9
	56 51.9 2	CL	2	115	10	5-6	100	8	-1.1		3.8 3.5	2.5
	C457.0 W	CL	2	<i>i</i> 20	10	56	100	5	71,1	12.	2.8	26
	163 25 1 11	R/s	3	140		5-7	100	8		971.3	-	1.2
4	5618 N 163.8 W	CL_	3	135-14	115	5						0.0
	12 37 0 W	<u>a</u>	16	152	12	5			-0.3	172.0	2.3	0.4
7	36°45,4'N	CL	10	180	R	-8			-0.9	9724	18	0.4
A ID	1640 17.3/W	CL	10	182	11	5			-0.7	972,80	1.3	0-1
٤	1000: SWE	L Dire	ction	w_0	70 a	udo	2/0 -			-		
	 			· <u> </u>								
									· · · · · · · · · · · · · · · · · · ·			
				,					· · ·	· · ·		
	_	<u> </u>										$\neg \neg$
					· · · · · · · · · · · · · · · · · · ·							
			 -		·					<u></u>		
	08M 27 100 10	161										

DECK LOG - WEATHER OBSERVATION SHEE

01 5 02 14 03 5 04 5 05 54 06 5 07 36	4014.9 W TO1.2.N 24.13.56 6.54.0 N 24.20.6 W 20.46 W 20.46 W 4.29.3 W	PRESENT WEATHER	O VISIBILITY	DIR. (True)	SPEED (Kts.)		SWEL	LL WAVES	WATER OC		1-9 TEMPE	ERAT
02 JE 03 5 04 5 05 56 06 S 07 3 6	158.2 N 14014.9 W 101.2 N 1713.5 W 17 30.6 W 17 30.6 W 17 30.6 W 17 30.6 W 17 30.6 W	CL	10			3 男王,			1 - 30	1 422		OC.
02 JE 03 5 04 5 05 56 06 S 07 3 6	158.2 N 14014.9 W 101.2 N 1713.5 W 17 30.6 W 17 30.6 W 17 30.6 W 17 30.6 W 17 30.6 W	CL	T-	1201		- 1 · ii	DIR. (True)	HEIGHT	SEA *	SEA LEVEL PRESSURE (mb)	DRY BULB	W BU
04 5 05 56 06 5 07 56	69-13.56 69-54-0 N 14-20-6 N 15-740-10 41-29-3 W			_		12	+		-0.8	973.2	 	
06 S	7.59.54		10		18	12	/	/	-1,1	973,8	-	
06 S	7.59.54	CL	12	190	8	12	+	+	-1.2	974.0	2.5	1.
07		CL	10	191	7	12	+	+	-1.0	979.0	2.0	1
07		CL	8-10			2	210	4	0.8	915,9	21	1
	47495W	CL		190	10	2		 	0.3	974.9	1.0	0.
08 //2	502.61 N 602.61 N 6024.27 524.01 W	ü	8-10		10	2	210		0,4	975,1	1.0	0
	5021.0 W	CL/S	8-10	1	08	4	230	5-6	40.4		0.8	0.
16	5 29.3 W	C45	3-10		12	4	240	5-6	0.8	975.5	1.0	0.
16	4 16.4 N 5 46.4 W	CL/R/s	5-10		16	2-4	240	I		976.1	1.9	1.
	056.9'W	CL, R	8-10	260	16	2-4	250	5-6	[976.6	1.3	1.
1 10	03.6.N	CLIL	8	250	18	2-4	240	5-7			2.5	2.
14	6-18.8.W	CL	10	241	25	3-5	235	6-8		978.9	3.7	3.1
160	0500W	CL	10	240	23	4-6	240	1-19				3. ₁
- 166	19.8 W	CL	10	240	22	4-6	245	5-7		24		3.0
166	"28.62	CL	/0	250	20	4-7	250	6-8			2.2	1.3
661	12.65 M 71.6W	CL	8	235	20	3-5	250	6-8				20
' VCL	29.44V	CL	10	230	20	3-6	250	6.8	2.0	980.4	3.8	2.4
554	56.4'N		10	233	थ।	6-10	230	6-10			3.9	1.8
55	75.0 N	CL	10	227	20	6-10	240	6-10	1.8	481.1	3.0	1.9
1166	24.8'W	PC	10	235	18	3-6		10-12			2.5	1.5
55	58.9 N			+	20	3-6	240				2.0	1.1
	6 3t.9 W	cr	10	230	20	3-6	240	10	1.8 4	82.0 7	7.0	(.2

NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION

DECK LOC WELL	AL OCEANIC AND ATMO
VEATI	TER OBSERVATION SHEET
	_ TOOLINA HON SHEET

L	MILLER	FREEM	an			Jun	γ	ATION S		J 7102	F 74.	
L				•		δι	NO44	_ 2	FEB :		E ZONE	
TIN	POSITION (Lat. and Long.	PRESEN WEATHE	IT E	OIR (Tru	WIND	AVE	sw	ELL WAVE				PERATU
01	55 558 N		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	OIR (Tru	SPEE	SEA W	SW DIF	111610		SEA LEVE	(qm)	0 c
02	166°54 0				0 2 2		24	1 (11)	- S		_	B BUL
03	16705.94		10	218		3-	5 2-				02.0	
04	55 40.5 N	1 CL	16			2-	, = 1			ı		
06	55°386 N	CL	10	220		3.1	47			982.		8.9
07	55 33,6 N	CL	10	218		, ,	270			981.9	2.1	1.2
08	55 30.3 N 167 52.6 W	CL	10	253		4-7	240			981.4		1.7
10	168 03,6W	PC	10	203	7	4	240		 	979.		1.0
11	148 04 ,46 55 22.42 168 10 9	10/5	10 5=10	205	18	5	240			980.1	2.2	1.3
12	55 22.1 N 108 12.8 W	PC	6	220	21	5	240	16-20	10.0	979.6		1.0
4	168 14.3W 56 21.2'N 1680 14.6'N	PC	10	218	19	5	240	14-16	3.2	979.5	2.1	3.0
5	55 ZZ.06 N	PC/3	10	200	15	<i>5</i>	240	14-16	2.9	979.5	3.9	2.8
	168,13.1 W	PC	10	205	14	5	240	14-16	2.9	979. ₁		2.8
	65 23.3 N	PC rc	10	205	14	5	, , , , ,	14-16		979.1	4.1	3.0
	168 12.3 W 55 22 4 N 168 15.4 W	PC	10	195 LIGHT	5 MRS	5°	240	16-18	3.1	979,5	3,2	1.8
) /	55 16.9 W 55 07.5 N	PC	10	020	10	4	240	15-18	3.0	980.0 980.5	4.5	2.2
//	55 07.0N	<u>u/s</u> 5	8	2116	08	2	240	10	2.8	981.9	4.7	3.9
	68 29.7 W 55 64.8 N 68 29.8 W	CL		345 350	15 18	2-3 2-3	240	4-2	2.86	982.7 983.9	4. <i>e</i> 5.0	3.0
	5 40.8'N 64.38'8,8'M	CL	10	346	27	5	240	8	2.7	985,8		3.1 2.9
									<u> </u>	,		
					<u> </u>		<u></u>	·	-			
												 .
				<u> </u>				·				
							 -	·	<u>_</u>	<u> </u>		

DECK LOG - WEATHER OBSERVATION SHEET

NOAA SHIP MILLER FREEMAN DAY TIME ZONE MUN DAY 21 Feb Zuw 19 POSITION TIME JILITY V.M.) (Lat. and Long.) PRESENT WAVE IGHT WIND WEATHER WATER SWELL WAVES SEA LEVEL PRESSURE (mb) TEMPERATURE VISIL (N. SEA HEI (FL 0_C DIR. SPEED (True) DIR. 54 58.2.N 68 45.7W HEIGHT (Kts.) 01 (True) DRY (Ft.)WET CL BULB 10 330 54 58 18 N 26 BULB 4-6 02 168 46.4W 5-050,71N 168 56.1 W 240 8 2.7 987.2 8 3,0 2.0 325 28 4-6 240 8-10 U3 2.7 988.1 Q L 2.5 2.0 330 28 697066 W 04 10 1990,1 ΙÒ **3.0** 330 4-6 54 39.7N 26 05 10-19 CL 990.3 3 40 2.0 320 54 9:39.8N 34813.8W 169 23.81 54 24.2N 169 38.4W Z5 4-8 340 15-18 2.7 06 993.0 CL 2.5 1.4 K 330 20 6 -3 345 15-18 2.7 994.9 07 1-4 330 C) 25 OA 2,5 340 22 240 10 10 3.2 496 4-19.90 09 1.6 69-49.9W CL 302 54 19.34N 149 50.48W 540 17.0 N 164 48.5 W 540 03.3 N 169 34.9 W 540 2.2 N 169 34.8 W 16 20 10 2.6 10 CL)S 335 10 22 6-8 310 12 2.0 998.9 0.5 R 325 340/ 3 10 20 240 1000.1) .0 0.7 12 PC 330 3 10 10 340 26 4 1902.0 2. 4.4 0 13 PC 10 320 3 15 315 5-7 2.6 1002.0 3.9 1.0 54 02 3 N 14 PC 169 35 8 W 10 3i5 2 16 320 7.6 3.1 1002.5 1.1 53 54 4 N 169 24 4 W 15 PC 10 305 3 16 2.7 1003.6 3,5 1.2 16 53 47. 6 N 17 PC 167 16.8 W 10 33°C 13 310 5 1003.4 10 2.5 2.5 0,0 53.45.5 N 18 169 14.6 6 340 315 0 10 106.2 Δ. 53 36.4 N 19 5 ₩ C 346 10 16903.7 W LO 320 60 3.4 10640 3.0 ۵,5 53 36.7 N 20 5 8 5 300 8 3-4 14902.94W 240 3.H 2.8 0.7 1004. 53 30. BN 21 7 3 5-10 260 16854.BW 280 8 2.6 2.8 1.1 1005.0 53 31.06 N 148 54.47W 53 24 4.N 168 14.8 W 53 26.5 N 168 44.9 W 22 5-10 CI LIGH MICS 3 3.5 0.0 105.2 1.2 23 CL 3 5-10 025 3.4 0.0 ー ひ、 子 24 3 030 8 3.5 10 3.0 1005.1 REMARKS 1600: NOTDONE - LIJG SCHERER 1700, TEMP TAKEN FROM STIDD SIDE (OPPOSITE OF SUN)

NOAA FORM 77~13D (3-76)

SUPERSEDES NOAA FORM 77-13D (7-72). EXISTING STOCK

- 1	A SHIP		DECK	LOG -	- WEAT	HER OI	SFPV	TION O	ANIC AN	D ATMOS	ARTMEN'	OF COL
1	M)) 100 -					DA			MEFL			
	HOUR	FREEMA	4N					DA	TE	ŤĮ	ME ZONE	
-	T					TI	LESDA	1 22	2 Feb 2			
TIME	POSITION			<u> </u>						-	+9	
	(Lat. and Long.) PRESE	NT R	3	WIND	W N	- F.W.		7			
				W. DIR		SEA WAVE	2	ELL WAVE	ES A	LEVEL	TESSIBLE (mp) DI (mp)	MPERATI
01	53°24.8'N	-		(Tru		SEA	DIR (True	1110	חיו כו	- A	(mp)	<u>oc</u>
1 /	16 * 43.8 'N		10	280	07		17) (F1.)	<u>"</u>		r Bui	-B BUI
 #	65 43.31.1	PC	10	- 1		+3	K-		3.4	1 100	01.	60.
	30 12.7'N	45	1	316		12	/		3.4	,	7	
0.4	5 13.9 N	CL	10			2	<		3.7	100		
- A IX	2 561 N 69 20.8 W		10	310		2			3.6			
06	A. 77.7 N	100	10			13	360	7-8	3.8			-100
07 5	241.6 N		10	300	8	2	260	7-8	1		4	
08	52° 34 .8'N		10	260	10	2	245			1005		
	zg° るス <i>4</i> /W	CL	10	115	20	4			4.0	1000		0.2
10 5	2° 32.9'N 2° 30.9'N	CL	10	132	20	4	240	5	3.5	997.		-0.4
_'' //3	20° 11.0'W	CL	10	120	24	4			2	9961		-0.
	10032.5'w	CL	10	122	30		240	5				0.0
	6.33.7 W	CLS	2	105	35	4	240		T		1-1-10	-0.
13 87	2 24.3 N	S. SW	(1	125		8	246	4-6	3.5	988.	7 2.0	6.6
. 52		5,SW	21		35		125	8-10	3.4	985.2	+	0.2
15 52	15.2 1		41	100	44	14-16		8-10	3.5	9835	0.8	1.0
N17 5	WE.36 0	Sisse	1-2	110	46	15-16		8-10		9.85.3	0.9	1.0
176 -	2 30.50	SW/CL	1-7	101	35	16-20	116	15-20	3.2	975.	1 .	1.0
8 5	210.80		100		— et	5 -						
53	19.3N	S	1-7	104	3#	20-25	140	20-25	3.1	974.3	1.5	1.2
9 /76	230.7W	<u> </u>	1-2	104	35	20-25	145	20-29	3 1	977 1		
° 740	2 23 5'W	ce/s	2	215	12	20-76	140	20-25	3.1	972.2	4.6	3.2
1 122	37.70	CL/DIE	2-5	205	16	3-5-	150	20-25	3.1		Fall	
2 52	1-07.7 N	C4/4-1	2-5	200	18	3-5	150	14-20	_	972.4		7.0
17.9	5.4 W	C. 10	2-5	190	20	3-5	150	16-20	3.1	972.2	3.2 4.0	3.0
3 130	20.6 W	CL_DK							4	144.6		
3 130		CL	25	200		3-5	150	16-20		971.9	4.1	3.1

DECK LOG - WEATHER OBSERVATION SHEET

1	niner t	REEMAN				DAY		DAT	E	TIM	EZONE	
						WE	ONESOA	4 23	Feb Zu	1	+9	
TIME	POSITION		7									
1	(Lat. and Long.) PRESEN	E 7	⊋	MIND		SW	ELL WAVE	s R	110	TEN	
			/IS/B	DIR.		SEA WAVE	3		┪┋	C C	3	PERATUR OC
01	5155.0N	UCL			(Kts.)	S.	DIR (Tru		SEA	SEA LEVEL	DR	_ "-
02	5) 53.5 N 176 22.3W		5	200	150	5-7	- 180	18-20		2	1 302	
03	51 52.3 N 170 22.0 4		5		52	8-10	180					3.1
04	5147.9 N		5+	200	30	8-10	185			971.		3.9
05	51 43.6 1	1 66	6	205	28	10-1	_				<u> </u>	38
06	170 20.5 1.		6	203	26	10-11	120	"	1000		11000	3.6
07	51 44.9 K	V CL	6	185	27	20-30	' 	20-2	1	961.	14.5	3.1
08	17021 176 51 46.61N		6	202	25	20-28			3.7	- 969.	03.5	2.8
	176 21. 7 W	CL	6	210	22		 	+	3.7	168.	83.5	1.8
09	170 18.81 W	CL	6	174		10 20			3.7	968.0	3.5	2.8
10	51-31.8N 170-11.9W	CL 5	5	210		30-5	4		3.6	967	3 3.6	
11	51-31.5NU	CLL			16	3-5	240	16-20	3.1	967.7		1.7
	51 31. 8 4N 70 13. 3 W	CL/L	5-10	180	18	3-5	240	16-20	3.1	947.0		2.0
13	70006'N	<u></u>	—	170	20	5	230	16-20	3.1	966.1		
. 5	1° 15.3'N 70°05 H'W	1	6-10		16	5	240	16-20	2.8	165.9	4.0	2.7
15	1 13.5 N 70.060 W	CLIR	5	196	16	5	240	8-10	29	964.5	_	3.0
A 10	/*/7.9 <i>h</i> /	CLIL	5-10	185	20	6	215	16-28	3,0	9640		3.0
7	0 04.5 4	CL	5-8	180	18	6	220	16-20	2.9	9641		2.1
. 6	126.5N				DINNE	-				1661	4.1	3.9
6	39.9 N	CL/L	5	186	11	4	230	16-20	5.1	761.1	"	
9 17	0"00.2 M	CL/L	5	186	11	1	240		-		4,5	3.5
//6	1 54.3'W	CL/L	5	350	6	3-6	220	16-18	3.5	960.4	41	3.4
1	950.3'W	CL/L/	8-10	340	12	3-6				961.8	6.7	3.0
	90 42.2'W	cr/2	8-10	350	(8	7	220		3.3	962.2	2.2	2.0
16	1º42.0'W	CL/L		347		3-6	220	16-18	3.7	964.1	2.8	2.3
	2°37.0'W	CL/L		358	13		250	14	3.5	964.8	2.6	2.1
MARKS	- 4 144 144	00/2		227	_/3	3-5	Z 20	_14	3.3	965.5	2.8	2.2

NOAA	FORM	77-13d	
10 -01			

NOAA FORM 77-13D (3-76)

U.S. DEPARTMENT OF COMMERCE NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION

DECK LOG - WEATHER OBSERVATION SHEET

Clast and Long WEATHER DIR. SPEED DIR. MEIGHT CPL DIR. WE DIR. CPL DIR. DIR. CPL DIR. CPL DIR. DIR. CPL DIR. DIR. CPL DIR. DI	IQAA'	SHIP					DAY		DATE		TIME ZO	NE	
01 52 30.9 N	N	IILLER FRE	EMAN				THURS	DAY	24FE	82000	+9	···	
01 52 30.9 N	IME	POSITION	PRESENT	ΣĹ	WIN	D	3 F	SWELL	WAVES	ER .	/EL		
01 52 30.9 N		(Lat. and Long.)	WEATHER	VISIBIL (N.M.)			SEA WA HEIGH (Ft.)			EA WAT	EA LEV RESSIII (mb)	DRY	WET
22 \$2 \$3.0 \\ 22 \$1.0 \\ 23 \$1.0 \\ 23 \$1.0 \\ 24 \$1.0 \\ 25 \$1.0	01	まんりつスク ダイムコー	CLL	8			3-5					_	
23	02	169°27,5'W	CL	8	350	23	9-13		17				
10 373 Al 7-13 121 (2 3.5 76.7 7 3.0 3.0 5.5 12.3 1.0 CL 10 345 20 9-13 185 12 3.6 96.5 8 3.0 3.0 5.5 11.4 M CL 10 340 18 9-12 1.55 12 3.6 970.0 3.0 2.0 17 162-17 M CL 10 340 18 8-10 170 10-12 3.6 970.0 2.8 2.0 18 118 3.5 N CL 10 300 12 84 3.9 970.0 2.8 2.0 18 118 3.5 N CL 10 300 12 84 3.5 N GL 10 300 14 1-3 050 3.4 3.5 970.0 2.8 2.0 10 53 45.5 N CL 10 300 19 1-3 030 4-5 3.5 970.0 2.8 2.0 11 53 55 N CL 10 300 19 1-3 030 4-5 3.5 970.0 3.0 2.0 11 53 55 N CL 10 300 19 1-3 030 4-5 3.5 970.0 3.0 2.0 11 53 55 N CL 10 300 19 1-3 020 3-4 3.2 971.0 3.0 2.0 11 54 55 N CL 10 300 9 1-3 020 3-4 3.2 971.0 3.0 2.0 11 54 55 N N CL 10 300 9 2-3 015 3-4 3.2 971.0 3.0 2.0 15 15 N N CL 10 300 9 2-3 015 3-4 3.3 972.1 2.7 2.0 15 160 152.0 N PC 10 300 9 2-3 015 3-4 3.3 972.1 2.7 2.0 15 160 152.0 N PC 10 300 9 2-3 015 3-4 3.3 972.1 2.7 2.0 16 160 152.0 N PC 10 255 11 2-3 0.50 3.4 3.2 975.0 1.2 3.0 16 160 152.0 N PC 10 255 11 2-3 0.50 3-4 3.2 975.0 1.2 3.0 16 160 152.0 N PC 10 255 11 2-3 0.50 3-4 3.2 975.0 1.2 3.0 15 160 152.0 N PC 10 255 11 2-3 0.50 3-4 3.1 975.1 5.1 2.0 16 165 1.3 N PC 10 260 11 2-3 0.50 3-4 3.1 975.1 5.1 2.0 16 165 1.3 N PC 10 260 13 2-4 1 2-4 1.8 974.9 3.8 2.0 16 165 1.3 N PC 10 240 14 2-4 1.8 974.9 3.8 2.0 16 165 1.2 N PC 10 240 14 2-4 1.8 974.9 3.8 2.0 16 165 1.2 N PC 10 240 14 2-4 1.8 974.9 3.8 2.0 16 165 1.2 N PC 10 240 14 2-4 1.8 974.9 3.8 2.0 16 165 1.2 N PC 10 240 14 2-4 1.8 974.9 3.8 2.0 16 165 1.2 N PC 10 240 14 2-4 1.8 974.9 3.8 2.0 16 165 1.2 N PC 10 240 14 2-4 1.8 974.9 3.8 2.0 16 165 1.2 N PC 10 240 14 2-4 1.8 974.9 3.8 2.0 16 165 1.2 N PC 10 240 14 2-4 1.8 974.9 3.8 2.0 16 165 1.2 N PC 10 240 14 2-4 1.8 974.9 3.8 2.0 16 165 1.2 N PC 10 240 14 2-4 1.8 974.9 3.8 2.0 16 165 1.2 N PC 10 240 14 2-4 1.8 974.9 3.8 2.0 16 165 1.2 N PC 10 240 14 2-4 1.8 974.9 3.8 2.0 16 165 1.2 N PC 10 240 14 2-4 1.8 974.9 3.8 2.0 16 165 1.2 N PC 10 240 14 2-4 1.8 974.9 3.8 2.0 16 165 1.2 N PC 10 240 14 2-4 1.8 974.9 3.8 2.0 16 165 1.2 N PC 10 240 14 2-4 1.8 974.9 N PC 10 240 14 2-4 1.8 974.9 N PC 10 240 14 2-4 1.8 974.9 N PC	03	52° 48.0'N											
25	04	52 57.9 N 168 19.2 N											
106 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	05	53983.1 N						AAA.		2/			
27	06	53011.4 N					7.73			2.6			
18	07	5822.0 N					7-12			3.6			
10 168 115 W CL 10 300 19 1-3 030 4-5 3.5 940.8 3.0 2. 11 168 58.0 W CL 10 300 19 1-3 030 4-5 3.5 940.8 3.0 2. 11 168 58.0 W CL 10 300 19 1-3 020 4-5 3.1 971.1 2.2 1. 12 54 05.1 W CL 10 30C 9 8-3 020 3-4 3.2 971.7 3.0 2. 13 54 05.1 W CL 10 30C 9 8-3 020 3-4 3.2 971.7 3.0 2. 14 166 54.2 W CL 10 300 9 2-3 015 3-4 3.3 972.1 2.7 2. 15 166 167 168 17 W CL 10 300 9 2-3 015 3-4 3.3 972.8 3.0 2. 15 166 167 168 17 W CL 10 281 11 2-3 0.15 3-4 3.3 972.8 3.0 2. 16 16 54 25.1 W CL 10 250 11 2-3 0.20 3.4 3.2 972.9 2.0 17 16 16 54 25.1 W CL 10 255 1/ 2-3 0.95 3-4 3.2 975.0 1.2 3.0 18 166 37.3 SW PC 10 300 11 2-3 0.50 3-4 3.1 975.1 5.1 3.0 18 166 37.0 W PC 10 290 11 2-3 0.50 3-4 3.1 975.1 5.1 3.0 18 166 37.0 W PC 10 300 11 2-3 0.50 3-4 3.1 975.1 5.1 3.0 18 166 37.0 W PC 10 290 13 2-4 3.1 975.1 5.1 3.0 19 166 37.0 W PC 10 290 13 2-4 3.1 975.1 5.1 3.0 20 165 14.9 W PC 10 290 14 2-4 1.8 975.2 3.8 2.0 21 155 -0.5 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 22 155 -0.5 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 23 54 25.7 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 24 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 25 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 26 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 26 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 26 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 26 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 27 165 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 28 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 29 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 20 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 20 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 20 165 16.5 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 20 165 16.5 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 20 165 16.5 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 20 165 16.5 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 21 165 16.5 W PC 10 200 14 2-4 16.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3	08	1/48 41 7 11/			= .			170	10-12				
10 168 115 W CL 10 300 19 1-3 030 4-5 3.5 940.8 3.0 2. 11 168 58.0 W CL 10 300 19 1-3 030 4-5 3.5 940.8 3.0 2. 11 168 58.0 W CL 10 300 19 1-3 020 4-5 3.1 971.1 2.2 1. 12 54 05.1 W CL 10 30C 9 8-3 020 3-4 3.2 971.7 3.0 2. 13 54 05.1 W CL 10 30C 9 8-3 020 3-4 3.2 971.7 3.0 2. 14 166 54.2 W CL 10 300 9 2-3 015 3-4 3.3 972.1 2.7 2. 15 166 167 168 17 W CL 10 300 9 2-3 015 3-4 3.3 972.8 3.0 2. 15 166 167 168 17 W CL 10 281 11 2-3 0.15 3-4 3.3 972.8 3.0 2. 16 16 54 25.1 W CL 10 250 11 2-3 0.20 3.4 3.2 972.9 2.0 17 16 16 54 25.1 W CL 10 255 1/ 2-3 0.95 3-4 3.2 975.0 1.2 3.0 18 166 37.3 SW PC 10 300 11 2-3 0.50 3-4 3.1 975.1 5.1 3.0 18 166 37.0 W PC 10 290 11 2-3 0.50 3-4 3.1 975.1 5.1 3.0 18 166 37.0 W PC 10 300 11 2-3 0.50 3-4 3.1 975.1 5.1 3.0 18 166 37.0 W PC 10 290 13 2-4 3.1 975.1 5.1 3.0 19 166 37.0 W PC 10 290 13 2-4 3.1 975.1 5.1 3.0 20 165 14.9 W PC 10 290 14 2-4 1.8 975.2 3.8 2.0 21 155 -0.5 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 22 155 -0.5 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 23 54 25.7 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 24 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 25 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 26 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 26 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 26 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 26 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 27 165 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 28 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 29 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 20 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 20 165 16.2 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 20 165 16.5 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 20 165 16.5 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 20 165 16.5 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 20 165 16.5 W PC 10 290 14 2-4 1.8 975.9 3.8 2.0 21 165 16.5 W PC 10 200 14 2-4 16.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3.0 3		168°23.3'\ \$1°36.7'N		10									2.
10 167 58.0 W CL 10 300 19 1-3 030 4-5 3.5 470.3 3.0 2. 11 1/3 38.5 W PCET 10 309 10 1-3 020 4-5 3.1 971.1 2.2 1. 12 540051 N CL 10 30C 9 1-3 020 3-4 3.2 971.3 3.0 2. 13 540051 N CCT 10 282 11 1-3 020 3-4 3.2 971.3 3.0 2. 14 161 540 20 N CL 10 300 9 2-3 015 3-4 3.3 972.1 2.7 2. 15 540 28.4 N CL 10 300 9 2-3 015 3-4 3.3 972.3 2.7 2.7 16 160 42.7 W CC 10 281 11 2-3 0.20 3.4 3.2 972.9 2.9 16 160 33.5 L PC 10 255 11 2-3 0.20 3.4 3.2 972.9 2.9 17 541 161 162 16 16 N PC 10 255 11 2-3 0.50 3-4 3.2 972.9 2.9 18 164 03.3 24 PC 10 300 11 2-3 0.50 3-4 3.2 975.0 4.2 3.1 18 164 03.3 24 PC 10 300 11 2-3 0.50 3-4 3.1 975.1 5.1 3.1 19 166 370 N PC 10 290 10 2-4 0.10 3-4 2.9 975.2 3.8 2.0 10 10 10 290 14 2-4 1.8 974.9 3.8 2.0 11 10 290 14 2-4 1.8 974.9 3.8 2.0 12 155 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0		768 161 W	_a	13	300	16	1-3	830	3-4	3.5	970.0	2.8	2.9
12 117°22.7'W CL 10 30C 9 11-3 020 3-4 3.2 971.8 3.0 2. 13 54°12.8N 147°10.5'W CCT 10 28Z 11 1-3 020 3-4 3.2 972.2 2.8 2. 14 166.55.9W CL 10 300 9 2-3 015 3-4 3.3 972.1 2.7 2. 15 54°25.1'N 8C 10 281 11 2-3 0.15 3-4 3.3 972.8 3.0 2. 16 16 16 16 1.2 W PC 10 250 11 2-3 0.20 3.4 3.2 972.9 2.8 4. 17 18 18 18 18 18 18 18 18 18 18 18 18 18	10	147 58.0 W	CL	10		19	1-3		4-5	3.5	970.8	3.0	2.
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$	11	104 38.5'W	PCer	10	309	10	1-3	020	4-5	3.1	971.1	2.2	1.
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	12	117°22.7'W	CL	10	30G	9	1-3	020	3-4	3.2	971,8	3.0	2.
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	13	167°10.5'W	PCCE	10	282	I/	1-3	020	3-4	3.2	972.2	2.8	
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	14	166 54.9 W	CL	10	300	9	2-3		3-4	3.3			2.0
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	15	SU° 18.H'N	ec.	10		11			-	 -		3 0	
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	16	57.25.1 N		10)					7.4	7 2	9720	6.8	
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	17	54 18.0 N		10	_					5 7	000		
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	18	54 19.7 N			~~~	1/	-		<u> </u>	34.4.		7.2	
$\begin{array}{cccccccccccccccccccccccccccccccccccc$						//				44.4.1			_
$\begin{array}{cccccccccccccccccccccccccccccccccccc$		165.37.0 h		10			7	0.10	3-4		1		2.
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$		165° 4.9'W	PC	10	290		2-4			3.6	9775	3.8	2.4
165 0 8.0 CC/R/S V 300 30 6-8 1.7 979.8 2.0 1.2 23 145-07.8 W CL/R/S 5 290 36 6-8 - 1.4 980.5 1.2 0.24 54 27.5 N CL/R/S 5 300 36 8-10 - 2.8 987.1 0.5 70	21	165.00.54	EL	10	240	14	2-4			1.8	9779	3.8	2-
14 54 22.5 N CLIR 6 300 36 8-10 - 2.8 982.1 0.5 0	22	165 08.0(2)	CL/R/S	8	300	30	6-8			1.7	979.8	2.0	1.4
" 165 16, 2W CL/R 6 300 36 8-10 - 2.8 982.1 0.5 0	23	145-07.8 W	CL/R/S	~	250	36	6-8	_		1.4	980.5	1.2	0.
	24		CLIR	6	300	36	B-10			2.8	9821	0.5	70.
												<u></u>	
						·	· · · · · · · · · · · · · · · · · · ·						
											-" -		

STRA

NOAA	FORM	77-13d
10 701		

U.S. DEPARTMENT OF COMMERCE NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION

		DEC	K LU	5 – WE	AIHER	OR2EK	VAIIU	N 2HEE	1			
NOAA	SHIP					DAY		DATE		TIME ZO	NE	
	MILLER	FREEMA	J			FRII	X4 Y	25 Fe	ep sam	19		
										· · · · · · · · · · · · · · · · · · ·		
TIME	POSITION (Lat. and Long.)	PRESENT WEATHER	VISIBILITY (N.M.)	WIN	D	SEA WAVE HEIGHT (Ft.)	SWELL	WAVES	SEA WATER TEMP.	SEA LEVEL PRESSIJRE (mb)	TEMPER	ATURE C
			(N.)	DIR. (True)	SPEED (Kts.)	SEA HEI (F	DIR. (True)	HEIGHT (Ft.)	SEA W	SEA L PRES	DRY BULB	WET BULB
01	54°20.5'N 169°27.3'N	R.5	10	300	43	8-10	190	10-12	3.0	983.1	1.0	0.0
02	540 26-3 19.9N	ci,R	10	280	37	8-10	290	14-16	2.9	985.1	0-1	-1.8
03	54019,31N, 165° 38.5 W 540/6.5 N 165° 51.441	CL, R	10	275	34	8-10	290	14-16	2.8	987.0		-1.8
04	165 51.420	CL.R	10	270	342	8-10	290	14-16	2.9	985.4	0.6	-1.8
05												
06						<u> </u>		1			ļ	
07	2							ļ			<u> </u>	
08									ļ			
09							<u> </u>			W	ļ	
10								<u> </u>		<u> </u>	ļ	
11									<u> </u>		ļ	
12								ļ	-	-		
13				-				ļ		<u> </u>	ļ	
14		-			-				 		 	<u> </u>
15					-					 		
-			-					1		1	-	
17			 							ļ	-	
19		<u> </u>	-	-		1	-			1	+	1
20	<u> </u>								 		-	-
21				1			_	 		 	-	
22								-		+	 	
23							 		 	1	†	
24										1		
REMA	RKS		٠	<u> </u>		<u>l</u>	<u> </u>		1			
	· · · · · · · · · · · · · · · · · · ·											
	<u> </u>	··· · · · · · · · · · · · · · · · · ·				-	 -					
									·			