

Introduction to the CDN log format

Click on the 「Logs」 to view it.

- By default, log files can be downloaded in hourly granularity. If the log file is larger than 128MB within an hour, the log file will be split.
- Log files will be compressed by GZIP.
- Usually the log delay is between 8 and 10 hours. For example: log from 0:00 to 1:00 on January 18th, it is expected to be available from 8:00 to 10:00 on January 18

Log file name format: Domainname_{yyyy-MM-dd-HH}_part.gz

//Example:

www.example.com_2017-03-01-00_part -00000.gz

Log content format:

ClientIP Hit/Miss/UNKNOWN ResponseTime [Time Zone] "Method URL Protocol" StatusCode
TrafficSize "Referer" "UserAgent"

Description: If the value of Hit/Miss/UNKNOWN field is - or UNKNOWN , it means that the client actively disconnects the link in this request

ClientIP: Client IP that initiated the request

Hit/Miss/UNKNOWN: Hit rate

ResponseTime : Response time in milliseconds

[Time Zone]: Time when the CDN server receives the request

Method: Request method

URL: Request URL

Protocol: Request protocol

StatusCode: HTTP status code of response

TrafficSize: Response size in bytes

Referer: Request referer in head

UserAgent: Client information that initiated the request

// Example:

```
110.110.110.110 HIT 10 [19/Apr/2016:00:00:00 +0800] "GET  
http://www.example.com/example.jpg HTTP/1.1" 200 5136 "-"  
"Dalvik/1.6.0(Linux;U;Android 4.4.4;1105 Build/KTU84P)"
```