LULEÅ UNIVERSITY OF TECHNOLOGY

UNIVERSITÉ DE LORRAINE | EEIGM

,

Education and Culture

Erasmus Mundus

UNIVERSITÄT DES SAARLANDES

LULEÅ UNIVERSITY OF TECHNOLOGY

Linköping University

UNIVERSITAT POLITÈCNICA DE CATALUNYA BARCELONATECH

UNIVERSITÉ DE LORRAINE

,

θ	$[^\circ]$
$\Delta\theta$	$[^\circ]$
δ	$[^\circ]$
	$[-]$
	$[\mu]$
	$[\mu]$
	$[\mu]$

- [–]
- [–]
- [–]
- [–]


$\underline{k}, z$
$D \equiv (-l, +l)$
$C \equiv (+l, +l)$
l
l
$(0, R_f)$
L
Γ_4
Q
H
Γ_2
I
l
$\Delta\theta$
$\Delta\theta$
R_f
$u(l, z) = \bar{\varepsilon} \cdot l$
$(-R_f, 0)$
θ
O
$(R_f, 0)$
$\underline{i}, x$
$u(-l, z) = -\bar{\varepsilon}_x \cdot l$
Ω_f
l
Γ_1
Γ_3
Ω_m
$(0, -R_f)$
$A \equiv (-l, -l)$
$B \equiv (+l, -l)$


$\underline{k}, z$
$D \equiv (-l, +l)$
$w(x, l) = w(l, l)$
$C \equiv (+l, +l)$
l
l
$(0, R_f)$
L
Γ_4
a
H
Γ_2
l
l
$\Delta\theta$
$\Delta\theta$
R_f
$u(l, z) = \bar{\varepsilon} \cdot l$
$(-R_f, 0)$
θ
O
$(R_f, 0)$
$\underline{i}, x$
$u(-l, z) = -\bar{\varepsilon}_x \cdot l$
Ω_f
l
Γ_1
Γ_3
Ω_m
$(0, -R_f)$
$A \equiv (-l, -l)$
$w(x, -l) = w(l, -l)$
$B \equiv (+l, -l)$


$\underline{k}, z$
$\begin{cases} u(x,l) = u(l,l)\frac{x}{l} \\ w(x,l) = w(l,l) \end{cases}$
$D \equiv (-l, +l)$
$C \equiv (+l, +l)$
l
l
$(0, R_f)$
L
Γ_4
a
H
Γ_2
l
l
$\Delta\theta$
$\Delta\theta$
R_f
$u(l,z)_x = \bar{\varepsilon} \cdot l$
$(-R_f, 0)$
θ
O
$(R_f, 0)$
$\underline{i}, x$
$u(-l,z) = -\bar{\varepsilon}_x \cdot l$
Ω_f
l
Γ_1
Γ_3
Ω_m
$(0, -R_f)$
$A \equiv (-l, -l)$
$B \equiv (+l, -l)$
$\begin{cases} u(x,-l) = u(l,-l)\frac{x}{l} \\ w(x,-l) = w(l,-l) \end{cases}$



$$\delta = \frac{\circ}{\alpha}$$

[] [] ν [–]

$$= \pi\sigma \frac{+}{\quad}$$

$$= \; -\nu$$

$$\sigma = \frac{\quad}{-\nu}\varepsilon$$

$$\Delta = \left|\Delta - \Delta\right|$$

$$\Delta = \left|\Delta - \Delta\right|$$

$$\beta = \begin{pmatrix} , \\ - \\ , \end{pmatrix}$$

$$\Delta = (\beta)\Delta + (\beta)\Delta\Delta_\theta = -(\beta)\Delta + (\beta)\Delta$$

$$= (\beta) + (\beta)_\theta = -(\beta) + (\beta)$$

$$= \frac{\Delta}{\delta} = \frac{{}_\theta\Delta_\theta}{\delta} = . \leftrightarrow \Delta = \delta$$

,

$\delta = \circ\delta = .\circ\delta = .\circ\delta = .\circ\delta = .\circ\delta = .\circ\delta = .\circ\delta = .\circ\delta = .$

,

$\delta = \circ\delta = .\circ\delta = .\circ\delta = .\circ\delta = .\circ\delta = .\circ\delta = .\circ\delta = .\circ\delta = .$

,

$\sigma\delta = .^\circ$



$\delta = .^{\circ}$


Total energy release rate for the infinite model $G0$ as function of crack angular semi-aperture $\Delta\theta$
$G0$, FEM model with debond
$G0 = \pi R_f \sigma_0^2 \frac{1-(3-4\nu_m)}{\mu_m}$, plane strain undamaged theoretical value
$G0\ [\frac{J}{m^2}]$
$\Delta\theta\ [^{\circ}]$

$\delta = .^\circ$

Normalized total energy release rate $\frac{G_{TOT}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with Abaqus built-in J-Integral post-processing routine (*CONTOUR INTEGRAL)



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based VCCT post-processing routine



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based VCCT and Abaqus built-in J-Integral (*CONTOUR INTEGRAL) post-processing routines



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$(\cdot\cdot)^{\delta} = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interface



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$(\cdot\cdot)\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interface



$\sigma\delta = .^{\circ}$



$\delta = .^{\circ}$


Total energy release rate for the infinite model $G0$ as function of crack angular semi-aperture $\Delta\theta$
$G0$, FEM model with debond
$G0 = \pi R_f \sigma_0^2 \frac{1-(3-4\nu_m)}{\mu_m}$, plane strain undamaged theoretical value
$G0\ [\frac{J}{m^2}]$
$\Delta\theta\ [^{\circ}]$

$\delta = .^{\circ}$

Normalized total energy release rate $\frac{G_{TOT}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with Abaqus built-in J-Integral post-processing routine (*CONTOUR INTEGRAL)



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based VCCT post-processing routine



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based VCCT and Abaqus built-in J-Integral (*CONTOUR INTEGRAL) post-processing routines



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$(\cdot\cdot)^{\delta} = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interface



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$(\cdot\cdot)^{\delta} = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interface



$\sigma\delta = .^{\circ}$



$\delta = .^\circ$


Total energy release rate for the infinite model $G0$ as function of crack angular semi-aperture $\Delta\theta$
$G0$, FEM model with debond
$G0 = \pi R_f \sigma_0^2 \frac{1-(3-4\nu_m)}{\mu_m}$, plane strain undamaged theoretical value
$G0\ [\frac{J}{m^2}]$
$\Delta\theta\ [^\circ]$

$\delta = .^\circ$

Normalized total energy release rate $\frac{G_{TOT}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with Abaqus built-in J-Integral post-processing routine (*CONTOUR INTEGRAL)



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based VCCT post-processing routine



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based VCCT and Abaqus built-in J-Integral (*CONTOUR INTEGRAL) post-processing routines



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$(\cdot\cdot)^{\delta} = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interface



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$(\cdot\cdot)^{\delta} = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interface



$\sigma\delta = .^{\circ}$



$\delta = .^{\circ}$


Total energy release rate for the infinite model $G0$ as function of crack angular semi-aperture $\Delta\theta$
$G0$, FEM model with debond
$G0 = \pi R_f \sigma_0^2 \frac{1-(3-4\nu_m)}{\mu_m}$, plane strain undamaged theoretical value
$G0\ [\frac{J}{m^2}]$
$\Delta\theta\ [^{\circ}]$

$\delta = .^{\circ}$

Normalized total energy release rate $\frac{G_{TOT}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with Abaqus built-in J-Integral post-processing routine (*CONTOUR INTEGRAL)



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(-)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based VCCT post-processing routine



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based VCCT and Abaqus built-in J-Integral (*CONTOUR INTEGRAL) post-processing routines



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$(\cdot\cdot)^{\delta = .^{\circ}}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interface



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$\delta = .^{\circ}\delta = .^{\circ}\delta = .^{\circ}\delta = .^{\circ}\delta = .^{\circ}$

$(\cdot\cdot)^{\delta} = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interface



$\sigma\delta = .^\circ$



$\delta = .^{\circ}$


Total energy release rate for the infinite model $G0$ as function of crack angular semi-aperture $\Delta\theta$
$G0$, FEM model with debond
$G0 = \pi R_f \sigma_0^2 \frac{1-(3-4\nu_m)}{\mu_m}$, plane strain undamaged theoretical value
$G0\ [\frac{J}{m^2}]$
$\Delta\theta\ [^{\circ}]$

$\delta = .^\circ$

Normalized total energy release rate $\frac{G_{TOT}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with Abaqus built-in J-Integral post-processing routine (*CONTOUR INTEGRAL)



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based VCCT post-processing routine



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based VCCT and Abaqus built-in J-Integral (*CONTOUR INTEGRAL) post-processing routines




Normalized energy release rate $\frac{G_i}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with forces extracted on the right-hand side of the interface
$\frac{G_I}{G_0}$, FEM-F-VCCT
$\frac{G_{II}}{G_0}$, FEM-F-VCCT
$\frac{G_I+G_{II}}{G_0}$, FEM-F-VCCT
$\frac{G_I}{G_0}$, FEM-SoF-VCCT, N Int El 1
$\frac{G_{II}}{G_0}$, FEM-SoF-VCCT, N Int El 1
$\frac{G_I+G_{II}}{G_0}$, FEM-SoF-VCCT, N Int El 1
$\frac{G_I}{G_0}$, FEM-SoF-VCCT, N Int El 2
$\frac{G_{II}}{G_0}$, FEM-SoF-VCCT, N Int El 2
$\frac{G_I+G_{II}}{G_0}$, FEM-SoF-VCCT, N Int El 2
$\frac{G_I}{G_0}$, FEM-SoF-VCCT, N Int El 3
$\frac{G_{II}}{G_0}$, FEM-SoF-VCCT, N Int El 3
$\frac{G_I+G_{II}}{G_0}$, FEM-SoF-VCCT, N Int El 3
$\frac{G_I}{G_0}$, FEM-SoF-VCCT, N Int El 4
$\frac{G_{II}}{G_0}$, FEM-SoF-VCCT, N Int El 4
$\frac{G_I+G_{II}}{G_0}$, FEM-SoF-VCCT, N Int El 4
$\frac{G_I}{G_0}$, FEM-SoF-VCCT, N Int El 5
$\frac{G_{II}}{G_0}$, FEM-SoF-VCCT, N Int El 5
$\frac{G_I+G_{II}}{G_0}$, FEM-SoF-VCCT, N Int El 5
$\frac{G_I}{G_0}$, FEM-SoF-VCCT, N Int El 6
$\frac{G_{II}}{G_0}$, FEM-SoF-VCCT, N Int El 6
$\frac{G_I+G_{II}}{G_0}$, FEM-SoF-VCCT, N Int El 6
$\frac{G_I}{G_0}$, FEM-SoF-VCCT, N Int El 7
$\frac{G_{(\cdot)}}{G_0}$
0.35
0.3
0.25
0.2
$5 \cdot 10^{-2}$
0
20
30
40
120
150
$\Delta\theta$ [°]

$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$(\cdot\cdot)^{\delta = .^{\circ}}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interface



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$(\cdot\cdot)^{\delta} = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interface



$\sigma\delta = .^\circ$



$\delta = .^{\circ}$


Total energy release rate for the infinite model $G0$ as function of crack angular semi-aperture $\Delta\theta$
$G0$, FEM model with debond
$G0 = \pi R_f \sigma_0^2 \frac{1-(3-4\nu_m)}{\mu_m}$, plane strain undamaged theoretical value
$G0\ [\frac{J}{m^2}]$
$\Delta\theta\ [^{\circ}]$

$\delta = .^\circ$

Normalized total energy release rate $\frac{G_{TOT}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with Abaqus built-in J-Integral post-processing routine (*CONTOUR INTEGRAL)



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based VCCT post-processing routine



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based VCCT and Abaqus built-in J-Integral (*CONTOUR INTEGRAL) post-processing routines



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$(\cdot\cdot)^{\delta} = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interface



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interface



$\sigma\delta = .^\circ$



$\delta = .^{\circ}$


Total energy release rate for the infinite model $G0$ as function of crack angular semi-aperture $\Delta\theta$
$G0$, FEM model with debond
$G0 = \pi R_f \sigma_0^2 \frac{1-(3-4\nu_m)}{\mu_m}$, plane strain undamaged theoretical value
$G0\ [\frac{J}{m^2}]$
$\Delta\theta\ [^{\circ}]$

$\delta = .^\circ$

Normalized total energy release rate $\frac{G_{TOT}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with Abaqus built-in J-Integral post-processing routine (*CONTOUR INTEGRAL)



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based VCCT post-processing routine



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based VCCT and Abaqus built-in J-Integral (*CONTOUR INTEGRAL) post-processing routines



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$(\cdot\cdot)^{\delta = .^{\circ}}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interface



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interface



$\sigma\delta = .^\circ$



$\delta = .^{\circ}$


Total energy release rate for the infinite model $G0$ as function of crack angular semi-aperture $\Delta\theta$
$G0$, FEM model with debond
$G0 = \pi R_f \sigma_0^2 \frac{1-(3-4\nu_m)}{\mu_m}$, plane strain undamaged theoretical value
$G0\ [\frac{J}{m^2}]$
$\Delta\theta\ [^{\circ}]$

$\delta = .^{\circ}$

Normalized total energy release rate $\frac{G_{TOT}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with Abaqus built-in J-Integral post-processing routine (*CONTOUR INTEGRAL)



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based VCCT post-processing routine



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based VCCT and Abaqus built-in J-Integral (*CONTOUR INTEGRAL) post-processing routines



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interfac



$(\cdot\cdot)^{\delta = .^{\circ}}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the fiber side of the interface



$\delta = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interf



$(\cdot\cdot)^{\delta} = .^{\circ}$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based and stress-based VCCT post-processing routines with stresses extracted on the matrix side of the interface



$\sigma\delta = .^\circ$



$\delta = .^\circ$


Total energy release rate for the infinite model $G0$ as function of crack angular semi-aperture $\Delta\theta$
$G0$, FEM model with debond
$G0 = \pi R_f \sigma_0^2 \frac{1-(3-4\nu_m)}{\mu_m}$, plane strain undamaged theoretical value
$G0\ [\frac{J}{m^2}]$
$\Delta\theta\ [^\circ]$
1.37
1.37
1.36
1.36
1.35
1.35
1.34
1.34
1.33
1.33
1.32
1.32
1.31
1.31
1.3
1.3
1.29
1.29
1.28
1.28
1.27
1.27
1.26
1.26
1.25
1.25
0
10
20
30
40
50
60
70
80
90
100
110
120
130
140
150
160
170
180

$\delta = .^\circ$

Normalized energy release rate $\frac{G_{(\cdot)}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, calculated with in-house force-based VCCT post-processing routine



Normalized energy release rate $\frac{G_I}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, $VF_f = 7.9 \cdot 10^{-5}$, $\frac{L}{R_f} \sim 100$ calculated with in-house force-based VCCT post-processing routine



Error of of normalized energy release rate with respect to BEM results $\Delta\frac{G_I}{G_0} = \frac{G_I}{G_0}|_{FEM} - \frac{G_I}{G_0}|_{BEM}$ as function of crack angular semi-aperture $\Delta\theta$, $VF_f = 7.9 \cdot 10^{-5}$, $\frac{L}{R_f} \sim 100$ calculated with in-house force-based VCCT post-p



Normalized energy release rate $\frac{G_{II}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, $VF_f = 7.9 \cdot 10^{-5}$, $\frac{L}{R_f} \sim 100$ calculated with in-house force-based VCCT post-processing routine



Error of of normalized energy release rate with respect to BEM results $\Delta\frac{G_I}{G_0} = \frac{G_I}{G_0}|_{FEM} - \frac{G_I}{G_0}|_{BEM}$ as function of crack angular semi-aperture $\Delta\theta$, $VF_f = 7.9 \cdot 10^{-5}$, $\frac{L}{R_f} \sim 100$ calculated with in-house force-based VCCT post-p



Normalized energy release rate $\frac{G_I+G_{II}}{G_0}$ as function of crack angular semi-aperture $\Delta\theta$, $VF_f = 7.9 \cdot 10^{-5}$, $\frac{L}{R_f} \sim 100$ calculated with in-house force-based VCCT post-processing routine



Error of of normalized energy release rate with respect to BEM results $\Delta\frac{G_I+G_{II}}{G_0} = \frac{G_I+G_{II}}{G_0}|_{FEM} - \frac{G_I+G_{II}}{G_0}|_{BEM}$ as function of crack angular semi-aperture $\Delta\theta$, $VF_f = 7.9 \cdot 10^{-5}$, $\frac{L}{R_f} \sim 100$ calculated with in-house force-based VC