

ESTIMATING THE AVERAGE SIZE OF FIBER/MATRIX INTERFACE CRACKS IN UD AND CROSS-PLY LAMINATES

Luca Di Stasio^{1,2,*}, Janis Varna², Zoubir Ayadi¹

¹ Université de Lorraine, EEIGM, IJL, 6 Rue Bastien Lepage, F-54010 Nancy, France

² Luleå University of Technology, University Campus, SE-97187 Luleå, Sweden

* luca.di.stasio@ltu.se

Characterization of fiber/matrix interface cracks (debonds) has mainly focused on the evaluation of the Energy Release Rate (ERR). However, the attention has been mostly devoted to the study of a single partially debonded fiber placed in an effectively infinite medium and to the effect of a small number of nearby fibers on debond ERR [1]. In this work, the Mode I and Mode II ERRs are evaluated for debonds appearing in Representative Volume Elements (RVEs) of regular microstructures of UD (Fig. 1) and cross-ply laminates. By adopting a 2-parameters energy-based criterion for propagation [2], we then proceed to the estimation of the expected average debond size in different microstructural arrangements (see Fig. 1). Finally, the results are compared with available microscopic observations [3].




Figure 1. Estimation of debond size by comparing the total ERR to the 2-parameters expression of critical G_c . Glass fiber/epoxy, $V_f = 60\%$, $\varepsilon_x = 1\%$.

References

- [1] C. Sandino, E. Correa and F. París (2016) Numerical analysis of the influence of a nearby fibre on the interface crack growth in composites under transverse tensile load. *Engineering Fracture Mechanics*, **168**, 58–75.
- [2] J.W. Hutchinson and Z. Suo (1992) Mixed mode cracking in layered materials. J.W. Hutchinson, T.Y. Wu (Eds.), *Advances in applied mechanics*, **29**, 63-191, Academic Press, New York.
- [3] E. Correa, M. I. Valverde, M .L. Velasco and F. París (2018) Microscopical observations of inter-fibre failure under tension. *Engineering Fracture Mechanics*, **155**, 213–220.