AC6385A Datasheet

Zhuhai Jieli Technology Co.,LTD

Version：V1.1

Date：2021.06.17

AC6385A Features

High performance 32-bit RISC CPU

- 32-bit DSP supports hardware Float Point Unit(FPU)
- Up to 160MHz programmable processor
- 64 Vectored interrupts
- 8 Levels interrupt priority

Flexible I/O

- 20 GPIO pins
- All GPIO pins can be programmable as input or output individually
- All GPIO pins are internal pull-up/pull-down selectable individually
- CMOS/TTL level schmitt triggered input
- External wake up/interrupt on all GPIOs

Peripheral Feature

- One Full Speed USB OTG controller
- Six Multi-function 32-bit timers, support capture and PWM mode
- Three full-duplex basic UART, support DMA mode
- Two SPI interface supports host and device mode
- One hardware IIC interface supports host and device mode
- Two Built-in low power Cap Sense Keys
- Built-in Cap Sense Key controller
- 10-bit ADC for analog sampling
- Power-on reset

Power Supply

- Low voltage LDO for internal digital and analog circuit supply
- 2uA current consumption in the soft-off mode
- Built-in LDO for the core, I/O, flash
- VBAT is 1.8V to 5.5V
  VDDIO is 1.8V to 3.4V

Packages

- QSOP24

Temperature

- Operating temperature: -40℃ to +85℃
- Storage temperature: -65℃ to +150℃

1. Pin Definition

1.1 Pin Assignment

|	AC6385A (QSOP24)	
USBDM	1	24 PC3
USBDP	2	23 PC4
PC2	3	22 PC5
PA6	4	21 PB1
PA5	5	20 PB2
PA4	6	19 PB3
PA3	7	18 BTVDD
PA2	8	17 VDDIO
PA1	9	16 LDOIN
PB8	10	15 VBAT
PB7	11	14 GND
PB6	12	13 PB4

Figure 1-1   AC6385A_QSOP24 Package Diagram

1.2 Pin Description

Table 1-1 AC6385A_QSOP24 Pin Description

PIN NO.	Name	I/O Type	Function	Other Function
1	USBDM	I/O	GPIO (pull down)	SPI2_DOB: SPI2 Data Out(B); IIC_SDA_A: IIC SDA(A); ADC11: ADC Channel 11; UART1_RXD: Uart1 Data In(D);
2	USBDP	I/O	GPIO (pull down)	SPI2_CLKB: SPI2 Clock(B); IIC_SCL_A: IIC SCL(A); ADC10: ADC Channel 10; UART1_TXD: Uart1 Data Out(D);
3	PC2	I/O	GPIO	SPI2_DIB: SPI2 Data In(B); IIC_SCL_C: IIC SCL(C); TOUCH4:Touch Input Channel 4; UART0_TXD: Uart0 Data Out(D); TMR1: Timer1 Clock In;
4	PA6	I/O	GPIO	UART1_RTS; SPI2_DOA: SPI2 Data Out(A); IIC_SDA_D: IIC SDA(D); ADC2: ADC Channel 2; TOUCH3:Touch Input Channel 3; UART0_RXA: Uart0 Data In(A); CAP0: Timer0 Capture;
5	PA5	I/O	GPIO	UART1_CTS; SPI2_CLKA: SPI2 Clock(A); IIC_SCL_D: IIC SCL(D); ADC1: ADC Channel 1; TOUCH2:Touch Input Channel 2; UART0_TXA: Uart0 Data Out(A); PWM5: Timer5 PWM Output;
6	PA4	I/O	GPIO (High Voltage)	SPI2_DIA: SPI2 Data In(A); UART2_RXA: Uart2 Data In(A); CAP2: Timer2 Capture;
7	PA3	I/O	GPIO	SPI1_DOC: SPI1 Data Out(C); ADC0: ADC Channel 0; TOUCH0:Touch Input Channel 0; UART2_TXA: Uart2 Data Out(A); PWM1: Timer1 PWM Output;

8	PA2	I/O	GPIO	CAP3: Timer3 Capture; UART1_RXC: Uart1 Data In(C);
9	PA1	I/O	GPIO	SPI1_DIC: SPI1 Data In(C); PWM0: Timer0 PWM Output; UART1_TXC: Uart1 Data Out(C);
10	PB8	I/O	GPIO (High Voltage)	UART0_RXB: Uart0 Data In(B); CAP4: Timer4 Capture;
11	PB7	I/O	GPIO	SPI1_DOA: SPI1 Data Out(A); Q-decoder1; TOUCH1:Touch Input Channel 6; ADC8: ADC Channel 8; UART0_TXB: Uart0 Data Out(B);
12	PB6	I/O	GPIO	SPI1_CLKA: SPI1 Clock(A) ; Q-decoder0; ADC9: ADC Channel 9; TOUCH7:Touch Input Channel 7; UART1_RXA: Uart1 Data In(A); PWM2: Timer2 PWM Output;
13	PB4	I/O	GPIO	CLKOUT0; LVD:Low Voltage Detect; SPI1_DIA: SPI1 Data In(A); ADC12: ADC Channel 12; TOUCH6:Touch Input Channel 6; UAR1_TXA: Uart1 Data Out(A); TMR2: Timer2 Clock In;
14	GND	P	GND	-
15	VBAT	P	LDO Power	-
16	LDOIN	P	Charge Power 5V	PWM3: Timer3 PWM Output; UART0_TXC: Uart0 Data Out(C); UART0_RXC: Uart0 Data In(C);
17	VDDIO	P	IO Power 3.3V	-
18	BTAVDD	P	Core Power 1.3V	-
19	PB3	I/O	GPIO	SPI2_DIC: SPI2 Data In(C); UART1_TXB: Uart1 Data Out(B); UART1_RXB: Uart1 Data In(B); TMR4: Timer4 Clock In;
20	PB2	I/O	GPIO	SPI2_DOC: SPI2 Data Out(C); ADC7: ADC Channel 7; UART2_RXC: Uart2 Data In(C); CAP5: Timer5 Capture; LP_TH1：Low Power Touch Channel 1;

21	PB1	I/O	GPIO (pull up)	Long Press Reset; UART2_TXC: Uart2 Data Out(C); ADC6: ADC Channel 6; LP_TH0：Low Power Touch Channel 0;
22	PC5	I/O	GPIO	SPI1_DOB: SPI1 Data Out(B); IIC_SDA_B: IIC SDA(B); ADC5: ADC Channel 5; UART2_RXD: Uart2 Data In(D);
23	PC4	I/O	GPIO	SPI1_CLKB: SPI1 Clock(B) ; IIC_SCL_B: IIC SCL(B); ADC4: ADC Channel 4; UART2_TXD: Uart2 Data Out(D); PWM4: Timer4 PWM Output;
24	PC3	I/O	GPIO	SPI1_DIB: SPI1 Data In(B); IIC_SDA_C: IIC SDA(C); ADC3: ADC Channel 3; TOUCH5:Touch Input Channel 5; UART0_RXD: Uart0 Data In(D); TMR3: Timer3 Clock In;

2. Electrical Characteristics

2.1 Absolute Maximum Ratings

Table 2-1

Symbol	Parameter	Min	Max	Unit
Topt	Operating temperature	-40	+85	°C
Tstg	Storage temperature	-65	+150	°C
VBAT	Supply Voltage	-0.3	5.5	V
LDOIN	Charge Input Voltage	-0.3	6	V
VDDIO	3.3V IO Input Voltage	-0.3	3.6	V

Note : The chip can be damaged by any stress in excess of the absolute maximum ratings listed below

2.2 Recommended Operating Conditions

Table 2-2

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
VBAT	Voltage Input	2.2	3.7	5.5	V	_
LDOIN	Voltage Input	4.5	5.0	5.5	V	_
Normal mode						
VDDIO	Voltage output	-	3.0	-	V	VBAT= 4.2V, 10mA loading
	Loading current	-	-	100	mA	VDDIO=3V@VBAT = 4.2V
BTAVDD	Voltage output	-	1.25	-	V	VDDIO=3V,10mA loading
	Loading current	-	-	60	mA	BTAVDD=1.25V@VDDIO = 3V
LP mode						
VDDIO	Loading current	-	-	5	mA	VDDIO=3V@VBAT = 4.2V

2.3 Battery Charge

Table 2-3

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
LDOIN	Charge Input Voltage	4.5	5	5.5	V	_
V_{Charge}	Charge Voltage	4.15	4.2	4.25	V	LDOIN>4.5V
		4.30	4.35	4.40	V	

I$_{Charge}$	Charge Current	20		200	mA	Charge current at fast charge mode
I$_{Trikl}$	Trickle Charge Current	20	45	70	mA	V$_{BAT}$ <V$_{Trikl}$

2.4 IO Input/Output Electrical Logical Characteristics

Table 2-4

IO input characteristics						
Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
V$_{IL}$	Low-Level Input Voltage	-0.3	–	0.3* VDDIO	V	VDDIO = 3.0V
V$_{IH}$	High-Level Input Voltage	0.7* VDDIO	–	VDDIO+0.3	V	VDDIO = 3.0V
IO output characteristics						
V$_{OL}$	Low-Level Output Voltage	–	–	0.3	V	VDDIO = 3.0V
V$_{OH}$	High-Level Output Voltage	2.7	–	–	V	VDDIO = 3.0V

2.5 Internal Resistor Characteristics

Table 2-5

| Port	Drive Strength	Internal Pull-Up Resistor	Internal Pull-Down Resistor	Comment
PA1-PA6, PB1-PB7, PC2-PC5,	drive_select[11] 64mA drive_select[10] 26.4mA drive_select[01] 8mA drive_select[00] 2.4mA	10K	10K	1. PB1 default pull up 2. USBDM&USBDP default pull down 3. Internal pull-up/pull-down resistance ∣ accuracy ±20% 4. PB8,P00 can pull-up resistance to 5V
PB8,P00	8mA	10K	10K	
USBDP	4mA	1.5K	15K	
USBDM	4mA	180K	15K	

3. Package Information

3.1 QSOP24

SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	—	—	1.75
A1	0.10	0.15	0.25
A2	1.30	1.40	1.50
A3	0.60	0.65	0.70
b	0.23	—	0.31
b1	0.22	0.25	0.28
c	0.20	—	0.24
c1	0.19	0.20	0.21
D	8.55	8.65	8.75
E	5.80	6.00	6.20
E1	3.80	3.90	4.00
e	0.635BSC		
h	0.30	—	0.50
L	0.50	—	0.80
L1	1.05REF		
θ	0	—	8°

Figure 3-1   AC6385A_QSOP24 Package

4. Package Type Specification

AC6385A4
① ②

①Represents different packages
②Represents different memory sizes
　　4: 4Mbit Flash

5. Revision History

Date	Revision	Description
2021.06.01	V1.0	Initial Release
2021.06.17	V1.1	