AD142A4 Datasheet

Zhuhai Jieli Technology Co.,LTD

Version：V1.2

Date：2024.09.05

ZHUHAI JIELI TECHNOLOGY CO., LTD

Copyright © Zhuhai Jieli Technology Co.,LTD. All rights reserved.

AD142A4 Features

CPU Core

- 32-bit CPU,the highest frequency is 160MHz

Clock Source

- RC Clock frequency about 16MHz
- LRC(low power RC) clock frequency about 32KHz
- HTC(low drift internal high frequency RC)clock frequency is 5MHz

Digital I/O

- 8 programmable digital I/O pins
- USB DP/DM can be configured to normal I/O pins
- General the IO supports pull-up(10k),pull-down(60k), strong,weak output,input and high impedance
- Up to 8 external interrupt/wake-up source(low power available,can be multiplexed to any I/O, with hardware filter)
- Input channel and Output channel, provide arbitrary IO input and output options for some modules

Digital peripherals

- One Full Speed USB 1.1 PHY
- Two UART Controllers(UART0/1) UART1 supports DMA and Flow Control
- Two SPI Controllers with DMA(SPI0/1) support master mode and slave mode.
- Built-in SPI flash
- One SD host controller
- Two 16-bit Asynchronous Divider Timers
- One IIC Controller
- Four channel PWM output
- 0.5 watt Class-D audio amplifier output
- Infrared remote control decoder
- Watchdog

Analog Peripherals

- MIC amplifier circuit
- Two analog audio input channels
- 10-bit high precision ADC
- 16-bit high precision ADC (mainly as recording)
- 16-bit high precision DAC
- Low voltage protection
- Power on reset

PMU

- Soft off current: <2uA
- Power down current: <30uA
- Music mode: <6mA@HSB 80M
- Recording mode: <11mA@HSB 80M
- LVD range(3bit):1.8V~2.5V, step100mV
- VBAT range : 2.0V~5.5V
- IOVDD range : 2.0V~3.4V

Temperature

- Operating temperature: -40℃ to +85℃
- Storage temperature: -65℃ to +150℃

Package

- SOP16

Application

- Sound Toy
- Audio player

ZHUHAI JIELI TECHNOLOGY CO，LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

1 Block Diagram



Figure 1-1 AD142A Block Diagram

ZHUHAI JIELI TECHNOLOGY CO., LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2 Pin Definition

2.1 Pin Assignment

Figure 2-1 AD142A4_SOP16 Package Diagram

ZHUHAI JIELI TECHNOLOGY CO., LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

2.2 Pin Description

Table 2-1 AD142A4_SOP16 Pin Description

PIN NO.	Name	Type	Drive (mA)	Function	Description
1	PA6	I/O	8/64	GPIO	SPI1DIC:SPI1 Data In(C); SD0DATD:SD0 Data(D);
2	PA5	I/O	8/64	GPIO	ADC7:ADC Input Channel 7; SPI0DAT3:SPI0 Data Out3; SPI1DOC:SPI1 Data Out(C); SD0CMDC:SD0 Command(C); SD0CMDD:SD0 Command(D); UART0RXA:Uart0 Data In(A); I2C_SDA(C); PWM1:PWM Channel1 Output;
3	PA4	I/O	8/64	GPIO	ADC6:ADC Input Channel 6; SPI0DAT2:SPI0 Data 2; SPI1CLKC:SPI1 Clock(C); SD0CLKC:SD0 Clock(C); SD0CLKD:SD0 Clock(D); UART0TXA:Uart0 Data Out(A); I2C_SCL(C); TMR2:Timer2 Clock In; PWM0:PWM Channel0 Output;
4	USBDM	I/O	10	USB Negative Data (pull down)	ADC5:ADC Input Channel 5; SPI1DOA:SPI1 Data Out(A); SD0DATC:SD0 Data(C); UART1TXA:Uart1 Data Out(A); I2C_SDA(A);
5	USBDP	I/O	10	USB Positive Data (pull down)	ADC4:ADC Input Channel 4; SPI1CLKA:SPI1 Clock(A); UART1RXA:Uart1 Data In(A); I2C_SCL(A);
6	PA0	I/O	8/64	GPIO (pull up)	Long Press Reset; ADC0:ADC Input Channel 0; UART0TXB:Uart0 Data Out(B);
	PA13	I/O	8/64	GPIO	ADC10:ADC Input Channel 10; AUX0:Analog Channel 0 Input; MIC_BIAS:Microphone Bias Output; CAP0:Timer0 Capture;
7	PB1	I/O	8/64	GPIO	MIC_IN:MIC Input Channel;

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

ZHUHAI JIELI TECHNOLOGY CO., LTD

8	AGND	G	/		Analog Ground;
9	PB0	I/O	8/64	GPIO	**DAC:Analog Audio Output;** ADC13:ADC Input Channel 13; LVD:Low Voltage Detect；
10	VDDIO	P	/		GPIO Power;
11	VBAT	P	/		Battery Power Supply;
12	GND	G	/		Digital Ground;
13	DACPO	O	/		Class-D APA Positive Output;
14	DACNO	O	/		Class-D APA Negative Output;
15	PA12	I/O	8/64	GPIO	SPI1DOB:SPI1 Data Out(B); MCAP3:Motor Timer3 Capture;
16	PA11	I/O	8/64	GPIO	ADC9:ADC Input Channel 9; SPI1CLKB:SPI1 Clock(B); MCAP2:Motor Timer2 Capture;
	PA9	I/O	8	GPIO (High Voltage Resistance)	UART1TXB:Uart1 Data Out(B); UART1RXB:Uart1 Data In(B); I2C_SDA(D); CAP1:Timer1 Capture; PWM3:PWM Channel3 Output;

ZHUHAI JIELI TECHNOLOGY CO., LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

3 Electrical Characteristics

3.1 Absolute Maximum Ratings

Table 3-1

Symbol	Parameter	Min	Max	Unit
Tamb	Ambient Temperature	-40	+85	℃
Tstg	Storage temperature	-65	+150	℃
VBAT	Supply Voltage	-0.3	5.5	V
$V_{VDDIO33}$	3.3V IO Input Voltage	-0.3	3.6	V

Note:The chip can be damaged by any stress in excess of the absolute maximum ratings listed below.

3.2 PMU Characteristics

Table 3-2

Symbol	Parameter	Min	Typ	Max	Unit	Test Conditions
VBAT	Voltage Input	2.0	3.7	5.5	V	_
V_{VDDIO}	Voltage output	2.0	3.0	3.4	V	VBAT = 3.7V, 100mA loading
I_{VDDIO}	Loading current	_	_	100	mA	VBAT=3.7V

3.3 IO Input/Output Electrical Logical Characteristics

Table 3-3

IO input characteristics						
Symbol	**Parameter**	**Min**	**Typ**	**Max**	**Unit**	**Test Conditions**
V_{IL}	Low-Level Input Voltage	-0.3	_	0.3* VDDIO	V	VDDIO = 3.3V
V_{IH}	High-Level Input Voltage	0.7* VDDIO	_	VDDIO+0.3	V	VDDIO = 3.3V
IO output characteristics						
V_{OL}	Low-Level Output Voltage	_	_	0.33	V	VDDIO = 3.3V
V_{OH}	High-Level Output Voltage	2.7	_	_	V	VDDIO = 3.3V

ZHUHAI JIELI TECHNOLOGY CO.,LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

3.4 Internal Resistor Characteristics

Table 3-4

Port	General Output	High Drive	Internal Pull-Up Resistor	Internal Pull-Down Resistor	Comment
PA0,PA4~PA6 PA11~PA13 PB0,PB1	8mA	64mA	10K	60K	1、PA0 default pull up 2、USBDM & USBDP default pull down 3、internal pull-up/pull-down resistance accuracy ±20%
PA9 (high voltage I/O)	8mA	_	10K	60K	
USBDP	10mA	_	1.5K	15K	
USBDM	10mA	_	180K	15K	

3.5 Analog DAC(PB0) Characteristics

Table 3-5

Parameter	Min	Typ	Max	Unit	Test Conditions
Frequency Response	20	_	16K	Hz	1KHz/0dB 100kohm loading With A-Weighted Filter
THD+N	_	-65	_	dB	
S/N	_	95	_	dB	
Output Swing	_	0.54	_	Vrms	
Dynamic Range	_	92	_	dB	1KHz/-60dB 100kohm loading With A-Weighted Filter
Output Resistance	_	8.3	_	K	_

3.6 ADC Characteristics

Table 3-6

Parameter	Min	Typ	Max	Unit	Test Conditions
Dynamic Range	_	75	_	dB	1KHz/210mVrms line mode :6dB with cap PGAIS=2
S/N	_	79	_	dB	
THD+N	_	-70	_	dB	

ZHUHAI JIELI TECHNOLOGY CO.,LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

4 Package Information

4.1 SOP16



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	—	—	1.75
A1	0.10	—	0.225
A2	1.30	1.40	1.50
A3	0.60	0.65	0.70
b	0.39	—	0.47
b1	0.38	0.41	0.44
c	0.20	—	0.24
c1	0.19	0.20	0.21
D	9.80	9.90	10.00
E	5.80	6.00	6.20
E1	3.80	3.90	4.00
e	1.27BSC		
h	0.25	—	0.50
L	0.50	—	0.80
L1	1.05REF		
θ	0	—	8°

Figure 4-1. AD142A4_SOP16 Package

ZHUHAI JIELI TECHNOLOGY CO., LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

5 IC Marking Information



① LLLLLLLLLL：Production Batch

② AD14Nx: Chip Model

③ x: Built-in flash size

0: No Flash Memory

2: 2Mbit Flash

4: 4Mbit Flash

8: 8Mbit Flash

ZHUHAI JIELI TECHNOLOGY CO., LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

6 Storage Condition

6.1 Moisture Sensitivity Level

AD142A is qualified to moisture sensitivity level MSL3 in accordance with JEDEC J-STD-033.

6.2 Storage Alert

1. Calculated shelf life in sealed bag 12 months at＜40°C and 90% relative humidity (RH).
2. Peak package body temperature≤260°C.
3. After bag is opened,devices that will be subjected to reflow solder or other high temperature process must be mounted within 168 hours of factory conditions≤30°C/60%RH or stored per J-STD-033.
4. Devices require bake before mounting if humidity indicator card reads＞10% for level 2a-5a devices or＞60% for level 2 devices when read at 23±5°C,or 3a or 3b are not met.

Please refer to IPC/JEDEC J-STD-033 for baking procedure if necessary.

ZHUHAI JIELI TECHNOLOGY CO., LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.

7 Revision History

Date	Revision	Description
2021.03.09	V1.0	Initial Release
2023.03.20	V1.1	Modify Features
2024.09.05	V1.2	Add Block Diagram Add IC Marking Information Add Storage Condition Update Features modification.

ZHUHAI JIELI TECHNOLOGY CO., LTD

Confidential
The information contained herein is the exclusive property of JIELI and shall not be distributed, reproduced, or disclosed in whole or in part without prior written permission of JIELI.