AW318B Datasheet

Zhuhai Jieli Technology Co.,LTD

Version 1.1

Date 2024.07.04

Revision History

Date	Revision	Description
2024.04.12	V1.0	Initial Release
2024.07.04	V1.1	Update IC Marking Information

Table of Contents

AW318B Features

SYSTEM

- 32bit CPU 160MHz
- Support MATH/AES128
- I-cache
- Support EMU
- On-chip SRAM 32kbyte
- Support MPU
- Support UDMA
- Built-In Flash
- 24MHz crystal oscillator
- Internal low jitter low power RC oscillator
- Internal PLL

Bluetooth

- BLE5.4 +2.4GHz-Proprietary (QDID 223418)
- Support AoA Transmitter
- Support long range BLE
- Maximum transmitting power 8dBm
- Receiver sensitivity
  - -92dBm @BLE-1Mbps
  - -89dBm @BLE-2Mbps
  - -94dBm @BLE-S2
  - -99dBm @BLE-S8

Peripherals

- 1 x Full speed USB
- 4 x Multi-function 32bit timer
- 1 x IR RX/TX
- 1 x UART interface
- 1 x I^2C Master/Slave interface
- 2 x SPI Master/Slave interface
- 1 x QDEC
- 2 x MCPWM
- 2 x LEDC
- 1 x 10bit ADC(2 Channel)
- 1 x GPIO Support function remapping

PMU

- Support temperature sensor
- VPWR range 2.7V to 5.5V
- IOVDD range 1.8V to 3.6V
- Deep sleep mode (IOVDD @3.0V)
  - 170nA (External wakeup)
  - 1.37uA (32kHz RC OSC+wakeup)
  - 2.9uA (32kHz RC OSC+wakeup+16k retention SRAM)

Packages

- SOP8

Temperature

- Operating temperature
  TC = -20℃ to +85℃(standard range)
  TC = -40℃ to +105℃(extended range)
- Storage temperature -65℃ to +150℃

Applications

- Mouse devices
- Non-audio remote controller
- Selfie stick
- Page turner
- Adaptive USB
- Bluetooth moudle
- Price tag and other diversified IOT product

1 Block Diagram



Figure 1-1 AW318B Block Diagram

2 Pin Definition

2.1 Pin Assignment



Figure 2-1 AW318B Pin Assignment

2.2 Pin Description

Table 2-2-1 AW318B Pin Description

Pin No.	Name	Type	IO Initial State	Description
1	VPWR	P	--	Battery Input
2	IOVDD	P	--	IO Power
3	VSS	G	--	Ground
4	BTRF	RF	--	Bluetooth RF Antenna
5	XOSCI	I	--	Crystal Oscillator Input
6	XOSCO	O	--	Crystal Oscillator Output
7	USBDM	I/O	15kΩ Pull-down	ADC13(ADC Input Channel 13)
8	USBDP	I/O	15kΩ Pull-down	ADC14(ADC Input Channel 14)
	PA10	I/O	Z	ADC10(ADC Input Channel 10)

Note

1.IO initial state abbreviations Z--High resistance, H--High level, L--Low level, X--May be changed during power on.

2.Timer, IR,MCPWM, QDEC, UART, LEDC, I^2C, SPI1 functions can be remapped to any I/O.

Table 2-2-2 Pin Types Description

Pin Type	Description	Pin Type	Description
P	Power	I/O	Input or Output
G	Ground	I	Input
RF	RF antenna	O	Output

3 Electrical Characteristics

3.1 Absolute Maximum Ratings

Table 3-1 Absolute Maximum Ratings

Symbol	Parameter	Min	Max	Unit
Topt	Operating temperature	-20	+85	℃
Tstg	Storage temperature	-65	+150	℃
VPWR	Supply Voltage	-0.3	6.0	V
IOVDD		-0.3	3.6	V
GPIO	Input voltage of GPIO (except PA7)	-0.3	3.6	V

Note

1.Stresses beyond those listed under absolute maximum ratings may cause permanent damage to the device.

3.2 ESD Ratings

Table 3-2 ESD Ratings

Parameter	Typ	Test pin	Reference standard
Human Body Mode	±8kV	All pins	JEDEC EIA/JESD22-A114
Machine Mode	±400V	All pins	JEDEC EIA/JESD22-A115
Charge Device Model	±2kV	All pins	ANSI/ESDA/JEDEC JS-002-2022

3.3 PMU Characteristics

Table 3-3-1 PMU Characteristics under VPWR supply

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
VPWR	Power supply	--	2.7	--	5.5	V
Operating mode						
Symbol	**Parameter**	**Conditions**	**Min**	**Typ**	**Max**	**Unit**
IOVDD	Voltage output	--	--	3.0	--	V
	Loading current	IOVDD=3.0V@VPWR = 3.7V	--	--	60	mA
Low Power mode						
Symbol	**Parameter**	**Conditions**	**Min**	**Typ**	**Max**	**Unit**
IOVDD	Loading current	IOVDD=3.0V@VPWR = 3.7V	--	--	8	mA

Table 3-3-2 PMU Characteristics under IOVDD supply

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
IOVDD	Power supply	--	1.8	--	3.6	V

3.4 IO Characteristics

Table 3-4 IO Characteristics

Input Characteristics						
Symbol	**Parameter**	**Conditions**	**IO**	**Min**	**Max**	**Unit**
V_{IL}	Low-Level Input Voltage	IOVDD = 3.0V	PA10	-0.3	1.4	V
V_{IH}	High-Level Input Voltage	IOVDD = 3.0V	USBDP USBDM	1.7	3.3	V
Output Characteristics						
Symbol	**Parameter**	**Conditions**	**IO**	**Typ**		**Unit**
$\lvert I_{OL} \rvert$	Output Current	IOVDD = 3.0V Voutput = 0.3V	PA10	3(HD=0) 9(HD=1) 21(HD=2) 54(HD=3)		mA
		IOVDD = 3.0V Voutput = 0.3V	USBDP USBDM	8		mA
$\lvert I_{OH} \rvert$	Output Current	IOVDD = 3.0V Voutput = 2.7V	PA10	3(HD=0) 9(HD=1) 21(HD=2) 54(HD=3)		mA
		IOVDD = 3.0V Voutput = 2.7V	USBDP USBDM	8		mA
Internal Resistance Characteristics						
Symbol	**Parameter**	**Conditions**	**IO**	**Typ**		**Unit**
R_{pu}	Pull-up Resistance	IOVDD = 3.0V	PA10	10k(PU=1) 100k(PU=2) 1M(PU=3)		Ω
		IOVDD = 3.0V	USBDP	1.5k		Ω
		IOVDD = 3.0V	USBDM	180k		Ω
R_{pd}	Pull-down Resistance	IOVDD = 3.0V	PA10	10k(PD=1) 100k(PD=2) 1M(PD=3)		Ω
		IOVDD = 3.0V	USBDP USBDM	15k		Ω

Note

1.Internal pull-up/pull-down resistance accuracy ±20%.

3.5 BT Characteristics

3.5.1 Transmitter

Table 3-5-1 Transmitter characteristics

Parameter	Conditions	Min	Typ	Max	Unit
Maximum RF Transmit Power	BLE-1Mbps	--	7	8	dBm

3.5.2 Receiver

Table 3-5-2 Receiver characteristics

Parameter	Conditions	Min	Typ	Max	Unit
Sensitivity	BLE-1Mbps	--	-92	--	dBm
	BLE-2Mbps	--	-89	--	dBm
	BLE-S2	--	-94	--	dBm
	BLE-S8	--	-99	--	dBm

4 Package Information

4.1 SOP8



SYMBOL	MILLIMETER		
	MIN	NOM	MAX
A	—	—	1.75
A1	0.10	—	0.225
A2	1.30	1.40	1.50
A3	0.60	0.65	0.70
b	0.39	—	0.47
b1	0.38	0.41	0.44
c	0.20	—	0.24
c1	0.19	0.20	0.21
D	4.80	4.90	5.00
E	5.80	6.00	6.20
E1	3.80	3.90	4.00
e	1.27BSC		
h	0.25	—	0.50
L	0.50	—	0.80
L1	1.05REF		
θ	0	—	8°

Figure 4-1 AW318B Package

5 IC Marking Information



Figure 5-1 AW318B Package Outline

① LLL.....LL LOT No. , It contains 7 to 18 alphanumerics

② AW31Nx Chip Model

③ x Built-in flash size

0 No Flash Memory

2 2Mbit Flash

4 4Mbit Flash

6 Solder-Reflow Condition



Figure 6-1 Classification Reflow Profile

Table 6-1 Classification Profiles

Profile Feature		Sn-Pb Eutectic Assembly	Pb-Free Assembly
Preheat/Soak	Temperature Min (T_{smin})	100℃	150℃
	Temperature Max (T_{smax})	150℃	200℃
	Time (ts) from (T_{smin} to T_{smax})	60-120 seconds	60-180 seconds
Average ramp-up rate (T_{smax} to T_p)		3℃/second max	3℃/second max
Liquidus temperature (T_L) Time (t_L) maintained above T_L		183℃ 60-150 seconds	217℃ 60-150 seconds
Peak package body temperature (T_p)		See Table 6-2	See Table 6-3
Time within 5℃ of actual Peak Temperature (tp)[2]		10-30 seconds	20-40 seconds
Ramp-down rate (T_p to T_L)		6℃/second max	6℃/second max
Time 25℃ to peak temperature		6 minutes max	8 minutes max

Note

1.All temperatures refer to topside of the package, measured on the package body surface

2.Time within 5℃ of actual peak temperature (tp) specified for the reflow profiles is a "supplier" and "user" maximum.

Table 6-2 SnPb Classification Temperature

Package Thickness	Volume mm^3 < 350	Volume mm^3 ≥ 350
<2.5 mm	240 +0/-5℃	225 +0/-5℃
≥2.5 mm	225 +0/-5℃	225 +0/-5℃

Table 6-3 Pb-free - Classification Temperature

Package Thickness	Volume mm³ < 350	Volume mm³ 350 - 2000	Volume mm³ > 2000
< 1.6mm	260℃	260℃	260℃
1.6 mm - 2.5mm	260℃	250℃	245℃
> 2.5mm	250℃	245℃	245℃

Note

1.*Tolerance The device manufacturer/supplier shall assure process compatibility up to and including the stated classification temperature (this means Peak reflow temperature +0℃.For example 260℃+0℃)at the rated MSL level.