

Computational Advertising

Greedy Algorithms

Competitive Algorithms

Picking the Best Ad

The Balance Algorithm

Jeffrey D. Ullman
Stanford University

Slides primarily taken
from Anand Rajaraman



Administrivia

Final Exam
Last Lectures

Final Exam

- To be held in Dinkelspiel Auditorium, 8:30-11:30AM, Wednesday March 16.
 - Do not go to Nvidia Aud.
- Exam will cover entire course.
 - No programming.
 - No proofs, but you may need to prove something to yourself to be sure of getting the right answer.
 - Open book/notes.
 - Internet allowed, but not communication with others.

Words of Advice Re Final

- Although you can access any on-line source of information, e.g., the text or Wikipedia, you will find that there are a lot of questions to be answered in very little time.
- If you have to read a section of the book for every question, you will waste too much time.


Last Lectures

- **March 3:** Jeff finishes up Computational Advertising + comparison between MapReduce-like systems and bulk-synchronous systems.
- **March 8:** Hima and Tim talk about submodular optimization.
- **March 10:** Caroline on multi-arm bandits + Jeff on the design of good MapReduce algorithms.

Online Algorithms


- Classic model of (*offline*) algorithms:
 - You get to see the entire input, then compute some function of it.
- *Online algorithm*:
 - You get to see the input one piece at a time, and need to make irrevocable decisions along the way.
 - Similar to data stream models.

Example: Bipartite Matching




- Two sets of nodes.
- Some edges between them.
- Maximize the number of nodes paired 1-1 by edges.

Bipartite Matching – (2)



$M = \{(1, a), (2, b), (3, d)\}$ is a *matching* of cardinality $|M| = 3$.

Bipartite Matching – (3)



$M = \{(1, c), (2, b), (3, d), (4, a)\}$ is a
perfect matching (all nodes matched).


Matching Algorithm

- **Problem:** Find a maximum-cardinality matching for a given bipartite graph.
 - A perfect one if it exists.
- There is a polynomial-time offline algorithm (Hopcroft and Karp 1973).
- But what if we don't have the entire graph initially?

Online Matching

- Initially, we are given the set of men.
- In each round, one woman's set of choices is revealed.
- At that time, we have to decide either to:
 - Pair the woman with a man.
 - Don't pair the woman with any man.
- **Example applications:** assigning tasks to servers or Web requests to threads.

Online Matching – (2)



(1,a)

(2,b)

(3,d)

Greedy Algorithm

- Pair the new woman with any eligible man.
 - If there is none, don't pair the woman.
- How good is the algorithm?

Competitive Ratio

- For input I , suppose greedy produces matching M_{greedy} while an optimal matching is M_{opt} .


Competitive ratio =

$$\min_{\text{all possible inputs } I} (|M_{\text{greedy}}| / |M_{\text{opt}}|).$$

Greedy Has Competitive Ratio $1/2$

- Let O be the optimal matching, and G the matches produced by a run of the greedy algorithm.
- Consider the sets of women:
 - A: Matched in G , not in O .
 - B: Matched in both.
 - C: Matched in O , not in G .

Proof of Competitive Ratio 1/2




- During the greedy matching, every woman in C found her optimal match taken by another woman.
- Thus, $|A| + |B| \geq |C|$.
- Surely, $|A| + |B| \geq |B|$.
- Thus, $|G| = |A| + |B| \geq (|B| + |C|)/2 = |O|/2$.

If you're greater than each of two things, you are greater than their average.



Worst-Case Scenario



(1,a)

(2,b)

$|\text{Greedy}| = 2;$

$|\text{Opt}| = 4.$

History of Web Advertising

- Banner ads (1995-2001).
 - Initial form of web advertising.
 - Popular websites charged X\$ for every 1000 “impressions” of ad.
 - Called “CPM” rate.
 - Modeled on TV, magazine ads.
 - Untargeted to demographically targeted.
 - Low clickthrough rates.
 - low ROI for advertisers.

Performance-Based Advertising

- Introduced by Overture around 2000.
 - Advertisers “bid” on search keywords.
 - When someone searches for that keyword, the highest bidder’s ad is shown.
 - Advertiser is charged only if the ad is clicked on.
- Similar model adopted by Google with some changes around 2002.
 - Called “Adwords.”

Web 2.0

- Performance-based advertising works!
 - Multi-billion-dollar industry.
- Interesting problems:
 - What ads to show for a search?
 - If I'm an advertiser, which search terms should I bid on and how much should I bid?

Adwords Problem

- A stream of queries arrives at the search engine
 - q_1, q_2, \dots
- Several advertisers bid on each query.
- When query q_i arrives, search engine must pick a subset of advertisers whose ads are shown.
- **Goal**: maximize search engine's revenues.
- Clearly we need an online algorithm!
- Simplest online algorithm is Greedy.

Complications – (1)

- Each ad has a different likelihood of being clicked.
- Example:
 - Advertiser 1 bids \$2, click probability = 0.1.
 - Advertiser 2 bids \$1, click probability = 0.5.
 - Click-through rate measured by historical performance.
- Simple solution:
 - Instead of raw bids, use the “expected revenue per click.”

The Adwords Innovation

Advertiser	Bid	CTR	Bid * CTR
A	\$1.00	1%	1 cent
B	\$0.75	2%	1.5 cents
C	\$0.50	2.5%	1.125 cents

The Adwords Innovation

Advertiser	Bid	CTR	Bid * CTR
B	\$0.75	2%	1.5 cents
C	\$0.50	2.5%	1.125 cents
A	\$1.00	1%	1 cent

Complications – (2)

- Each advertiser has a limited budget
 - Search engine guarantees that the advertiser will not be charged more than their daily budget.

Simplified Model (For Now)

- Assume all bids are 0 or 1.
- Each advertiser has the same budget B .
- One advertiser is chosen per query.
- Let's try the greedy algorithm:
 - Arbitrarily pick an eligible advertiser for each keyword.

Bad Scenario For Greedy

- Two advertisers A and B.
- A bids on query x, B bids on x and y.
- Both have budgets of \$4.
- Query stream: x x x x y y y y.
- Possible greedy choice: B B B B _ _ _ _.
- Optimal: A A A A B B B B.
- Competitive ratio = $1/2$.
 - This is actually the worst case.

Balance Algorithm [MSVV]

- [Mehta, Saberi, Vazirani, and Vazirani].
- For each query, pick the advertiser with the largest unspent budget who bid on this query.
 - Break ties arbitrarily.


Example: Balance

- Two advertisers A and B.
- A bids on query x, B bids on x and y.
- Both have budgets of \$4.
- Query stream: x x x x y y y y.
- **Balance choice**: B A B A B B _ _.
- **Optimal**: A A A A B B B B.
- Competitive ratio = $3/4$.

Analyzing Balance

- Consider simple case: two advertisers, A_1 and A_2 , each with budget $B > 1$, an even number.
- We'll consider the case where the optimal solution exhausts both advertisers' budgets.
 - I.e., optimal revenue to search engine = $2B$.
- Balance must exhaust at least one advertiser's budget.
 - If not, we can allocate more queries.
 - Assume Balance exhausts A_2 's budget.

Analyzing Balance




■ Queries allocated to A₁ in optimal solution

■ Queries allocated to A₂ in optimal solution

Opt revenue = $2B$

Balance revenue = $2B - x = B + y$

Note: only green queries can be assigned to neither.
A blue query could have been assigned to A₁.



Balance allocation


We claim $y \geq x$ (next slide).

Balance revenue is minimum for $x=y=B/2$.

Minimum Balance revenue = $3B/2$.

Competitive Ratio = $3/4$.

Analyzing Balance: Two Cases




- **Case 1:** At least half the blue queries are assigned to A_1 by Balance.

- Then $y \geq B/2$, since the blues alone are $\geq B/2$.



- **Case 2:** Fewer than half the blue queries are assigned to A_1 by Balance.

- Let q be the last blue query assigned by Balance to A_2 .



Balance allocation

Analyzing Balance – (3)



Balance allocation

- Since A_1 obviously bid on q , at that time, the budget of A_2 must have been at least as great as that of A_1 .
- Since more than half the blue queries are assigned to A_2 , at the time of q , A_2 's remaining budget was at most $B/2$.
- Therefore so was A_1 's, which implies $x \leq B/2$, and therefore $y \geq B/2$ and $y \geq x$.
- Thus Balance uses $\geq 3B/2$.

General Result

- In the general case, competitive ratio of Balance is $1 - 1/e = \text{approx. } 0.63$.
- Interestingly, no online algorithm has a better competitive ratio.
- Won't go through the details here, but let's see the worst case that gives this ratio.


Worst Case for Balance

- N advertisers, each with budget $B \gg N \gg 1$.
- $N*B$ queries appear in N rounds.
- Each round consists of a single query repeated B times.
- Round 1 queries: bidders A_1, A_2, \dots, A_N .
- Round 2 queries: bidders $A_2, A_3, \dots, A_N, \dots$
- Round i queries: bidders A_i, \dots, A_N, \dots
- Round N queries: only A_N bids.
- Optimum allocation: round i queries to A_i .
 - Optimum revenue $N*B$.

Pattern to Remember

- After i rounds, the first i advertisers have dropped out of the bidding.
 - **Why?** All subsequent queries are ones they do not bid on.
- Thus, they never get any more queries, even though they have budget left.

Balance Allocation




After k rounds, sum of allocations to each of A_k, \dots, A_N is
$$S_k = S_{k+1} = \dots = S_N = \sum_{1 \leq i \leq k} B/(N-i+1).$$

If we find the smallest k such that $S_k \geq B$, then after k rounds we cannot allocate any queries to any advertiser.


BALANCE Analysis

$B/1$ $B/2$ $B/3 \dots B/(N-k+1) \dots$ $B/(N-1)$ B/N

Each width represents the amount of budget spent after k rounds.




Or in terms of fractions (dividing by B):



BALANCE analysis

- **Fact:** $H_n = \sum_{1 \leq i \leq n} 1/i \approx \log_e(n)$ for large n .
 - Result due to Euler.



$S_k = 1$ implies $H_{N-k} = \log(N) - 1 = \log(N/e)$.

$N-k = N/e$ (Why? $\log(N-k) = H_{N-k} = \log(N/e)$).

$k = N(1-1/e) \approx 0.63N$.

Balance analysis

- So after the first $N(1-1/e)$ rounds, we cannot allocate a query to any advertiser.
- Revenue = $BN(1-1/e)$.
- Competitive ratio = $1-1/e$.

General Version of Problem

- Arbitrary bids, budgets.
- Balance can be terrible.
- **Example:** Consider two advertisers A_1 and A_2 , each bidding on query q .
 - A_1 : $x_1 = 1$, $b_1 = 110$.
 - A_2 : $x_2 = 10$, $b_2 = 100$.
- First 10 occurrences of q all go to A_1 , and A_1 then gets 10 q 's for every one that A_2 gets.
 - What if there are only 10 occurrences of q ?
 - Opt yields \$100; Balance yields \$10.

Generalized Balance

- Arbitrary bids; consider query q , bidder i .
 - Bid = x_i .
 - Budget = b_i .
 - Amount spent so far = m_i .
 - Fraction of budget remaining $f_i = 1 - m_i/b_i$.
- Define $\psi_i(q) = x_i(1 - e^{-f_i})$.
- Allocate query q to bidder i with largest value of $\psi_i(q)$.
- Same competitive ratio $(1 - 1/e)$.